



Art.-Nr. / Item No.	Länge / Length (L)
72315	500 ± 20 mm
72316	1000 ± 30 mm
72317	1500 ± 30 mm
72318	2000 ± 30 mm
72319	3000 ± 30 mm



**Premium High-Speed-HDMI™ Kabel mit Ethernet**  
 - offiziell zertifiziert durch das Premium-HDMI™-Kabel-Zertifizierungsprogramm

Anschlüsse: 2x HDMI™-Stecker (Typ A)  
 Kontakte: vergoldet  
 Material: PE, PVC 45P  
 AWG: 30  
 Kontaktwiderstand: 3 Ω max.  
 Isolationswiderstand: 5 MΩ min.  
 Max. Auflösung: 4K Ultra HD 2160p (60 Hz)  
 Max. Datenübertragungsrate: 18 Gbit/s  
 Unterstützte Farbräume: Deep Color (36 Bit), x.v.Colour (xvYCC), YCbCr 4:4:4  
 Unterstützte Standards: HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, HDCP 2.2, Consumer Electronics Control (CEC), Audio Return Channel (ARC), Audio (1536 kHz)

**Premium High Speed HDMI™ cable with Ethernet**  
 - officially certified by the Premium HDMI™ cable certification program

Connectors: 2x HDMI™ plug (Type A)  
 Contacts: gold-plated  
 Material: PE, PVC 45P  
 AWG: 30  
 Contact resistance: 3 Ω max.  
 Insulation resistance: 5 MΩ min.  
 Max. resolution: 4K Ultra HD 2160p (60 Hz)  
 Max. data transmission rate: 18 Gbit/s  
 Supported colour spaces: Deep Color (36 Bit), x.v.Colour (xvYCC), YCbCr 4:4:4  
 Supported standards: HDR (High Dynamic Range), HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, HDCP 2.2, Consumer Electronics Control (CEC), Audio Return Channel (ARC), Audio (1536 kHz)

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	26.07.2021	HDMI 2.0 Kabel Zert. XXXX Xm STD sw	1/1
		gepr.:	26.07.2021		
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change				72315, 72316, 72317, 72318, 72319	

