



### **ALSEYE X240** – 240mm AiO water cooling

The X240 AiO water cooling of the X series from ALSEYE impresses with its compact design and, thanks to the cooling plate made of copper and the radiator made of pure aluminum, ensures that the generated heat is reliably removed. The two 120mm X12 fans reliably transport the heat away at up to 1600 rpm and also shine in rich RGB colors.

The lighting and fan speed are controlled centrally via the enclosed control unit, to which up to six additional X12 fans, which are available separately, can be connected. The RGB effects can be managed either via the RF wireless remote control or via the 5V 3pin RGB header.

The pump with high-quality ceramic bearing and integrated RGB LEDs as well as the high-quality sleeved, swiveling FEP tubes with a length of 300 mm ensure safe, reliable and long-lasting operation.

- ✓ AiO water cooling with a compact design
- ✓ High quality materials made of copper and aluminum
- ✓ Two powerful 120mm X12 fans with RGB lighting
- ✓ TDP up to 280W

## Specifications

CPU sockets	Intel® Socket LGA2011, 2066 Square ILM Intel® Socket LGA775, 1150, 1151, 1155, 1156, 1200, 1366 AMD® Socket AM2, AM2+, AM3, AM3+, FM1, FM2, AM4
Fan dimensions (H/W/D)	120x120x30mm
Rated voltage	12V
Fan speed	1600rpm
Air flow per fan	95.65m <sup>3</sup> /h
Air pressure per fan	1.97mmH <sub>2</sub> O
Noise level	35.6dba
Fan connector	4pin PWM
Tube length	300mm
Cooling fluid	Ecofriendly liquid with anti-corrosion protection
Net dimensions (H/W/D)	Water block: 62/62/90mm Radiator: 27/275/120mm
Package dimensions (H/W/D)	320/220/145mm
Weight (net)	0.93kg
Weight (gross)	1.57kg
Packing units (VE/VPE)	1/8
Warranty	24 Months
Article number	88885494
EAN-Code	4897059872728
Scope of delivery	Mounting kit for Intel® socket LGA775, 1150, 1155, 1151, 1156, 1200, 1366, 2011, 2066 Square ILM Mounting kit for AMD® Socket AM2, AM2+, AM3, AM3+, AM4, FM1, FM2 Backplate mounting kit Control unit for X12 fan (magnetically attachment in the case, up to 8 fans connectable in total) RF wireless remote control Power cord for control unit (Connection over S-ATA power connector) Combo cable for 5V 3pin RGB header and PWM Thermal compound Manual (English)
Features	Cooling plate with copper base Pump with high quality ceramic bearing and RGB LEDs Space-saving radiator made of pure aluminum 2x 120mm X12 fans with each 26 RGB LEDs RGB LEDs controllable via remote control or 5V 3pin RGB 3pin RGB header connection for 5V RGB mainboard control High quality sleeved, swiveling FEP tubes Supports CPUs with a max. TDP of 280W