



**C&D ELETTRONICA** SRL

BERGAMO 24126  
Via Oprandi, 17  
Tel. 035 199 55 011  
Fax 035 199 55 099

E-COMMERCE  
www.cedelettronica.com

E-MAIL: mail@cedelettronica.com  
PEC: cedelettronica@pec.it



LABORATORIO EMC  
PROVE DI COMPATIBILITA'  
ELETTROMAGNETICA



[WWW.CEDELETRONICA.COM](http://WWW.CEDELETRONICA.COM)

[WWW.MTEK.IT](http://WWW.MTEK.IT)

P. IVA e Cod. Fisc. 00895950160 C.C.I.A.A. R.E.A. di BG n. 180921  
Cap. Soc. 500.000,00 Euro i.v. Registro Imprese di BG n. 15669



Registro A.E.E.n.IT08020000003208  
Registro PILE n. IT 16010P00003973

Listino prezzi MOXA - [www.moxa.com](http://www.moxa.com)

Prezzi IVA esclusa f.co ns magazzino

*LUGLIO 2024*

Per quantità e offerte speciali contattare:

**C&D Elettronica srl**

tel. **035.19955011** [info@mtek.it](mailto:info@mtek.it)

**[www.mtek.it](http://www.mtek.it)**

MODELLO	DESCRIZIONE	PREZZO €	Std Lead Time
<b>3G Antenna Package</b>	3G external antenna with QMA (male) to SMA (female) adapter and 2 50 cm cables, 3G external antenna with 2 SMA connectors, cellular extension cable	<b>270,00 €</b>	8~12W
<b>45ML-5401</b>	Module for the ioThinX 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -20 to 60°C operating temperature	<b>683,00 €</b>	8~12W
<b>45ML-5401-T</b>	Module for the ioThinX 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -40 to 75°C operating temperature	<b>819,00 €</b>	8~12W
<b>45MR-1600</b>	Module for the ioThinX 4500 Series, 16 DIs, 24 VDC, PNP, -20 to 60°C operating temperature	<b>215,00 €</b>	2~4W
<b>45MR-1600-T</b>	Module for the ioThinX 4500 Series, 16 DIs, 24 VDC, PNP, -40 to 75°C operating temperature	<b>290,00 €</b>	4~8W
<b>45MR-1601</b>	Module for the ioThinX 4500 Series with 16 DIs, 24 VDC, NPN, -20 to 60°C operating temperature	<b>215,00 €</b>	4~8W
<b>45MR-1601-T</b>	Module for the ioThinX 4500 Series with 16 DIs, 24 VDC, NPN, -40 to 75°C operating temperature	<b>290,00 €</b>	12~16W
<b>45MR-2404</b>	Module for the ioThinX 4500 Series with 4 relays, form A, -20 to 60°C operating temperature	<b>193,00 €</b>	4~8W
<b>45MR-2404-T</b>	Module for the ioThinX 4500 Series, 4 relays, form A, -40 to 75°C operating temperature	<b>271,00 €</b>	12~16W
<b>45MR-2600</b>	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, sink, -20 to 60°C operating temperature	<b>231,00 €</b>	4~8W
<b>45MR-2600-T</b>	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	<b>310,00 €</b>	4~8W
<b>45MR-2601</b>	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, source, -20 to 60°C operating temperature	<b>231,00 €</b>	4~8W
<b>45MR-2601-T</b>	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, source, -40 to 75°C operating temperature	<b>310,00 €</b>	12~16W
<b>45MR-2606</b>	Module for the ioThinX 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -20 to 60°C operating temperature	<b>240,00 €</b>	4~8W
<b>45MR-2606-T</b>	Module for the ioThinX 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -40 to 75°C operating temperature	<b>313,00 €</b>	12~16W
<b>45MR-3800</b>	Module for the ioThinX 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	<b>511,00 €</b>	4~8W
<b>45MR-3800-T</b>	Module for the ioThinX 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	<b>668,00 €</b>	12~16W
<b>45MR-3810</b>	Module for the ioThinX 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -20 to 60°C operating temperature	<b>511,00 €</b>	4~8W
<b>45MR-3810-T</b>	Module for the ioThinX 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -40 to 75°C operating temperature	<b>668,00 €</b>	12~16W
<b>45MR-4420</b>	Module for the ioThinX 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	<b>442,00 €</b>	4~8W
<b>45MR-4420-T</b>	Module for the ioThinX 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	<b>597,00 €</b>	8~12W
<b>45MR-6600</b>	Module for the ioThinX 4500 Series, 6 RTDs, -20 to 60°C operating temperature	<b>480,00 €</b>	4~8W
<b>45MR-6600-T</b>	Module for the ioThinX 4500 Series, 6 RTDs, -40 to 75°C operating temperature	<b>625,00 €</b>	12~16W
<b>45MR-6810</b>	Module for the ioThinX 4500 Series, 8 TCs, -20 to 60°C operating temperature	<b>484,00 €</b>	4~8W
<b>45MR-6810-T</b>	Module for the ioThinX 4500 Series, 8 TCs, -40 to 75°C operating temperature	<b>625,00 €</b>	12~16W
<b>45MR-7210</b>	Module for the ioThinX 4500 Series, system and field power inputs, -20 to 60°C operating temperature	<b>234,00 €</b>	4~8W
<b>45MR-7210-T</b>	Module for the ioThinX 4500 Series, system and field power inputs, -40 to 75°C operating temperature	<b>269,00 €</b>	12~16W
<b>45MR-7820</b>	Module for the ioThinX 4500 Series, potential distributor module, -20 to 60°C operating temperature	<b>143,00 €</b>	4~8W
<b>45MR-7820-T</b>	Module for the ioThinX 4500 Series, potential distributor module, -40 to 75°C operating temperature	<b>181,00 €</b>	8~12W
<b>85M-1602-T</b>	Module for the ioPAC 8500/8600 Series, 16 DIs, 24 VDC, sink/source, -40 to 75°C operating temperature	<b>510,00 €</b>	8~12W
<b>85M-2600-T</b>	Module for the ioPAC 8500/8600 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	<b>510,00 €</b>	8~12W
<b>85M-3800-T</b>	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, -40 to 75°C operating temperature	<b>851,00 €</b>	8~12W
<b>85M-3801-T</b>	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, 40 kHz, -40 to 75°C operating temperature	<b>1.013,00 €</b>	8~12W
<b>85M-3810-T</b>	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, -40 to 75°C operating temperature	<b>851,00 €</b>	8~12W
<b>85M-3811-T</b>	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, 40 kHz, -40 to 75°C operating temperature	<b>1.013,00 €</b>	8~12W
<b>85M-5401-T</b>	Module for the ioPAC 8500/8600 Series, 4-port serial, DB44 connectors, -40 to 75°C operating temperature	<b>1.135,00 €</b>	8~12W
<b>85M-6600-T</b>	Module for the ioPAC 8500/8600 Series, 6 RTDs, -40 to 75°C operating temperature	<b>960,00 €</b>	8~12W
<b>85M-6810-T</b>	Module for the ioPAC 8500/8600 Series, 8 TCs, -40 to 75°C operating temperature	<b>1.062,00 €</b>	8~12W
<b>85M-BKTES</b>	Empty slot cover (3 pieces per package)	<b>67,00 €</b>	4~8W
<b>86M-1620D-T</b>	Module for the ioPAC 8600 Series, 16 DIs, 24 to 110 VDC, sink, channel LED, -40 to 75°C operating temperature	<b>769,00 €</b>	8~12W
<b>86M-1832D-T</b>	Module for the ioPAC 8600 Series with 8 DIs, 24 VDC, sink/source, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	<b>691,00 €</b>	8~12W
<b>86M-2604D-T</b>	Module for the ioPAC 8600 Series, 6 Relays, form A (N.O.), channel LED, -40 to 75°C operating temperature	<b>527,00 €</b>	8~12W
<b>86M-2821D-T</b>	Module for the ioPAC 8600 Series, 8 DOs, 24 to 110 VDC, source, channel LED, -40 to 75°C operating temperature	<b>955,00 €</b>	8~12W
<b>86M-2830D-T</b>	Module for the ioPAC 8600 Series with 8 DOs, 24 VDC, sink, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	<b>955,00 €</b>	8~12W
<b>86M-4420-T</b>	Module for the ioPAC 8600 Series, 4 AOs, 0 to 10 V, -10 to 10 V, 0 to 20 mA, or 4 to 20 mA, -40 to 75°C operating temperature	<b>850,00 €</b>	8~12W
<b>86M-5212U-T</b>	Module for the ioPAC 8600 Series, 2-port 2-wire Ethernet switch, -40 to 75°C operating temperature	<b>1.343,00 €</b>	8~12W
<b>86M-5250-T</b>	Module for the ioPAC 8600 Series, 2 CAN ports, -40 to 75°C operating temperature	<b>769,00 €</b>	8~12W
<b>A52-DB25F w/ Adapter</b>	RS-232/422/485 converter with adapter, DB25F cable	<b>66,00 €</b>	8~12W
<b>A52-DB25F w/o Adapter</b>	RS-232/422/485 converter with DB25F cable	<b>56,00 €</b>	8~12W
<b>A52-DB9F w/ Adapter</b>	RS-232/422/485 converter with adapter, DB9F cable	<b>66,00 €</b>	2~4W
<b>A52-DB9F w/o Adapter</b>	RS-232/422/485 converter with DB9F cable	<b>56,00 €</b>	2~4W
<b>A53-DB25F w/ Adapter</b>	RS-232/422/485 converter with 2 kV isolation, adapter, DB25F cable	<b>121,00 €</b>	8~12W
<b>A53-DB25F w/o Adapter</b>	RS-232/422/485 converter with 2 kV isolation, DB25F cable	<b>108,00 €</b>	8~12W

<b>A53-DB9F w/ Adapter</b>	RS-232/422/485 converter with 2 kV isolation, adapter, DB9F cable	<b>121,00 €</b>	2~4W
<b>A53-DB9F w/o Adapter</b>	RS-232/422/485 converter with 2 kV isolation, DB9F cable	<b>108,00 €</b>	4~8W
<b>A-ADP-QMAM-RF</b>	Antenna adapter with QMA (male) to SMA (female) connectors	<b>20,00 €</b>	12~14W
<b>A-ADP-RJ458P-DB9F-ABC01</b>	DB9 female to RJ45 connector for the ABC-01 Series	<b>20,00 €</b>	12~14W
<b>A-ADP-SM-RF Golden</b>	SMA adapter for UC-2104 and UC-5100 Series	<b>10,00 €</b>	10~12W
<b>ABC-01</b>	Configuration backup and restoration tool for managed Ethernet switches and AWK Series wireless APs/bridges/clients, 0 to 60°C operating temperature	<b>98,00 €</b>	4~8W
<b>ABC-01-M12</b>	Configuration backup and restoration tool with M12 connector for managed Ethernet switches and wireless APs/Bridges/Clients, 0 to 60°C operating temperature	<b>136,00 €</b>	8~12W
<b>ABC-01-P-M12-CT-T</b>	Configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	<b>248,00 €</b>	4~8W
<b>ABC-02-P-USB-M12-CT-T</b>	USB-based configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	<b>289,00 €</b>	12~16W
<b>ABC-02-USB</b>	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature	<b>203,00 €</b>	2~4W
<b>ABC-02-USB-T</b>	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, -40 to 75°C operating temperature	<b>236,00 €</b>	4~8W
<b>ABC-03-microSD-T</b>	MicroSD-based configuration backup and restoration tool, firmware upgrades, and log file storage tool for managed Ethernet switches and WLAN products, -40 to 85°C operating temperature	<b>81,00 €</b>	8~12W
<b>A-CAP-M12F-M</b>	Metal cap for M12 female connector	<b>10,00 €</b>	56~60W
<b>A-CAP-M12F-M-PP</b>	Metal cap for M12 female push-pull connector	<b>6,00 €</b>	8~10W
<b>A-CAP-M12M-M</b>	Metal cap for M12 male connector	<b>10,00 €</b>	56~60W
<b>A-CAP-M30M-MIP67</b>	Metal cap for M30 male connector	<b>20,00 €</b>	10~12W
<b>A-CAP-NM-MIP67</b>	A-CAP-NM-MIP67	<b>14,00 €</b>	10~12W
<b>A-CAP-WPRJ45-MC</b>	Metal cap with chain for RJ45 connector	<b>26,00 €</b>	12~14W
<b>A-CRF-CTPSF-R2-50</b>	GPS Extension Cable TNC to SMA (female) adapter with 50 cm cable x 1	<b>66,00 €</b>	16~20W
<b>A-CRF-MHFQMAF-D1.13-14.2</b>	Digital Interface Mini card internal antenna with QMA connector x 1, locking washer x 1, O-ring x 1, nut x 1	<b>16,00 €</b>	16~20W
<b>A-CRF-MHFSF</b>	A-CRF-MHFSF	<b>17,00 €</b>	10~12W
<b>A-CRF-NMNM-LL4-300</b>	N-type (male) to N-type (male) LMR-400 Lite cable, 3 m	<b>112,00 €</b>	10~12W
<b>A-CRF-NMNM-LL4-600</b>	N-type (male) to N-type (male) LMR-400 Lite cable, 6 m	<b>166,00 €</b>	10~12W
<b>A-CRF-NMNM-LL4-900</b>	N-type (male) to N-type (male) LMR-400 Lite cable, 9 m	<b>262,00 €</b>	10~12W
<b>A-CRF-QMAMNM-R2-50</b>	QMA (male) to N-type (male) RG-316 cable, 0.5 m	<b>89,00 €</b>	12~16W
<b>A-CRF-RFRM-C2-300</b>	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 3 m	<b>36,00 €</b>	8~10W
<b>A-CRF-RFRM-C2-500</b>	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 5 m	<b>49,00 €</b>	8~10W
<b>A-CRF-RFRM-J1-60</b>	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, JSF-141 type, 0.6 m	<b>89,00 €</b>	12~14W
<b>A-CRF-RFRM-R4-150</b>	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, magnetic base, RG-174 type, 1.5 m	<b>45,00 €</b>	10~12W
<b>A-CRF-RMNM-L1-300</b>	N-type (male) to RP SMA (male) LMR-195 Lite cable, 3 m	<b>109,00 €</b>	10~12W
<b>A-CRF-RMNM-L1-600</b>	N-type (male) to RP SMA (male) LMR-195 Lite cable, 6 m	<b>161,00 €</b>	10~12W
<b>A-CRF-RMNM-L1-900</b>	N-type (male) to RP SMA (male) LMR-195 Lite cable, 9 m	<b>253,00 €</b>	10~12W
<b>A-CRF-SMSF-C2-300</b>	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 3 m	<b>36,00 €</b>	4~8W
<b>A-CRF-SMSF-C2-500</b>	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 5 m	<b>49,00 €</b>	8~10W
<b>A-CRF-SMSF-L1-300</b>	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, LMR195 type, 3 m	<b>59,00 €</b>	16~20W
<b>A-CRF-SMSF-R3-100</b>	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, RG-174 type, 1 m	<b>39,00 €</b>	10~12W
<b>ADP-DB9M-DB9M</b>	DB9 to DB9 male connector	<b>7,00 €</b>	12~14W
<b>ADP-RJ458P-DB9F</b>	DB9 female to RJ45 connector	<b>10,00 €</b>	12~14W
<b>ADP-RJ458P-DB9M</b>	RJ45 to DB9 male connector	<b>10,00 €</b>	12~14W
<b>ADP-Scm-STf-M</b>	Multi-mode male SC to female ST duplex adapter, grey color	<b>80,00 €</b>	4~8W
<b>ADP-Scm-STf-S</b>	Single-mode male SC to female ST duplex adapter, blue color	<b>80,00 €</b>	4~8W
<b>AIG-101-T</b>	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with -40 to 70°C operating temperature	<b>915,00 €</b>	4~8W
<b>AIG-101-T-AP</b>	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the Asia-Pacific region, -40 to 70°C operating temperature	<b>1.216,00 €</b>	12~16W
<b>AIG-101-T-EU</b>	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the EU region, -40 to 70°C operating temperature	<b>1.216,00 €</b>	12~16W
<b>AIG-101-T-US</b>	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the U.S. region, -40 to 70°C operating temperature	<b>1.216,00 €</b>	12~16W
<b>AIG-301-AP-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -20 to 70°C operating temperature	<b>1.804,00 €</b>	12~16W
<b>AIG-301-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -20 to 70°C operating temperature	<b>1.189,00 €</b>	4~8W
<b>AIG-301-EU-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -20 to 70°C operating temperature	<b>1.804,00 €</b>	12~16W
<b>AIG-301-T-AP-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	<b>1.941,00 €</b>	4~8W
<b>AIG-301-T-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	<b>1.308,00 €</b>	4~8W
<b>AIG-301-T-EU-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	<b>1.941,00 €</b>	4~8W

<b>AIG-301-T-US-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	<b>1.941,00 €</b>	4~8W
<b>AIG-301-US-AZU-LX</b>	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -20 to 70°C operating temperature	<b>1.804,00 €</b>	12~16W
<b>AIG-302-T-AP-AZU-LX</b>	AIG-302-T-AP-AZU-LX	<b>1.957,00 €</b>	
<b>AIG-302-T-AZU-LX</b>	AIG-302-T-AZU-LX	<b>1.324,00 €</b>	
<b>AIG-302-T-EU-AZU-LX</b>	AIG-302-T-EU-AZU-LX	<b>1.957,00 €</b>	
<b>AIG-302-T-US-AZU-LX</b>	AIG-302-T-US-AZU-LX	<b>1.957,00 €</b>	
<b>AIG-501-T-AP-AZU-LX</b>	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	<b>3.167,00 €</b>	8~12W
<b>AIG-501-T-AZU-LX</b>	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	<b>2.516,00 €</b>	8~12W
<b>AIG-501-T-EU-AZU-LX</b>	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	<b>3.167,00 €</b>	8~12W
<b>AIG-501-T-US-AZU-LX</b>	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	<b>3.167,00 €</b>	8~12W
<b>ANT-3G-SMA</b>	ANT-3G-SMA	<b>30,00 €</b>	
<b>ANT-5G-ASM-02</b>	2 dBi LTE/5G NR dipole antenna with SMA (male) connector	<b>27,00 €</b>	12~14W
<b>ANT-5G-ASM-03</b>	3 dBi GSM/UMTS/LTE/5G NR dipole antenna with SMA (male) connector	<b>25,00 €</b>	10~12W
<b>ANT-5G-ASM-07</b>	7 dBi, omnidirectional rubber-duck antenna for GSM, UMTS, LTE, and 5G NR applications	<b>52,00 €</b>	4~8W
<b>ANT-5G-OSM-03-1.5m</b>	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1.5 m cable	<b>43,00 €</b>	10~12W
<b>ANT-5G-OSM-03-1m</b>	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1 m cable	<b>41,00 €</b>	10~12W
<b>ANT-5G-OSM-03-2m</b>	3 dBi LTE/5G NR omnidirectional adhesive antenna, 2 m cable	<b>45,00 €</b>	10~12W
<b>ANT-GNSS-CSM-02-3m</b>	2 dBic GNSS antenna with SMA (male) connector, 3 m cable	<b>336,00 €</b>	10~12W
<b>ANT-GPS-CSM-04-0.2m BK</b>	1575 MHz active GPS/GLONASS 4 dBi antenna with SMA (male) connector and 20-cm cable	<b>50,00 €</b>	
<b>ANT-GPS-OSM-05-3M</b>	26 dBi at 1575.42 MHz, SMA (male), omnidirectional active GPS antenna, 3 m cable	<b>89,00 €</b>	12~16W
<b>ANT-LTE-ASM-02</b>	GPRS/EDGE/UMTS/HSPA/LTE, 2 dBi, omnidirectional rubber-duck antenna	<b>25,00 €</b>	10~12W
<b>ANT-LTE-ASM-04 BK</b>	704 to 960/1710 to 2620 MHz, LTE omnidirectional stick antenna, 4.5 dBi	<b>40,00 €</b>	4~8W
<b>ANT-LTE-ASM-05 BK</b>	704-960/1710-2620 MHz, LTE stick antenna, 5 dBi	<b>67,00 €</b>	4~8W
<b>ANT-LTE-OSM-03-3m BK</b>	700-2700 MHz, multiband antenna, specifically designed for 2G, 3G, and 4G applications, 3 m cable	<b>93,00 €</b>	8~10W
<b>ANT-LTE-OSM-06-3m BK MIMO</b>	Multiband antenna with screw-fastened mounting option for 700-2700/2400-2500/5150-5850 MHz frequencies	<b>212,00 €</b>	4~8W
<b>ANT-LTEUS-ASM-01</b>	GSM/GPRS/EDGE/UMTS/HSPA/LTE, 1 dBi, omnidirectional rubber-duck antenna	<b>30,00 €</b>	10~12W
<b>ANT-LTEUS-OSM-02</b>	698 to 960/1710 to 2700 MHz, 1/4 λ omnidirectional 1.5 dBi antenna with SMA (male) connector	<b>13,00 €</b>	
<b>ANT-WDB-ANM-0306</b>	3 dBi at 2.4 GHz or 6 dBi at 5 GHz, N-type (male), omnidirectional antenna	<b>43,00 €</b>	10~12W
<b>ANT-WDB-ANM-0502</b>	5 dBi at 2.4 GHz or 2 dBi at 5 GHz, N-type (male), omnidirectional antenna	<b>28,00 €</b>	10~12W
<b>ANT-WDB-ARM-02</b>	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male) omnidirectional rubber-duck antenna	<b>8,00 €</b>	10~12W
<b>ANT-WDB-ARM-0202</b>	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male), dual-band, omnidirectional antenna	<b>9,00 €</b>	10~12W
<b>ANT-WDB-ARM-0202 plus ADP</b>	2.4/5 GHz omni-directional antenna, 2/2 dBi, RP-SMA-type (male) connector	<b>13,00 €</b>	10~12W
<b>ANT-WDB-ARM-0405</b>	2.4/5 GHz 1/2 λ 4 to 5 dBi omnidirectional antenna with RP-SMA (female) connector	<b>13,00 €</b>	
<b>ANT-WDB-ONF-0709</b>	7 dBi at 2.4 GHz or 9 dBi at 5 GHz, N-type (female), dual-band, omnidirectional antenna	<b>178,00 €</b>	16~20W
<b>ANT-WDB-ONM-0707</b>	07 dBi at 2.4 GHz and 07 dBi at 5 GHz, N-type (male), dual-band omnidirectional antenna	<b>148,00 €</b>	12~14W
<b>ANT-WDB-PNF-1011</b>	10 dBi at 2.4 GHz and 11 dBi at 5 GHz, N-type (female), dual-band directional antenna	<b>389,00 €</b>	10~12W
<b>ANT-WSB5-PNF-16</b>	16 dBi at 5 GHz, N-type (female), single-band directional antenna	<b>317,00 €</b>	10~12W
<b>ANT-WSB-AHRM-05-1.5m</b>	5 dBi at 2.4 GHz, RP-SMA (male), omnidirectional/dipole antenna, 1.5 m cable	<b>25,00 €</b>	10~12W
<b>ANT-WSB-PNF-12-02</b>	12 dBi at 2.4 GHz, N-type (female), single-band directional antenna	<b>304,00 €</b>	10~12W
<b>A-PLG-WPM23-01-IP67</b>	Crimp type M23 connector, female 6-pin, IP67-rated	<b>136,00 €</b>	32~36W
<b>A-PLG-WPM30IP67-01</b>	Field-Installation for M30 plug	<b>73,00 €</b>	28~32W
<b>A-PLG-WPRJ</b>	Field-installation RJ-type plug	<b>10,00 €</b>	12~14W
<b>A-SA-NFNF-02</b>	0 to 6 GHz, N-type (female) to N-type (female) surge arrester	<b>82,00 €</b>	10~12W
<b>A-SA-NMNF-02</b>	0 to 6 GHz, N-type (male) to N-type (female) surge arrester	<b>82,00 €</b>	10~12W
<b>A-TRM-50-NM</b>	50-ohm termination resistor with N-type male connector	<b>36,00 €</b>	10~12W
<b>A-TRM-50-RM</b>	50-ohm terminating resistor with RP-SMA male connector	<b>38,00 €</b>	20~24W
<b>AVK-17</b>	Anti-vibration wiring kit	<b>16,00 €</b>	4~8W
<b>AWK-1131A-EU</b>	802.11a/b/g/n access point, EU band, 0 to 60°C operating temperature	<b>713,00 €</b>	2~4W
<b>AWK-1131A-EU-T</b>	802.11a/b/g/n access point, EU band, -40 to 75°C operating temperature	<b>805,00 €</b>	4~8W
<b>AWK-1131A-JP</b>	802.11a/b/g/n access point, JP band, 0 to 60°C operating temperature	<b>713,00 €</b>	4~8W
<b>AWK-1131A-JP-T</b>	802.11a/b/g/n access point, JP band, -40 to 75°C operating temperature	<b>805,00 €</b>	12~16W
<b>AWK-1131A-US</b>	802.11a/b/g/n access point, US band, 0 to 60°C operating temperature	<b>713,00 €</b>	2~4W
<b>AWK-1131A-US-T</b>	802.11a/b/g/n access point, US band, -40 to 75°C operating temperature	<b>805,00 €</b>	4~8W
<b>AWK-1137C-EU</b>	802.11a/b/g/n wireless client, EU band, 0 to 60°C operating temperature	<b>633,00 €</b>	2~4W
<b>AWK-1137C-EU-T</b>	802.11a/b/g/n wireless client, EU band, -40 to 75°C operating temperature	<b>708,00 €</b>	2~4W
<b>AWK-1137C-JP</b>	802.11a/b/g/n wireless client, JP band, 0 to 60°C operating temperature	<b>633,00 €</b>	12~16W
<b>AWK-1137C-JP-T</b>	802.11a/b/g/n wireless client, JP band, -40 to 75°C operating temperature	<b>708,00 €</b>	12~16W
<b>AWK-1137C-US</b>	802.11a/b/g/n wireless client, US band, 0 to 60°C operating temperature	<b>633,00 €</b>	2~4W
<b>AWK-1137C-US-T</b>	802.11a/b/g/n wireless client, US band, -40 to 75°C operating temperature	<b>708,00 €</b>	4~8W
<b>AWK-1151C-UN</b>	Industrial 802.11a/b/g/n/ac wireless client, IP30, universal band, 0 to 60°C operating temperature	<b>663,00 €</b>	4~8W
<b>AWK-1151C-UN-T</b>	Industrial 802.11a/b/g/n/ac wireless client, IP30, universal band, -40 to 75°C operating temperature	<b>756,00 €</b>	4~8W
<b>AWK-1151C-US</b>	Industrial 802.11a/b/g/n/ac wireless client, IP30, US band, 0 to 60°C operating temperature	<b>663,00 €</b>	4~8W
<b>AWK-1151C-US-T</b>	Industrial 802.11a/b/g/n/ac wireless client, IP30, US band, -40 to 75°C operating temperature	<b>756,00 €</b>	4~8W

<b>AWK-1161A-UN</b>	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	<b>845,00 €</b>	
<b>AWK-1161A-UN-T</b>	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	<b>973,00 €</b>	
<b>AWK-1161A-US</b>	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	<b>845,00 €</b>	
<b>AWK-1161A-US-T</b>	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	<b>973,00 €</b>	
<b>AWK-1161C-UN</b>	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	<b>736,00 €</b>	
<b>AWK-1161C-UN-T</b>	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	<b>845,00 €</b>	
<b>AWK-1161C-US</b>	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	<b>736,00 €</b>	
<b>AWK-1161C-US-T</b>	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	<b>845,00 €</b>	
<b>AWK-1165A-UN</b>	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	<b>947,00 €</b>	
<b>AWK-1165A-UN-T</b>	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	<b>1.120,00 €</b>	
<b>AWK-1165A-US</b>	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	<b>947,00 €</b>	
<b>AWK-1165A-US-T</b>	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	<b>1.120,00 €</b>	
<b>AWK-1165C-UN</b>	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	<b>832,00 €</b>	
<b>AWK-1165C-UN-T</b>	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	<b>998,00 €</b>	
<b>AWK-1165C-US</b>	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	<b>832,00 €</b>	
<b>AWK-1165C-US-T</b>	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	<b>998,00 €</b>	
<b>AWK-3131A-EU</b>	802.11a/b/g/n access point, EU band, -25 to 60°C operating temperature	<b>851,00 €</b>	2~4W
<b>AWK-3131A-EU-T</b>	802.11a/b/g/n access point, EU band, -40 to 75°C operating temperature	<b>1.000,00 €</b>	4~8W
<b>AWK-3131A-JP</b>	802.11a/b/g/n access point, JP band, -25 to 60°C operating temperature	<b>851,00 €</b>	4~8W
<b>AWK-3131A-JP-T</b>	802.11a/b/g/n access point, JP band, -40 to 75°C operating temperature	<b>1.000,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-EU</b>	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -25 to 60°C operating temperature	<b>2.026,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-EU-CT</b>	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -25 to 60°C operating temperature, conformal coating	<b>2.402,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-EU-CT-T</b>	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.611,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-EU-T</b>	802.11n rail onboard indoor single-radio AP/client, IP30, EU band, -40 to 75°C operating temperature	<b>2.176,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-JP</b>	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -25 to 60°C operating temperature	<b>2.026,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-JP-CT</b>	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -25 to 60°C operating temperature, conformal coating	<b>2.402,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-JP-CT-T</b>	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.611,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-JP-T</b>	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -40 to 75°C operating temperature	<b>2.176,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-US</b>	802.11n railway onboard indoor single radio access point/client, US band, IP30, -25 to 60°C operating temperature	<b>2.026,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-US-CT</b>	802.11n railway onboard indoor single radio access point/client, US band, IP30, -25 to 60°C operating temperature, conformal coating	<b>2.402,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-US-CT-T</b>	802.11n railway onboard indoor single radio access point/client, US band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.611,00 €</b>	12~16W
<b>AWK-3131A-M12-RCC-US-T</b>	802.11n rail onboard indoor single-radio AP/client, IP30, US band, -40 to 75°C operating temperature	<b>2.176,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-EU-CT-T</b>	802.11n railway onboard indoor single radio access point/client, M12, EU band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.225,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-EU-T</b>	802.11n railway onboard indoor single radio access point/client, M12, EU band, IP30, -40 to 75°C operating temperature	<b>1.924,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-JP-CT-T</b>	802.11n railway onboard indoor single radio access point/client, M12, JP band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.225,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-JP-T</b>	802.11n railway onboard indoor single radio access point/client, M12, JP band, IP30, -40 to 75°C operating temperature	<b>1.924,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-US-CT-T</b>	802.11n railway onboard indoor single radio access point/client, M12, US band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.225,00 €</b>	12~16W
<b>AWK-3131A-M12-RTG-US-T</b>	802.11n railway onboard indoor single radio access point/client, M12, US band, IP30, -40 to 75°C operating temperature	<b>1.924,00 €</b>	12~16W
<b>AWK-3131A-SSC-RTG-EU-CT-T</b>	802.11n railway trackside indoor single radio access point/client, SC, EU band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.506,00 €</b>	12~16W
<b>AWK-3131A-SSC-RTG-EU-T</b>	802.11n railway trackside indoor single radio access point/client, SC, EU band, IP30, -40 to 75°C operating temperature	<b>2.196,00 €</b>	12~16W

<b>AWK-3131A-SSC-RTG-JP-CT-T</b>	802.11n railway trackside indoor single radio access point/client, SC, JP band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.506,00 €</b>	12~16W
<b>AWK-3131A-SSC-RTG-JP-T</b>	802.11n railway trackside indoor single radio access point/client, SC, JP band, IP30, -40 to 75°C operating temperature	<b>2.196,00 €</b>	12~16W
<b>AWK-3131A-SSC-RTG-US-CT-T</b>	802.11n railway trackside indoor single radio access point/client, SC, US band, IP30, -40 to 75°C operating temperature, conformal coating	<b>2.506,00 €</b>	12~16W
<b>AWK-3131A-SSC-RTG-US-T</b>	802.11n railway trackside indoor single radio access point/client, SC, US band, IP30, -40 to 75°C operating temperature	<b>2.196,00 €</b>	12~16W
<b>AWK-3131A-US</b>	802.11a/b/g/n access point, US band, -25 to 60°C operating temperature	<b>851,00 €</b>	2~4W
<b>AWK-3131A-US-T</b>	802.11a/b/g/n access point, US band, -40 to 75°C operating temperature	<b>1.000,00 €</b>	2~4W
<b>AWK-3251A-M12-RCC-UN</b>	Railway Wi-Fi 5 AP/client, universal band, IP30, -25 to 60°C operating temperature	<b>2.387,00 €</b>	12~16W
<b>AWK-3251A-M12-RCC-UN-CT-T</b>	Railway Wi-Fi 5 AP/client, universal band, IP30, -40 to 75°C operating temperature, conformal coating	<b>3.049,00 €</b>	12~16W
<b>AWK-3251A-M12-RCC-UN-T</b>	Railway Wi-Fi 5 AP/client, universal band, IP30, -40 to 75°C operating temperature	<b>2.585,00 €</b>	12~16W
<b>AWK-3251A-M12-RCC-US</b>	Railway Wi-Fi 5 AP/client, US band, IP30, -25 to 60°C operating temperature	<b>2.387,00 €</b>	12~16W
<b>AWK-3251A-M12-RCC-US-CT-T</b>	Railway Wi-Fi 5 AP/client, US band, IP30, -40 to 75°C operating temperature, conformal coating	<b>3.049,00 €</b>	12~16W
<b>AWK-3251A-M12-RCC-US-T</b>	Railway Wi-Fi 5 AP/client, US band, IP30, -40 to 75°C operating temperature	<b>2.585,00 €</b>	12~16W
<b>AWK-3252A-UN</b>	802.11a/b/g/n/ac access point, UN band, -25 to 60°C operating temperature	<b>1.024,00 €</b>	4~8W
<b>AWK-3252A-UN-T</b>	802.11a/b/g/n/ac access point, UN band, -40 to 75°C operating temperature	<b>1.205,00 €</b>	4~8W
<b>AWK-3252A-US</b>	802.11a/b/g/n/ac access point, US band, -25 to 60°C operating temperature	<b>1.024,00 €</b>	4~8W
<b>AWK-3252A-US-T</b>	802.11a/b/g/n/ac access point, US band, -40 to 75°C operating temperature	<b>1.205,00 €</b>	4~8W
<b>AWK-4131A-EU-T</b>	802.11a/b/g/n access point, EU band, IP68, -40 to 75°C operating temperature	<b>1.807,00 €</b>	2~4W
<b>AWK-4131A-JP-T</b>	802.11a/b/g/n access point, JP band, IP68, -40 to 75°C operating temperature	<b>1.807,00 €</b>	4~8W
<b>AWK-4131A-US-T</b>	802.11a/b/g/n access point, US band, IP68, -40 to 75°C operating temperature	<b>1.807,00 €</b>	2~4W
<b>AWK-4252A-UN-T</b>	802.11a/b/g/n/ac access point, UN band, IP68, -40 to 75°C operating temperature	<b>2.181,00 €</b>	4~8W
<b>AWK-4252A-US-T</b>	802.11a/b/g/n/ac access point, US band, IP68, -40 to 75°C operating temperature	<b>2.181,00 €</b>	4~8W
<b>BKT-DB44L</b>	Cannot find any data	<b>9,00 €</b>	8~10W
<b>BKT-PWR</b>	Chassis converter rackmount kit accessory package, 2 L-shaped metal plates, 8 screws (FMS M4 x 6 mm)	<b>41,00 €</b>	4~8W
<b>BXP-A100-E2-2L3C-T</b>	Box computer with Intel Atom® x6211E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.510,00 €</b>	4~8W
<b>BXP-A100-E2-8C-T</b>	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.464,00 €</b>	4~8W
<b>BXP-A100-E2-8L-T</b>	Box computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.963,00 €</b>	4~8W
<b>BXP-A100-E2-T</b>	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>1.966,00 €</b>	4~8W
<b>BXP-A100-E2-T-Win10</b>	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>2.797,00 €</b>	4~8W
<b>BXP-A100-E4-2L3C-T</b>	Box computer with Intel Atom® x6425E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.600,00 €</b>	4~8W
<b>BXP-A100-E4-8C-T</b>	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.570,00 €</b>	4~8W
<b>BXP-A100-E4-8L-T</b>	Box computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.978,00 €</b>	4~8W
<b>BXP-A100-E4-T</b>	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.207,00 €</b>	4~8W
<b>BXP-A100-E4-T-Win10</b>	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>2.857,00 €</b>	4~8W
<b>BXP-C100-C1-2L3C-T</b>	Box computer with Intel® Celeron® 6305E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.555,00 €</b>	4~8W
<b>BXP-C100-C1-8C-T</b>	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.525,00 €</b>	4~8W
<b>BXP-C100-C1-8L-T</b>	Box computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.888,00 €</b>	4~8W
<b>BXP-C100-C1-T</b>	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.253,00 €</b>	4~8W



<b>BXP-C100-C1-T-Win10</b>	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>3.296,00 €</b>	4~8W
<b>BXP-C100-C5-2L3C-T</b>	Box computer with Intel® Core® i5-1145G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.795,00 €</b>	4~8W
<b>BXP-C100-C5-8C-T</b>	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.825,00 €</b>	4~8W
<b>BXP-C100-C5-8L-T</b>	Box computer with Intel® Core® i5-1145G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.157,00 €</b>	4~8W
<b>BXP-C100-C5-T</b>	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.371,00 €</b>	4~8W
<b>BXP-C100-C5-T-Win10</b>	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>4.460,00 €</b>	4~8W
<b>BXP-C100-C7-2L3C-T</b>	Box computer with Intel® Core® i7-1185G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.157,00 €</b>	4~8W
<b>BXP-C100-C7-8C-T</b>	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.127,00 €</b>	4~8W
<b>BXP-C100-C7-8L-T</b>	Box computer with Intel® Core® i7-1185G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.550,00 €</b>	4~8W
<b>BXP-C100-C7-T</b>	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.885,00 €</b>	4~8W
<b>BXP-C100-C7-T-Win10</b>	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>5.140,00 €</b>	4~8W
<b>CA-104</b>	PC/104 bus, 4-port RS-232 module, 0 to 55°C operating temperature	<b>160,00 €</b>	8~12W
<b>CA-104-T</b>	PC/104 bus, 4-port RS-232 module, -40 to 85°C operating temperature	<b>217,00 €</b>	8~12W
<b>CA-108</b>	PC/104 bus, 8-port RS-232 module, 0 to 55°C operating temperature	<b>266,00 €</b>	4~8W
<b>CA-108-T</b>	PC/104 bus, 8-port RS-232 module, -40 to 85°C operating temperature	<b>360,00 €</b>	8~12W
<b>CA-114</b>	PC/104 bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	<b>266,00 €</b>	4~8W
<b>CA-114-T</b>	PC/104 bus with 4-port RS-232/422/485 module, -40 to 85°C operating temperature	<b>360,00 €</b>	8~12W
<b>CA-132</b>	PC/104 bus, 2-port RS-422/485 module, 0 to 55°C operating temperature	<b>179,00 €</b>	8~12W
<b>CA-132I</b>	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation	<b>266,00 €</b>	8~12W
<b>CA-132I-T</b>	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	<b>360,00 €</b>	8~12W
<b>CA-132-T</b>	PC/104 bus, 2-port RS-422/485 module, -40 to 85°C operating temperature	<b>233,00 €</b>	8~12W
<b>CA-134I</b>	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	<b>483,00 €</b>	8~12W
<b>CA-134I-T</b>	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	<b>638,00 €</b>	8~12W
<b>CB-108</b>	PC/104-Plus bus, 8-port RS-232 module, 0 to 55°C operating temperature	<b>360,00 €</b>	8~12W
<b>CB-108-T</b>	PC/104-Plus bus, 8-port RS-232 module, -40 to 85°C operating temperature	<b>457,00 €</b>	8~12W
<b>CB-114</b>	PC/104-Plus bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	<b>389,00 €</b>	8~12W
<b>CB-114-T</b>	PC/104-Plus bus, 4-port RS-232/422/485 module, -40 to 85°C operating temperature	<b>497,00 €</b>	8~12W
<b>CB-134I</b>	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	<b>638,00 €</b>	8~12W
<b>CB-134I-T</b>	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	<b>816,00 €</b>	8~12W
<b>CB-602I w/o Cable</b>	2-port CAN bus PC/104-Plus module, with isolation, 0 to 55°C operating temperature	<b>521,00 €</b>	8~12W
<b>CB-602I-T w/o Cable</b>	2-port CAN bus PC/104-Plus module, with isolation, -40 to 85°C operating temperature	<b>598,00 €</b>	8~12W
<b>CBL-F37M37-1M</b>	DB37 female to 4 x DB37 male serial cable, 1 m	<b>27,00 €</b>	
<b>CBL-F9DPF1x4-BK-100</b>	Console cable with 4-pin connector, 1 m	<b>6,00 €</b>	12~14W
<b>CBL-F9M9-150</b>	DB9 female to DB9 male serial cable, 1.5 m	<b>20,00 €</b>	12~14W
<b>CBL-F9M9-20</b>	DB9 female to DB9 male serial cable, 20 cm	<b>14,00 €</b>	12~14W
<b>CBL-HSF2x10-15</b>	20-pin female to 20-pin female serial cable, 15 cm	<b>13,00 €</b>	8~10W
<b>CBL-M12(FF4P)OPEN-BK-100-IP68</b>	A-coded female M12-to-4-pin open cable, black, IP68-rated, 1 m	<b>74,00 €</b>	16~20W
<b>CBL-M12(FF5P)OPEN-100-IP67</b>	A-coded female M12-to-5-pin open wire cable, black, IP67-rated, 1 m	<b>29,00 €</b>	10~12W
<b>CBL-M12(FF5P)OPEN-200-IP67</b>	M12 IP67 5 pin to Open 200m cable	<b>39,00 €</b>	16~20W
<b>CBL-M12BMM5PF9-BK-150-IP68</b>	B-coded male M12-to-5-pin DB9 console cable, black, IP68-rated, 1.5 m	<b>82,00 €</b>	10~12W
<b>CBL-M12D(MM4P)/RJ45-100-IP67</b>	D-coded male M12-to-RJ45 Ethernet cable, black, IP67-rated, 1 m	<b>29,00 €</b>	10~12W
<b>CBL-M12DFF4PRJ45-BK-10-IP67</b>	M12 D-coded IP67 to RJ45 10m cable	<b>54,00 €</b>	10~12W
<b>CBL-M12DMM4PM12DMM4P-BK-100-IP67</b>	D-coded male M12-to-D-coded female M12 Ethernet cable, black, IP67-rated, 1 m	<b>116,00 €</b>	10~12W
<b>CBL-M12FF4POPEN-150-IP67</b>	M12-Open power cable, 4-pin A-coded female connector, IP67, 1.5 m	<b>78,00 €</b>	24~28W

<b>CBL-M12FF4POPEN-300-IP67</b>	M12-Open power cable, 4-pin A-coded female connector, IP67, 3 m	<b>95,00 €</b>	24~28W
<b>CBL-M12FF5PF9-BK-150-IP67</b>	A-coded female M12-to-5-pin DB9 console cable, black, IP67-rated, 1.5 m	<b>69,00 €</b>	10~12W
<b>CBL-M12KFF5POPEN-O-150-IP67</b>	K-coded female M12-to-5-pin open wire power cable, orange, IP67-rated, 1.5 m	<b>360,00 €</b>	24~28W
<b>CBL-M12MM8PRJ45-BK-100-IP67</b>	M12 IP67 to RJ45 100m cable	<b>60,00 €</b>	16~20W
<b>CBL-M12XMM8PRJ45-BK-100-IP67</b>	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 1 m	<b>386,00 €</b>	24~28W
<b>CBL-M12XMM8PRJ45-BK-200-IP67</b>	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 2 m	<b>212,00 €</b>	24~28W
<b>CBL-M12XMM8PRJ45-Y-200-IP67</b>	X-coded male M12-to-RJ45 Ethernet cable, yellow, IP67-rated, 2 m	<b>208,00 €</b>	16~20W
<b>CBL-M12XMM8P-Y-100-IP67</b>	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 1 m	<b>327,00 €</b>	56~60W
<b>CBL-M12XMM8P-Y-300-IP67</b>	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 3 m	<b>367,00 €</b>	56~60W
<b>CBL-M23(FF6P)/OPEN-BK-100 IP67</b>	M23 female M23-to-6-pin open wire power cable, black, IP67-rated, 1 m	<b>153,00 €</b>	4~8W
<b>CBL-M25M9x2-50</b>	DB25 male to 2 x DB9 male serial cable, 50 cm	<b>14,00 €</b>	16~20W
<b>CBL-M44M25x4-50</b>	DB44 male to 4 DB25 male serial cable, 50 cm	<b>27,00 €</b>	16~20W
<b>CBL-M44M9x4-50</b>	DB44 male to DB9 male serial cable, 50 cm	<b>23,00 €</b>	16~20W
<b>CBL-M44M9x4-50 (POS)</b>	DB44 male to 4 x DB9 male serial cable, 50 cm	<b>23,00 €</b>	16~20W
<b>CBL-M62F62-150</b>	DB62 male to DB62 female serial cable, 1.5 m	<b>49,00 €</b>	12~14W
<b>CBL-M62M25x8-100</b>	DB62 male to 8 x DB25 male serial cable, 1 m	<b>53,00 €</b>	16~20W
<b>CBL-M62M62-150</b>	DB62 male to DB62 male serial cable, 1.5 m	<b>46,00 €</b>	16~20W
<b>CBL-M62M9x8-100</b>	DB62 male to 8 x DB9 male serial cable, 1 m	<b>46,00 €</b>	16~20W
<b>CBL-M68F62-150</b>	DB68 male to DB62 female serial cable, 1.5 m	<b>59,00 €</b>	16~20W
<b>CBL-M68M25x8-100</b>	SCSI VHDCI 68 to 8 x DB25 male serial cable, 1 m	<b>84,00 €</b>	16~20W
<b>CBL-M68M62-150</b>	DB68 male to DB62 male serial cable, 1.5 m	<b>78,00 €</b>	16~20W
<b>CBL-M68M9x8-100</b>	SCSI VHDCI 68 to 8 x DB9 male serial cable, 1 m	<b>81,00 €</b>	16~20W
<b>CBL-M78M25x8-100</b>	DB78 male to 8 x DB25 male serial cable, 1 m	<b>90,00 €</b>	16~20W
<b>CBL-M78M9x8-100</b>	DB78 male to 8 x DB9 male serial cable, 1 m	<b>87,00 €</b>	16~20W
<b>CBL-M9HSF1x10H-15-01</b>	10-pin female to 1 DB9 male serial cable, 15 cm	<b>11,00 €</b>	10~12W
<b>CBL-M9HSF1x10H-15-02</b>	10-pin female to 1 DB9 male serial cable, 15 cm	<b>11,00 €</b>	10~12W
<b>CBL-M9x2HSF2x10H-15</b>	20-pin female to 2 DB9 male serial cables, 15 cm	<b>17,00 €</b>	10~12W
<b>CBL-PJ21NOPEN-BK-30 w/Nut</b>	CBL-PJ21NOPEN-BK-30 w/Nut	<b>10,00 €</b>	10~12W
<b>CBL-PJTB-10</b>	Non-locking barrel plug to bare-wire cable	<b>6,00 €</b>	4~8W
<b>CBL-RJ458P-100</b>	8-pin RJ45 CAT5 Ethernet cable, 1 m	<b>7,00 €</b>	12~14W
<b>CBL-RJ45F25-150</b>	8-pin RJ45 to DB25 female serial cable, 1.5 m	<b>8,00 €</b>	12~14W
<b>CBL-RJ45F9-150</b>	8-pin RJ45 to DB9 female serial cable, 1.5m	<b>13,00 €</b>	12~14W
<b>CBL-RJ45M25-150</b>	8-pin RJ45 to DB25 male serial cable, 1.5m	<b>8,00 €</b>	16~20W
<b>CBL-RJ45M9-150</b>	8-pin RJ45 to DB9 male serial cable, 1.5m	<b>13,00 €</b>	12~14W
<b>CBL-RJ45SF25-150</b>	8-pin RJ45 to DB25 female serial cable with shielding, 1.5m	<b>14,00 €</b>	12~14W
<b>CBL-RJ45SF9-150</b>	8-pin RJ45 to DB9 female serial cable with shielding, 1.5m	<b>10,00 €</b>	12~14W
<b>CBL-RJ45SM25-150</b>	8-pin RJ45 to DB25 male serial cable with shielding, 1.5m	<b>10,00 €</b>	16~20W
<b>CBL-RJ45SM9-150</b>	8-pin RJ45 to DB9 male serial cable with shielding, 1.5m	<b>10,00 €</b>	12~14W
<b>CBL-USB3-BA-BK-120</b>	USB 3.2 Gen 1 cable, type A-to-type B, 1.2 m	<b>19,00 €</b>	10~12W
<b>CBL-USB3-BA-G-028</b>	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 0.28 m	<b>29,00 €</b>	10~12W
<b>CBL-USB3-BA-G-120</b>	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 1.2 m	<b>27,00 €</b>	10~12W
<b>CBL-USB A/B-100</b>	USB 2.0 cable, type A-to-type B, 1 m	<b>5,00 €</b>	16~20W
<b>CBL-USBAMM12BMM5P-BK-120-IP68</b>	120cm B-coded USB-to-5-pin cable with IP68-rated, 5-pin male M12 connector	<b>87,00 €</b>	20~24W
<b>CBL-USBAP-50</b>	USB A male/2.1 mm DC Jack cable, 50 cm	<b>5,00 €</b>	16~20W
<b>CCG-1510-T</b>	Industrial private 5G cellular gateway, n1, n3, n28, n41, n48, n77, n78 bands, IP30, -40 to 70°C operating temperature	<b>1.727,00 €</b>	12~16W
<b>CM-600-2MSC/2TX</b>	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	<b>667,00 €</b>	4~8W
<b>CM-600-2SSC/2TX</b>	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	<b>1.523,00 €</b>	4~8W
<b>CM-600-3MSC/1TX</b>	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	<b>836,00 €</b>	8~12W
<b>CM-600-3SSC/1TX</b>	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	<b>1.897,00 €</b>	4~8W
<b>CM-600-4MSC</b>	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	<b>1.014,00 €</b>	4~8W
<b>CM-600-4MST</b>	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, ST connectors, -40 to 75°C operating temperature	<b>1.014,00 €</b>	4~8W
<b>CM-600-4SSC</b>	Fast Ethernet interface module with 4 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	<b>2.433,00 €</b>	4~8W
<b>CM-600-4TX</b>	Fast Ethernet interface module with 4 10/100BaseT(X) ports, RJ45 connectors, -40 to 75°C operating temperature	<b>314,00 €</b>	4~8W
<b>CN20030</b>	10-pin RJ45 to DB25 female serial cable	<b>10,00 €</b>	16~20W



<b>CN20040</b>	10-pin RJ45 to DB25 male serial cable	<b>10,00 €</b>	16~20W
<b>CN20060</b>	10-pin RJ45 to DB9 male serial cable	<b>10,00 €</b>	16~20W
<b>CN20070</b>	10-pin RJ45 to DB9 female serial cable	<b>8,00 €</b>	16~20W
<b>CN2510-16</b>	16-port RS-232 Async Server, 100 to 240 VAC power input	<b>1.463,00 €</b>	4~8W
<b>CN2510-16-48V</b>	16-port RS-232 Async Server, +/-48 VDC power input	<b>1.550,00 €</b>	8~12W
<b>CN2510-8</b>	8-port RS-232 Async Server, 100 to 240 VAC power input	<b>1.311,00 €</b>	8~12W
<b>CN2510-8-48V</b>	8-port RS-232 Async Server, +/-48 VDC power input	<b>1.404,00 €</b>	8~12W
<b>CN2610-16</b>	Dual-LAN terminal server with 16 RS-232 ports	<b>2.059,00 €</b>	8~12W
<b>CN2610-16-2AC</b>	Dual-LAN, dual-AC-power terminal server with 16 RS-232 ports	<b>2.207,00 €</b>	8~12W
<b>CN2610-8</b>	Dual-LAN terminal server with 8 RS-232 ports	<b>1.625,00 €</b>	8~12W
<b>CN2610-8-2AC</b>	Dual-LAN, dual-AC-power terminal server with 8 RS-232 ports	<b>1.773,00 €</b>	8~12W
<b>CN2650-16</b>	Dual-LAN terminal server with 16 RS-232/422/485 ports	<b>2.148,00 €</b>	4~8W
<b>CN2650-16-2AC</b>	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports	<b>2.297,00 €</b>	4~8W
<b>CN2650-16-2AC-T</b>	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, -40 to 75°C operating temperature	<b>3.131,00 €</b>	4~8W
<b>CN2650-8</b>	Dual-LAN terminal server with 8 RS-232/422/485 ports	<b>1.658,00 €</b>	4~8W
<b>CN2650-8-2AC</b>	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports	<b>1.807,00 €</b>	4~8W
<b>CN2650-8-2AC-T</b>	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, -40 to 75°C operating temperature	<b>2.459,00 €</b>	8~12W
<b>CN2650I-16</b>	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	<b>2.972,00 €</b>	4~8W
<b>CN2650I-16-2AC</b>	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	<b>3.116,00 €</b>	4~8W
<b>CN2650I-16-HV-T</b>	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>3.579,00 €</b>	8~12W
<b>CN2650I-8</b>	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	<b>2.074,00 €</b>	4~8W
<b>CN2650I-8-2AC</b>	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	<b>2.222,00 €</b>	4~8W
<b>CN2650I-8-HV-T</b>	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.584,00 €</b>	8~12W
<b>CP-102E</b>	2-port RS-232 PCI Express x1 serial board	<b>129,00 €</b>	2~4W
<b>CP-102EL-DB9M</b>	2-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	<b>139,00 €</b>	2~4W
<b>CP-102N-I-T</b>	2-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	<b>325,00 €</b>	8~12W
<b>CP-102N-T</b>	2-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	<b>179,00 €</b>	8~12W
<b>CP-102U</b>	2-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	<b>80,00 €</b>	2~4W
<b>CP-102UL-DB9M</b>	2-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>90,00 €</b>	4~8W
<b>CP-102UL-T</b>	2-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	<b>129,00 €</b>	8~12W
<b>CP-102U-T</b>	2-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	<b>111,00 €</b>	8~12W
<b>CP-104EL-A w/o Cable</b>	4-port RS-232 low-profile PCI Express x1 serial board, without cable	<b>236,00 €</b>	2~4W
<b>CP-104EL-A-DB25M</b>	4-port RS-232 low-profile PCI Express x1 serial board (includes DB25 male cable)	<b>248,00 €</b>	2~4W
<b>CP-104EL-A-DB9M</b>	4-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	<b>248,00 €</b>	2~4W
<b>CP-104JU</b>	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, 0 to 55°C operating temperature	<b>170,00 €</b>	8~12W
<b>CP-104JU-T</b>	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, -40 to 85°C operating temperature	<b>190,00 €</b>	8~12W
<b>CP-104N-I-T</b>	4-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	<b>580,00 €</b>	8~12W
<b>CP-104N-T</b>	4-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	<b>320,00 €</b>	8~12W
<b>CP-104UL w/o Cable</b>	4-port RS-232 low-profile Universal PCI serial board, without cable	<b>139,00 €</b>	2~4W
<b>CP-104UL-DB25M</b>	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	<b>150,00 €</b>	2~4W
<b>CP-104UL-DB9M</b>	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>150,00 €</b>	2~4W
<b>CP-104UL-T</b>	4-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	<b>207,00 €</b>	8~12W
<b>CP-112UL-DB9M</b>	2-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>170,00 €</b>	4~8W
<b>CP-112UL-I-DB9M</b>	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	<b>298,00 €</b>	4~8W
<b>CP-112UL-I-T</b>	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, -40 to 85°C operating temperature	<b>380,00 €</b>	8~12W
<b>CP-112UL-T</b>	2-port RS-232/422/485 low-profile Universal PCI board, -40 to 85°C operating temperature	<b>254,00 €</b>	8~12W
<b>CP-114EL</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board	<b>285,00 €</b>	2~4W
<b>CP-114EL-DB25M</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB25 male cable)	<b>298,00 €</b>	2~4W
<b>CP-114EL-DB9M</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	<b>298,00 €</b>	2~4W
<b>CP-114EL-I</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation	<b>584,00 €</b>	2~4W
<b>CP-114EL-I-DB25M</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB25 male cable)	<b>598,00 €</b>	2~4W
<b>CP-114EL-I-DB9M</b>	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	<b>598,00 €</b>	2~4W
<b>CP-114N-T</b>	4-port RS-232/422/485 Mini PCI Express serial board, -40°C to 85 operating temperature	<b>401,00 €</b>	8~12W
<b>CP-114UL w/o Cable</b>	4-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature	<b>277,00 €</b>	4~8W
<b>CP-114UL-DB25M</b>	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	<b>294,00 €</b>	4~8W
<b>CP-114UL-DB9M</b>	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>294,00 €</b>	4~8W

<b>CP-114UL-I</b>	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	<b>613,00 €</b>	4~8W
<b>CP-114UL-I-DB25M</b>	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB25 male cable)	<b>618,00 €</b>	4~8W
<b>CP-114UL-I-DB9M</b>	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	<b>618,00 €</b>	4~8W
<b>CP-114UL-I-T</b>	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	<b>770,00 €</b>	8~12W
<b>CP-114UL-T</b>	4-port RS-232/422/485 low-profile Universal PCI serial board, -40 to 85°C operating temperature	<b>308,00 €</b>	8~12W
<b>CP-116E-A w/o cable</b>	16-port RS-232/422/485 PCI Express board with 4 kV surge protection, 0 to 55°C operating temperature	<b>1.091,00 €</b>	2~4W
<b>CP-118E-A-I w/o cable</b>	8-port RS-232/422/485 PCI Express x1 serial board with surge protection and electrical isolation	<b>1.195,00 €</b>	4~8W
<b>CP-118EL-A w/o Cable</b>	8-port RS-232/422/485 low-profile PCI Express x1 serial board	<b>556,00 €</b>	2~4W
<b>CP-118U</b>	8-port RS-232/422/485 Universal PCI serial board, 0 to 55°C operating temperature	<b>478,00 €</b>	2~4W
<b>CP-118U-I</b>	8-port RS-232/422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	<b>1.105,00 €</b>	4~8W
<b>CP-118U-I-T</b>	8-port RS-232/422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	<b>1.149,00 €</b>	8~12W
<b>CP-118U-T</b>	8-port RS-232/422/485 Universal PCI serial board, -40 to 85°C operating temperature	<b>507,00 €</b>	8~12W
<b>CP-132EL-DB9M</b>	2-port RS-422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	<b>170,00 €</b>	2~4W
<b>CP-132EL-I-DB9M</b>	2-port RS-422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	<b>302,00 €</b>	2~4W
<b>CP-132N-I-T</b>	2-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	<b>338,00 €</b>	8~12W
<b>CP-132N-T</b>	2-port RS-422/485 Mini PCI Express serial board, -40 to 85°C operating temperature	<b>184,00 €</b>	8~12W
<b>CP-132UL-DB9M</b>	2-port RS-422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>135,00 €</b>	2~4W
<b>CP-132UL-I-DB9M</b>	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	<b>326,00 €</b>	2~4W
<b>CP-132UL-I-T</b>	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, -40°C to 85 operating temperature	<b>300,00 €</b>	8~12W
<b>CP-132UL-T</b>	2-port RS-422/485 low-profile Universal PCI serial board, -40°C to 85 operating temperature	<b>170,00 €</b>	8~12W
<b>CP-134EL-A-I w/o cable</b>	4-port RS-422/485 low-profile PCI Express x1 serial board with surge protection and electrical isolation	<b>570,00 €</b>	2~4W
<b>CP-134EL-A-I-DB25M</b>	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	<b>584,00 €</b>	2~4W
<b>CP-134EL-A-I-DB9M</b>	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	<b>584,00 €</b>	2~4W
<b>CP-134N-I-T</b>	4-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	<b>676,00 €</b>	8~12W
<b>CP-134U w/o Cable</b>	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	<b>268,00 €</b>	4~8W
<b>CP-134U-DB25M</b>	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	<b>289,00 €</b>	4~8W
<b>CP-134U-DB9M</b>	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	<b>289,00 €</b>	4~8W
<b>CP-134U-I w/o Cable</b>	4-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	<b>618,00 €</b>	4~8W
<b>CP-134U-I-DB25M</b>	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	<b>644,00 €</b>	4~8W
<b>CP-134U-I-DB9M</b>	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	<b>644,00 €</b>	4~8W
<b>CP-134U-I-T</b>	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	<b>630,00 €</b>	8~12W
<b>CP-134U-T</b>	4-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	<b>282,00 €</b>	8~12W
<b>CP-138E-A-I w/o cable</b>	8-port RS-422/485 PCI Express board with 4 kV surge protection, 2 kV electrical isolation, 0 to 55°C operating temperature	<b>1.033,00 €</b>	4~8W
<b>CP-138U</b>	8-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	<b>451,00 €</b>	4~8W
<b>CP-138U-I</b>	8-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	<b>895,00 €</b>	8~12W
<b>CP-138U-I-T</b>	8-port RS-422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	<b>956,00 €</b>	8~12W
<b>CP-138U-T</b>	8-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	<b>462,00 €</b>	8~12W
<b>CP-168EL-A w/o Cable</b>	8-port RS-232 low-profile PCI Express x1 serial board	<b>302,00 €</b>	2~4W
<b>CP-168U</b>	8-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	<b>222,00 €</b>	2~4W
<b>CP-168U-T</b>	8-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	<b>282,00 €</b>	8~12W
<b>CP-602E-I w/o Cable</b>	2-port CAN bus PCI Express board with 2 kV electrical isolation, 0 to 55°C operating temperature	<b>543,00 €</b>	4~8W
<b>CP-602E-I-T w/o Cable</b>	2-port CAN bus PCI Express board with 2 kV electrical isolation, -40 to 85°C operating temperature	<b>630,00 €</b>	4~8W
<b>CP-602U-I w/o Cable</b>	2-port CAN bus Universal PCI board with 2 kV electrical isolation, 0 to 55°C operating temperature	<b>483,00 €</b>	8~12W
<b>CP-602U-I-T w/o Cable</b>	2-port CAN bus Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	<b>561,00 €</b>	8~12W
<b>CRF-MHF/SMA(M)-14.2</b>	CRF-MHF/SMA(M)-14.2	<b>10,00 €</b>	10~12W
<b>CRF-SMA(M)/N(M)-300</b>	N-type (male) to SMA (male) CFD200 cable, 3 m	<b>57,00 €</b>	10~12W
<b>CSM-200-1213</b>	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode ST connector	<b>323,00 €</b>	4~8W
<b>CSM-200-1214</b>	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode SC connector	<b>323,00 €</b>	4~8W
<b>CSM-200-1218</b>	10/100BaseT(X) to 100BaseFX slide-in module media converter, single-mode SC connector	<b>454,00 €</b>	2~4W
<b>CSM-400-1213</b>	10/100BaseT(X)-to-100BaseFX slide-in management module converter with ST connector, multi-mode, 0 to 55°C operating temperature	<b>365,00 €</b>	8~12W
<b>CSM-400-1213-T</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode ST connector, -40 to 75°C operating temperature	<b>454,00 €</b>	8~12W

<b>CSM-400-1214</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -20 to 55°C operating temperature	<b>365,00 €</b>	8~12W
<b>CSM-400-1214-T</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -40 to 75°C operating temperature	<b>454,00 €</b>	8~12W
<b>CSM-400-1218</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -20 to 55°C operating temperature	<b>483,00 €</b>	4~8W
<b>CSM-400-1218-T</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -40 to 75°C operating temperature	<b>598,00 €</b>	8~12W
<b>CSM-400-1224</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -20 to 55°C operating temperature	<b>483,00 €</b>	8~12W
<b>CSM-400-1224-T</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -40 to 75°C operating temperature	<b>598,00 €</b>	8~12W
<b>CSM-400-1225</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -20 to 55°C operating temperature	<b>483,00 €</b>	8~12W
<b>CSM-400-1225-T</b>	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -40 to 75°C operating temperature	<b>598,00 €</b>	8~12W
<b>CSM-G200-1221</b>	10/100/1000BaseT(X)-to-100/1000BaseSFP slide-in media converter module	<b>362,00 €</b>	4~8W
<b>DA-680-I-16-WL3-H</b>	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operating temperature	<b>4.044,00 €</b>	12~16W
<b>DA-680-I-16-WL3-HH</b>	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operating temperature	<b>4.150,00 €</b>	12~16W
<b>DA-680-I-8-WL3-H</b>	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operating temperature	<b>3.646,00 €</b>	12~16W
<b>DA-680-I-8-WL3-HH</b>	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operating temperature	<b>3.739,00 €</b>	12~16W
<b>DA-681C-KL1-HH-T</b>	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	<b>4.963,00 €</b>	8~12W
<b>DA-681C-KL1-H-T</b>	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, single power, -40 to 70°C operating temperature	<b>4.104,00 €</b>	8~12W
<b>DA-681C-KL3-HH-T</b>	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	<b>6.530,00 €</b>	8~12W
<b>DA-682C-KL1-HH-T</b>	Intel® Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	<b>5.290,00 €</b>	8~12W
<b>DA-682C-KL3-HH-T</b>	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	<b>6.615,00 €</b>	8~12W
<b>DA-682C-KL5-HH-T</b>	Intel® 7th Gen Core™ i5-7300U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	<b>7.718,00 €</b>	8~12W
<b>DA-682C-KL7-HH-T</b>	Intel® 7th Gen Core™ i7-7600U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	<b>8.704,00 €</b>	4~8W
<b>DA-720 HDD Kit</b>	DA-720 HDD/SSD kit	<b>54,00 €</b>	8~10W
<b>DA-720-C5-DPP</b>	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	<b>6.961,00 €</b>	4~8W
<b>DA-720-C5-DPP-LX</b>	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	<b>7.351,00 €</b>	12~16W
<b>DA-720-C7-DPP</b>	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	<b>8.064,00 €</b>	4~8W
<b>DA-720-C7-DPP-LX</b>	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperature	<b>8.443,00 €</b>	12~16W
<b>DA-820C-KL3-HH-T</b>	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	<b>7.107,00 €</b>	12~16W
<b>DA-820C-KL3-H-T</b>	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	<b>6.662,00 €</b>	12~16W
<b>DA-820C-KL5-HH-T</b>	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	<b>8.714,00 €</b>	4~8W
<b>DA-820C-KL5-H-T</b>	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	<b>8.287,00 €</b>	12~16W

<b>DA-820C-KL7-H</b>	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	<b>8.866,00 €</b>	12~16W
<b>DA-820C-KL7-HH</b>	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	<b>9.314,00 €</b>	4~8W
<b>DA-820C-KLXL-HH-T</b>	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	<b>9.816,00 €</b>	4~8W
<b>DA-820C-KLXL-H-T</b>	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	<b>9.366,00 €</b>	12~16W
<b>DA-820C-KLXM-H</b>	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	<b>9.669,00 €</b>	12~16W
<b>DA-820C-KLXM-HH</b>	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	<b>10.115,00 €</b>	4~8W
<b>DA-IRIG-B-S-02-T</b>	IRIG-B expansion module, PCI interface, 1 fiber IRIG-B input, 1 DB9M input/output, 1 DB9M output, -40 to 75°C operating temperature	<b>446,00 €</b>	4~8W
<b>DA-PRP-HSR-I210</b>	PRP/HSR expansion card with RJ45 and SFP combo port	<b>2.103,00 €</b>	4~8W
<b>DE-211</b>	1-port RS-232/422/485 device server with 10 Mbps Ethernet connection	<b>200,00 €</b>	4~8W
<b>DE-2-IRIGB-4-DI/DO</b>	2-port IRIG-B time synchronization module with 4DI/DO	<b>650,00 €</b>	12~16W
<b>DE-2-SATA</b>	Expansion module with 2 2.5-inch SSD/HDD slots	<b>704,00 €</b>	12~16W
<b>DE-311</b>	1-port RS-232/422/485 device server with 10/100 Mbps Ethernet connection	<b>210,00 €</b>	2~4W
<b>DE-FX02-SFP-T</b>	2-port 100 Mbps fiber card, 2 SFP slots, PCIe interface, -40 to 75°C operating temperature (SFP module excluded)	<b>801,00 €</b>	8~12W
<b>DE-LN04-RJ</b>	4-port 10/100/1000 Mbps PCIe LAN module	<b>500,00 €</b>	12~16W
<b>DE-LN08-RJ</b>	8-port 10/100/1000 Mbps PCIe LAN module	<b>643,00 €</b>	12~16W
<b>DE-PRP-HSR-EF</b>	2-port 100/1000 Mbps PCIe PRP/HSR LAN module	<b>2.103,00 €</b>	8~12W
<b>DE-SP08-I-TB</b>	8-port RS-232/422/485 PCIe serial module	<b>665,00 €</b>	4~8W
<b>DK-25-01</b>	DIN-rail mounting kit, 2 screws	<b>9,00 €</b>	16~20W
<b>DK35A</b>	DIN-rail mounting kit, 35 mm	<b>5,00 €</b>	8~10W
<b>DK-DC50131</b>	DIN-rail mounting kit	<b>35,00 €</b>	12~14W
<b>DK-M12-305</b>	DIN-rail mounting kit for EDS-305-M12	<b>20,00 €</b>	8~10W
<b>DK-TN-5308</b>	DIN-rail mounting kit for the TN-5308 Series	<b>35,00 €</b>	8~12W
<b>DK-UC-5000</b>	DIN-rail mounting kit with screws for the UC-5000 Series	<b>23,00 €</b>	4~8W
<b>DK-UP1200</b>	DIN rail (25x48.3 mm) with 2 screws (FMS M3X6)	<b>21,00 €</b>	10~12W
<b>DK-UP1400</b>	DIN-rail/wall-mounting kit, 2 plates, 6 screws, and 2 DIN-rail plates, 4 screws	<b>21,00 €</b>	10~12W
<b>DK-UP1400-G2</b>	DIN Rail mounting kits for UPort 1400-G2	<b>32,00 €</b>	4~8W
<b>DK-UP-14168</b>	DIN-rail kit with 2 plates (89 x 19 mm), 6 screws (FMS M3 x 5 mm) for the UPort 1400 (V1.5.0 and after) and 1600-8 (V1.4.0 and after) models	<b>43,00 €</b>	4~8W
<b>DK-UP1600-G2</b>	DIN Rail mounting kits for UPort 1600-G2	<b>37,00 €</b>	4~8W
<b>DK-UP-42A</b>	DIN-rail mounting kit for the UPort 400A/200A Series, 107 x 29 mm (4.21 x 1.14 in), with 4 M3 x 5 mm screws	<b>18,00 €</b>	4~8W
<b>DN-FX04</b>	4-port 100M/1000M SFP Ethernet module	<b>1.247,00 €</b>	4~8W
<b>DN-LN04-RJ</b>	4-port 10/100/1000 Mbps PCIe LAN module with RJ45 connectors	<b>883,00 €</b>	4~8W
<b>DN-PRP-HSR-I210</b>	PRP/HSR expansion module with RJ45 and SFP combo port	<b>2.108,00 €</b>	8~12W
<b>DN-SP08-I-DB</b>	8-port software-selectable RS-232/422/485 PCIe serial module with DB9 connector	<b>1.062,00 €</b>	4~8W
<b>DN-SP08-I-TB</b>	8-port software-selectable RS-232/422/485 PCIe serial module with terminal-block connector	<b>1.062,00 €</b>	4~8W
<b>DRP-A100-E2-2L4C-T</b>	DIN-rail computer with Intel Atom® x6211E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.721,00 €</b>	4~8W
<b>DRP-A100-E2-6C-T</b>	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.600,00 €</b>	4~8W
<b>DRP-A100-E2-8L-T</b>	DIN-rail computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.994,00 €</b>	4~8W
<b>DRP-A100-E2-T</b>	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.064,00 €</b>	4~8W
<b>DRP-A100-E2-T-Win10</b>	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>2.888,00 €</b>	4~8W
<b>DRP-A100-E4-2L4C-T</b>	DIN-rail computer with Intel Atom® x6425E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.842,00 €</b>	4~8W
<b>DRP-A100-E4-6C-T</b>	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.676,00 €</b>	4~8W
<b>DRP-A100-E4-8L-T</b>	DIN-rail computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.084,00 €</b>	4~8W

<b>DRP-A100-E4-T</b>	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.268,00 €</b>	4~8W
<b>DRP-A100-E4-T-Win10</b>	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>2.948,00 €</b>	4~8W
<b>DRP-C100-C1-2L4C-T</b>	DIN-rail computer with Intel® Celeron® 6305E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.827,00 €</b>	4~8W
<b>DRP-C100-C1-6C-T</b>	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.706,00 €</b>	4~8W
<b>DRP-C100-C1-8L-T</b>	DIN-rail computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.099,00 €</b>	4~8W
<b>DRP-C100-C1-T</b>	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.132,00 €</b>	4~8W
<b>DRP-C100-C1-T-Win10</b>	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>3.024,00 €</b>	4~8W
<b>DRP-C100-C5-2L4C-T</b>	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.127,00 €</b>	4~8W
<b>DRP-C100-C5-6C-T</b>	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.931,00 €</b>	4~8W
<b>DRP-C100-C5-8L-T</b>	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.248,00 €</b>	4~8W
<b>DRP-C100-C5-T</b>	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.371,00 €</b>	4~8W
<b>DRP-C100-C5-T-Win10</b>	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>4.339,00 €</b>	4~8W
<b>DRP-C100-C7-2L4C-T</b>	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.823,00 €</b>	4~8W
<b>DRP-C100-C7-6C-T</b>	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.596,00 €</b>	4~8W
<b>DRP-C100-C7-8L-T</b>	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>5.110,00 €</b>	4~8W
<b>DRP-C100-C7-T</b>	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.203,00 €</b>	4~8W
<b>DRP-C100-C7-T-Win10</b>	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>5.352,00 €</b>	4~8W
<b>EDF-G1002-BP</b>	Industrial firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), industrial deep packet inspection (DPI), Gen3 Bypass, centralized management through MXsecurity, -10 to 60°C operating temperature	<b>1.177,00 €</b>	
<b>EDF-G1002-BP-T</b>	Industrial firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), industrial deep packet inspection (DPI), Gen3 Bypass, centralized management through MXsecurity, -40 to 75°C operating temperature	<b>1.305,00 €</b>	
<b>EDR-8010-2GSFP</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	<b>1.446,00 €</b>	4~8W
<b>EDR-8010-2GSFP-CT</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	<b>1.791,00 €</b>	12~16W
<b>EDR-8010-2GSFP-CT-T</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	<b>1.951,00 €</b>	12~16W
<b>EDR-8010-2GSFP-T</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	<b>1.612,00 €</b>	12~16W
<b>EDR-8010-VPN-2GSFP</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	<b>1.612,00 €</b>	4~8W
<b>EDR-8010-VPN-2GSFP-CT</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	<b>1.951,00 €</b>	12~16W
<b>EDR-8010-VPN-2GSFP-CT-T</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	<b>2.124,00 €</b>	12~16W
<b>EDR-8010-VPN-2GSFP-T</b>	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	<b>1.778,00 €</b>	12~16W
<b>EDR-810-2GSFP</b>	8+2G SFP industrial multiport secure router with Firewall/NAT, -10 to 60°C operating temperature	<b>1.450,00 €</b>	2~4W
<b>EDR-810-2GSFP-T</b>	8+2G SFP industrial multiport secure router with Firewall/NAT, -40 to 75°C operating temperature	<b>1.613,00 €</b>	2~4W
<b>EDR-810-VPN-2GSFP</b>	8+2G SFP industrial multiport secure router with Firewall/NAT/VPN, -10 to 60°C operating temperature	<b>1.613,00 €</b>	2~4W

<b>EDR-810-VPN-2GSFP-T</b>	8+2G SFP industrial multiport secure router with Firewall/NAT/VPN, -40 to 75°C operating temperature	<b>1.778,00 €</b>	4~8W
<b>EDR-G9010-VPN-2MGSFP</b>	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	<b>3.577,00 €</b>	4~8W
<b>EDR-G9010-VPN-2MGSFP-HV</b>	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -10 to 60°C operating temperature	<b>3.900,00 €</b>	8~12W
<b>EDR-G9010-VPN-2MGSFP-HV-T</b>	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -40 to 75°C operating temperature	<b>4.047,00 €</b>	8~12W
<b>EDR-G9010-VPN-2MGSFP-T</b>	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	<b>3.917,00 €</b>	4~8W
<b>EDR-G902</b>	Industrial Gigabit firewall/NAT secure router with 1 WAN port, 10 VPN tunnels, 0 to 60°C operating temperature	<b>2.060,00 €</b>	4~8W
<b>EDR-G902-T</b>	Industrial Gigabit firewall/NAT secure router with 1 WAN port, 10 VPN tunnels, -40 to 75°C operating temperature	<b>2.284,00 €</b>	8~12W
<b>EDR-G903</b>	Industrial Gigabit firewall/VPN secure router with 3 combo 10/100/1000BaseT(X) ports or 100/1000BaseSFP slots, 0 to 60°C operating temperature	<b>2.716,00 €</b>	4~8W
<b>EDR-G903-T</b>	Industrial Gigabit firewall/VPN secure router with 3 combo 10/100/1000BaseT(X) ports or 100/1000BaseSFP slots, -40 to 75°C operating temperature	<b>2.936,00 €</b>	4~8W
<b>EDS-2005-EL</b>	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>132,00 €</b>	2~4W
<b>EDS-2005-ELP</b>	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	<b>114,00 €</b>	2~4W
<b>EDS-2005-EL-T</b>	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>195,00 €</b>	2~4W
<b>EDS-2008-EL</b>	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>192,00 €</b>	2~4W
<b>EDS-2008-EL-M-SC</b>	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>298,00 €</b>	4~8W
<b>EDS-2008-EL-M-SC-T</b>	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>371,00 €</b>	8~12W
<b>EDS-2008-EL-M-ST</b>	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>298,00 €</b>	8~12W
<b>EDS-2008-EL-M-ST-T</b>	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>371,00 €</b>	8~12W
<b>EDS-2008-ELP</b>	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	<b>165,00 €</b>	2~4W
<b>EDS-2008-EL-T</b>	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>266,00 €</b>	4~8W
<b>EDS-2010-ML-2GTXSFP</b>	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 power inputs, -10 to 60°C operating temperature	<b>630,00 €</b>	2~4W
<b>EDS-2010-ML-2GTXSFP-T</b>	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 power inputs, -40 to 75°C operating temperature	<b>743,00 €</b>	4~8W
<b>EDS-2016-ML</b>	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 power inputs, -10 to 60°C operating temperature	<b>577,00 €</b>	2~4W
<b>EDS-2016-ML-MM-SC</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	<b>816,00 €</b>	4~8W
<b>EDS-2016-ML-MM-SC-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>910,00 €</b>	8~12W
<b>EDS-2016-ML-MM-ST</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	<b>816,00 €</b>	8~12W
<b>EDS-2016-ML-MM-ST-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>910,00 €</b>	8~12W
<b>EDS-2016-ML-SS-SC</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60°C operating temperature	<b>1.179,00 €</b>	4~8W
<b>EDS-2016-ML-SS-SC-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.282,00 €</b>	8~12W
<b>EDS-2016-ML-T</b>	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 power inputs, -40 to 75°C operating temperature	<b>683,00 €</b>	4~8W
<b>EDS-2018-ML-2GTXSFP</b>	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	<b>960,00 €</b>	4~8W
<b>EDS-2018-ML-2GTXSFP-T</b>	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	<b>1.064,00 €</b>	4~8W
<b>EDS-205</b>	Entry-level unmanaged Ethernet switch with 5 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	<b>131,00 €</b>	2~4W
<b>EDS-205A</b>	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -10 to 60°C operating temperature	<b>154,00 €</b>	2~4W
<b>EDS-205A-M-SC</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	<b>320,00 €</b>	2~4W
<b>EDS-205A-M-SC-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	<b>439,00 €</b>	4~8W
<b>EDS-205A-M-ST</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	<b>320,00 €</b>	2~4W
<b>EDS-205A-M-ST-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	<b>439,00 €</b>	4~8W
<b>EDS-205A-S-SC</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	<b>532,00 €</b>	2~4W
<b>EDS-205A-S-SC-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	<b>652,00 €</b>	2~4W

<b>EDS-205A-T</b>	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>293,00 €</b>	2~4W
<b>EDS-208</b>	Entry-level unmanaged Ethernet switch with 8 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	<b>192,00 €</b>	2~4W
<b>EDS-208A</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -10 to 60°C operating temperature	<b>224,00 €</b>	2~4W
<b>EDS-208A-MM-SC</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	<b>533,00 €</b>	2~4W
<b>EDS-208A-MM-SC-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>614,00 €</b>	4~8W
<b>EDS-208A-MM-ST</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	<b>533,00 €</b>	4~8W
<b>EDS-208A-MM-ST-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>614,00 €</b>	4~8W
<b>EDS-208A-M-SC</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	<b>395,00 €</b>	2~4W
<b>EDS-208A-M-SC-T</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	<b>482,00 €</b>	4~8W
<b>EDS-208A-M-ST</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	<b>395,00 €</b>	4~8W
<b>EDS-208A-M-ST-T</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	<b>482,00 €</b>	4~8W
<b>EDS-208A-S-SC</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	<b>607,00 €</b>	2~4W
<b>EDS-208A-S-SC-T</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	<b>725,00 €</b>	4~8W
<b>EDS-208A-SS-SC</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60°C operating temperature	<b>860,00 €</b>	2~4W
<b>EDS-208A-SS-SC-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>985,00 €</b>	4~8W
<b>EDS-208A-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>371,00 €</b>	2~4W
<b>EDS-208-M-SC</b>	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, plastic housing, -10 to 60°C operating temperature	<b>332,00 €</b>	2~4W
<b>EDS-208-M-ST</b>	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, plastic housing, -10 to 60°C operating temperature	<b>332,00 €</b>	4~8W
<b>EDS-305</b>	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	<b>271,00 €</b>	2~4W
<b>EDS-305-M-SC</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	<b>416,00 €</b>	4~8W
<b>EDS-305-M-SC-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>514,00 €</b>	4~8W
<b>EDS-305-M-ST</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, 0 to 60°C operating temperature	<b>416,00 €</b>	4~8W
<b>EDS-305-M-ST-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	<b>514,00 €</b>	4~8W
<b>EDS-305-S-SC</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	<b>605,00 €</b>	4~8W
<b>EDS-305-S-SC-80</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	<b>1.709,00 €</b>	8~12W
<b>EDS-305-S-SC-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>669,00 €</b>	4~8W
<b>EDS-305-T</b>	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	<b>335,00 €</b>	4~8W
<b>EDS-308</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	<b>340,00 €</b>	2~4W
<b>EDS-308-MM-SC</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	<b>598,00 €</b>	2~4W
<b>EDS-308-MM-SC-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	<b>669,00 €</b>	4~8W
<b>EDS-308-MM-ST</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	<b>598,00 €</b>	4~8W
<b>EDS-308-MM-ST-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connector, -40 to 75°C operating temperature	<b>669,00 €</b>	4~8W
<b>EDS-308-M-SC</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	<b>493,00 €</b>	4~8W
<b>EDS-308-M-SC-T</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>539,00 €</b>	8~12W
<b>EDS-308-S-SC</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	<b>609,00 €</b>	4~8W
<b>EDS-308-S-SC-80</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	<b>1.501,00 €</b>	8~12W
<b>EDS-308-S-SC-T</b>	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>712,00 €</b>	8~12W
<b>EDS-308-SS-SC</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	<b>849,00 €</b>	2~4W
<b>EDS-308-SS-SC-80</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, 0 to 60°C operating temperature	<b>2.565,00 €</b>	8~12W



<b>EDS-308-SS-SC-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	<b>960,00 €</b>	4~8W
<b>EDS-308-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	<b>398,00 €</b>	2~4W
<b>EDS-309-3M-SC</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	<b>815,00 €</b>	4~8W
<b>EDS-309-3M-SC-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	<b>897,00 €</b>	4~8W
<b>EDS-309-3M-ST</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	<b>815,00 €</b>	4~8W
<b>EDS-309-3M-ST-T</b>	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	<b>897,00 €</b>	8~12W
<b>EDS-316</b>	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -10 to 60°C operating temperature	<b>719,00 €</b>	2~4W
<b>EDS-316-MM-SC</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	<b>1.031,00 €</b>	2~4W
<b>EDS-316-MM-SC-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	<b>1.150,00 €</b>	4~8W
<b>EDS-316-MM-ST</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -10 to 60°C operating temperature	<b>1.031,00 €</b>	4~8W
<b>EDS-316-MM-ST-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	<b>1.150,00 €</b>	4~8W
<b>EDS-316-M-SC</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	<b>917,00 €</b>	4~8W
<b>EDS-316-M-SC-T</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>1.045,00 €</b>	4~8W
<b>EDS-316-MS-SC</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	<b>1.258,00 €</b>	8~12W
<b>EDS-316-M-ST</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -10 to 60°C operating temperature	<b>917,00 €</b>	4~8W
<b>EDS-316-M-ST-T</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	<b>1.045,00 €</b>	8~12W
<b>EDS-316-S-SC</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	<b>1.084,00 €</b>	4~8W
<b>EDS-316-S-SC-T</b>	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	<b>1.180,00 €</b>	8~12W
<b>EDS-316-SS-SC</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	<b>1.501,00 €</b>	4~8W
<b>EDS-316-SS-SC-80</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, -10 to 60°C operating temperature	<b>3.440,00 €</b>	8~12W
<b>EDS-316-SS-SC-T</b>	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	<b>1.601,00 €</b>	4~8W
<b>EDS-316-T</b>	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	<b>844,00 €</b>	2~4W
<b>EDS-4008-2GT-2GS-HV</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.649,00 €</b>	8~12W
<b>EDS-4008-2GT-2GS-HV-T</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>1.842,00 €</b>	12~16W
<b>EDS-4008-2GT-2GS-LV</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.494,00 €</b>	4~8W
<b>EDS-4008-2GT-2GS-LV-T</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.686,00 €</b>	12~16W
<b>EDS-4008-2MSC-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.901,00 €</b>	8~12W
<b>EDS-4008-2MSC-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.076,00 €</b>	12~16W
<b>EDS-4008-2MSC-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.759,00 €</b>	8~12W
<b>EDS-4008-2MSC-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.936,00 €</b>	12~16W
<b>EDS-4008-2MST-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.901,00 €</b>	8~12W
<b>EDS-4008-2MST-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.076,00 €</b>	12~16W
<b>EDS-4008-2MST-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.759,00 €</b>	8~12W
<b>EDS-4008-2MST-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.936,00 €</b>	12~16W
<b>EDS-4008-2SSC-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.216,00 €</b>	8~12W
<b>EDS-4008-2SSC-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.385,00 €</b>	12~16W
<b>EDS-4008-2SSC-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.076,00 €</b>	8~12W
<b>EDS-4008-2SSC-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.245,00 €</b>	12~16W

<b>EDS-4008-4P-2GT-2GS-LVA</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	<b>1.943,00 €</b>	8~12W
<b>EDS-4008-4P-2GT-2GS-LVA-T</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	<b>2.128,00 €</b>	12~16W
<b>EDS-4008-4P-2GT-2GS-LVB</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.112,00 €</b>	8~12W
<b>EDS-4008-4P-2GT-2GS-LVB-T</b>	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.296,00 €</b>	12~16W
<b>EDS-4008-HV</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.452,00 €</b>	8~12W
<b>EDS-4008-HV-T</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>1.620,00 €</b>	12~16W
<b>EDS-4008-LV</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.310,00 €</b>	4~8W
<b>EDS-4008-LV-T</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.482,00 €</b>	12~16W
<b>EDS-4009-3MSC-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.291,00 €</b>	8~12W
<b>EDS-4009-3MSC-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.468,00 €</b>	12~16W
<b>EDS-4009-3MSC-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.149,00 €</b>	8~12W
<b>EDS-4009-3MSC-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.321,00 €</b>	12~16W
<b>EDS-4009-3MST-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.291,00 €</b>	8~12W
<b>EDS-4009-3MST-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.468,00 €</b>	12~16W
<b>EDS-4009-3MST-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.149,00 €</b>	8~12W
<b>EDS-4009-3MST-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.321,00 €</b>	12~16W
<b>EDS-4009-3SSC-HV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.761,00 €</b>	8~12W
<b>EDS-4009-3SSC-HV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.930,00 €</b>	12~16W
<b>EDS-4009-3SSC-LV</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.620,00 €</b>	8~12W
<b>EDS-4009-3SSC-LV-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.790,00 €</b>	12~16W
<b>EDS-4012-4GC-HV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.965,00 €</b>	4~8W
<b>EDS-4012-4GC-HV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.135,00 €</b>	12~16W
<b>EDS-4012-4GC-LV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.826,00 €</b>	4~8W
<b>EDS-4012-4GC-LV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.995,00 €</b>	4~8W
<b>EDS-4012-4GS-HV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>1.826,00 €</b>	8~12W
<b>EDS-4012-4GS-HV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>1.995,00 €</b>	12~16W
<b>EDS-4012-4GS-LV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>1.686,00 €</b>	4~8W
<b>EDS-4012-4GS-LV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>1.855,00 €</b>	12~16W
<b>EDS-4012-8P-4GS-LVA</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 48 VDC for PoE, -10 to 60°C operating temperature	<b>2.422,00 €</b>	8~12W
<b>EDS-4012-8P-4GS-LVA-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 48 VDC for PoE, -40 to 75°C operating temperature	<b>2.591,00 €</b>	4~8W
<b>EDS-4012-8P-4GS-LVB</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.577,00 €</b>	8~12W
<b>EDS-4012-8P-4GS-LVB-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.745,00 €</b>	12~16W
<b>EDS-4014-4GS-2QGS-HV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.291,00 €</b>	8~12W
<b>EDS-4014-4GS-2QGS-HV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.468,00 €</b>	12~16W
<b>EDS-4014-4GS-2QGS-LV</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.149,00 €</b>	4~8W
<b>EDS-4014-4GS-2QGS-LV-T</b>	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.321,00 €</b>	12~16W

<b>EDS-405A</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -10°C to 60°C operating temperature	<b>454,00 €</b>	2~4W
<b>EDS-405A-EIP</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	<b>454,00 €</b>	4~8W
<b>EDS-405A-EIP-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	<b>570,00 €</b>	8~12W
<b>EDS-405A-MM-SC</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>815,00 €</b>	2~4W
<b>EDS-405A-MM-SC-T</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>957,00 €</b>	2~4W
<b>EDS-405A-MM-ST</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>815,00 €</b>	4~8W
<b>EDS-405A-MM-ST-T</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>957,00 €</b>	4~8W
<b>EDS-405A-PN</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	<b>454,00 €</b>	4~8W
<b>EDS-405A-PN-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	<b>570,00 €</b>	8~12W
<b>EDS-405A-PTP</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PTPv2 protocol support, -10°C to 60°C operating temperature	<b>1.285,00 €</b>	4~8W
<b>EDS-405A-PTP-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PTPv2 protocol support, -40°C to 75°C operating temperature	<b>1.433,00 €</b>	8~12W
<b>EDS-405A-SS-SC</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.106,00 €</b>	2~4W
<b>EDS-405A-SS-SC-T</b>	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.225,00 €</b>	2~4W
<b>EDS-405A-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>570,00 €</b>	2~4W
<b>EDS-408A</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -10°C to 60°C operating temperature	<b>719,00 €</b>	2~4W
<b>EDS-408A-1M2S-SC</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.658,00 €</b>	8~12W
<b>EDS-408A-1M2S-SC-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.775,00 €</b>	8~12W
<b>EDS-408A-2M1S-SC</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, 0 to 60°C operating temperature	<b>1.509,00 €</b>	8~12W
<b>EDS-408A-2M1S-SC-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, -40 to 75°C operating temperature	<b>1.643,00 €</b>	8~12W
<b>EDS-408A-3M-SC</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.374,00 €</b>	4~8W
<b>EDS-408A-3M-SC-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.493,00 €</b>	4~8W
<b>EDS-408A-3M-ST</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>1.374,00 €</b>	4~8W
<b>EDS-408A-3M-ST-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>1.493,00 €</b>	8~12W
<b>EDS-408A-3S-SC</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.792,00 €</b>	4~8W
<b>EDS-408A-3S-SC-48</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, ±24/±48 VDC input voltage, 0 to 60°C operating temperature	<b>2.106,00 €</b>	8~12W
<b>EDS-408A-3S-SC-48-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, ±24/±48 VDC input voltage, -40 to 75°C operating temperature	<b>2.249,00 €</b>	12~16W
<b>EDS-408A-3S-SC-T</b>	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.910,00 €</b>	4~8W
<b>EDS-408A-EIP</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	<b>719,00 €</b>	4~8W
<b>EDS-408A-EIP-T</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	<b>987,00 €</b>	8~12W
<b>EDS-408A-MM-SC</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.046,00 €</b>	2~4W
<b>EDS-408A-MM-SC-T</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.313,00 €</b>	2~4W
<b>EDS-408A-MM-ST</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>1.046,00 €</b>	2~4W
<b>EDS-408A-MM-ST-T</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>1.313,00 €</b>	2~4W
<b>EDS-408A-PN</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	<b>719,00 €</b>	4~8W
<b>EDS-408A-PN-T</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	<b>987,00 €</b>	4~8W
<b>EDS-408A-SS-SC</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.475,00 €</b>	2~4W
<b>EDS-408A-SS-SC-T</b>	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.597,00 €</b>	2~4W
<b>EDS-408A-T</b>	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>987,00 €</b>	2~4W
<b>EDS-505A</b>	Managed Ethernet switch with 5 10/100BaseT(X) ports, 0 to 60°C operating temperature	<b>822,00 €</b>	4~8W

<b>EDS-505A-MM-SC</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.494,00 €</b>	8~12W
<b>EDS-505A-MM-SC-T</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.699,00 €</b>	8~12W
<b>EDS-505A-MM-ST</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>1.494,00 €</b>	8~12W
<b>EDS-505A-MM-ST-T</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>1.699,00 €</b>	8~12W
<b>EDS-505A-SS-SC</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.851,00 €</b>	4~8W
<b>EDS-505A-SS-SC-T</b>	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>2.029,00 €</b>	4~8W
<b>EDS-505A-T</b>	Managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>1.134,00 €</b>	4~8W
<b>EDS-508A</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, 0 to 60°C operating temperature	<b>1.134,00 €</b>	2~4W
<b>EDS-508A-MM-SC</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>1.717,00 €</b>	2~4W
<b>EDS-508A-MM-SC-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>1.865,00 €</b>	4~8W
<b>EDS-508A-MM-ST</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>1.717,00 €</b>	4~8W
<b>EDS-508A-MM-ST-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>1.865,00 €</b>	4~8W
<b>EDS-508A-SS-SC</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	<b>2.148,00 €</b>	4~8W
<b>EDS-508A-SS-SC-80</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 0 to 60°C operating temperature	<b>4.948,00 €</b>	8~12W
<b>EDS-508A-SS-SC-80-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, -40 to 75°C operating temperature	<b>5.098,00 €</b>	8~12W
<b>EDS-508A-SS-SC-T</b>	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	<b>2.295,00 €</b>	4~8W
<b>EDS-508A-T</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>1.285,00 €</b>	4~8W
<b>EDS-510A-1GT2SFP</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>1.940,00 €</b>	4~8W
<b>EDS-510A-1GT2SFP-T</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>2.106,00 €</b>	4~8W
<b>EDS-510A-3GT</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	<b>1.940,00 €</b>	4~8W
<b>EDS-510A-3GT-T</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	<b>2.106,00 €</b>	4~8W
<b>EDS-510A-3SFP</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>1.940,00 €</b>	4~8W
<b>EDS-510A-3SFP-T</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>2.106,00 €</b>	4~8W
<b>EDS-510E-3GTXSFP</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	<b>1.418,00 €</b>	2~4W
<b>EDS-510E-3GTXSFP-T</b>	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	<b>1.535,00 €</b>	2~4W
<b>EDS-516A</b>	Managed Ethernet switch with 16 10/100BaseT(X) ports, 0 to 60°C operating temperature	<b>1.775,00 €</b>	2~4W
<b>EDS-516A-MM-SC</b>	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	<b>2.236,00 €</b>	4~8W
<b>EDS-516A-MM-SC-T</b>	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>2.372,00 €</b>	4~8W
<b>EDS-516A-MM-ST</b>	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	<b>2.236,00 €</b>	4~8W
<b>EDS-516A-MM-ST-T</b>	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>2.372,00 €</b>	12~16W
<b>EDS-516A-T</b>	Managed Ethernet switch with 16 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>1.911,00 €</b>	4~8W
<b>EDS-518A</b>	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>2.550,00 €</b>	4~8W
<b>EDS-518A-MM-SC</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>3.070,00 €</b>	4~8W
<b>EDS-518A-MM-SC-T</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>3.251,00 €</b>	12~16W
<b>EDS-518A-MM-ST</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>3.070,00 €</b>	4~8W
<b>EDS-518A-MM-ST-T</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>3.251,00 €</b>	12~16W
<b>EDS-518A-SS-SC</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>3.457,00 €</b>	4~8W

<b>EDS-518A-SS-SC-80</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	<b>6.361,00 €</b>	8~12W
<b>EDS-518A-SS-SC-T</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>3.652,00 €</b>	4~8W
<b>EDS-518A-T</b>	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	<b>2.731,00 €</b>	4~8W
<b>EDS-518E-4GTXSFP</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	<b>1.998,00 €</b>	2~4W
<b>EDS-518E-4GTXSFP-T</b>	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	<b>2.148,00 €</b>	2~4W
<b>EDS-518E-MM-SC-4GTXSFP</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX (multi-mode, SC Connector), -10 to 60°C operating temperature	<b>2.419,00 €</b>	4~8W
<b>EDS-518E-MM-SC-4GTXSFP-T</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with SC connector, -40 to 75°C operating temperature	<b>2.561,00 €</b>	8~12W
<b>EDS-518E-MM-ST-4GTXSFP</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	<b>2.419,00 €</b>	8~12W
<b>EDS-518E-MM-ST-4GTXSFP-T</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>2.561,00 €</b>	8~12W
<b>EDS-518E-SS-SC-4GTXSFP</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	<b>2.731,00 €</b>	4~8W
<b>EDS-518E-SS-SC-4GTXSFP-T</b>	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	<b>2.860,00 €</b>	4~8W
<b>EDS-528E-4GTXSFP-HV</b>	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -10 to 60°C operating temperature	<b>2.939,00 €</b>	4~8W
<b>EDS-528E-4GTXSFP-HV-T</b>	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -40 to 75°C operating temperature	<b>3.070,00 €</b>	4~8W
<b>EDS-528E-4GTXSFP-LV</b>	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -10 to 60°C operating temperature	<b>2.939,00 €</b>	4~8W
<b>EDS-528E-4GTXSFP-LV-T</b>	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -40 to 75°C operating temperature	<b>3.070,00 €</b>	4~8W
<b>EDS-608</b>	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, 0 to 60°C operating temperature	<b>1.642,00 €</b>	4~8W
<b>EDS-608-T</b>	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, -40 to 75°C operating temperature	<b>1.881,00 €</b>	4~8W
<b>EDS-611</b>	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, 0 to 60°C operating temperature	<b>2.565,00 €</b>	8~12W
<b>EDS-611-T</b>	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, -40 to 75°C operating temperature	<b>2.818,00 €</b>	12~16W
<b>EDS-616</b>	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, 0 to 60°C operating temperature	<b>2.744,00 €</b>	4~8W
<b>EDS-616-T</b>	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, -40 to 75°C operating temperature	<b>2.999,00 €</b>	4~8W
<b>EDS-619</b>	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, 0 to 60°C operating temperature	<b>3.578,00 €</b>	4~8W
<b>EDS-619-T</b>	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, -40 to 75°C operating temperature	<b>3.833,00 €</b>	4~8W
<b>EDS-G2005-EL</b>	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>263,00 €</b>	2~4W
<b>EDS-G2005-ELP</b>	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	<b>234,00 €</b>	2~4W
<b>EDS-G2005-EL-T</b>	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>320,00 €</b>	2~4W
<b>EDS-G2008-EL</b>	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	<b>363,00 €</b>	2~4W
<b>EDS-G2008-ELP</b>	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	<b>299,00 €</b>	2~4W
<b>EDS-G2008-EL-T</b>	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	<b>419,00 €</b>	2~4W
<b>EDS-G205-1GTXSFP</b>	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -10 to 60°C operating temperature	<b>308,00 €</b>	2~4W
<b>EDS-G205-1GTXSFP-T</b>	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -40 to 75°C operating temperature	<b>410,00 €</b>	2~4W
<b>EDS-G205A-4PoE</b>	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, 0 to 60°C operating temperature	<b>822,00 €</b>	2~4W

<b>EDS-G205A-4PoE-1GSFP</b>	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, 0 to 60°C operating temperature	<b>879,00 €</b>	4~8W
<b>EDS-G205A-4PoE-1GSFP-T</b>	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, -40 to 75°C operating temperature	<b>966,00 €</b>	4~8W
<b>EDS-G205A-4PoE-T</b>	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, -40 to 75°C operating temperature	<b>909,00 €</b>	2~4W
<b>EDS-G308</b>	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	<b>451,00 €</b>	2~4W
<b>EDS-G308-2SFP</b>	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	<b>557,00 €</b>	2~4W
<b>EDS-G308-2SFP-T</b>	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	<b>652,00 €</b>	2~4W
<b>EDS-G308-T</b>	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	<b>547,00 €</b>	2~4W
<b>EDS-G4008-HV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.200,00 €</b>	8~12W
<b>EDS-G4008-HV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.371,00 €</b>	12~16W
<b>EDS-G4008-LV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.061,00 €</b>	4~8W
<b>EDS-G4008-LV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.232,00 €</b>	12~16W
<b>EDS-G4012-4GC-HV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>2.716,00 €</b>	4~8W
<b>EDS-G4012-4GC-HV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>2.885,00 €</b>	12~16W
<b>EDS-G4012-4GC-LV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>2.569,00 €</b>	4~8W
<b>EDS-G4012-4GC-LV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>2.745,00 €</b>	4~8W
<b>EDS-G4012-8P-4QGS-LVA</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	<b>3.504,00 €</b>	8~12W
<b>EDS-G4012-8P-4QGS-LVA-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	<b>3.680,00 €</b>	4~8W
<b>EDS-G4012-8P-4QGS-LVB</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>3.665,00 €</b>	4~8W
<b>EDS-G4012-8P-4QGS-LVB-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature,	<b>3.835,00 €</b>	4~8W
<b>EDS-G4014-6QGS-HV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	<b>3.600,00 €</b>	8~12W
<b>EDS-G4014-6QGS-HV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	<b>3.769,00 €</b>	12~16W
<b>EDS-G4014-6QGS-LV</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	<b>3.459,00 €</b>	8~12W
<b>EDS-G4014-6QGS-LV-T</b>	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	<b>3.636,00 €</b>	12~16W
<b>EDS-G508E</b>	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	<b>1.763,00 €</b>	4~8W
<b>EDS-G508E-T</b>	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	<b>1.940,00 €</b>	4~8W
<b>EDS-G509</b>	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 0 to 60°C operating temperature	<b>1.959,00 €</b>	2~4W
<b>EDS-G509-T</b>	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, -40 to 75°C operating temperature	<b>2.135,00 €</b>	2~4W
<b>EDS-G512E-4GSFP</b>	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	<b>1.821,00 €</b>	2~4W
<b>EDS-G512E-4GSFP-T</b>	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	<b>1.986,00 €</b>	2~4W
<b>EDS-G512E-8PoE-4GSFP</b>	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) PoE/PoE+ ports, 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	<b>2.655,00 €</b>	2~4W
<b>EDS-G512E-8PoE-4GSFP-T</b>	12-port full Gigabit managed Ethernet switch, 8 10/100/1000BaseT(X) PoE/PoE+ ports with 4 100/1000BaseSFP slots, -40 to 75°C operating temperature	<b>2.878,00 €</b>	2~4W
<b>EDS-G516E-4GSFP</b>	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	<b>2.611,00 €</b>	2~4W
<b>EDS-G516E-4GSFP-T</b>	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	<b>2.791,00 €</b>	2~4W
<b>EDS-P206A-4PoE</b>	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -10 to 60°C operating temperature	<b>507,00 €</b>	2~4W
<b>EDS-P206A-4PoE-MM-SC</b>	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	<b>742,00 €</b>	4~8W
<b>EDS-P206A-4PoE-MM-SC-T</b>	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	<b>841,00 €</b>	4~8W

<b>EDS-P206A-4PoE-MM-ST</b>	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	<b>742,00 €</b>	4~8W
<b>EDS-P206A-4PoE-MM-ST-T</b>	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	<b>841,00 €</b>	4~8W
<b>EDS-P206A-4PoE-M-SC</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	<b>615,00 €</b>	4~8W
<b>EDS-P206A-4PoE-M-SC-T</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	<b>712,00 €</b>	4~8W
<b>EDS-P206A-4PoE-M-ST</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	<b>615,00 €</b>	4~8W
<b>EDS-P206A-4PoE-M-ST-T</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	<b>712,00 €</b>	4~8W
<b>EDS-P206A-4PoE-S-SC</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	<b>849,00 €</b>	4~8W
<b>EDS-P206A-4PoE-S-SC-T</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	<b>930,00 €</b>	4~8W
<b>EDS-P206A-4PoE-SS-SC</b>	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	<b>1.061,00 €</b>	4~8W
<b>EDS-P206A-4PoE-SS-SC-T</b>	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	<b>1.179,00 €</b>	4~8W
<b>EDS-P206A-4PoE-T</b>	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -40 to 75°C operating temperature	<b>597,00 €</b>	2~4W
<b>EDS-P506E-4PoE-2GTXSFP</b>	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	<b>1.657,00 €</b>	2~4W
<b>EDS-P506E-4PoE-2GTXSFP-T</b>	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	<b>1.822,00 €</b>	2~4W
<b>EDS-P510</b>	Managed Gigabit Ethernet switch with 3 10/100BaseT(X) ports, 4 PoE 10/100BaseT(X) ports, 3 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	<b>1.895,00 €</b>	4~8W
<b>EDS-P510A-8PoE-2GTXSFP</b>	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	<b>2.117,00 €</b>	2~4W
<b>EDS-P510A-8PoE-2GTXSFP-T</b>	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	<b>2.342,00 €</b>	2~4W
<b>EDS-P510-T</b>	Managed Gigabit Ethernet switch with 3 10/100BaseT(X) ports, 4 PoE 10/100BaseT(X) ports, 3 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	<b>2.090,00 €</b>	4~8W
<b>EOM-104</b>	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>328,00 €</b>	2~4W
<b>EOM-104 20PCS</b>	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, 20 pcs, -40 to 75°C operating temperature	<b>6.476,00 €</b>	8~12W
<b>EOM-104 Evaluation Kit</b>	Evaluation kit with an EOM-104 switch module and evaluation board with 4 10/100BaseT(X) ports for testing and application development	<b>434,00 €</b>	8~12W
<b>EOM-104-FO</b>	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature	<b>380,00 €</b>	8~12W
<b>EOM-104-FO 20PCS</b>	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature, 20 pcs package	<b>7.555,00 €</b>	8~12W
<b>EOM-104-FO Evaluation Kit</b>	Evaluation kit with an EOM-104-FO switch module and evaluation board with 2 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connector for testing and application development	<b>865,00 €</b>	8~12W
<b>EOM-G103-PHR-PTP</b>	IEC 62439-3 managed redundancy module with 3 SGMII pinouts reserved for 2 IEC 62439-3 ports and 1 standard Ethernet port, with an extra 1 SGMII reserved for Ethernet console connection, 3.3 V operating power input voltage, -40 to 85°C operating temperature	<b>1.244,00 €</b>	8~12W
<b>EOM-G103-PHR-PTP-ST</b>	IEC 62439-3 managed redundancy module with 3 SGMII pinouts reserved for 2 IEC 62439-3 ports, 1 standard Ethernet port, an evaluation board with 3 10/100/1000BaseT(X) and 100/1000BaseSFP slot combo ports for testing and application development, -40 to 85°C operating temperature	<b>1.817,00 €</b>	8~12W
<b>EXPC-F2120W-TL1-AC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>6.628,00 €</b>	24~28W
<b>EXPC-F2120W-TL1-DC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>6.628,00 €</b>	24~28W
<b>EXPC-F2120W-TL3-AC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>7.159,00 €</b>	24~28W
<b>EXPC-F2120W-TL3-DC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>7.159,00 €</b>	24~28W
<b>EXPC-F2120W-TL7-AC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>8.484,00 €</b>	24~28W
<b>EXPC-F2120W-TL7-DC</b>	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>8.484,00 €</b>	24~28W
<b>EXPC-F2150W-TL3-AC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>7.954,00 €</b>	24~28W



<b>EXPC-F2150W-TL3-DC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>7.821,00 €</b>	24~28W
<b>EXPC-F2150W-TL5-AC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>8.617,00 €</b>	24~28W
<b>EXPC-F2150W-TL5-DC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>8.484,00 €</b>	24~28W
<b>EXPC-F2150W-TL7-AC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>9.280,00 €</b>	24~28W
<b>EXPC-F2150W-TL7-DC</b>	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temperature	<b>9.280,00 €</b>	24~28W
<b>GPS Antenna Package</b>	External antenna with TNC to SMA (female) adapter and a 50-cm cable, SMA antenna (26 dBi, 1572 MHz, L1 band), GPS extension cable	<b>126,00 €</b>	16~20W
<b>HDR-60-24</b>	60 W/2.5 A DIN-rail 24 VDC power supply, universal 85 to 264 VAC or 120 to 370 VDC input voltage, -30 to 70°C operating temperature	<b>86,00 €</b>	8~12W
<b>ICF-1150I-M-SC</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	<b>498,00 €</b>	8~12W
<b>ICF-1150I-M-SC-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	<b>576,00 €</b>	8~12W
<b>ICF-1150I-M-SC-T</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	<b>652,00 €</b>	4~8W
<b>ICF-1150I-M-SC-T-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	<b>748,00 €</b>	8~12W
<b>ICF-1150I-M-ST</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	<b>498,00 €</b>	4~8W
<b>ICF-1150I-M-ST-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	<b>576,00 €</b>	8~12W
<b>ICF-1150I-M-ST-T</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	<b>652,00 €</b>	2~4W
<b>ICF-1150I-M-ST-T-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	<b>748,00 €</b>	8~12W
<b>ICF-1150I-S-SC</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	<b>884,00 €</b>	4~8W
<b>ICF-1150I-S-SC-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	<b>1.014,00 €</b>	4~8W
<b>ICF-1150I-S-SC-T</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	<b>1.136,00 €</b>	4~8W
<b>ICF-1150I-S-SC-T-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	<b>1.297,00 €</b>	8~12W
<b>ICF-1150I-S-ST</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	<b>884,00 €</b>	4~8W
<b>ICF-1150I-S-ST-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	<b>1.014,00 €</b>	8~12W
<b>ICF-1150I-S-ST-T</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	<b>1.136,00 €</b>	4~8W
<b>ICF-1150I-S-ST-T-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	<b>1.297,00 €</b>	8~12W
<b>ICF-1150-M-SC</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 0 to 60°C operating temperature	<b>386,00 €</b>	4~8W
<b>ICF-1150-M-SC-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	<b>443,00 €</b>	8~12W
<b>ICF-1150-M-SC-T</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, -40 to 85°C operating temperature	<b>498,00 €</b>	4~8W
<b>ICF-1150-M-SC-T-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	<b>576,00 €</b>	8~12W
<b>ICF-1150-M-ST</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 0 to 60°C operating temperature	<b>386,00 €</b>	4~8W
<b>ICF-1150-M-ST-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	<b>443,00 €</b>	8~12W
<b>ICF-1150-M-ST-T</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, -40 to 85°C operating temperature	<b>498,00 €</b>	4~8W
<b>ICF-1150-M-ST-T-IEX</b>	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	<b>576,00 €</b>	8~12W
<b>ICF-1150-S-SC</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 0 to 60°C operating temperature	<b>673,00 €</b>	2~4W
<b>ICF-1150-S-SC-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	<b>776,00 €</b>	8~12W
<b>ICF-1150-S-SC-T</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, -40 to 85°C operating temperature	<b>884,00 €</b>	4~8W
<b>ICF-1150-S-SC-T-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	<b>1.014,00 €</b>	8~12W
<b>ICF-1150-S-ST</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 0 to 60°C operating temperature	<b>673,00 €</b>	4~8W

<b>ICF-1150-S-ST-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	<b>776,00 €</b>	8~12W
<b>ICF-1150-S-ST-T</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, -40 to 85°C operating temperature	<b>884,00 €</b>	4~8W
<b>ICF-1150-S-ST-T-IEX</b>	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	<b>1.014,00 €</b>	8~12W
<b>ICF-1170I-M-ST</b>	CANbus to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	<b>498,00 €</b>	4~8W
<b>ICF-1170I-M-ST-T</b>	CANbus to fiber converter, multi-mode, ST connector, -40 to 85°C operating temperature	<b>576,00 €</b>	4~8W
<b>ICF-1171I-M-ST</b>	Industrial CAN-to-fiber converter for distance extension, ST multi-mode	<b>534,00 €</b>	8~12W
<b>ICF-1171I-M-ST-T</b>	Industrial CAN-to-fiber converter for distance extension, ST multi-mode, -40 to 75°C	<b>611,00 €</b>	12~16W
<b>ICF-1171I-S-ST</b>	Industrial CAN-to-fiber converter for distance extension, ST single-mode	<b>692,00 €</b>	4~8W
<b>ICF-1171I-S-ST-T</b>	Industrial CAN-to-fiber converter for distance extension, ST single-mode, -40 to 75°C	<b>795,00 €</b>	12~16W
<b>ICF-1180I-M-ST</b>	PROFIBUS to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	<b>697,00 €</b>	2~4W
<b>ICF-1180I-M-ST-T</b>	PROFIBUS to fiber converter, multi-mode, ST connector, -40 to 75°C operating temperature	<b>800,00 €</b>	4~8W
<b>ICF-1180I-S-ST</b>	PROFIBUS to fiber converter, single-mode, ST connector, 0 to 60°C operating temperature	<b>1.210,00 €</b>	
<b>ICF-1180I-S-ST-T</b>	PROFIBUS to fiber converter, single-mode, ST connector, -40 to 75°C operating temperature	<b>1.315,00 €</b>	
<b>ICF-1280I-M-ST</b>	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, 0 to 60°C operating temperature	<b>1.075,00 €</b>	4~8W
<b>ICF-1280I-M-ST-T</b>	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, -40 to 75°C operating temperature	<b>1.225,00 €</b>	8~12W
<b>ICF-1280I-S-ST</b>	PROFIBUS to fiber converter, single-mode, 2 ST connectors, 0 to 60°C operating temperature	<b>1.851,00 €</b>	
<b>ICF-1280I-S-ST-T</b>	PROFIBUS to fiber converter, single-mode, 2 ST connectors, -40 to 75°C operating temperature	<b>1.998,00 €</b>	
<b>ICS-G7526A-20GSFP-2XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>13.715,00 €</b>	8~12W
<b>ICS-G7526A-2XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>13.715,00 €</b>	12~16W
<b>ICS-G7526A-8GSFP-2XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>13.715,00 €</b>	12~16W
<b>ICS-G7528A-20GSFP-4XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>17.129,00 €</b>	8~12W
<b>ICS-G7528A-4XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>17.129,00 €</b>	12~16W
<b>ICS-G7528A-8GSFP-4XG-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>17.129,00 €</b>	12~16W
<b>ICS-G7748A-HV-HV</b>	Full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, -10 to 60°C operating temperature	<b>15.078,00 €</b>	8~12W
<b>ICS-G7750A-2XG-HV-HV</b>	Full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, -10 to 60°C operating temperature	<b>20.109,00 €</b>	8~12W
<b>ICS-G7752A-4XG-HV-HV</b>	Full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, -10 to 60°C operating temperature	<b>25.142,00 €</b>	8~12W
<b>ICS-G7826A-20GSFP-2XG-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>14.889,00 €</b>	8~12W
<b>ICS-G7826A-2XG-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>14.889,00 €</b>	12~16W
<b>ICS-G7826A-8GSFP-2XG-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>14.889,00 €</b>	4~8W
<b>ICS-G7828A-20GSFP-4XG-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>18.336,00 €</b>	4~8W
<b>ICS-G7828A-4XG-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>18.336,00 €</b>	4~8W
<b>ICS-G7828A-8GSFP-4XG-HV-HV-T</b>	Layer 3 Full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>18.336,00 €</b>	4~8W
<b>ICS-G7848A-HV-HV</b>	Layer 3 full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, 0 to 60°C operating temperature	<b>16.799,00 €</b>	4~8W
<b>ICS-G7850A-2XG-HV-HV</b>	Layer 3 full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, 0 to 60°C operating temperature	<b>21.830,00 €</b>	12~16W
<b>ICS-G7852A-4XG-HV-HV</b>	Layer 3 full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, 0 to 60°C operating temperature	<b>26.864,00 €</b>	4~8W
<b>IKS-6726A-2GTXSFP-24-24-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	<b>2.539,00 €</b>	4~8W

<b>IKS-6726A-2GTXSFP-24-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	<b>2.133,00 €</b>	4~8W
<b>IKS-6726A-2GTXSFP-48-48-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	<b>2.539,00 €</b>	8~12W
<b>IKS-6726A-2GTXSFP-48-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	<b>2.133,00 €</b>	8~12W
<b>IKS-6726A-2GTXSFP-HV-HV-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>2.027,00 €</b>	2~4W
<b>IKS-6726A-2GTXSFP-HV-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, and 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	<b>1.642,00 €</b>	2~4W
<b>IKS-6728A-4GTXSFP-24-24-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	<b>2.950,00 €</b>	12~16W
<b>IKS-6728A-4GTXSFP-24-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	<b>2.550,00 €</b>	4~8W
<b>IKS-6728A-4GTXSFP-48-48-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	<b>2.950,00 €</b>	8~12W
<b>IKS-6728A-4GTXSFP-48-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	<b>2.550,00 €</b>	8~12W
<b>IKS-6728A-4GTXSFP-HV-HV-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>2.478,00 €</b>	2~4W
<b>IKS-6728A-4GTXSFP-HV-T</b>	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	<b>2.061,00 €</b>	4~8W
<b>IKS-6728A-8PoE-4GTXSFP-48-48-T</b>	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	<b>4.090,00 €</b>	4~8W
<b>IKS-6728A-8PoE-4GTXSFP-48-T</b>	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	<b>3.639,00 €</b>	4~8W
<b>IKS-6728A-8PoE-4GTXSFP-HV-HV-T</b>	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>3.536,00 €</b>	4~8W
<b>IKS-6728A-8PoE-4GTXSFP-HV-T</b>	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	<b>3.104,00 €</b>	4~8W
<b>IKS-G6524A-20GSFP-4GTXSFP-HV-HV</b>	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>5.517,00 €</b>	4~8W
<b>IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>6.007,00 €</b>	4~8W
<b>IKS-G6524A-4GTXSFP-HV-HV</b>	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>5.517,00 €</b>	2~4W
<b>IKS-G6524A-4GTXSFP-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>6.007,00 €</b>	4~8W
<b>IKS-G6524A-8GSFP-4GTXSFP-HV-HV</b>	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>5.517,00 €</b>	4~8W
<b>IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T</b>	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>6.007,00 €</b>	4~8W
<b>IKS-G6824A-20GSFP-4GTXSFP-HV-HV</b>	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>7.571,00 €</b>	4~8W
<b>IKS-G6824A-20GSFP-4GTXSFP-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>8.029,00 €</b>	12~16W
<b>IKS-G6824A-4GTXSFP-HV-HV</b>	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>7.571,00 €</b>	4~8W

<b>IKS-G6824A-4GTXSFP-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>8.029,00 €</b>	4~8W
<b>IKS-G6824A-8GSFP-4GTXSFP-HV-HV</b>	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	<b>7.571,00 €</b>	4~8W
<b>IKS-G6824A-8GSFP-4GTXSFP-HV-HV-T</b>	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	<b>8.029,00 €</b>	4~8W
<b>IM-6700A-2MSC4TX</b>	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	<b>432,00 €</b>	4~8W
<b>IM-6700A-2MST4TX</b>	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	<b>432,00 €</b>	8~12W
<b>IM-6700A-2SSC4TX</b>	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	<b>689,00 €</b>	4~8W
<b>IM-6700A-4MSC2TX</b>	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connector, 2 10/100BaseT(X) ports	<b>606,00 €</b>	4~8W
<b>IM-6700A-4MST2TX</b>	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	<b>606,00 €</b>	8~12W
<b>IM-6700A-4SSC2TX</b>	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	<b>1.105,00 €</b>	2~4W
<b>IM-6700A-6MSC</b>	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	<b>772,00 €</b>	4~8W
<b>IM-6700A-6MST</b>	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	<b>772,00 €</b>	4~8W
<b>IM-6700A-6SSC</b>	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	<b>1.537,00 €</b>	4~8W
<b>IM-6700A-8PoE</b>	Fast Ethernet PoE+ module with 8 100BaseT(X) PoE/PoE+ ports (for IKS-6728A-8PoE Series only)	<b>764,00 €</b>	2~4W
<b>IM-6700A-8SFP</b>	Fast Ethernet module with 8 100BaseSFP slots	<b>515,00 €</b>	2~4W
<b>IM-6700A-8TX</b>	Fast Ethernet module with 8 10/100T(X) ports	<b>230,00 €</b>	2~4W
<b>IMC-101G</b>	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, 0 to 60°C operating temperature	<b>608,00 €</b>	2~4W
<b>IMC-101G-IEX</b>	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, 0 to 60°C operating temperature	<b>701,00 €</b>	8~12W
<b>IMC-101G-T</b>	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, -40 to 75°C operating temperature	<b>712,00 €</b>	2~4W
<b>IMC-101G-T-IEX</b>	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, -40 to 75°C operating temperature	<b>817,00 €</b>	4~8W
<b>IMC-101-M-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, 0 to 60°C operating temperature	<b>333,00 €</b>	2~4W
<b>IMC-101-M-SC-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, 0 to 60°C operating temperature	<b>380,00 €</b>	4~8W
<b>IMC-101-M-SC-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	<b>462,00 €</b>	4~8W
<b>IMC-101-M-SC-T-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, -40 to 75°C operating temperature	<b>529,00 €</b>	4~8W
<b>IMC-101-M-ST</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, 0 to 60°C operating temperature	<b>333,00 €</b>	2~4W
<b>IMC-101-M-ST-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, 0 to 60°C operating temperature	<b>380,00 €</b>	8~12W
<b>IMC-101-M-ST-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	<b>462,00 €</b>	4~8W
<b>IMC-101-M-ST-T-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, -40 to 75°C operating temperature	<b>529,00 €</b>	4~8W
<b>IMC-101-S-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 40 km, 0 to 60°C operating temperature	<b>535,00 €</b>	2~4W
<b>IMC-101-S-SC-80</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, 0 to 60°C operating temperature	<b>1.997,00 €</b>	8~12W
<b>IMC-101-S-SC-80-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, -40 to 75°C operating temperature	<b>2.087,00 €</b>	12~16W
<b>IMC-101-S-SC-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, 0 to 60°C operating temperature	<b>613,00 €</b>	4~8W
<b>IMC-101-S-SC-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	<b>630,00 €</b>	2~4W
<b>IMC-101-S-SC-T-IEX</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, -40 to 75°C operating temperature	<b>725,00 €</b>	4~8W
<b>IMC-21A-M-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -10 to 60°C operating temperature	<b>241,00 €</b>	2~4W
<b>IMC-21A-M-SC-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	<b>311,00 €</b>	2~4W
<b>IMC-21A-M-ST</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -10 to 60°C operating temperature	<b>241,00 €</b>	2~4W
<b>IMC-21A-M-ST-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	<b>311,00 €</b>	2~4W
<b>IMC-21A-S-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -10 to 60°C operating temperature	<b>363,00 €</b>	2~4W
<b>IMC-21A-S-SC-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	<b>479,00 €</b>	2~4W
<b>IMC-21GA</b>	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -10 to 60°C operating temperature	<b>293,00 €</b>	2~4W
<b>IMC-21GA-LX-SC</b>	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -10 to 60°C operating temperature	<b>570,00 €</b>	2~4W
<b>IMC-21GA-LX-SC-T</b>	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -40 to 75°C operating temperature	<b>714,00 €</b>	2~4W

<b>IMC-21GA-SX-SC</b>	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -10 to 60°C operating temperature	<b>413,00 €</b>	2~4W
<b>IMC-21GA-SX-SC-T</b>	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -40 to 75°C operating temperature	<b>512,00 €</b>	4~8W
<b>IMC-21GA-T</b>	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -40 to 75°C operating temperature	<b>369,00 €</b>	2~4W
<b>IMC-21-M-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector	<b>241,00 €</b>	2~4W
<b>IMC-21-M-ST</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector	<b>241,00 €</b>	2~4W
<b>IMC-21-S-SC</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector	<b>340,00 €</b>	2~4W
<b>IMC-P101-M-SC</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, 0 to 60°C operating temperature	<b>653,00 €</b>	4~8W
<b>IMC-P101-M-SC-T</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, -40 to 75°C operating temperature	<b>815,00 €</b>	12~16W
<b>IMC-P101-M-ST</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, 0 to 60°C operating temperature	<b>719,00 €</b>	12~16W
<b>IMC-P101-M-ST-T</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, -40 to 75°C operating temperature	<b>956,00 €</b>	12~16W
<b>IMC-P101-S-SC</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, 0 to 60°C operating temperature	<b>912,00 €</b>	4~8W
<b>IMC-P101-S-SC-T</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, -40 to 75°C operating temperature	<b>1.134,00 €</b>	4~8W
<b>IMC-P101-S-ST</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, 0 to 60°C operating temperature	<b>985,00 €</b>	12~16W
<b>IMC-P101-S-ST-T</b>	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, -40 to 75°C operating temperature	<b>1.329,00 €</b>	12~16W
<b>IM-G7000A-4GSFP</b>	Gigabit Ethernet interface module with 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	<b>987,00 €</b>	2~4W
<b>IM-G7000A-4GTX</b>	Gigabit Ethernet interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	<b>987,00 €</b>	2~4W
<b>IM-G7000A-4PoE</b>	Gigabit Ethernet PoE+ interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	<b>1.537,00 €</b>	8~12W
<b>INJ-24</b>	PoE+ Injector, maximum output of 30 W at 24/48 VDC, 0 to 60°C operating temperature	<b>281,00 €</b>	2~4W
<b>INJ-24A</b>	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, 0 to 60°C operating temperature	<b>454,00 €</b>	2~4W
<b>INJ-24A-T</b>	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, -40 to 75°C operating temperature	<b>572,00 €</b>	2~4W
<b>INJ-24-T</b>	PoE+ Injector, maximum output of 30 W at 24/48 VDC, -40 to 75°C operating temperature	<b>381,00 €</b>	2~4W
<b>ioLogik 2512</b>	Universal controller, 8 Dis, 8 DIOs, Click&Go Plus, -10 to 60°C operating temperature	<b>747,00 €</b>	4~8W
<b>ioLogik 2512-T</b>	Universal controller, 8 Dis, 8 DIOs, Click&Go Plus, -40 to 75°C operating temperature	<b>926,00 €</b>	4~8W
<b>ioLogik 2542</b>	Universal controller, 4 Als, 12 DIOs, Click&Go Plus, -10 to 60°C operating temperature	<b>999,00 €</b>	4~8W
<b>ioLogik 2542-T</b>	Universal controller, 4 Als, 12 DIOs, Click&Go Plus, -40 to 75°C operating temperature	<b>1.165,00 €</b>	4~8W
<b>ioLogik E1210</b>	Universal I/O, 16 Dis, -10 to 60°C operating temperature	<b>249,00 €</b>	2~4W
<b>ioLogik E1210-T</b>	Universal I/O, 16 Dis, -40 to 75°C operating temperature	<b>410,00 €</b>	2~4W
<b>ioLogik E1211</b>	Universal I/O, 16 DOs, -10 to 60°C operating temperature	<b>272,00 €</b>	2~4W
<b>ioLogik E1211-T</b>	Universal I/O, 16 DOs, -40 to 75°C operating temperature	<b>441,00 €</b>	4~8W
<b>ioLogik E1212</b>	Universal I/O, 8 Dis, 8 DIOs, -10 to 60°C operating temperature	<b>272,00 €</b>	2~4W
<b>ioLogik E1212-T</b>	Universal I/O, 8 Dis, 8 DIOs, -40 to 75°C operating temperature	<b>441,00 €</b>	2~4W
<b>ioLogik E1213</b>	Universal I/O, 8 Dis, 4 DOs, 4 DIOs, -10 to 60°C operating temperature	<b>359,00 €</b>	2~4W
<b>ioLogik E1213-T</b>	Universal I/O, 8 Dis, 4 DOs, 4 DIOs, -40 to 75°C operating temperature	<b>481,00 €</b>	4~8W
<b>ioLogik E1214</b>	Universal I/O, 6 Dis, 6 relays, -10 to 60°C operating temperature	<b>281,00 €</b>	2~4W
<b>ioLogik E1214-T</b>	Universal I/O, 6 Dis, 6 relays, -40 to 75°C operating temperature	<b>464,00 €</b>	2~4W
<b>ioLogik E1240</b>	Universal I/O, 8 Als, -10 to 60°C operating temperature	<b>390,00 €</b>	2~4W
<b>ioLogik E1240-T</b>	Universal I/O, 8 Als, -40 to 75°C operating temperature	<b>623,00 €</b>	2~4W
<b>ioLogik E1241</b>	Universal I/O, 4 AOs, -10 to 60°C operating temperature	<b>508,00 €</b>	2~4W
<b>ioLogik E1241-T</b>	Universal I/O, 4 AOs, -40 to 75°C operating temperature	<b>725,00 €</b>	4~8W
<b>ioLogik E1242</b>	Universal I/O, 4 Als, 4 Dis, 4 DIOs, -10 to 60°C operating temperature	<b>422,00 €</b>	2~4W
<b>ioLogik E1242-T</b>	Universal I/O, 4 Als, 4 Dis, 4 DIOs, -40 to 75°C operating temperature	<b>623,00 €</b>	4~8W
<b>ioLogik E1260</b>	Universal I/O, 6 RTDs, -10 to 60°C operating temperature	<b>464,00 €</b>	2~4W
<b>ioLogik E1260-T</b>	Universal I/O, 6 RTDs, -40 to 75°C operating temperature	<b>672,00 €</b>	4~8W
<b>ioLogik E1262</b>	Universal I/O, 8 TCs, -10 to 60°C operating temperature	<b>508,00 €</b>	4~8W
<b>ioLogik E1262-T</b>	Universal I/O, 8 TCs, -40 to 75°C operating temperature	<b>725,00 €</b>	8~12W
<b>ioLogik E1510-M12-CT-T</b>	Rugged I/O, 12 Dis, -40 to 85°C operating temperature, conformal coating	<b>1.850,00 €</b>	12~16W
<b>ioLogik E1510-M12-T</b>	Rugged I/O, 12 Dis, -40 to 85°C operating temperature	<b>1.432,00 €</b>	8~12W
<b>ioLogik E1512-M12-CT-T</b>	Rugged I/O, 4 Dis, 4 DIOs, -40 to 85°C operating temperature, conformal coating	<b>1.809,00 €</b>	12~16W
<b>ioLogik E1512-M12-T</b>	Rugged I/O, 4 Dis, 4 DIOs, -40 to 85°C operating temperature	<b>1.403,00 €</b>	12~16W
<b>ioLogik E2210</b>	Universal controller, 12 Dis, 8 DOs, Click&Go, -10 to 60°C operating temperature	<b>421,00 €</b>	2~4W
<b>ioLogik E2210-T</b>	Universal controller, 12 Dis, 8 DOs, Click&Go, -40 to 75°C operating temperature	<b>644,00 €</b>	4~8W
<b>ioLogik E2212</b>	Universal controller, 8 Dis, 8 DOs, 4 DIOs, Click&Go, -10 to 60°C operating temperature	<b>571,00 €</b>	4~8W
<b>ioLogik E2212-T</b>	Universal controller, 8 Dis, 8 DOs, 4 DIOs, Click&Go, -40 to 75°C operating temperature	<b>829,00 €</b>	8~12W
<b>ioLogik E2214</b>	Universal controller, 6 Dis, 6 relays, Click&Go, -10 to 60°C operating temperature	<b>624,00 €</b>	4~8W
<b>ioLogik E2214-T</b>	Universal controller, 6 Dis, 6 relays, Click&Go, -40 to 75°C operating temperature	<b>890,00 €</b>	4~8W
<b>ioLogik E2240</b>	Universal controller, 8 Als, 2 AOs, Click&Go, -10 to 60°C operating temperature	<b>741,00 €</b>	4~8W
<b>ioLogik E2240-T</b>	Universal controller, 8 Als, 2 AOs, Click&Go, -40 to 75°C operating temperature	<b>1.061,00 €</b>	4~8W
<b>ioLogik E2242</b>	Universal controller, 4 Als, 12 DIOs, Click&Go, -10 to 60°C operating temperature	<b>794,00 €</b>	2~4W

<b>ioLogik E2242-T</b>	Universal controller, 4 AIs, 12 DIos, Click&Go, -40 to 75°C operating temperature	<b>1.001,00 €</b>	4~8W
<b>ioLogik E2260</b>	Universal controller, 6 RTD, 4 DOs, Click&Go, -10 to 60°C operating temperature	<b>712,00 €</b>	8~12W
<b>ioLogik E2260-T</b>	Universal controller, 6 RTD, 4 DOs, Click&Go, -40 to 75°C operating temperature	<b>1.001,00 €</b>	12~16W
<b>ioLogik E2262</b>	Universal controller, 8 TCs, 4 DOs, Click&Go, -10 to 60°C operating temperature	<b>794,00 €</b>	8~12W
<b>ioLogik E2262-T</b>	Universal controller, 8 TCs, 4 DOs, Click&Go, -40 to 75°C operating temperature	<b>1.122,00 €</b>	12~16W
<b>ioLogik R1210</b>	Universal I/O, 16 Dis, -10 to 75°C operating temperature	<b>247,00 €</b>	2~4W
<b>ioLogik R1210-T</b>	Universal I/O, 16 Dis, -40 to 85°C operating temperature	<b>332,00 €</b>	4~8W
<b>ioLogik R1212</b>	Universal I/O, 8 Dis, 8 DIos, -10 to 75°C operating temperature	<b>276,00 €</b>	2~4W
<b>ioLogik R1212-T</b>	Universal I/O, 8 Dis, 8 DIos, -40 to 85°C operating temperature	<b>352,00 €</b>	8~12W
<b>ioLogik R1214</b>	Universal I/O, 6 Dis, 6 relays, -10 to 75°C operating temperature	<b>284,00 €</b>	4~8W
<b>ioLogik R1214-T</b>	Universal I/O, 6 Dis, 6 relays, -40 to 85°C operating temperature	<b>412,00 €</b>	8~12W
<b>ioLogik R1240</b>	Universal I/O, 8 AIs, -10 to 75°C operating temperature	<b>392,00 €</b>	4~8W
<b>ioLogik R1240-T</b>	Universal I/O, 8 AIs, -40 to 85°C operating temperature	<b>532,00 €</b>	8~12W
<b>ioLogik R1241</b>	Universal I/O, 4 AOs, -10 to 75°C operating temperature	<b>486,00 €</b>	4~8W
<b>ioLogik R1241-T</b>	Universal I/O, 4 AOs, -40 to 85°C operating temperature	<b>545,00 €</b>	12~16W
<b>ioMirror E3210</b>	Universal Peer-to-Peer I/O, 8 Dis, 8 DOs, -10 to 60°C operating temperature	<b>389,00 €</b>	4~8W
<b>ioPAC 8600-BM005-T</b>	Module for the ioPAC 8600 Series, 5 slots, -40 to 75°C operating temperature	<b>1.378,00 €</b>	8~12W
<b>ioPAC 8600-BM009-T</b>	Module for the ioPAC 8600 Series, 9 slots, -40 to 75°C operating temperature	<b>2.345,00 €</b>	8~12W
<b>ioPAC 8600-BM012-T</b>	Module for the ioPAC 8600 Series, 12 slots, -40 to 75°C operating temperature	<b>2.984,00 €</b>	8~12W
<b>ioPAC 8600-CPU30-M12-C-T</b>	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, C/C++, -40 to 75°C operating temperature	<b>1.806,00 €</b>	8~12W
<b>ioPAC 8600-CPU30-M12-IEC-T</b>	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	<b>2.373,00 €</b>	8~12W
<b>ioPAC 8600-CPU30-RJ45-C-T</b>	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, C/C++, -40 to 75°C operating temperature	<b>1.701,00 €</b>	8~12W
<b>ioPAC 8600-CPU30-RJ45-IEC-T</b>	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	<b>2.257,00 €</b>	8~12W
<b>ioPAC 8600-PW10-15W-T</b>	Module for the ioPAC 8600 Series, 24-110 VDC, 15 W, dual-power inputs, -40 to 75°C operating temperature	<b>1.239,00 €</b>	12~16W
<b>ioPAC 8600-PW10-30W-T</b>	Module for the ioPAC 8600 Series, 24-110 VDC, 30 W, dual-power inputs, -40 to 75°C operating temperature	<b>1.445,00 €</b>	12~16W
<b>ioThinX 4510</b>	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -20 to 60°C operating temperature	<b>458,00 €</b>	2~4W
<b>ioThinX 4510-T</b>	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -40 to 75°C operating temperature	<b>569,00 €</b>	4~8W
<b>ioThinX 4533-LX</b>	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -20 to 60°C operating temperature	<b>1.199,00 €</b>	4~8W
<b>ioThinX 4533-LX (V1)</b>	ioThinX 4533-LX (V1)	<b>1.061,00 €</b>	16~20W
<b>ioThinX 4533-LX-T</b>	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -40 to 75°C operating temperature	<b>1.345,00 €</b>	4~8W
<b>ioThinX 4533-LX-T (V1)</b>	ioThinX 4533-LX-T (V1)	<b>1.187,00 €</b>	16~20W
<b>ISD-1110-T</b>	7 data line entry surge protector, RS-232, 4 kV surge protection, -40 to 85°C operating temperature	<b>117,00 €</b>	4~8W
<b>ISD-1130-T</b>	4 data line entry surge protector, RS-422/485, 4 kV surge protection, -40 to 85°C operating temperature	<b>104,00 €</b>	4~8W
<b>ISD-1210-T</b>	4 data line advanced surge protector, RS-232, 20 kV surge protection, -40 to 85°C operating temperature	<b>288,00 €</b>	8~12W
<b>ISD-1230-T</b>	4 data line advanced surge protector, RS-422/485, 20 kV surge protection, -40 to 85°C operating temperature	<b>288,00 €</b>	2~4W
<b>LB-DB9F-G-01</b>	Serial loopback DB9 adaptor	<b>7,00 €</b>	12~14W
<b>LB-RJ458P-RS232</b>	RS-232 Loopback Header 8-pin RJ45	<b>6,00 €</b>	12~14W
<b>LB-RJ458P-RS422</b>	RS-422 Loopback Header 8-pin RJ45	<b>6,00 €</b>	12~14W
<b>LIC-IPS-DEVICE-NEW-1Y-1N-MR</b>	1-year device-based IPS license	<b>733,00 €</b>	
<b>LIC-IPS-DEVICE-RENEW-1Y-1N-MR</b>	1-year device-based IPS renewal license	<b>733,00 €</b>	
<b>LIC-IPS-MXsecurity-ADD-XM-XN-DMR</b>	IPS add-on license for MXsecurity with customizable duration and node quantity (minimum 1 month, minimum 1 node)	<b>62,00 €</b>	
<b>LIC-IPS-MXsecurity-NEW-XM-XN-DMR</b>	IPS license for MXsecurity with customizable duration and node quantity (minimum 1 month, minimum 1 node)	<b>62,00 €</b>	
<b>LIC-MRCQL-ADD-1Y-XGB-SR</b>	1-year MRC Quick Link add-on license with customizable data volume (minimum 1 GB)	<b>10,00 €</b>	
<b>LIC-MXsecurity-NEW-XN-SR</b>	MXsecurity perpetual node license with customizable node quantity (minimum 1 node)	<b>126,00 €</b>	
<b>LIC-MXview-ADD-WIRELESS-MR</b>	MXview Wireless module add-on license	<b>1.182,00 €</b>	
<b>LIC-MXview-ADD-XN-SR</b>	MXview add-on license with customizable node quantity (minimum 1 node)	<b>23,00 €</b>	
<b>LIC-MXview-NEW-XN-SR</b>	MXview license with customizable node quantity (minimum 1 node)	<b>23,00 €</b>	
<b>LIC-MXviewOne-ADD-POWER-MR</b>	MXview One add-on license for power substation package	<b>19.830,00 €</b>	
<b>LIC-MXviewOne-ADD-WIRELESS-MR</b>	MXview One add-on license for wireless package	<b>1.221,00 €</b>	
<b>LIC-MXviewOneCM-ADD-POWER-XS-SR</b>	MXview One Central Manager license to enable the Power add-on for MXview One sites, customizable site quantity (minimum 1 site)	<b>19.830,00 €</b>	
<b>LIC-MXviewOneCM-ADD-WIRELESS-XS-SR</b>	MXview One Central Manager license to enable the Wireless add-on for MXview One sites, customizable site quantity (minimum 1 site)	<b>1.221,00 €</b>	
<b>LIC-MXviewOneCM-NEW-XS-SR</b>	MXview One Central Manager site license with customizable site quantity (minimum 1 site)	<b>392,00 €</b>	

<b>LIC-MXviewOne-NEW-XN-SR</b>	MXview One node license with customizable node quantity (minimum 1 node)	<b>67,00 €</b>	
<b>LM-7000H-2GPHR</b>	Gigabit Ethernet module with 2 100/1000BaseT(X) PRP/HSR or 100/1000BaseSFP PRP/HSR combo ports, -40 to 75°C operating temperature	<b>2.364,00 €</b>	4~8W
<b>LM-7000H-4GPOE</b>	Gigabit Ethernet module with 4 10/100/1000BaseT(X) IEEE 802.3af/at PoE+ ports	<b>1.165,00 €</b>	16~20W
<b>LM-7000H-4GSFP</b>	Gigabit Ethernet module with 4 100/1000BaseSFP slots	<b>800,00 €</b>	2~4W
<b>LM-7000H-4GTX</b>	Gigabit Ethernet module with 4 10/100/1000BaseT(X) ports	<b>800,00 €</b>	2~4W
<b>LM-7000H-4POE</b>	Fast Ethernet module with 4 10/100BaseT(X) IEEE 802.3af/at PoE+ ports	<b>795,00 €</b>	8~12W
<b>LM-7000H-4TX</b>	Fast Ethernet module with 4 10/100BaseT(X) ports	<b>479,00 €</b>	2~4W
<b>LM-7000H-DMY</b>	LM-7000H dummy module, 3 pcs	<b>43,00 €</b>	8~12W
<b>LNA-1120-T</b>	Industrial 5G low-noise amplifier, n48, n78, n79, n1, n3, and n7 bands, IP30, -40°C to 70°C operating temperature	<b>180,00 €</b>	8~12W
<b>M12A-4PFF-IP67</b>	M12 cable connector, female 4-pin, A-coded	<b>141,00 €</b>	36~40W
<b>M12A-4PMM-IP67</b>	M12 cable connector, male 4-pin, A-coded	<b>135,00 €</b>	36~40W
<b>M12A-5PFF-IP67-HTG (5 Pin)</b>	Crimp type M12 connector, female 5-pin, A-coded, IP67-rated	<b>141,00 €</b>	16~20W
<b>M12A-5P-IP68</b>	Solder type M12 connector, female 5-pin, A-coded, IP68-rated	<b>23,00 €</b>	20~24W
<b>M12A-5PMM-IP68</b>	5-pin male circular threaded D-coded M12 USB connector, IP68	<b>32,00 €</b>	24~28W
<b>M12A-8PFF-IP68</b>	Field-installation A-coded M12 screw-in 8-pin connector, female connector female PIN	<b>26,00 €</b>	24~28W
<b>M12A-8PMM-IP67</b>	IDC type M12 connector, male 8-pin, A-coded, IP67-rated	<b>141,00 €</b>	28~32W
<b>M12A-8PMM-IP68</b>	Field-installation A-coded screw-in Gigabit Ethernet connector, 8-pin male M12 connector, IP68-rated	<b>17,00 €</b>	10~12W
<b>M12D-4P-IP68</b>	Solder type M12 connector, male 4-pin, D-coded, IP68-rated	<b>23,00 €</b>	20~24W
<b>M12D-4PMM-IP67</b>	IDC type M12 connector, male 4-pin, D-coded, IP67-rated	<b>98,00 €</b>	28~32W
<b>M12K-5PFF-IP65-PxC</b>	Crimp type M12 connector, female 5-pin, K-coded, IP65-rated	<b>160,00 €</b>	20~24W
<b>M12X-8PMM-IP65</b>	M12 cable connector, male 8-pin, X-coded	<b>266,00 €</b>	24~28W
<b>M12X-8PMM-IP67</b>	8-pin male X-coded circular threaded gigabit Ethernet connector, IP67	<b>235,00 €</b>	24~28W
<b>M12X-8PMM-IP67-HTG</b>	Crimp type M12 connector, male 8-pin, X-coded, IP67-rated	<b>153,00 €</b>	16~20W
<b>MAT-5G-PA-SM-2-06-3m</b>	6 dBi MIMO panel antenna with 2 SMA (male) connectors for cellular applications, 3 m cable	<b>527,00 €</b>	12~14W
<b>MAT-5G-PA-SM-3-06-3m</b>	6 dBi MIMO panel antenna with 3 SMA (male) connectors for cellular and GNSS applications, 3 m cable	<b>659,00 €</b>	12~14W
<b>MAT-5G-PA-SM-4-05-1m</b>	5 dBi at 3300 to 5925 MHz, LTE/NR MIMO panel antenna with 4 SMA connectors (male), 4 1-meter cables	<b>617,00 €</b>	10~12W
<b>MAT-WDB-CA-RM-2-0205</b>	2.4/5 GHz, ceiling antenna, 2/5 dBi, MIMO 2x2, RP-SMA-type (male)	<b>95,00 €</b>	10~12W
<b>MAT-WDB-DA-RM-2-0203-1m</b>	2.4/5 GHz, desktop antenna, 2/3 dBi, MIMO 2x2, RP-SMA-type (male), 1 m cable	<b>95,00 €</b>	12~14W
<b>MAT-WDB-PA-NF-2-0708</b>	2.4/5 GHz, panel antenna, 7/8 dBi, MIMO 2x2, N-type (female)	<b>314,00 €</b>	10~12W
<b>MC-1100 DIN-Rail Kit</b>	DIN-rail mounting kit, 4 screws	<b>15,00 €</b>	4~8W
<b>MC-1100 Wallmount Kit</b>	Wall-mounting kit, 4 screws	<b>19,00 €</b>	4~8W
<b>MC-1111-E2-T</b>	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.569,00 €</b>	8~12W
<b>MC-1111-E4-T</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.659,00 €</b>	8~12W
<b>MC-1112-E2-T</b>	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.596,00 €</b>	8~12W
<b>MC-1112-E4-T</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.675,00 €</b>	8~12W
<b>MC-1121-E2-T</b>	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 Dis, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.900,00 €</b>	8~12W
<b>MC-1121-E4-T</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 Dis, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.985,00 €</b>	4~8W
<b>MC-1121-E4-T-W7E</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 1 CFast socket with 32 GB card preinstalled, Windows Embedded Standard 7 preinstalled, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 Dis, 4 DOs, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>2.448,00 €</b>	8~12W
<b>MC-1122-E2-T</b>	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 Dis, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.847,00 €</b>	8~12W
<b>MC-1122-E4-T</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 Dis, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature	<b>1.923,00 €</b>	8~12W
<b>MC-1122-E4-TPM-T</b>	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 Dis, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating temperature, TPM 1.2	<b>1.923,00 €</b>	4~8W
<b>MC-1220 DIN-Rail Kit</b>	DIN-rail mounting kit for MC-1200 with 4 M3 screws	<b>15,00 €</b>	4~8W
<b>MC-1220 Wallmount Kit</b>	Wall-mounting kit for MC-1200 with 4 M3 screws	<b>18,00 €</b>	8~10W



<b>MC-1220-KL1-T-S</b>	Intel® Celeron® 3965U 2C/2T 2.2 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	<b>3.158,00 €</b>	12~16W
<b>MC-1220-KL5-T-S</b>	Intel® Core™ i5-7300U 2C/4T 2.6 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	<b>4.607,00 €</b>	12~16W
<b>MC-1220-KL7-T-S</b>	Intel® Core™ i7-7600U 2C/4T 2.8 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	<b>5.238,00 €</b>	4~8W
<b>MC-1220-LTE Cat4-EU</b>	Wireless package for the MC-1200 Series with LE910C4-NF 4G module and mPCIe module for the EU region	<b>246,00 €</b>	56~60W
<b>MC-1220-WLAN11-AC</b>	Wireless package for the MC-1200 Series with WPEQ-261ACNI(BT) 802.11ac/a/b/g/n Wi-Fi module and mPCIe module	<b>214,00 €</b>	20~24W
<b>MC-3201-TGL1-M-S</b>	Intel® Celeron® 6305E, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 Dis, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>3.552,00 €</b>	8~12W
<b>MC-3201-TGL1-S-S</b>	Intel® Celeron® 6305E, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>2.593,00 €</b>	8~12W
<b>MC-3201-TGL3-M-S</b>	Intel® Core™ i3-1115G4E, 2C/4T, 2.2 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 Dis, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>4.108,00 €</b>	8~12W
<b>MC-3201-TGL3-S-S</b>	Intel® Core™ i3-1115G4E, 2C/4T, 2.2 GHz computer with 2 DisplayPorts, 4 Gigabit LAN ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>3.419,00 €</b>	8~12W
<b>MC-3201-TGL5-M-S</b>	Intel® Core™ i5-1145G7E, 4C/8T, 1.5 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 Dis, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>4.851,00 €</b>	8~12W
<b>MC-3201-TGL5-S-S</b>	Intel® Core™ i5-1145G7E, 4C/8T, 1.5 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>4.175,00 €</b>	8~12W
<b>MC-3201-TGL7-M-S</b>	Intel® Core™ i7-1185G7E, 4C/8T, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 Dis, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>5.034,00 €</b>	8~12W
<b>MC-3201-TGL7-S-S</b>	Intel® Core™ i7-1185G7E, 4C/8T, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	<b>4.785,00 €</b>	8~12W
<b>MC-7410-C1-AC</b>	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power input	<b>4.218,00 €</b>	8~12W
<b>MC-7410-C1-DC</b>	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power input	<b>4.218,00 €</b>	8~12W
<b>MC-7410-C5-AC</b>	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power input	<b>6.228,00 €</b>	8~12W
<b>MC-7410-C5-DC</b>	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power input	<b>6.228,00 €</b>	8~12W
<b>MC-7410-C7-AC</b>	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, AC power input	<b>6.510,00 €</b>	8~12W
<b>MC-7410-C7-DC</b>	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, DC power input	<b>6.648,00 €</b>	8~12W
<b>MC-7420-C1-AC</b>	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 Dis, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power inputs	<b>4.990,00 €</b>	8~12W
<b>MC-7420-C1-DC</b>	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 Dis, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power inputs	<b>4.990,00 €</b>	8~12W
<b>MC-7420-C5-AC</b>	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 Dis, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power inputs	<b>7.005,00 €</b>	8~12W
<b>MC-7420-C5-DC</b>	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 Dis, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power inputs	<b>7.005,00 €</b>	8~12W
<b>MC-7420-C7-AC</b>	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 4 NMEA 0183 ports, 4 Dis, 4 DOs, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, AC power input	<b>7.361,00 €</b>	8~12W
<b>MC-7420-C7-DC</b>	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 4 NMEA 0183 ports, 4 Dis, 4 DOs, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, DC power inputs	<b>7.347,00 €</b>	8~12W
<b>MDR-40-24</b>	DIN-rail 24 VDC power supply with 40W/1.7A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	<b>101,00 €</b>	2~4W
<b>MDR-60-24</b>	DIN-rail 24 VDC power supply with 60W/2.5A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	<b>139,00 €</b>	4~8W

<b>MDS-G4012</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>2.937,00 €</b>	12~16W
<b>MDS-G4012-4XGS-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>6.668,00 €</b>	12~16W
<b>MDS-G4012-L3</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>4.589,00 €</b>	16~20W
<b>MDS-G4012-L3-4XGS-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>8.758,00 €</b>	16~20W
<b>MDS-G4012-L3-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>5.032,00 €</b>	16~20W
<b>MDS-G4012-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>3.353,00 €</b>	16~20W
<b>MDS-G4020</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>3.190,00 €</b>	12~16W
<b>MDS-G4020-4XGS-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>7.978,00 €</b>	12~16W
<b>MDS-G4020-L3</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>4.853,00 €</b>	16~20W
<b>MDS-G4020-L3-4XGS-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>10.053,00 €</b>	16~20W
<b>MDS-G4020-L3-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>5.297,00 €</b>	16~20W
<b>MDS-G4020-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>3.592,00 €</b>	16~20W
<b>MDS-G4028</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>3.417,00 €</b>	12~16W
<b>MDS-G4028-4XGS-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>9.274,00 €</b>	12~16W
<b>MDS-G4028-L3</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	<b>5.087,00 €</b>	16~20W
<b>MDS-G4028-L3-4XGS-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>11.364,00 €</b>	16~20W
<b>MDS-G4028-L3-T</b>	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>5.539,00 €</b>	16~20W
<b>MDS-G4028-T</b>	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	<b>3.819,00 €</b>	16~20W
<b>ME-10-T</b>	1-slot chassis with redundant 12 to 48 VDC power inputs	<b>158,00 €</b>	8~12W
<b>MGate 4101-MB-PBS</b>	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, 0 to 60°C operating temperature	<b>1.014,00 €</b>	4~8W
<b>MGate 4101-MB-PBS-T</b>	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, -40 to 75°C operating temperature	<b>1.224,00 €</b>	8~12W
<b>MGate 4101-MB-PBS</b>	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, 0 to 60°C operating temperature	<b>850,00 €</b>	4~8W
<b>MGate 4101-MB-PBS-T</b>	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, -40 to 75°C operating temperature	<b>1.074,00 €</b>	8~12W
<b>MGate 5101-PBM-MN</b>	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, 0 to 60°C operating temperature	<b>1.465,00 €</b>	4~8W
<b>MGate 5101-PBM-MN-T</b>	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, -40 to 75°C operating temperature	<b>1.759,00 €</b>	8~12W
<b>MGate 5102-PBM-PN</b>	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, 0 to 60°C operating temperature	<b>1.465,00 €</b>	4~8W
<b>MGate 5102-PBM-PN-T</b>	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, -40 to 75°C operating temperature	<b>1.836,00 €</b>	8~12W
<b>MGate 5103</b>	1-port Modbus/EtherNet/IP-to-PROFINET gateway, 0 to 60°C operating temperature	<b>807,00 €</b>	2~4W
<b>MGate 5103-T</b>	1-port Modbus/EtherNet/IP-to-PROFINET gateway, -40 to 75°C operating temperature	<b>1.000,00 €</b>	4~8W
<b>MGate 5105-MB-EIP</b>	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, 0 to 60°C operating temperature	<b>807,00 €</b>	2~4W
<b>MGate 5105-MB-EIP-T</b>	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	<b>1.015,00 €</b>	4~8W
<b>MGate 5109</b>	1-port Modbus-to-DNP3 gateway, 0 to 60°C operating temperature	<b>807,00 €</b>	4~8W
<b>MGate 5109-T</b>	1-port Modbus-to-DNP3 gateway, -40 to 75°C operating temperature	<b>1.015,00 €</b>	4~8W
<b>MGate 5111</b>	1-port Modbus/PROFINET/EtherNet/IP to PROFIBUS Slave gateway, 0 to 60°C operating temperature	<b>807,00 €</b>	2~4W
<b>MGate 5111-T</b>	1-port Modbus/PROFINET/EtherNet/IP-to-PROFIBUS Slave gateway, -40 to 75°C operating temperature	<b>1.000,00 €</b>	8~12W

<b>MGate 5114</b>	1-port Modbus/IEC101 to IEC104 gateway, 0 to 60°C operating temperature	<b>807,00 €</b>	4~8W
<b>MGate 5114-T</b>	1-port Modbus/IEC101 to IEC104 gateway, -40 to 75°C operating temperature	<b>1.000,00 €</b>	8~12W
<b>MGate 5118</b>	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, 0 to 60°C operating temperature	<b>807,00 €</b>	2~4W
<b>MGate 5118-T</b>	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, -40 to 75°C operating temperature	<b>1.015,00 €</b>	4~8W
<b>MGate 5119-T</b>	1-port DNP3/IEC 101/IEC 104/Modbus-to-IEC 61850 gateways, -40 to 75°C operating temperature	<b>1.465,00 €</b>	4~8W
<b>MGate 5121</b>	1-port CANopen/J1939-to-Modbus TCP gateways, -10 to 60°C operating temperature	<b>960,00 €</b>	8~12W
<b>MGate 5121-T</b>	1-port CANopen/J1939-to-Modbus TCP gateways, -40 to 75°C operating temperature	<b>1.196,00 €</b>	8~12W
<b>MGate 5122</b>	1-port CANopen/J1939-to-EtherNet/IP gateways, -10 to 60°C operating temperature	<b>960,00 €</b>	8~12W
<b>MGate 5122-T</b>	1-port CANopen/J1939-to-EtherNet/IP gateways, -40 to 75°C operating temperature	<b>1.196,00 €</b>	8~12W
<b>MGate 5123</b>	1-port CANopen/J1939-to-PROFINET gateways, -10 to 60°C operating temperature	<b>960,00 €</b>	8~12W
<b>MGate 5123-T</b>	1-port CANopen/J1939-to-PROFINET gateways, -40 to 75°C operating temperature	<b>1.196,00 €</b>	8~12W
<b>MGate 5134</b>	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -10 to 60°C operating temperature	<b>807,00 €</b>	4~8W
<b>MGate 5134-T</b>	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -40 to 75°C operating temperature	<b>1.000,00 €</b>	8~12W
<b>MGate 5135</b>	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	<b>807,00 €</b>	4~8W
<b>MGate 5135-T</b>	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	<b>1.000,00 €</b>	4~8W
<b>MGate 5192-T</b>	MGate 5192-T	<b>1.497,00 €</b>	12~16W
<b>MGate 5217I-1200-T</b>	2-port Modbus-to-BACnet/IP gateway, 1200 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	<b>1.498,00 €</b>	4~8W
<b>MGate 5217I-600-T</b>	2-port Modbus-to-BACnet/IP gateway, 600 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	<b>826,00 €</b>	4~8W
<b>MGate 5435</b>	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	<b>1.344,00 €</b>	4~8W
<b>MGate 5435-T</b>	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	<b>1.663,00 €</b>	12~16W
<b>MGate EIP3170</b>	1-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	<b>466,00 €</b>	4~8W
<b>MGate EIP3170I</b>	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	<b>535,00 €</b>	8~12W
<b>MGate EIP3170I-T</b>	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, -40 to 75°C operating temperature	<b>702,00 €</b>	8~12W
<b>MGate EIP3170-T</b>	1-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	<b>605,00 €</b>	8~12W
<b>MGate EIP3270</b>	2-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	<b>770,00 €</b>	8~12W
<b>MGate EIP3270I</b>	2-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	<b>926,00 €</b>	8~12W
<b>MGate EIP3270I-T</b>	2-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	<b>1.000,00 €</b>	8~12W
<b>MGate MB3170</b>	1-port advanced Modbus gateway, 0 to 60°C operating temperature	<b>457,00 €</b>	2~4W
<b>MGate MB3170I</b>	1-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	<b>535,00 €</b>	2~4W
<b>MGate MB3170I-M-SC</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	<b>697,00 €</b>	8~12W
<b>MGate MB3170I-M-SC-T</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	<b>926,00 €</b>	8~12W
<b>MGate MB3170I-S-SC</b>	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	<b>807,00 €</b>	8~12W
<b>MGate MB3170I-S-SC-T</b>	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	<b>1.061,00 €</b>	8~12W
<b>MGate MB3170I-T</b>	1-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	<b>776,00 €</b>	2~4W
<b>MGate MB3170-M-SC</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 60°C operating temperature	<b>597,00 €</b>	4~8W
<b>MGate MB3170-M-SC-T</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	<b>780,00 €</b>	8~12W
<b>MGate MB3170-M-ST</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 60°C operating temperature	<b>597,00 €</b>	4~8W
<b>MGate MB3170-M-ST-T</b>	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	<b>780,00 €</b>	4~8W
<b>MGate MB3170-S-SC</b>	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 60°C operating temperature	<b>679,00 €</b>	4~8W
<b>MGate MB3170-S-SC-T</b>	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	<b>890,00 €</b>	4~8W
<b>MGate MB3170-T</b>	1-port advanced Modbus gateway, -40 to 75°C operating temperature	<b>659,00 €</b>	2~4W
<b>MGate MB3180</b>	1-port standard Modbus gateway	<b>339,00 €</b>	4~8W
<b>MGate MB3270</b>	2-port advanced Modbus gateway, 0 to 60°C operating temperature	<b>850,00 €</b>	2~4W
<b>MGate MB3270I</b>	2-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	<b>1.017,00 €</b>	2~4W
<b>MGate MB3270I-T</b>	2-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	<b>1.313,00 €</b>	2~4W
<b>MGate MB3270-T</b>	2-port advanced Modbus gateway, -40 to 75°C operating temperature	<b>1.107,00 €</b>	4~8W
<b>MGate MB3280</b>	2-port standard Modbus gateway	<b>598,00 €</b>	2~4W
<b>MGate MB3480</b>	4-port standard Modbus gateway	<b>912,00 €</b>	2~4W
<b>MGate MB3660-16-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	<b>2.472,00 €</b>	4~8W
<b>MGate MB3660-16-2DC</b>	Modbus gateway with dual LANs, dual DC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	<b>2.596,00 €</b>	4~8W
<b>MGate MB3660-16-J-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	<b>2.639,00 €</b>	4~8W
<b>MGate MB3660-8-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	<b>1.969,00 €</b>	4~8W
<b>MGate MB3660-8-2DC</b>	Modbus gateway with dual LANs, dual DC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	<b>2.087,00 €</b>	4~8W
<b>MGate MB3660-8-J-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	<b>2.087,00 €</b>	4~8W
<b>MGate MB3660I-16-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	<b>3.578,00 €</b>	4~8W

<b>MGate MB3660I-8-2AC</b>	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	<b>2.400,00 €</b>	4~8W
<b>MiiNePort E1</b>	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 0 to 55°C operating temperature	<b>83,00 €</b>	2~4W
<b>MiiNePort E1-H</b>	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	<b>102,00 €</b>	4~8W
<b>MiiNePort E1-H-ST</b>	Starter Kit for the Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	<b>254,00 €</b>	8~12W
<b>MiiNePort E1-H-T</b>	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, -40°C to 85°C operating temperature	<b>148,00 €</b>	8~12W
<b>MiiNePort E1-SDK</b>	MiiNePort E1 software development kit	<b>420,00 €</b>	8~12W
<b>MiiNePort E1-ST</b>	Starter kit for the MiiNePort E1 Series, module included	<b>247,00 €</b>	8~12W
<b>MiiNePort E1-ST (w/o Module)</b>	Starter kit for the MiiNePort E1 Series, module not included	<b>161,00 €</b>	8~12W
<b>MiiNePort E1-T</b>	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, -40 to 85°C operating temperature	<b>118,00 €</b>	2~4W
<b>MiiNePort E2</b>	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	<b>72,00 €</b>	2~4W
<b>MiiNePort E2-H</b>	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	<b>75,00 €</b>	4~8W
<b>MiiNePort E2-H-ST</b>	Starter kit for the MiiNePort E2-H Series, module included	<b>255,00 €</b>	8~12W
<b>MiiNePort E2-H-T</b>	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	<b>102,00 €</b>	2~4W
<b>MiiNePort E2-SDK</b>	MiiNePort E2 software development kit	<b>420,00 €</b>	8~12W
<b>MiiNePort E2-ST</b>	Starter kit for the MiiNePort E2 Series, module included	<b>250,00 €</b>	8~12W
<b>MiiNePort E2-T</b>	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	<b>99,00 €</b>	2~4W
<b>MiiNePort E3</b>	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	<b>75,00 €</b>	2~4W
<b>MiiNePort E3-H</b>	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	<b>83,00 €</b>	4~8W
<b>MiiNePort E3-H-ST</b>	Starter kit for the MiiNePort E3-H Series, module included	<b>219,00 €</b>	8~12W
<b>MiiNePort E3-H-T</b>	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	<b>109,00 €</b>	4~8W
<b>MiiNePort E3-ST</b>	Starter kit for the MiiNePort E3 Series, module included	<b>215,00 €</b>	8~12W
<b>MiiNePort E3-T</b>	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	<b>106,00 €</b>	4~8W
<b>Mini DB9F-to-TB</b>	DB9 female to terminal block connector	<b>14,00 €</b>	2~4W
<b>Moxa EtherNet/IP Demo Kit</b>	EtherNet/IP Demo Kit	<b>7.282,00 €</b>	12~16W
<b>Moxa PI Demo Kit</b>	PI Demo Kit	<b>10.022,00 €</b>	8~12W
<b>Moxa PROFINET Demo Kit</b>	PROFINET Demo Kit	<b>13.199,00 €</b>	8~12W
<b>MPC-2070-E2-LB-T</b>	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	<b>2.505,00 €</b>	12~16W
<b>MPC-2070-E2-LB-T-W7E</b>	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	<b>3.375,00 €</b>	12~16W
<b>MPC-2070-E2-T</b>	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	<b>2.743,00 €</b>	4~8W
<b>MPC-2070-E2-T-W7E</b>	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	<b>3.611,00 €</b>	12~16W
<b>MPC-2-07-12-VESAMTK</b>	MPC-2-07-12-VESAMTK	<b>43,00 €</b>	4~8W
<b>MPC-2101-E4-CT-T</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.156,00 €</b>	12~16W
<b>MPC-2101-E4-CT-T-LX</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN50155, -40 to 70°C operating temperature, conformal coating	<b>6.530,00 €</b>	12~16W
<b>MPC-2101-E4-CT-T-W7E</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 1000-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>7.263,00 €</b>	12~16W
<b>MPC-2101-E4-LB-CT-T</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>5.756,00 €</b>	12~16W
<b>MPC-2101-E4-LB-CT-T-LX</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.082,00 €</b>	12~16W
<b>MPC-2101-E4-LB-CT-T-W7E</b>	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.768,00 €</b>	12~16W
<b>MPC-2120-E2-LB-T</b>	12-inch panel computer with Intel Atom® E3826 1.46 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	<b>3.345,00 €</b>	12~16W
<b>MPC-2120-E2-LB-T-W7E</b>	12-inch panel computer with Intel Atom® E3826 1.46 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	<b>4.208,00 €</b>	12~16W

<b>MPC-2120-E2-T</b>	12-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	<b>3.813,00 €</b>	12~16W
<b>MPC-2120-E2-T-W7E</b>	12-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	<b>4.395,00 €</b>	12~16W
<b>MPC-2120-E4-LB-T</b>	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	<b>3.613,00 €</b>	12~16W
<b>MPC-2120-E4-LB-T-W7E</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	<b>4.518,00 €</b>	12~16W
<b>MPC-2120-E4-T</b>	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	<b>3.965,00 €</b>	4~8W
<b>MPC-2120-E4-T-W7E</b>	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	<b>4.694,00 €</b>	12~16W
<b>MPC-2121-E4-CT-T</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.555,00 €</b>	12~16W
<b>MPC-2121-E4-CT-T-LX</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>7.037,00 €</b>	12~16W
<b>MPC-2121-E4-CT-T-W7E</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 1000-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>7.796,00 €</b>	12~16W
<b>MPC-2121-E4-LB-CT-T</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.056,00 €</b>	20~24W
<b>MPC-2121-E4-LB-CT-T-LX</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>6.530,00 €</b>	20~24W
<b>MPC-2121-E4-LB-CT-T-W7E</b>	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	<b>7.263,00 €</b>	20~24W
<b>MRC-1002-LTE-EU</b>	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, EU region, -10 to 60°C operating temperature	<b>1.493,00 €</b>	8~12W
<b>MRC-1002-LTE-EU-T</b>	Moxa Remote Connect gateway with 1 LTE cellular port and 2 Ethernet ports, EU region, -30 to 70°C operating temperature	<b>1.643,00 €</b>	12~16W
<b>MRC-1002-LTE-JP</b>	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, Japan region, -10 to 60°C operating temperature	<b>1.493,00 €</b>	8~12W
<b>MRC-1002-LTE-JP-T</b>	Moxa Remote Connect gateway with 1 LTE cellular port and 2 Ethernet ports, Japan region, -30 to 70°C operating temperature	<b>1.643,00 €</b>	12~16W
<b>MRC-1002-LTE-US-T</b>	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, US region, -40 to 70°C operating temperature	<b>1.643,00 €</b>	12~16W
<b>MRC-1002-T</b>	Moxa Remote Connect gateway with 2 Ethernet ports, -40 to 75°C operating temperature	<b>972,00 €</b>	4~8W
<b>MRX-G4064-L3-8XGS</b>	Layer 3 modular managed Gigabit Ethernet switch with 3 slots for 16-port Gigabit Ethernet modules, 8 10GbE SFP+ slots, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	<b>24.623,00 €</b>	12~16W
<b>MRX-Q4064-L3-16XGS</b>	Layer 3 modular managed 2.5 Gigabit Ethernet switch with 16 10GbE SFP+ ports, 3 slots for 16-port Gigabit or 2.5 Gigabit Ethernet modules, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	<b>34.663,00 €</b>	12~16W
<b>MX-AOPC UA Server</b>	OPC UA Server software for converting fieldbus to the OPC UA standard	<b>774,00 €</b>	
<b>MXview Upgrade-50</b>	MXview license expansion for 50 nodes	<b>306,00 €</b>	
<b>MXview-100</b>	MXview license for 100 nodes	<b>1.095,00 €</b>	
<b>MXview-1000</b>	MXview license for 1000 nodes	<b>6.521,00 €</b>	
<b>MXview-2000</b>	MXview license for 2000 nodes	<b>12.408,00 €</b>	
<b>MXview-250</b>	MXview license for 250 nodes	<b>1.990,00 €</b>	
<b>MXview-50</b>	MXview license for 50 nodes	<b>789,00 €</b>	
<b>MXview-500</b>	MXview license for 500 nodes	<b>3.509,00 €</b>	
<b>NAT-102</b>	2-port industrial Network Address Translation (NAT) devices, -10 to 60°C operating temperature	<b>781,00 €</b>	2~4W
<b>NAT-102-T</b>	2-port industrial Network Address Translation (NAT) devices, -40 to 75°C operating temperature	<b>913,00 €</b>	4~8W
<b>NDR-120-24</b>	120 W/5.0 A DIN-rail 24 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	<b>156,00 €</b>	8~12W
<b>NDR-120-48</b>	120 W/2.5 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	<b>156,00 €</b>	8~12W
<b>NDR-240-48</b>	240 W/5.0 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	<b>379,00 €</b>	8~12W
<b>NE-4100-ST</b>	Starter Kit for NE-4100T, NE-4100T-P	<b>136,00 €</b>	8~12W
<b>NE-4100T</b>	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package	<b>80,00 €</b>	2~4W
<b>NE-4100T-P</b>	Programmable 10/100 Mbps embedded serial device servers, wide temp	<b>83,00 €</b>	8~12W
<b>NE-4100T-T</b>	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package, -40 to 75°C operating temperature	<b>105,00 €</b>	4~8W
<b>NE-4110A</b>	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	<b>86,00 €</b>	4~8W
<b>NE-4110A-P</b>	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	<b>105,00 €</b>	8~12W
<b>NE-4110A-T</b>	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector, -40 to 75°C operating temperature	<b>124,00 €</b>	4~8W
<b>NE-4110S</b>	Device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	<b>86,00 €</b>	2~4W
<b>NE-4110S-P</b>	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	<b>96,00 €</b>	8~12W

<b>NE-4110S-T</b>	Device server module for RS-232 devices, supports 10/100BaseT(X) with RJ45 connector, -40 to 75°C operating temperature	<b>114,00 €</b>	4~8W
<b>NE-4110-ST</b>	Starter Kit for NE-4110S, NE-4110A, NE-4110S-P, NE-4110A-P	<b>147,00 €</b>	8~12W
<b>NE-4120A</b>	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	<b>102,00 €</b>	8~12W
<b>NE-4120A-P</b>	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	<b>102,00 €</b>	8~12W
<b>NE-4120A-T</b>	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	<b>156,00 €</b>	4~8W
<b>NE-4120S</b>	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	<b>92,00 €</b>	8~12W
<b>NE-4120S-P</b>	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	<b>92,00 €</b>	8~12W
<b>NE-4120S-T</b>	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	<b>144,00 €</b>	8~12W
<b>NE-4120-ST</b>	Starter Kit for NE-4120S, NE-4120A, NE-4120S-P, NE-4120A-P	<b>153,00 €</b>	8~12W
<b>NM-FX01-M-SC</b>	1 100BaseFX port, multi-mode, SC connector	<b>153,00 €</b>	4~8W
<b>NM-FX01-M-SC-T</b>	1 100BaseFX port, multi-mode, SC connector, -40 to 75°C operating temperature	<b>210,00 €</b>	8~12W
<b>NM-FX01-S-SC</b>	1 100BaseFX port, single-mode, SC connector	<b>190,00 €</b>	4~8W
<b>NM-FX01-S-SC-T</b>	1 100BaseFX port, single-mode, SC connector, -40 to 75°C operating temperature	<b>257,00 €</b>	8~12W
<b>NM-FX02-M-SC</b>	2 100BaseFX ports, multi-mode, SC connector	<b>323,00 €</b>	8~12W
<b>NM-FX02-M-SC-T</b>	2 100BaseFX ports, multi-mode, SC connector, -40 to 75°C operating temperature	<b>440,00 €</b>	8~12W
<b>NM-FX02-S-SC</b>	2 100BaseFX ports, single-mode, SC connector	<b>386,00 €</b>	4~8W
<b>NM-FX02-S-SC-T</b>	2 100BaseFX ports, single-mode, SC connector, -40 to 75°C operating temperature	<b>529,00 €</b>	8~12W
<b>NM-TX01</b>	1 10/100BaseT(X) port	<b>51,00 €</b>	8~12W
<b>NM-TX01-T</b>	1 10/100BaseT(X) port, -40 to 75°C operating temperature	<b>68,00 €</b>	8~12W
<b>NM-TX02</b>	2 10/100BaseT(X) ports	<b>101,00 €</b>	4~8W
<b>NM-TX02-T</b>	2 10/100BaseT(X) ports, -40 to 75°C operating temperature	<b>138,00 €</b>	8~12W
<b>NP21101</b>	DB25 male to DB9 female cable for RS-232 transmission, 30 cm	<b>14,00 €</b>	16~20W
<b>NP21102</b>	DB25 male to DB9 male cable for RS-232 transmission, 30 cm	<b>14,00 €</b>	16~20W
<b>NP21103</b>	DB25 male to terminal block for RS-422/485 transmission	<b>10,00 €</b>	4~8W
<b>NPort 5110</b>	1-port RS-232 device server, 0 to 55°C operating temperature	<b>184,00 €</b>	2~4W
<b>NPort 5110 w/o adapter</b>	1-port RS-232 device server without adapter, 0 to 55°C operating temperature	<b>175,00 €</b>	2~4W
<b>NPort 5110A</b>	1-port RS-232 device server, 0 to 60°C operating temperature	<b>187,00 €</b>	2~4W
<b>NPort 5110A-T</b>	1-port RS-232 device server with surge protection, -40 to 75°C operating temperature	<b>289,00 €</b>	4~8W
<b>NPort 5110-T</b>	1-port RS-232 device server, -40 to 75°C operating temperature	<b>269,00 €</b>	2~4W
<b>NPort 5130</b>	1-port RS-422/485 device server, 0 to 55°C operating temperature	<b>200,00 €</b>	4~8W
<b>NPort 5130A</b>	1-port RS-422/485 device server, 0 to 60°C operating temperature	<b>217,00 €</b>	2~4W
<b>NPort 5130A-T</b>	1-port RS-422/485 device server, -40 to 75°C operating temperature	<b>289,00 €</b>	2~4W
<b>NPort 5150</b>	1-port RS-232/422/485 device server, 0 to 55°C operating temperature	<b>210,00 €</b>	4~8W
<b>NPort 5150 w/o adapter</b>	1-port RS-232/422/485 device server without adapter, 0 to 55°C operating temperature	<b>204,00 €</b>	4~8W
<b>NPort 5150A</b>	1-port RS-232/422/485 device server, 0 to 60°C operating temperature	<b>227,00 €</b>	2~4W
<b>NPort 5150AI-M12</b>	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature	<b>1.015,00 €</b>	8~12W
<b>NPort 5150AI-M12-CT</b>	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	<b>1.315,00 €</b>	12~16W
<b>NPort 5150AI-M12-CT-T</b>	1-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	<b>1.479,00 €</b>	12~16W
<b>NPort 5150AI-M12-T</b>	1-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	<b>1.269,00 €</b>	12~16W
<b>NPort 5150A-T</b>	1-port RS-232/422/485 device server, -40 to 75°C operating temperature	<b>298,00 €</b>	2~4W
<b>NPort 5210</b>	2-port RS-232 device server, 0 to 55°C operating temperature	<b>282,00 €</b>	2~4W
<b>NPort 5210 w/ adapter</b>	2-port RS-232 device server, 0 to 55°C operating temperature without adapter	<b>300,00 €</b>	2~4W
<b>NPort 5210A</b>	2-port RS-232 device server, 0 to 60°C operating temperature	<b>302,00 €</b>	2~4W
<b>NPort 5210A-T</b>	2-port RS-232 device server with surge protection, -40 to 75°C operating temperature	<b>380,00 €</b>	4~8W
<b>NPort 5210-T</b>	2-port RS-232 device server, -40 to 75°C operating temperature	<b>401,00 €</b>	4~8W
<b>NPort 5230</b>	2-port device server with 1 RS-232 port and 1 RS-422/485 port, 0 to 55°C operating temperature	<b>282,00 €</b>	2~4W
<b>NPort 5230 w/ adapter</b>	2-port device server with 1 RS-232 port and 1 RS-422/485 port with adapter, 0 to 55°C operating temperature	<b>300,00 €</b>	4~8W
<b>NPort 5230A</b>	2-port RS-422/485 device server, 0 to 60°C operating temperature	<b>302,00 €</b>	2~4W
<b>NPort 5230A-T</b>	2-port RS-422/485 device server, -40 to 75°C operating temperature	<b>380,00 €</b>	4~8W
<b>NPort 5230-T</b>	2-port device server with 1 RS-232 port and 1 RS-422/485 port, -40 to 75°C operating temperature	<b>393,00 €</b>	4~8W
<b>NPort 5232</b>	2-port RS-422/485 device server, 0 to 55°C operating temperature	<b>282,00 €</b>	2~4W
<b>NPort 5232 w/ adapter</b>	2-port RS-422/485 device server with adapter, 0 to 55°C operating temperature	<b>302,00 €</b>	2~4W
<b>NPort 5232I</b>	2-port RS-422/485 device server with 2 kV optical isolation, 0 to 55°C operating temperature	<b>380,00 €</b>	2~4W
<b>NPort 5232I w/ adapter</b>	2-port RS-422/485 device server with 2 kV optical isolation, with adapter, -40 to 75°C operating temperature	<b>389,00 €</b>	4~8W
<b>NPort 5232I-T</b>	2-port RS-422/485 device server with 2 kV optical isolation, -40 to 75°C operating temperature	<b>483,00 €</b>	4~8W
<b>NPort 5232-T</b>	2-port RS-422/485 device server, -40 to 75°C operating temperature	<b>414,00 €</b>	4~8W
<b>NPort 5250A</b>	2-port RS-232/422/485 device server, 0 to 60°C operating temperature	<b>339,00 €</b>	2~4W
<b>NPort 5250A w/o ADP</b>	2-port RS-232/422/485 device server without adapter, 0 to 60°C operating temperature	<b>326,00 €</b>	4~8W
<b>NPort 5250AI-M12</b>	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	<b>1.194,00 €</b>	8~12W

<b>NPort 5250AI-M12-CT</b>	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	<b>1.551,00 €</b>	12~16W
<b>NPort 5250AI-M12-CT-T</b>	2-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	<b>1.912,00 €</b>	12~16W
<b>NPort 5250AI-M12-T</b>	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	<b>1.496,00 €</b>	12~16W
<b>NPort 5250A-T</b>	2-port RS-232/422/485 device server, -40 to 75°C operating temperature	<b>425,00 €</b>	4~8W
<b>NPort 5410</b>	4-port RS-232 serial device server	<b>719,00 €</b>	2~4W
<b>NPort 5410 w/ adapter</b>	4-port RS-232 serial device server with adapter	<b>734,00 €</b>	2~4W
<b>NPort 5430</b>	4-port RS-422/485 serial device server	<b>822,00 €</b>	2~4W
<b>NPort 5430 w/ adapter</b>	4-port RS-422/485 serial device server without adapter	<b>829,00 €</b>	4~8W
<b>NPort 5430I</b>	4-port RS-422/485 serial device server with 2 kV isolation	<b>1.089,00 €</b>	2~4W
<b>NPort 5430I w/ adapter</b>	4-port RS-422/485 serial device server with 2 kV isolation, with adapter	<b>1.105,00 €</b>	4~8W
<b>NPort 5450</b>	4-port RS-232/422/485 serial device server	<b>862,00 €</b>	2~4W
<b>NPort 5450 w/ adapter</b>	4-port RS-232/422/485 serial device server with adapter	<b>883,00 €</b>	4~8W
<b>NPort 5450AI-M12</b>	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	<b>1.615,00 €</b>	4~8W
<b>NPort 5450AI-M12-CT</b>	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	<b>2.091,00 €</b>	12~16W
<b>NPort 5450AI-M12-CT-T</b>	4-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	<b>2.356,00 €</b>	12~16W
<b>NPort 5450AI-M12-T</b>	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	<b>2.015,00 €</b>	4~8W
<b>NPort 5450I</b>	4-port RS-232/422/485 device server with 2 kV isolation protection	<b>1.224,00 €</b>	4~8W
<b>NPort 5450I w/ adapter</b>	4-port RS-232/422/485 device server with 2 kV isolation protection, with adapter	<b>1.236,00 €</b>	4~8W
<b>NPort 5450I-T</b>	4-port RS-232/422/485 device server with 2 kV isolation protection, -40 to 75°C operating temperature	<b>1.284,00 €</b>	4~8W
<b>NPort 5450-T</b>	4-port RS-232/422/485 device server, -40 to 75°C operating temperature	<b>984,00 €</b>	2~4W
<b>NPort 5610-16</b>	16-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	<b>1.447,00 €</b>	2~4W
<b>NPort 5610-16-48V</b>	16-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	<b>1.583,00 €</b>	4~8W
<b>NPort 5610-8</b>	8-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	<b>1.120,00 €</b>	2~4W
<b>NPort 5610-8-48V</b>	8-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	<b>1.225,00 €</b>	8~12W
<b>NPort 5610-8-DT</b>	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input	<b>1.120,00 €</b>	2~4W
<b>NPort 5610-8-DT w/o adaptor</b>	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	<b>1.002,00 €</b>	4~8W
<b>NPort 5610-8-DT-J</b>	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input	<b>1.120,00 €</b>	4~8W
<b>NPort 5610-8-DT-J w/o adaptor</b>	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	<b>1.002,00 €</b>	8~12W
<b>NPort 5610-8-DT-T</b>	8-port RS-232 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	<b>1.158,00 €</b>	8~12W
<b>NPort 5630-16</b>	16-port RS-422/485 rackmount device server with RJ45 connectors, 100 to 240 VAC power input	<b>1.507,00 €</b>	2~4W
<b>NPort 5630-8</b>	8-port RS-422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	<b>1.195,00 €</b>	4~8W
<b>NPort 5650-16</b>	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	<b>1.672,00 €</b>	2~4W
<b>NPort 5650-16-HV-T</b>	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.622,00 €</b>	8~12W
<b>NPort 5650-16-M-SC</b>	16-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	<b>2.105,00 €</b>	8~12W
<b>NPort 5650-16-S-SC</b>	16-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	<b>2.194,00 €</b>	8~12W
<b>NPort 5650-16-T</b>	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	<b>2.268,00 €</b>	4~8W
<b>NPort 5650-8</b>	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	<b>1.432,00 €</b>	2~4W
<b>NPort 5650-8-DT</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input	<b>1.255,00 €</b>	2~4W
<b>NPort 5650-8-DT w/o adaptor</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	<b>1.125,00 €</b>	4~8W
<b>NPort 5650-8-DT-J</b>	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input	<b>1.255,00 €</b>	4~8W
<b>NPort 5650-8-DT-J w/o adaptor</b>	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	<b>1.125,00 €</b>	4~8W
<b>NPort 5650-8-DT-T</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	<b>1.760,00 €</b>	4~8W
<b>NPort 5650-8-HV-T</b>	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.148,00 €</b>	8~12W
<b>NPort 5650-8-M-SC</b>	8-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	<b>1.686,00 €</b>	8~12W
<b>NPort 5650-8-S-SC</b>	8-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	<b>1.773,00 €</b>	8~12W
<b>NPort 5650-8-T</b>	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	<b>1.791,00 €</b>	4~8W
<b>NPort 5650I-8-DT</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation	<b>1.909,00 €</b>	2~4W
<b>NPort 5650I-8-DT w/o adaptor</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation, without adapter	<b>1.737,00 €</b>	4~8W
<b>NPort 5650I-8-DT-T</b>	8-port RS-232/422/485 desktop device server with DB9 male connectors and 2 kV isolation, -40 to 75°C operating temperature	<b>2.743,00 €</b>	4~8W
<b>NPort 6150</b>	1-port RS-232/422/485 secure device server	<b>372,00 €</b>	2~4W
<b>NPort 6150-T</b>	1-port RS-232/422/485 secure device server, -40 to 75°C operating temperature	<b>451,00 €</b>	4~8W
<b>NPort 6250</b>	2-port RS-232/422/485 to Ethernet secure device server	<b>638,00 €</b>	2~4W

<b>NPort 6250-M-SC</b>	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server	<b>794,00 €</b>	4~8W
<b>NPort 6250-M-SC-T</b>	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	<b>808,00 €</b>	4~8W
<b>NPort 6250-S-SC</b>	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server	<b>890,00 €</b>	8~12W
<b>NPort 6250-S-SC-T</b>	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	<b>910,00 €</b>	8~12W
<b>NPort 6250-T</b>	2-port RS-232/422/485 to Ethernet secure device server, -40 to 75°C operating temperature	<b>719,00 €</b>	4~8W
<b>NPort 6450</b>	4-port RS-232/422/485 to Ethernet secure serial port server	<b>822,00 €</b>	2~4W
<b>NPort 6450-T</b>	4-port secure device server, RS-232/422/485 to Ethernet, -40 to 75°C operating temperature	<b>1.005,00 €</b>	4~8W
<b>NPort 6610-16</b>	16-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	<b>1.956,00 €</b>	4~8W
<b>NPort 6610-16-48V</b>	16-port RS-232 to Ethernet secure device server, ±48 VDC input	<b>1.984,00 €</b>	8~12W
<b>NPort 6610-32</b>	32-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	<b>2.435,00 €</b>	4~8W
<b>NPort 6610-32-48V</b>	32-port RS-232 to Ethernet secure device server, ±48 VDC input	<b>2.682,00 €</b>	8~12W
<b>NPort 6610-8</b>	8-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	<b>1.493,00 €</b>	4~8W
<b>NPort 6610-8-48V</b>	8-port RS-232 to Ethernet secure device server, ±48 VDC input	<b>1.569,00 €</b>	8~12W
<b>NPort 6650-16</b>	16-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	<b>1.773,00 €</b>	2~4W
<b>NPort 6650-16-48V</b>	16-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	<b>1.775,00 €</b>	4~8W
<b>NPort 6650-16-HV-T</b>	16-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.459,00 €</b>	8~12W
<b>NPort 6650-16-T</b>	16-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	<b>2.831,00 €</b>	4~8W
<b>NPort 6650-32</b>	32-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	<b>2.538,00 €</b>	2~4W
<b>NPort 6650-32-48V</b>	32-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	<b>2.672,00 €</b>	4~8W
<b>NPort 6650-32-HV-T</b>	32-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.923,00 €</b>	8~12W
<b>NPort 6650-8</b>	8-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	<b>1.746,00 €</b>	4~8W
<b>NPort 6650-8-48V</b>	8-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	<b>1.612,00 €</b>	4~8W
<b>NPort 6650-8-HV-T</b>	8-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	<b>2.163,00 €</b>	8~12W
<b>NPort 6650-8-T</b>	8-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	<b>2.178,00 €</b>	4~8W
<b>NPort IA-5150</b>	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	<b>401,00 €</b>	2~4W
<b>NPort IA5150A</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	<b>436,00 €</b>	2~4W
<b>NPort IA5150AI</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	<b>561,00 €</b>	4~8W
<b>NPort IA5150A-IEEX</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, 0 to 60°C operating temperature	<b>497,00 €</b>	8~12W
<b>NPort IA5150AI-IEEX</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, 0 to 60°C operating temperature	<b>630,00 €</b>	8~12W
<b>NPort IA5150AI-T</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	<b>712,00 €</b>	4~8W
<b>NPort IA5150AI-T-IEEX</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, -40 to 75°C operating temperature	<b>794,00 €</b>	12~16W
<b>NPort IA5150A-T</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	<b>543,00 €</b>	4~8W
<b>NPort IA5150A-T-IEEX</b>	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, -40 to 75°C operating temperature	<b>630,00 €</b>	8~12W
<b>NPort IA-5150I</b>	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 kV optical isolation, 0 to 55°C operating temperature	<b>521,00 €</b>	4~8W
<b>NPort IA-5150I-M-SC</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	<b>748,00 €</b>	8~12W
<b>NPort IA-5150I-M-SC-T</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	<b>970,00 €</b>	12~16W
<b>NPort IA-5150I-S-SC</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	<b>829,00 €</b>	8~12W
<b>NPort IA-5150I-S-SC-T</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	<b>1.074,00 €</b>	12~16W
<b>NPort IA-5150I-T</b>	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 kV optical isolation, -40 to 75°C operating temperature	<b>666,00 €</b>	4~8W
<b>NPort IA-5150-M-SC</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 55°C operating temperature	<b>561,00 €</b>	4~8W
<b>NPort IA-5150-M-SC-T</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	<b>788,00 €</b>	12~16W
<b>NPort IA-5150-M-ST</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 55°C operating temperature	<b>561,00 €</b>	8~12W
<b>NPort IA-5150-M-ST-T</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	<b>785,00 €</b>	12~16W
<b>NPort IA-5150-S-SC</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 55°C operating temperature	<b>630,00 €</b>	4~8W
<b>NPort IA-5150-S-SC-T</b>	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	<b>897,00 €</b>	4~8W
<b>NPort IA-5150-T</b>	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	<b>535,00 €</b>	4~8W



<b>NPort IA-5250</b>	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	<b>443,00 €</b>	2~4W
<b>NPort IA5250A</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	<b>483,00 €</b>	2~4W
<b>NPort IA5250AI</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	<b>687,00 €</b>	2~4W
<b>NPort IA5250A-IEEX</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEx, 0 to 60°C operating temperature	<b>556,00 €</b>	8~12W
<b>NPort IA5250AI-IEEX</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEx, 0 to 60°C operating temperature	<b>701,00 €</b>	8~12W
<b>NPort IA5250AI-T</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	<b>849,00 €</b>	2~4W
<b>NPort IA5250AI-T-IEEX</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEx, -40 to 75°C operating temperature	<b>959,00 €</b>	12~16W
<b>NPort IA5250A-T</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	<b>598,00 €</b>	4~8W
<b>NPort IA5250A-T-IEEX</b>	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEx, -40 to 75°C operating temperature	<b>693,00 €</b>	12~16W
<b>NPort IA-5250I</b>	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, 0 to 55°C operating temperature	<b>600,00 €</b>	4~8W
<b>NPort IA-5250I-T</b>	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, -40 to 75°C operating temperature	<b>770,00 €</b>	12~16W
<b>NPort IA-5250-T</b>	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	<b>592,00 €</b>	4~8W
<b>NPort IA5450A</b>	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	<b>816,00 €</b>	2~4W
<b>NPort IA5450AI</b>	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation protection	<b>1.149,00 €</b>	2~4W
<b>NPort IA5450AI-T</b>	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation protection	<b>1.448,00 €</b>	2~4W
<b>NPort IA5450A-T</b>	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	<b>1.016,00 €</b>	2~4W
<b>NPort P5150A</b>	1-port RS-232/422/485 PoE device server, 0 to 60°C operating temperature	<b>371,00 €</b>	2~4W
<b>NPort P5150A-T</b>	1-port RS-232/422/485 PoE device server, -40 to 75°C operating temperature	<b>464,00 €</b>	4~8W
<b>NPort S8455I</b>	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, 0 to 60°C operating temperature	<b>1.569,00 €</b>	8~12W
<b>NPort S8455I-MM-SC</b>	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	<b>1.984,00 €</b>	4~8W
<b>NPort S8455I-MM-SC-T</b>	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	<b>2.160,00 €</b>	4~8W
<b>NPort S8455I-SS-SC</b>	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	<b>2.400,00 €</b>	4~8W
<b>NPort S8455I-SS-SC-T</b>	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	<b>2.772,00 €</b>	4~8W
<b>NPort S8455I-T</b>	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, -40 to 75°C operating temperature	<b>1.937,00 €</b>	4~8W
<b>NPort S9450I-2M-SC-HV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	<b>2.876,00 €</b>	8~12W
<b>NPort S9450I-2M-SC-WV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	<b>2.876,00 €</b>	8~12W
<b>NPort S9450I-2M-ST-HV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	<b>2.876,00 €</b>	4~8W
<b>NPort S9450I-2M-ST-WV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	<b>2.876,00 €</b>	8~12W
<b>NPort S9450I-2S-SC-HV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	<b>3.444,00 €</b>	8~12W
<b>NPort S9450I-2S-SC-WV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	<b>3.444,00 €</b>	8~12W
<b>NPort S9450I-2S-ST-HV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	<b>3.444,00 €</b>	8~12W
<b>NPort S9450I-2S-ST-WV-T</b>	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	<b>3.444,00 €</b>	8~12W
<b>NPort S9450I-HV-T</b>	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	<b>2.148,00 €</b>	8~12W
<b>NPort S9450I-WV-T</b>	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 24/48 VDC, -40 to 85°C operating temperature	<b>2.148,00 €</b>	8~12W
<b>NPort S9650I-16-2HV-E-T</b>	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	<b>4.457,00 €</b>	4~8W
<b>NPort S9650I-16-2HV-MSC-T</b>	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	<b>4.920,00 €</b>	8~12W
<b>NPort S9650I-16-2HV-SSC-T</b>	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	<b>5.785,00 €</b>	8~12W
<b>NPort S9650I-16B-2HV-IRIG-T</b>	16-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	<b>5.307,00 €</b>	8~12W

<b>NPort S9650I-16F-2HV-E-T</b>	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	<b>4.845,00 €</b>	8~12W
<b>NPort S9650I-16F-2HV- MSC-T</b>	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	<b>5.307,00 €</b>	8~12W
<b>NPort S9650I-16F-2HV- SSC-T</b>	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	<b>6.247,00 €</b>	8~12W
<b>NPort S9650I-8-2HV-E-T</b>	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	<b>3.757,00 €</b>	8~12W
<b>NPort S9650I-8-2HV- MSC-T</b>	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	<b>4.144,00 €</b>	8~12W
<b>NPort S9650I-8-2HV- SSC-T</b>	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	<b>4.993,00 €</b>	8~12W
<b>NPort S9650I-8B-2HV- IRIG-T</b>	8-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	<b>4.391,00 €</b>	8~12W
<b>NPort S9650I-8F-2HV-E-T</b>	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	<b>4.055,00 €</b>	8~12W
<b>NPort S9650I-8F-2HV- MSC-T</b>	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	<b>4.531,00 €</b>	8~12W
<b>NPort S9650I-8F-2HV- SSC-T</b>	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	<b>5.162,00 €</b>	8~12W
<b>NPort W2150A-CN</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN CN band, 12 to 48 VDC, 0 to 55°C operating temperature, with CN plug	<b>454,00 €</b>	8~12W
<b>NPort W2150A-EU</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, 0 to 55°C operating temperature, with EU plug	<b>454,00 €</b>	2~4W
<b>NPort W2150A-JP</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN JP band, 12 to 48 VDC, 0 to 55°C operating temperature, with JP plug	<b>454,00 €</b>	8~12W
<b>NPort W2150A-T-CN</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN CN band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>701,00 €</b>	8~12W
<b>NPort W2150A-T-EU</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>701,00 €</b>	4~8W
<b>NPort W2150A-T-JP</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN JP band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>701,00 €</b>	8~12W
<b>NPort W2150A-T-US</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN US band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>701,00 €</b>	8~12W
<b>NPort W2150A-US</b>	1-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN US band, 12 to 48 VDC, 0 to 55°C operating temperature, with US plug	<b>454,00 €</b>	4~8W
<b>NPort W2150A-W4-EU</b>	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug, 12 to 48 VDC, 0 to 55°C operating temperature	<b>454,00 €</b>	4~8W
<b>NPort W2150A-W4-T-EU</b>	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>701,00 €</b>	12~16W
<b>NPort W2250A-CN</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN CN band, 12 to 48 VDC, 0 to 55°C operating temperature, with CN plug	<b>556,00 €</b>	8~12W
<b>NPort W2250A-EU</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, 0 to 55°C operating temperature, with EU plug	<b>556,00 €</b>	4~8W
<b>NPort W2250A-JP</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN JP band, 12 to 48 VDC, 0 to 55°C operating temperature, with JP plug	<b>556,00 €</b>	8~12W
<b>NPort W2250A-T-CN</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN CN band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>776,00 €</b>	8~12W
<b>NPort W2250A-T-EU</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>776,00 €</b>	8~12W
<b>NPort W2250A-T-JP</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN JP band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>776,00 €</b>	8~12W
<b>NPort W2250A-T-US</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN US band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>776,00 €</b>	8~12W
<b>NPort W2250A-US</b>	2-port wireless device server, 3-in-1, 802.11a/b/g/n WLAN US band, 12 to 48 VDC, 0 to 55°C operating temperature, with US plug	<b>556,00 €</b>	4~8W
<b>NPort W2250A-W4-EU</b>	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug, 12 to 48 VDC, 0 to 55°C operating temperature	<b>556,00 €</b>	4~8W
<b>NPort W2250A-W4-T-EU</b>	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	<b>776,00 €</b>	8~12W
<b>OBU-102-SS-LC</b>	2-channel optical fiber bypass unit with 4 single-mode ports, LC, -20 to 70°C operating temperature	<b>1.786,00 €</b>	8~12W
<b>OBU-102-SS-SC</b>	2-channel optical fiber bypass unit with 4 single-mode ports, SC, -20 to 70°C operating temperature	<b>1.786,00 €</b>	8~12W
<b>OBU-102-SS-ST</b>	2-channel optical fiber bypass unit with 4 single-mode ports, ST, -20 to 70°C operating temperature	<b>1.786,00 €</b>	8~12W
<b>OnCell 3120-LTE-1-AU</b>	Industrial LTE Cat. 1 cellular gateway, B3/B5/B8/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	<b>850,00 €</b>	8~12W
<b>OnCell 3120-LTE-1-AU-T</b>	Industrial LTE Cat. 1 cellular gateway, B3/B5/B8/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>911,00 €</b>	12~16W

<b>OnCell 3120-LTE-1-EU</b>	Industrial LTE Cat. 1 cellular gateway, B1/B3/B8/B20/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	<b>850,00 €</b>	4~8W
<b>OnCell 3120-LTE-1-EU-T</b>	Industrial LTE Cat. 1 cellular gateway, B1/B3/B8/B20/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>911,00 €</b>	4~8W
<b>OnCell 3120-LTE-1-US</b>	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/14/B66/B71, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	<b>850,00 €</b>	8~12W
<b>OnCell 3120-LTE-1-US-T</b>	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/14/B66/B71, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>911,00 €</b>	4~8W
<b>OnCell G4302-LTE4-AU</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	<b>1.631,00 €</b>	4~8W
<b>OnCell G4302-LTE4-AU-T</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>1.759,00 €</b>	4~8W
<b>OnCell G4302-LTE4-EU</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	<b>1.631,00 €</b>	2~4W
<b>OnCell G4302-LTE4-EU-T</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>1.759,00 €</b>	2~4W
<b>OnCell G4302-LTE4-JP</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	<b>1.631,00 €</b>	8~12W
<b>OnCell G4302-LTE4-JP-T</b>	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>1.759,00 €</b>	12~16W
<b>OnCell G4302-LTE4-US</b>	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	<b>1.631,00 €</b>	4~8W
<b>OnCell G4302-LTE4-US-T</b>	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	<b>1.759,00 €</b>	4~8W
<b>OPT 8A</b>	M62 to 8 x DB25 female connection box with DB62 male to DB62 female serial cable	<b>133,00 €</b>	4~8W
<b>OPT 8A+</b>	VHDCI 68 to 8 x DB25 female connection box	<b>139,00 €</b>	4~8W
<b>OPT 8B</b>	M62 to 8 x DB25 male connection box with DB62 male to DB62 female cable, 1.5 m	<b>133,00 €</b>	4~8W
<b>OPT 8B+</b>	VHDCI 68 to 8 x DB25 male connection box	<b>139,00 €</b>	4~8W
<b>OPT 8S</b>	M62 to 8 x DB25 female connection box with surge protection and a DB62 male to DB62 male cable, 1.5 m	<b>285,00 €</b>	8~12W
<b>OPT 8S+</b>	VHDCI 68 to 8 x DB25 female connection box with surge protection	<b>285,00 €</b>	8~12W
<b>OPT8-M9</b>	M62 to 8 x DB9 male connection box, DB62 male to DB62 female cable, 1.5 m	<b>145,00 €</b>	4~8W
<b>OPT8-M9+</b>	VHDCI 68 to 8 x DB9 male connection box	<b>170,00 €</b>	2~4W
<b>OPT8-RJ45</b>	M62 to 8 x RJ45 (8-pin) connection box, 30 cm	<b>129,00 €</b>	8~12W
<b>OPT8-RJ45+</b>	VHDCI 68 to 8 x RJ45 (8-pin) connection box	<b>204,00 €</b>	4~8W
<b>PK-DC2DOF</b>	Pole mounting kit	<b>57,00 €</b>	12~14W
<b>PK-DC2DOF-02</b>	PK-DC2DOF-02	<b>65,00 €</b>	4~8W
<b>Plate-1</b>	Chassis converter bracket accessory package, 9 brackets, 9 screws (FMS M3 X 6 mm)	<b>114,00 €</b>	4~8W
<b>PM-7500-2GTXSFP</b>	Gigabit Ethernet module with 2 100/1000BaseSFP slots or 2 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>338,00 €</b>	8~12W
<b>PM-7500-2MSC</b>	Fast Ethernet module with 2 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>493,00 €</b>	8~12W
<b>PM-7500-2MST</b>	Fast Ethernet module with 2 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>493,00 €</b>	8~12W
<b>PM-7500-2SSC</b>	Fast Ethernet module with 2 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>740,00 €</b>	8~12W
<b>PM-7500-4GTXSFP</b>	Gigabit Ethernet module with 4 100/1000BaseSFP slots or 4 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>672,00 €</b>	4~8W
<b>PM-7500-4MSC</b>	Fast Ethernet module with 4 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>850,00 €</b>	8~12W
<b>PM-7500-4MST</b>	Fast Ethernet module with 4 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>850,00 €</b>	8~12W
<b>PM-7500-4SSC</b>	Fast Ethernet module with 4 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	<b>1.388,00 €</b>	8~12W
<b>POS-104UL w/o Cable</b>	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature, without cable	<b>166,00 €</b>	8~12W
<b>POS-104UL-DB9M</b>	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature (DB9 male cable included)	<b>181,00 €</b>	8~12W
<b>POS-104UL-T</b>	4-port RS-232 low-profile Universal PCI board with serial port power, -40 to 85°C operating temperature	<b>210,00 €</b>	8~12W
<b>PT-508-MM-LC-24</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	<b>1.775,00 €</b>	4~8W
<b>PT-508-MM-LC-48</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	<b>1.775,00 €</b>	8~12W
<b>PT-508-MM-LC-HV</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>1.732,00 €</b>	8~12W
<b>PT-508-MM-SC-24</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	<b>1.775,00 €</b>	4~8W
<b>PT-508-MM-SC-48</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (48 VDC), -40 to 85°C operating temperature	<b>1.775,00 €</b>	8~12W
<b>PT-508-MM-SC-HV</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>1.732,00 €</b>	4~8W
<b>PT-508-MM-ST-24</b>	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with ST connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	<b>1.775,00 €</b>	4~8W





<b>PT-7528-8MSC-16TX-4GSFP-HV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>4.872,00 €</b>	8~12W
<b>PT-7528-8MSC-16TX-4GSFP-HV-HV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>5.215,00 €</b>	8~12W
<b>PT-7528-8MSC-16TX-4GSFP-WV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	<b>4.872,00 €</b>	12~16W
<b>PT-7528-8MSC-16TX-4GSFP-WV-WV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	<b>5.215,00 €</b>	12~16W
<b>PT-7528-8MST-16TX-4GSFP-HV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>4.872,00 €</b>	12~16W
<b>PT-7528-8MST-16TX-4GSFP-HV-HV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>5.215,00 €</b>	12~16W
<b>PT-7528-8MST-16TX-4GSFP-WV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 1 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	<b>4.872,00 €</b>	12~16W
<b>PT-7528-8MST-16TX-4GSFP-WV-WV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (MST), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	<b>5.215,00 €</b>	12~16W
<b>PT-7528-8SSC-16TX-4GSFP-HV-HV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (SSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>6.317,00 €</b>	8~12W
<b>PT-7528-8SSC-16TX-4GSFP-WV-WV</b>	IEC 61850-3 managed rackmount Ethernet switch with 8 100BaseFX ports (SSC), 16 10/100BaseT(X) ports, and 4 1000BaseSFP ports, for a total of up to 28 ports, 2 isolated power supply (18 to 72 VDC), -40 to 85°C operating temperature	<b>6.317,00 €</b>	8~12W
<b>PTC-101-M12-S-SC-LV-CT-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, M12 connector, single-mode with SC connector, 20 to 72 VDC power input, -40 to 85°C operating temperature, conformal coating	<b>1.268,00 €</b>	12~16W
<b>PTC-101-M12-S-SC-LV-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, M12 connector, single-mode with SC connector, 20 to 72 VDC power input, -40 to 85°C operating temperature	<b>1.178,00 €</b>	12~16W
<b>PTC-101-M12-S-ST-LV-CT-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, M12 connector, single-mode with ST connector, 20 to 72 VDC power input, -40 to 85°C operating temperature, conformal coating	<b>1.268,00 €</b>	12~16W
<b>PTC-101-M12-S-ST-LV-T</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, M12 connector, single-mode with ST connector, 20 to 72 VDC power input, -40 to 85°C operating temperature	<b>1.178,00 €</b>	12~16W
<b>PTC-101-M-LC-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with LC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>755,00 €</b>	4~8W
<b>PTC-101-M-LC-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with LC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>755,00 €</b>	4~8W
<b>PTC-101-M-SC-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with SC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>755,00 €</b>	4~8W
<b>PTC-101-M-SC-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with SC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>755,00 €</b>	12~16W
<b>PTC-101-M-ST-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>755,00 €</b>	4~8W
<b>PTC-101-M-ST-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode with ST connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>755,00 €</b>	12~16W
<b>PTC-101-S-LC-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with L connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	4~8W
<b>PTC-101-S-LC-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with LC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	4~8W
<b>PTC-101-S-SC-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	8~12W
<b>PTC-101-S-SC-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	12~16W
<b>PTC-101-S-ST-HV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	8~12W
<b>PTC-101-S-ST-LV</b>	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	<b>1.045,00 €</b>	12~16W
<b>PT-G503-PHR-PTP-HV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	<b>3.220,00 €</b>	4~8W
<b>PT-G503-PHR-PTP-WV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (24/48 VDC), -40 to 85°C operating temperature	<b>3.731,00 €</b>	4~8W
<b>PT-G510-4GTX4GSFP-PHR-HV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	12~16W
<b>PT-G510-4GTX4GSFP-PHR-HV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G510-4GTX4GSFP-PHR-WV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	12~16W

<b>PT-G510-4GTX4GSFP-PHR-WV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G510-8GSFP-PHR-HV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	12~16W
<b>PT-G510-8GSFP-PHR-HV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G510-8GSFP-PHR-WV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	12~16W
<b>PT-G510-8GSFP-PHR-WV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G510-8GTX-PHR-HV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	8~12W
<b>PT-G510-8GTX-PHR-HV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G510-8GTX-PHR-WV</b>	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	<b>3.580,00 €</b>	8~12W
<b>PT-G510-8GTX-PHR-WV-CT</b>	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	<b>4.507,00 €</b>	12~16W
<b>PT-G7728</b>	Layer 2 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	<b>4.132,00 €</b>	2~4W
<b>PT-G7828</b>	Layer 3 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	<b>4.990,00 €</b>	4~8W
<b>PWC-C13AU-3B-183</b>	Power cord with AU plug, 1.83 m	<b>10,00 €</b>	4~8W
<b>PWC-C13CN-3B-183</b>	Power cord with three-prong CN plug, 1.83 m	<b>13,00 €</b>	56~60W
<b>PWC-C13EU-3B-183</b>	Power cord with EU/KR plug, 1.83 m	<b>10,00 €</b>	10~12W
<b>PWC-C13JP-3B-183</b>	Power cord with JP plug plug, 7A/125V, 1.83 m	<b>13,00 €</b>	4~8W
<b>PWC-C13UK-3B-183</b>	Power cord with UK plug, 1.83 m	<b>17,00 €</b>	4~8W
<b>PWC-C13US-3B-183</b>	Power cord with US plug, 1.83 m	<b>10,00 €</b>	4~8W
<b>PWC-C15CN-3B-183</b>	C15 power cord with CN plug, 1.83 m	<b>26,00 €</b>	10~12W
<b>PWC-C15EU-3B-183</b>	C15 power cord with EU plug, 1.83 m	<b>26,00 €</b>	10~12W
<b>PWC-C15US-3B-183</b>	C15 power cord with US plug, 1.83 m	<b>26,00 €</b>	4~8W
<b>PWR-100-LV</b>	Power module for the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, 9.6 to 60 VDC operating voltage	<b>409,00 €</b>	4~8W
<b>PWR-101-LV-BP-I</b>	Power module for PoE models in the EDS-4000/G4000 Series with 48 VDC redundant dual inputs, power isolation, 44 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	<b>544,00 €</b>	4~8W
<b>PWR-103-LV-VB-I</b>	Power module for PoE models in the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, power isolation, 12 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	<b>952,00 €</b>	4~8W
<b>PWR-105-HV-I</b>	Power module for the EDS-4000/G4000 Series with 110/220 VDC/VAC single input, power isolation, 88 to 300 VDC or 85 to 264 VAC operating voltage	<b>680,00 €</b>	4~8W
<b>PWR-12050-AU-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-AU-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-CN-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-CN-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-EU-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-EU-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-IN-S2</b>	PWR-12050-IN-S2	<b>39,00 €</b>	20~24W
<b>PWR-12050-KR-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-KR-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-UK-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-UK-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	<b>39,00 €</b>	16~20W
<b>PWR-12050-USJP-S1</b>	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12050-USJP-S2</b>	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	<b>39,00 €</b>	20~24W
<b>PWR-12150-AU-SA-T</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, -40 to 75°C operating temperature	<b>48,00 €</b>	28~32W
<b>PWR-12150-CN-S2</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, China (CN) plug, 0 to 40°C operating temperature	<b>29,00 €</b>	
<b>PWR-12150-CN-SA-T</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, -40 to 75°C operating temperature	<b>48,00 €</b>	28~32W
<b>PWR-12150-EU-SA-T</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, -40 to 75°C operating temperature	<b>48,00 €</b>	28~32W
<b>PWR-12150-IN-SA-T</b>	PWR-12150-IN-SA-T	<b>49,00 €</b>	28~32W
<b>PWR-12150-UK-SA-T</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, -40 to 75°C operating temperature	<b>48,00 €</b>	28~32W
<b>PWR-12150-USJP-SA-T</b>	Locking barrel plug, 12 VDC 1.5 A, 100 to 240 VAC, US/JP plug, -40 to 75°C operating temperature	<b>50,00 €</b>	28~32W
<b>PWR-12150-WPAU-S2</b>	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPAU-S4</b>	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPCN-S2</b>	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPCN-S4</b>	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPEU-S2</b>	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPEU-S4</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPIN-S2</b>	PWR-12150-WPIN-S2	<b>39,00 €</b>	28~32W
<b>PWR-12150-WPIN-S4</b>	PWR-12150-WPIN-S4	<b>39,00 €</b>	28~32W
<b>PWR-12150-WPKR-S4</b>	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPUK-S2</b>	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W



<b>PWR-12150-WPUK-S4</b>	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPUSJP-S2</b>	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12150-WPUSJP-S4</b>	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	<b>39,00 €</b>	24~28W
<b>PWR-12300-WPAU-S2</b>	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	<b>70,00 €</b>	24~28W
<b>PWR-12300-WPCN-S2</b>	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	<b>70,00 €</b>	24~28W
<b>PWR-12300-WPEU-S2</b>	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	<b>70,00 €</b>	24~28W
<b>PWR-12300-WPUK-S2</b>	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	<b>70,00 €</b>	24~28W
<b>PWR-12300-WPUSJP-S2</b>	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	<b>70,00 €</b>	24~28W
<b>PWR-12500-DT-S1</b>	PWR-12500-DT-S1	<b>56,00 €</b>	32~36W
<b>PWR-190-AC</b>	110 to 240 VAC power supply for the TRC-190-AC	<b>289,00 €</b>	4~8W
<b>PWR-190-DC-48</b>	36 to 53 VDC power supply for the TRC-190-DC-48	<b>522,00 €</b>	8~12W
<b>PWR-2190-AC</b>	110 to 240 VAC power supply for the TRC-2190-AC	<b>301,00 €</b>	8~12W
<b>PWR-2190-DC-48V</b>	36 to 53 VDC power supply for the TRC-2190-DC-48	<b>537,00 €</b>	8~12W
<b>PWR-24250-DT-S1</b>	Desktop power supply (requires power cord), 24 VDC, 2.5 A, 100 to 240 VAC, 0 to 40°C operating temperature	<b>80,00 €</b>	32~36W
<b>PWR-300-HVA-IF</b>	Isolated power supply module (110/220 VAC/VDC) with system power input, AC power inlet, intake fan	<b>1.011,00 €</b>	24~28W
<b>PWR-G7000A-AC</b>	Power supply module (85 to 264 VAC) for ICS-G7748A/G7750A/G7752A/G7848A/G7850A/G7852A Series, -10 to 60°C operating temperature	<b>2.698,00 €</b>	8~12W
<b>PWR-HV-NP</b>	Power supply module (110/220 VAC/VDC) with system power input, relay	<b>800,00 €</b>	2~4W
<b>PWR-HV-P48</b>	Power supply module (110/220 VAC/VDC) with system power input, relay, PoE power input	<b>925,00 €</b>	4~8W
<b>PWR-HV-P48-A</b>	110/220 VAC/VDC power supply module with system power, relay, PoE power input, advanced heat sink	<b>1.060,00 €</b>	8~12W
<b>PWR-LV-NP</b>	Power supply module (24/48 VDC) with system power input, relay	<b>800,00 €</b>	4~8W
<b>PWR-LV-P48</b>	Power supply module (24/48 VDC) with system power input, relay, PoE power input	<b>925,00 €</b>	4~8W
<b>PWR-LV-P48-A</b>	24/48 VDC power supply module with system power, relay, PoE power input, advanced heat sink	<b>1.060,00 €</b>	8~12W
<b>PWR-Plug-AU-02</b>	AU plug for the PWR-12150-WPAU and the PWR-12300-WPAU	<b>6,00 €</b>	8~10W
<b>PWR-Plug-AU-03</b>	AU plug for PWR-12300-WPAU	<b>6,00 €</b>	10~12W
<b>PWR-Plug-CN-02</b>	CN plug for PWR-12150-WPCN and PWR-12300-WPCN	<b>4,00 €</b>	10~12W
<b>PWR-Plug-EU-02</b>	EU plug for PWR-12150-WPEU and PWR-12300-WPEU	<b>6,00 €</b>	8~10W
<b>PWR-Plug-IN-02</b>	PWR-Plug-IN-02	<b>6,00 €</b>	8~10W
<b>PWR-Plug-KR-02</b>	KR plug for the PWR-12150-WPKR and the PWR-12300-WPKR	<b>6,00 €</b>	8~10W
<b>PWR-Plug-UK-02</b>	UK plug for PWR-12150-WPUK and PWR-12300-WPUK	<b>6,00 €</b>	8~10W
<b>PWR-Plug-USJP-02</b>	US/JP plug for PWR-12150-WPUSJP and PWR-12300-WPUSJP	<b>4,00 €</b>	8~10W
<b>PWS-24W24V-OF-01</b>	Open frame power supply	<b>45,00 €</b>	44~48W
<b>RK-3U-02</b>	Rack-mounting kit with 4 L-shaped plates for the MDS-G4000 and MDS-G4000-4XGS Series	<b>661,00 €</b>	10~12W
<b>RK-4U</b>	19-inch rack-mounting kit	<b>222,00 €</b>	10~12W
<b>RKP-A110-E2-2L4C-T</b>	Rackmount 1U computer with Intel Atom® x6211E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.978,00 €</b>	4~8W
<b>RKP-A110-E2-8C-T</b>	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.857,00 €</b>	4~8W
<b>RKP-A110-E2-8L-T</b>	Rackmount 1U computer with Intel Atom® x6211E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.311,00 €</b>	4~8W
<b>RKP-A110-E2-T</b>	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.585,00 €</b>	4~8W
<b>RKP-A110-E2-T-Win10</b>	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>3.250,00 €</b>	4~8W
<b>RKP-A110-E4-2L4C-T</b>	Rackmount 1U computer with Intel Atom® x6425E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.145,00 €</b>	4~8W
<b>RKP-A110-E4-8C-T</b>	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.024,00 €</b>	4~8W
<b>RKP-A110-E4-8L-T</b>	Rackmount 1U computer with Intel Atom® x6425E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.341,00 €</b>	4~8W
<b>RKP-A110-E4-T</b>	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.676,00 €</b>	4~8W
<b>RKP-A110-E4-T-Win10</b>	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>3.371,00 €</b>	4~8W
<b>RKP-C110-C1-2L4C-T</b>	Rackmount 1U computer with Intel® Celeron® 6305E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.500,00 €</b>	4~8W
<b>RKP-C110-C1-8C-T</b>	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.311,00 €</b>	4~8W



<b>RKP-C110-C1-8L-T</b>	Rackmount 1U computer with Intel® Celeron® 6305E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>3.840,00 €</b>	4~8W
<b>RKP-C110-C1-T</b>	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>2.963,00 €</b>	4~8W
<b>RKP-C110-C1-T-Win10</b>	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>3.870,00 €</b>	4~8W
<b>RKP-C110-C5-2L4C-T</b>	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.717,00 €</b>	4~8W
<b>RKP-C110-C5-8C-T</b>	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.611,00 €</b>	4~8W
<b>RKP-C110-C5-8L-T</b>	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>5.064,00 €</b>	4~8W
<b>RKP-C110-C5-T</b>	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.142,00 €</b>	4~8W
<b>RKP-C110-C5-T-Win10</b>	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>5.095,00 €</b>	4~8W
<b>RKP-C110-C7-2L4C-T</b>	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>5.337,00 €</b>	4~8W
<b>RKP-C110-C7-8C-T</b>	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>5.261,00 €</b>	4~8W
<b>RKP-C110-C7-8L-T</b>	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>5.760,00 €</b>	4~8W
<b>RKP-C110-C7-T</b>	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	<b>4.823,00 €</b>	4~8W
<b>RKP-C110-C7-T-Win10</b>	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	<b>5.790,00 €</b>	4~8W
<b>RKS-G4028-4GS-2HV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>4.424,00 €</b>	4~8W
<b>RKS-G4028-4GS-2LV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>5.218,00 €</b>	12~16W
<b>RKS-G4028-4GS-HV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>4.255,00 €</b>	4~8W
<b>RKS-G4028-4GS-LV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>4.651,00 €</b>	12~16W
<b>RKS-G4028-4GT-2HV-T</b>	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>4.284,00 €</b>	4~8W
<b>RKS-G4028-4GT-2LV-T</b>	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>5.071,00 €</b>	12~16W
<b>RKS-G4028-4GT-HV-T</b>	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>4.114,00 €</b>	4~8W
<b>RKS-G4028-4GT-LV-T</b>	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>4.512,00 €</b>	12~16W
<b>RKS-G4028-L3-4GS-2HV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.682,00 €</b>	12~16W
<b>RKS-G4028-L3-4GS-2LV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>7.470,00 €</b>	12~16W
<b>RKS-G4028-L3-4GS-HV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.514,00 €</b>	12~16W
<b>RKS-G4028-L3-4GS-LV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>6.904,00 €</b>	12~16W
<b>RKS-G4028-L3-4GT-2HV-T</b>	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.543,00 €</b>	12~16W
<b>RKS-G4028-L3-4GT-2LV-T</b>	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>7.331,00 €</b>	12~16W
<b>RKS-G4028-L3-4GT-HV-T</b>	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.374,00 €</b>	12~16W
<b>RKS-G4028-L3-4GT-LV-T</b>	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>6.764,00 €</b>	12~16W
<b>RKS-G4028-L3-PoE-4GS-2HV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>8.935,00 €</b>	12~16W
<b>RKS-G4028-L3-PoE-4GS-2LV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>9.723,00 €</b>	12~16W

<b>RKS-G4028-L3-PoE-4GS-HV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>8.766,00 €</b>	12~16W
<b>RKS-G4028-L3-PoE-4GS-LV-T</b>	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>9.156,00 €</b>	12~16W
<b>RKS-G4028-PoE-4GS-2HV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.682,00 €</b>	12~16W
<b>RKS-G4028-PoE-4GS-2LV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	<b>7.470,00 €</b>	12~16W
<b>RKS-G4028-PoE-4GS-HV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	<b>6.514,00 €</b>	12~16W
<b>RKS-G4028-PoE-4GS-LV-T</b>	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	<b>6.904,00 €</b>	12~16W
<b>RK-UP1600-G2</b>	Rack mounting kits for UPort 1400/1600-G2	<b>89,00 €</b>	8~10W
<b>RM-G4000-2MSC4TX</b>	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	<b>825,00 €</b>	8~12W
<b>RM-G4000-2MST4TX</b>	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	<b>892,00 €</b>	8~12W
<b>RM-G4000-2SSC4TX</b>	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	<b>1.310,00 €</b>	8~12W
<b>RM-G4000-4MSC2TX</b>	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	<b>1.259,00 €</b>	8~12W
<b>RM-G4000-4MST2TX</b>	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	<b>1.399,00 €</b>	8~12W
<b>RM-G4000-4SSC2TX</b>	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	<b>2.232,00 €</b>	8~12W
<b>RM-G4000-6MSC</b>	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	<b>1.695,00 €</b>	8~12W
<b>RM-G4000-6MST</b>	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	<b>1.901,00 €</b>	8~12W
<b>RM-G4000-6SSC</b>	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	<b>3.151,00 €</b>	8~12W
<b>RM-G4000-8GPoE</b>	Gigabit Ethernet module with 8 10/100/1000BaseT(X) IEEE 802.3bt PoE ports	<b>1.561,00 €</b>	4~8W
<b>RM-G4000-8GSFP</b>	Gigabit Ethernet module with 8 100/1000BaseSFP slots	<b>1.627,00 €</b>	4~8W
<b>RM-G4000-8GTX</b>	Gigabit Ethernet module with 8 10/100/1000BaseT(X) ports	<b>1.038,00 €</b>	4~8W
<b>RM-G4000-8PoE</b>	Fast Ethernet module with 8 10/100BaseT(X) IEEE 802.3bt PoE ports	<b>1.038,00 €</b>	8~12W
<b>RM-G4000-8SFP</b>	Fast Ethernet module with 8 100BaseSFP slots	<b>818,00 €</b>	4~8W
<b>RM-G4000-8TX</b>	Fast Ethernet module with 8 10/100BaseT(X) ports	<b>523,00 €</b>	4~8W
<b>S-Cybersecurity_Network Inspection</b>	S-Cybersecurity_Network Inspection	<b>3.831,00 €</b>	
<b>SDS-3008</b>	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	<b>613,00 €</b>	2~4W
<b>SDS-3008 Rackmount Kit</b>	1U-high 19" rack mounting kit for SDS-3008	<b>211,00 €</b>	4~8W
<b>SDS-3008-T</b>	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	<b>687,00 €</b>	4~8W
<b>SDS-3016-2GSFP</b>	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	<b>1.163,00 €</b>	4~8W
<b>SDS-3016-2GSFP-T</b>	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	<b>1.289,00 €</b>	4~8W
<b>SDS-3016-2GTX</b>	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	<b>1.163,00 €</b>	2~4W
<b>SDS-3016-2GTX-T</b>	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	<b>1.289,00 €</b>	4~8W
<b>S-Factory Acceptance Test</b>		<b>3.831,00 €</b>	
<b>SFP-10GERLC-T</b>	SFP+ module with 1 10GBase-ER port, LC connector for 40 km transmission, -40 to 85°C operating temperature	<b>10.037,00 €</b>	8~12W
<b>SFP-10GLRLC-T</b>	SFP+ module with 1 10GBase-LR port, LC connector for 10 km transmission, -40 to 85°C operating temperature	<b>3.072,00 €</b>	4~8W
<b>SFP-10GSRLC-T</b>	SFP+ module with 1 10GBase-SR port, LC connector for 33m/82m/300m/400m transmission, -40 to 85°C operating temperature	<b>1.883,00 €</b>	4~8W
<b>SFP-10GZRLC-T</b>	SFP+ module with 1 10GBase-ZR port, LC connector for 80 km transmission, -40 to 85°C operating temperature	<b>13.315,00 €</b>	8~12W
<b>SFP-1FELLC-T</b>	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature	<b>1.357,00 €</b>	4~8W
<b>SFP-1FEMLC-T</b>	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature	<b>163,00 €</b>	2~4W
<b>SFP-1FESLC-T</b>	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature	<b>368,00 €</b>	2~4W
<b>SFP-1G10ALC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	<b>428,00 €</b>	4~8W
<b>SFP-1G10ALC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	<b>524,00 €</b>	4~8W
<b>SFP-1G10BLC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	<b>926,00 €</b>	4~8W

<b>SFP-1G10BLC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	<b>1.016,00 €</b>	4~8W
<b>SFP-1G20ALC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	<b>768,00 €</b>	8~12W
<b>SFP-1G20ALC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	<b>851,00 €</b>	8~12W
<b>SFP-1G20BLC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	<b>1.595,00 €</b>	8~12W
<b>SFP-1G20BLC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	<b>1.671,00 €</b>	8~12W
<b>SFP-1G40ALC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	<b>1.987,00 €</b>	8~12W
<b>SFP-1G40ALC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	<b>2.074,00 €</b>	8~12W
<b>SFP-1G40BLC</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	<b>2.180,00 €</b>	8~12W
<b>SFP-1G40BLC-T</b>	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	<b>2.267,00 €</b>	8~12W
<b>SFP-1GEZXLC</b>	SFP module with 1 1000BaseEZ port with LC connector for 110 km transmission, 0 to 60°C operating temperature	<b>2.522,00 €</b>	8~12W
<b>SFP-1GEZXLC-120</b>	SFP module with 1 1000BaseEZ port with LC connector for 120 km transmission, 0 to 60°C operating temperature	<b>3.026,00 €</b>	8~12W
<b>SFP-1GLHLC</b>	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature	<b>440,00 €</b>	2~4W
<b>SFP-1GLHLC-T</b>	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature	<b>500,00 €</b>	2~4W
<b>SFP-1GLHXLC</b>	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature	<b>1.060,00 €</b>	4~8W
<b>SFP-1GLHXLC-T</b>	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature	<b>1.136,00 €</b>	4~8W
<b>SFP-1GLSXLC</b>	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature	<b>371,00 €</b>	2~4W
<b>SFP-1GLSXLC-T</b>	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature	<b>453,00 €</b>	2~4W
<b>SFP-1GLXLC</b>	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature	<b>344,00 €</b>	2~4W
<b>SFP-1GLXLC-T</b>	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature	<b>405,00 €</b>	2~4W
<b>SFP-1GSXLC</b>	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature	<b>195,00 €</b>	2~4W
<b>SFP-1GSXLC-T</b>	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature	<b>264,00 €</b>	2~4W
<b>SFP-1GTXRJ45-T</b>	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature	<b>428,00 €</b>	2~4W
<b>SFP-1GZXLC</b>	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature	<b>1.775,00 €</b>	4~8W
<b>SFP-1GZXLC-T</b>	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature	<b>1.834,00 €</b>	4~8W
<b>SFP-2.5GLSLC-T</b>	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 20 km transmission, -40 to 85 °C operating temperature	<b>890,00 €</b>	10~12W
<b>SFP-2.5GMLC-T</b>	SFP module with 1 2.5GBaseFX port with LC connector, multi-mode, for 170, 200, 550, 600 m transmission, -40 to 85 °C operating temperature	<b>359,00 €</b>	10~12W
<b>SFP-2.5GSLC-T</b>	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 5 km transmission, -40 to 85 °C operating temperature	<b>579,00 €</b>	10~12W
<b>SFP-2.5GSLHLC-T</b>	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 45 km transmission, -40 to 85 °C operating temperature	<b>2.654,00 €</b>	10~12W
<b>S-IIoT-Consulting</b>	Order only against quotation! Engineering Service for IIoT Consulting. See "S-IIOT-Consulting" outline document for details. Prior customer agreement required. Price for full day service.	<b>3.831,00 €</b>	
<b>S-IIoT-PoC</b>	Order only against quotation! Two Days workshop with PoC for IIOT . Conditions "S-IIOT-PoC" outline document for details. Price for 2 full days service. UC-8112A or similar included	<b>7.659,00 €</b>	
<b>S-IIoT-SLA-Level1</b>	Order only against quotation! Support for Moxa Industrial Linux. . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.		
<b>S-IIoT-SLA-Level2</b>	Order only against quotation! Support for Moxa Industrial Linux and ThingsPro Gateway . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.		
<b>S-IIoT-SLA-Level3</b>	Order only against quotation! Support for Moxa Industrial Linux and Things pro Edge (incl. cloud-based device management). Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.		
<b>S-MRC-PoC</b>	Order only against quotation! One Day workshop with PoC for MRC . Conditions"S-MRC-PoC" outline document for details. Price for full day service.	<b>3.831,00 €</b>	
<b>S-Network Consulting-Addresses</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Consulting-Audit</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.831,00 €</b>	

<b>S-Network Consulting-Configuration</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Consulting-Design</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Consulting-Onsite</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Consulting-Preparation</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Consulting-Test Plan</b>	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Network Inspection</b>	Order only against quotation! Engineering Service for Network Inspection. See "S-Network Inspection" outline document for details. Prior customer agreement required. Price for full day service.	<b>3.065,00 €</b>	
<b>S-Onsite Support</b>	Order only against quotation! Engineering Service for Onsite Support. Prior customer agreement required. Travel & accomodation excluded. Price for full day service. See onsite outline document for details.	<b>2.554,00 €</b>	
<b>SPL-24</b>	PoE splitter with maximum output of 12.95 W at 24 VDC, 0 to 60°C operating temperature	<b>210,00 €</b>	4~8W
<b>SPL-24-T</b>	PoE splitter with maximum output of 12.95 W at 24 VDC, -40 to 75°C operating temperature	<b>313,00 €</b>	4~8W
<b>S-Project Management-Execution</b>	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	<b>511,00 €</b>	
<b>S-Project Management-Preparation</b>	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	<b>511,00 €</b>	
<b>S-Sample Provisioning</b>	Order only against quotation! Samples from MEU stock are loaned to customers for evaluation purpose. Conditions see "S-Sample Provisioning" outline document for details.. Price charged per service week.		
<b>S-Technical Support-SLA Basic Post-Warranty</b>	Order only against quotation! Technical Support service commitment based on deployed hardware/software after warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price charged per service year.		
<b>S-Technical Support-SLA Basic Warranty</b>	Order only against quotation! Technical Support service commitment based on deployed hardware/software under warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price charged per service year.		
<b>S-Training-IES-Standard-Classroom</b>	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order per participant and day. Provide number of participants in comment field. Classroom training is hosted in Munich.	<b>766,00 €</b>	
<b>S-Training-IES-Standard-onsite</b>	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodation excluded.	<b>2.554,00 €</b>	
<b>S-Training-IloT-Classroom</b>	Order only against quotation! IloT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order per participant and day. Provide number of participants in comment field.	<b>1.022,00 €</b>	
<b>S-Training-IloT-onsite</b>	Order only against quotation! IloT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order for 4* participants and day. Provide number of participants in comment field and location. Travel & accomodation excluded.	<b>3.831,00 €</b>	
<b>S-Training-Power-classroom</b>	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEE 1588. Order per participant and day. Provide number of participants in comment field. Classroom training in Munich.	<b>1.022,00 €</b>	
<b>S-Training-Power-onsite</b>	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEE 1588. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodation excluded.	<b>3.831,00 €</b>	
<b>TAP-213-EU-CT-T</b>	802.11n railway onboard outdoor single radio access point/client, M12, EU band, IP68, -40 to 75°C operating temperature, conformal coating	<b>4.172,00 €</b>	12~16W
<b>TAP-213-JP-CT-T</b>	802.11n railway onboard outdoor single radio access point/client, M12, JP band, IP68, -40 to 75°C operating temperature, conformal coating	<b>4.172,00 €</b>	12~16W
<b>TAP-213-US-CT-T</b>	802.11n railway onboard outdoor single radio access point/client, M12, US band, IP68, -40 to 75°C operating temperature, conformal coating	<b>4.172,00 €</b>	12~16W
<b>TAP-323-EU-CT-T</b>	802.11n railway trackside outdoor dual radio access point, EU band, IP68, -40 to 75°C operating temperature, conformal coating	<b>9.746,00 €</b>	16~20W
<b>TAP-323-JP-CT-T</b>	802.11n railway trackside outdoor dual radio access point, JP band, IP68, -40 to 75°C operating temperature, conformal coating	<b>9.746,00 €</b>	16~20W
<b>TAP-323-US-CT-T</b>	802.11n railway trackside outdoor dual radio access point, US band, IP68, -40 to 75°C operating temperature, conformal coating	<b>9.746,00 €</b>	16~20W
<b>TB-F25</b>	DB25 female DIN-rail wiring terminal	<b>65,00 €</b>	8~12W
<b>TB-F9</b>	DB9 female DIN-rail wiring terminal	<b>49,00 €</b>	4~8W
<b>TB-M25</b>	DB25 male DIN-rail wiring terminal	<b>65,00 €</b>	8~12W
<b>TB-M9</b>	DB9 male DIN-rail wiring terminal	<b>49,00 €</b>	4~8W
<b>TCC-100</b>	RS-232 to RS-422/485 converter	<b>108,00 €</b>	2~4W
<b>TCC-100I</b>	RS-232 to RS-422/485 converter with optical isolation	<b>173,00 €</b>	2~4W
<b>TCC-100I-T</b>	RS-232 to RS-422/485 converter with optical isolation, -40 to 85°C operating temperature	<b>217,00 €</b>	2~4W
<b>TCC-100-T</b>	RS-232 to RS-422/485 converter, -40 to 85°C operating temperature	<b>141,00 €</b>	4~8W

<b>TCC-120</b>	RS-422/485 converter/repeater	<b>141,00 €</b>	4~8W
<b>TCC-120I</b>	RS-422/485 converter/repeater with optical isolation	<b>188,00 €</b>	2~4W
<b>TCC-80</b>	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and terminal block on the RS-422/485 side	<b>60,00 €</b>	2~4W
<b>TCC-80-DB9</b>	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and DB9 male connector on the RS-422/485 side	<b>60,00 €</b>	2~4W
<b>TCC-80I</b>	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection, terminal block on the RS-422/485 side, and 2.5 kV optical isolation	<b>124,00 €</b>	2~4W
<b>TCC-80I-DB9</b>	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection, DB9 male connector on the RS-422/485 side, and 2.5 kV optical isolation	<b>124,00 €</b>	4~8W
<b>TCC-82</b>	Port-powered RS-232 isolator with 4 kV isolation and 15 kV serial ESD protection	<b>99,00 €</b>	2~4W
<b>TCF-142-M-SC</b>	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	<b>271,00 €</b>	2~4W
<b>TCF-142-M-SC-RM</b>	RS-232/422/485 to multi-mode fiber slide-in module converter, SC connector	<b>264,00 €</b>	4~8W
<b>TCF-142-M-SC-T</b>	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	<b>351,00 €</b>	4~8W
<b>TCF-142-M-ST</b>	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	<b>271,00 €</b>	2~4W
<b>TCF-142-M-ST-RM</b>	RS-232/422/485 to multi-mode fiber slide-in module converter, ST connector	<b>264,00 €</b>	8~12W
<b>TCF-142-M-ST-T</b>	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	<b>351,00 €</b>	2~4W
<b>TCF-142-S-SC</b>	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	<b>652,00 €</b>	2~4W
<b>TCF-142-S-SC-RM</b>	RS-232/422/485 to single-mode fiber slide-in module converter, SC connector	<b>556,00 €</b>	4~8W
<b>TCF-142-S-SC-T</b>	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	<b>862,00 €</b>	2~4W
<b>TCF-142-S-ST</b>	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	<b>652,00 €</b>	2~4W
<b>TCF-142-S-ST-RM</b>	RS-232/422/485 to single-mode fiber slide-in module converter, ST connector	<b>556,00 €</b>	8~12W
<b>TCF-142-S-ST-T</b>	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	<b>862,00 €</b>	4~8W
<b>TCF-90-M-ST</b>	RS-232 to multi-mode ST fiber optic converter, port powered	<b>217,00 €</b>	2~4W
<b>TCF-90-S-ST</b>	RS-232 to single-mode ST fiber optic converter, port powered	<b>366,00 €</b>	4~8W
<b>TN-4512A-WV-CT-T</b>	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>2.898,00 €</b>	12~16W
<b>TN-4512A-WV-T</b>	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>2.685,00 €</b>	12~16W
<b>TN-4516A-12PoE-2GPoE-2GODC-WV-CT-T</b>	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>8.409,00 €</b>	24~28W
<b>TN-4516A-12PoE-2GPoE-2GODC-WV-T</b>	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>7.783,00 €</b>	24~28W
<b>TN-4516A-12PoE-2GPoE-2GTXPB-WV-CT-T</b>	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>6.634,00 €</b>	24~28W
<b>TN-4516A-12PoE-2GPoE-2GTXPB-WV-T</b>	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>6.160,00 €</b>	24~28W
<b>TN-4516A-12PoE-4GPoE-WV-CT-T</b>	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>6.607,00 €</b>	24~28W
<b>TN-4516A-12PoE-4GPoE-WV-T</b>	Layer 2 managed switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, 12 PoE 10/100BaseT(X) ports with M12 connector, -40 to 75°C operating temperature	<b>6.117,00 €</b>	24~28W
<b>TN-4516A-4GTXPB-WV-CT-T</b>	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conformal coating	<b>4.457,00 €</b>	24~28W
<b>TN-4516A-4GTXPB-WV-T</b>	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	<b>4.126,00 €</b>	24~28W
<b>TN-4516A-4GTX-WV-CT-T</b>	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conformal coating	<b>4.140,00 €</b>	24~28W
<b>TN-4516A-4GTX-WV-T</b>	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	<b>3.837,00 €</b>	24~28W
<b>TN-4516A-WV-CT-T</b>	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	<b>3.867,00 €</b>	12~16W
<b>TN-4516A-WV-T</b>	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	<b>3.585,00 €</b>	12~16W
<b>TN-4520A-16PoE-4GPoE-WV-CT-T</b>	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	<b>6.460,00 €</b>	24~28W
<b>TN-4520A-16PoE-4GPoE-WV-T</b>	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	<b>5.980,00 €</b>	24~28W

<b>TN-4524A-16PoE-WV-CT-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>6.634,00 €</b>	12~16W
<b>TN-4524A-16PoE-WV-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>6.160,00 €</b>	12~16W
<b>TN-4528A-16PoE-2GPoE-2GODC-WV-CT-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>10.929,00 €</b>	24~28W
<b>TN-4528A-16PoE-2GPoE-2GODC-WV-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>10.108,00 €</b>	24~28W
<b>TN-4528A-16PoE-2GPoE-2GTXP-WV-CT-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>9.151,00 €</b>	24~28W
<b>TN-4528A-16PoE-2GPoE-2GTXP-WV-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>8.487,00 €</b>	24~28W
<b>TN-4528A-16PoE-4GPoE-WV-CT-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	<b>9.127,00 €</b>	24~28W
<b>TN-4528A-16PoE-4GPoE-WV-T</b>	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	<b>8.443,00 €</b>	24~28W
<b>TN-4908-4GPoE-4GTX-WV-CT-T</b>	Industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>7.530,00 €</b>	28~32W
<b>TN-4908-4GTX-WV-CT-T</b>	Industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>5.700,00 €</b>	24~28W
<b>TN-4908-8GTX-WV-CT-T</b>	Industrial secure router with 8 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>6.741,00 €</b>	28~32W
<b>TN-4908-ETBN-4GPoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>9.107,00 €</b>	28~32W
<b>TN-4908-ETBN-4GTX-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>8.153,00 €</b>	28~32W
<b>TN-4908-ETBN-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>7.092,00 €</b>	24~28W
<b>TN-4908-ETBN-4TXBP-WV-CT-T</b>	TN-4908-ETBN-4TXBP-WV-CT-T	<b>6.005,00 €</b>	16~20W
<b>TN-4908-ETBN-F-4GPoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>9.386,00 €</b>	28~32W
<b>TN-4908-ETBN-F-4GTX-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>8.418,00 €</b>	28~32W
<b>TN-4908-ETBN-F-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>7.357,00 €</b>	24~28W
<b>TN-4908-ETBN-F-4TXBP-WV-CT-T</b>	TN-4908-ETBN-F-4TXBP-WV-CT-T	<b>6.270,00 €</b>	16~20W
<b>TN-4908-WV-CT-T</b>	Industrial secure router with 8 Fast Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>4.574,00 €</b>	16~20W
<b>TN-4916-12PoE-4GTX-WV-CT-T</b>	Industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>6.761,00 €</b>	24~28W
<b>TN-4916-4GTX-WV-CT-T</b>	Industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>6.337,00 €</b>	24~28W
<b>TN-4916-8PoE-4GPoE-4GTX-WV-CT-T</b>	Industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>8.405,00 €</b>	28~32W
<b>TN-4916-ETBN-12PoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>8.219,00 €</b>	24~28W
<b>TN-4916-ETBN-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>7.689,00 €</b>	24~28W
<b>TN-4916-ETBN-8PoE-4GPoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>9.850,00 €</b>	28~32W
<b>TN-4916-ETBN-F-12PoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>8.484,00 €</b>	24~28W
<b>TN-4916-ETBN-F-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>7.954,00 €</b>	24~28W

<b>TN-4916-ETBN-F-8PoE-4GPoE-4GTXP-WV-CT-T</b>	IEC 61375 ETBN industrial secure firewall router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>10.141,00 €</b>	28~32W
<b>TN-5305</b>	Unmanaged IP67-rated Ethernet switch with 5 10/100BaseT(X) ports with M12 connectors, -25 to 60°C operating temperature, M12 power cable	<b>371,00 €</b>	4~8W
<b>TN-5305A-WV-CT-T</b>	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>597,00 €</b>	12~16W
<b>TN-5305A-WV-T</b>	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	<b>555,00 €</b>	12~16W
<b>TN-5305-T</b>	Unmanaged IP67-rated Ethernet switch with 5 10/100BaseT(X) ports with M12 connectors, -40 to 75°C operating temperature, M12 power cable	<b>452,00 €</b>	4~8W
<b>TN-5308-4PoE-48</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports and 4 PoE ports with M12 connectors, -25 to 60°C operating temperature	<b>838,00 €</b>	8~12W
<b>TN-5308-4PoE-48-CT-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) M12 ports and 4 10/100BaseT(X) PoE M12 ports, 48 VDC, -40 to 75°C operating temperature, conformal coating	<b>1.086,00 €</b>	16~20W
<b>TN-5308-4PoE-48-T</b>	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports and 4 PoE ports with M12 connectors, -40 to 75°C operating temperature	<b>940,00 €</b>	12~16W
<b>TN-5308-8PoE-48</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connectors, 1 isolated power inputs (48 VDC), -25 to 60°C operating temperature	<b>1.015,00 €</b>	8~12W
<b>TN-5308-8PoE-48-CT-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) PoE M12 ports, 48 VDC, -40 to 75°C operating temperature, conformal coating	<b>1.319,00 €</b>	16~20W
<b>TN-5308-8PoE-48-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connectors, 1 isolated power inputs (48 VDC), -40 to 75°C operating temperature	<b>1.104,00 €</b>	12~16W
<b>TN-5308A-WV-CT-T</b>	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>1.174,00 €</b>	12~16W
<b>TN-5308A-WV-T</b>	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	<b>1.087,00 €</b>	12~16W
<b>TN-5308-LV</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 7 to 60 VDC, -25 to 60°C operating temperature, M12 power cable	<b>645,00 €</b>	8~12W
<b>TN-5308-LV-CT</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) M12 ports, 12 to 48 VDC, -25 to 60°C operating temperature, conformal coating	<b>755,00 €</b>	12~16W
<b>TN-5308-LV-CT-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 7 to 60 VDC, -40 to 75°C operating temperature, M12 power cable, conformal coating	<b>891,00 €</b>	12~16W
<b>TN-5308-LV-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 7 to 60 VDC, -40 to 75°C operating temperature, M12 power cable	<b>741,00 €</b>	12~16W
<b>TN-5308-MV</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 50.4 to 154 VDC, -25 to 60°C operating temperature, M23 power cable	<b>830,00 €</b>	8~12W
<b>TN-5308-MV-CT</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) M12 ports, 72 to 110 VDC, -25 to 60°C operating temperature, conformal coating	<b>971,00 €</b>	12~16W
<b>TN-5308-MV-CT-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 50.4 to 154 VDC, -40 to 75°C operating temperature, M23 power cable, conformal coating	<b>1.104,00 €</b>	12~16W
<b>TN-5308-MV-T</b>	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, 50.4 to 154 VDC, -40 to 75°C operating temperature, M23 power cable	<b>925,00 €</b>	12~16W
<b>TN-5508A-8PoE-WV-CT-T</b>	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>3.448,00 €</b>	12~16W
<b>TN-5508A-8PoE-WV-T</b>	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	<b>3.192,00 €</b>	12~16W
<b>TN-5508A-WV-CT-T</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connector, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature, conformal coating	<b>2.709,00 €</b>	16~20W
<b>TN-5508A-WV-T</b>	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	<b>2.507,00 €</b>	16~20W
<b>TN-5510A-2GLSX-ODC-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	<b>5.854,00 €</b>	16~20W
<b>TN-5510A-2GLSX-ODC-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24-110 VDC dual power input, -40 to 75°C operating temperature	<b>5.423,00 €</b>	16~20W
<b>TN-5510A-2GTXP-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	<b>3.700,00 €</b>	24~28W
<b>TN-5510A-2GTXP-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	<b>3.428,00 €</b>	24~28W
<b>TN-5510A-2GTX-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	<b>3.545,00 €</b>	28~32W
<b>TN-5510A-2GTX-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	<b>3.280,00 €</b>	20~24W
<b>TN-5510A-8PoE-2GLSX-ODC-WV-CT-T</b>	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>6.184,00 €</b>	12~16W
<b>TN-5510A-8PoE-2GLSX-ODC-WV-T</b>	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature	<b>5.681,00 €</b>	12~16W
<b>TN-5510A-8PoE-2GTXP-WV-CT-T</b>	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>4.566,00 €</b>	24~28W
<b>TN-5510A-8PoE-2GTXP-WV-T</b>	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature	<b>4.254,00 €</b>	24~28W
<b>TN-5510A-8PoE-2GTX-WV-CT-T</b>	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>4.413,00 €</b>	24~28W

<b>TN-5510A-8PoE-2GTX-WV-T</b>	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	<b>4.057,00 €</b>	24~28W
<b>TN-5516A-8PoE-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>4.724,00 €</b>	12~16W
<b>TN-5516A-8PoE-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24-110 VDC, -40 to 75°C operating temperature	<b>4.379,00 €</b>	12~16W
<b>TN-5516A-WV-CT-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>3.532,00 €</b>	12~16W
<b>TN-5516A-WV-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	<b>3.267,00 €</b>	12~16W
<b>TN-5518A-2GTXBP-WV-CT-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>4.334,00 €</b>	24~28W
<b>TN-5518A-2GTXBP-WV-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	<b>4.012,00 €</b>	24~28W
<b>TN-5518A-2GTX-WV-CT-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>4.257,00 €</b>	24~28W
<b>TN-5518A-2GTX-WV-T</b>	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24-110 VDC, -40 to 75°C operating temperature	<b>3.944,00 €</b>	24~28W
<b>TN-5518A-8PoE-2GTXBP-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>5.743,00 €</b>	24~28W
<b>TN-5518A-8PoE-2GTXBP-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature	<b>5.321,00 €</b>	24~28W
<b>TN-5518A-8PoE-2GTX-WV-CT-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	<b>5.568,00 €</b>	24~28W
<b>TN-5518A-8PoE-2GTX-WV-T</b>	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) with M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature	<b>5.156,00 €</b>	24~28W
<b>TN-G4516-8GPoE-2XGPOE-2XGTXBP-WV-CT-T</b>	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	<b>10.962,00 €</b>	12~16W
<b>TN-G4516-8GPoE-2XGPOE-2XGTXBP-WV-T</b>	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	<b>10.621,00 €</b>	12~16W
<b>TN-G4516-8GPoE-4XGPOE-WV-CT-T</b>	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP40, conformal coating	<b>11.081,00 €</b>	12~16W
<b>TN-G4516-8GPoE-4XGPOE-WV-T</b>	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	<b>10.272,00 €</b>	12~16W
<b>TN-G6512-8GPoE-WV-CT-T</b>	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) with 802.3at PoE+, 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature, conformal coating model	<b>6.635,00 €</b>	24~28W
<b>TN-G6512-8GPoE-WV-T</b>	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) ports with 802.3at PoE+ and 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature	<b>6.142,00 €</b>	24~28W
<b>TRC-190-AC</b>	Rack chassis, 2U, single 110 to 240 VAC input, with 19 slots on front panel	<b>865,00 €</b>	4~8W
<b>TRC-190-DC-48</b>	Rack chassis, 2U, single 36 to 53 VDC input, with 19 slots on front panel	<b>1.092,00 €</b>	8~12W
<b>TRC-2190-AC</b>	2U rackmount chassis, with a single 110 to 240 VAC input, 18 slots on the front panel, and CSM-MN01 managed module	<b>1.421,00 €</b>	4~8W
<b>TRC-2190-DC-48V</b>	2U rackmount chassis, with a single 36 to 53 VDC input, 18 slots on the front panel, and CSM-MN01 managed module	<b>1.663,00 €</b>	8~12W
<b>TSN-G5004</b>	4G-port full Gigabit managed Ethernet switch, 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	<b>1.983,00 €</b>	8~12W
<b>TSN-G5008-2GTXSFP</b>	8G-port full Gigabit managed Ethernet switch, 6 10/100/1000BaseT(X) ports, and 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots, -10 to 60°C operating temperature	<b>2.834,00 €</b>	4~8W
<b>UBLOX LTE module for EU</b>	UBLOX LTE module for the EU region	<b>325,00 €</b>	56~60W
<b>UC-1222A</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 60°C operating temperature	<b>650,00 €</b>	8~12W
<b>UC-2101-LX</b>	Mini RISC-based embedded computer with 600 MHz processor, 1 serial port and 1 LAN port	<b>421,00 €</b>	2~4W
<b>UC-2102-LX</b>	Mini RISC-based embedded computer with 600 MHz processor and 2 LAN ports	<b>421,00 €</b>	8~12W
<b>UC-2104-LX</b>	Mini RISC-based embedded computer with 600 MHz processor, 1 LAN port, 1 Mini PCIe slot for wireless capability	<b>445,00 €</b>	8~12W
<b>UC-2111-LX</b>	Compact RISC-based embedded computer with 600 MHz processor, 2 serial ports, 2 LAN ports, 1 microSD slot	<b>515,00 €</b>	4~8W
<b>UC-2112-LX</b>	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 LAN ports (1 Gb Ethernet), and microSD slot	<b>615,00 €</b>	2~4W
<b>UC-2112-T-LX</b>	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 Ethernet ports (1 Gigabit Ethernet), microSD slot and -40 to 75°C operating temperature	<b>689,00 €</b>	4~8W
<b>UC-2222A-T</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 75°C operating temperature	<b>783,00 €</b>	12~16W



<b>UC-2222A-T-AP</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the Asia-Pacific region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	<b>1.041,00 €</b>	12~16W
<b>UC-2222A-T-CN</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot for wireless module, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	<b>809,00 €</b>	12~16W
<b>UC-2222A-T-EU</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the European region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	<b>1.041,00 €</b>	12~16W
<b>UC-2222A-T-US</b>	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the U.S. region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 70°C operating temperature	<b>1.041,00 €</b>	12~16W
<b>UC-3100 Antenna Set</b>	4 dBi at 1575 MHz to 1610 MHz, SMA (male), active GPS/GLONASS, adhesive-type antenna with 20-cm cable; 2.4 dBi at 2.4 GHz or 5 dBi at 5 GHz, RP-SMA (female), omnidirectional antennas; 2 1.5 dBi 698 to 960 MHz or 1710 to 2700 MHz, SMA (male), LTE, swivel-type omnidirectional portable antennas	<b>63,00 €</b>	16~20W
<b>UC-3100 DIN-Rail Kit</b>	DIN-rail kit with screws	<b>13,00 €</b>	4~8W
<b>UC-3100 Wall-Mounting Kit</b>	Wall-mounting kit with screws	<b>8,00 €</b>	4~8W
<b>UC-3101-T-AP-LX</b>	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	<b>944,00 €</b>	12~16W
<b>UC-3101-T-AU-LX</b>	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 module, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -30 to 70°C operating temperature	<b>944,00 €</b>	8~12W
<b>UC-3101-T-EU-LX</b>	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	<b>944,00 €</b>	12~16W
<b>UC-3101-T-US-LX</b>	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	<b>944,00 €</b>	12~16W
<b>UC-3111-T-AP-LX</b>	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.282,00 €</b>	12~16W
<b>UC-3111-T-AP-LX-NW</b>	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.221,00 €</b>	8~12W
<b>UC-3111-T-AU-LX</b>	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -30 to 70°C operating temperature	<b>1.282,00 €</b>	8~12W
<b>UC-3111-T-EU-LX</b>	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.282,00 €</b>	4~8W
<b>UC-3111-T-EU-LX-NW</b>	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.221,00 €</b>	8~12W
<b>UC-3111-T-US-LX</b>	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.282,00 €</b>	4~8W
<b>UC-3111-T-US-LX-NW</b>	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.221,00 €</b>	8~12W
<b>UC-3121-T-AP-LX</b>	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.225,00 €</b>	12~16W
<b>UC-3121-T-AU-LX</b>	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, -30 to 70°C operating temperature	<b>1.225,00 €</b>	8~12W
<b>UC-3121-T-EU-LX</b>	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.225,00 €</b>	12~16W
<b>UC-3121-T-US-LX</b>	Arm-based computer for the U.S. region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	<b>1.225,00 €</b>	12~16W
<b>UC-5101-LX</b>	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 Dis, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	<b>944,00 €</b>	4~8W
<b>UC-5101-T-LX</b>	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 Dis, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	<b>1.178,00 €</b>	8~12W
<b>UC-5102-LX</b>	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 Dis, 4 DOs, 1 USB port, -10 to 60°C operating temperature	<b>1.122,00 €</b>	8~12W
<b>UC-5102-T-LX</b>	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 Dis, 4 DOs, 1 USB port, -40 to 85°C operating temperature	<b>1.343,00 €</b>	12~16W
<b>UC-5111-LX</b>	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 Dis, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	<b>1.178,00 €</b>	8~12W
<b>UC-5111-T-LX</b>	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 Dis, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	<b>1.418,00 €</b>	8~12W

<b>UC-5112-LX</b>	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 Dis, 4 DOs, 1 USB port, -10 to 60°C operating temperature	<b>1.343,00 €</b>	8~12W
<b>UC-5112-T-LX</b>	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 Dis, 4 DOs, 1 USB port, -40 to 85°C operating temperature	<b>1.583,00 €</b>	8~12W
<b>UC-8100 LTE-CAT4-AP</b>	Telit LE910C4-AP LTE Cat. 4 mini card with 2 M2 screws for the Asia-Pacific region	<b>278,00 €</b>	56~60W
<b>UC-8100 LTE-CAT4-EU</b>	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2 screws for the EMEA region	<b>278,00 €</b>	56~60W
<b>UC-8100A-ME DIN-Rail Kit</b>	DIN-rail mounting kit for UC-8100A-ME-T Series	<b>10,00 €</b>	4~8W
<b>UC-8100A-ME Wall Mount Kit</b>	Wall-mounting kit for UC-8100A-ME-T Series	<b>26,00 €</b>	4~8W
<b>UC-8100-ME Din-Rail Kit</b>	DIN-rail mounting kit for UC-8100-ME Series	<b>42,00 €</b>	4~8W
<b>UC-8100-ME Wall Mount Kit</b>	Wall-mounting kit with screws	<b>32,00 €</b>	
<b>UC-8112A-ME-T-LX</b>	Arm-based DIN-rail industrial computer with 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot for Wi-Fi or LTE, -40 to 75°C operating temperature	<b>912,00 €</b>	4~8W
<b>UC-8112-LX</b>	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	<b>652,00 €</b>	2~4W
<b>UC-8112-ME-T-LX</b>	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 512 MB RAM, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot, -40 to 85°C operating temperature	<b>824,00 €</b>	4~8W
<b>UC-8112-ME-T-LX1</b>	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 1 GB RAM, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot, -40 to 85°C operating temperature	<b>895,00 €</b>	8~12W
<b>UC-8131-LX</b>	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet, 1 Serial port	<b>509,00 €</b>	8~12W
<b>UC-8132-LX</b>	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	<b>559,00 €</b>	8~12W
<b>UC-8162-LX</b>	Arm-based wireless-enabled DIN-rail industrial computer with 600 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	<b>574,00 €</b>	4~8W
<b>UC-8200 Wall-mounting Kit</b>	Wall-mounting kit for UC-8200 with 4 M3 screws	<b>36,00 €</b>	4~8W
<b>UC-8200 WiFi-AC</b>	Wi-Fi package for UC-8200, includes Wi-Fi module, 6 screws, 1 heat sink, 1 pad	<b>117,00 €</b>	56~60W
<b>UC-8200-WLAN22-AC</b>	Wireless package for UC-8200 V2.0 or later with Wi-Fi module, 2 screws, 2 spacers, 1 heat sink, 1 pad	<b>130,00 €</b>	20~24W
<b>UC-8210 DIN-rail Mounting Kit</b>	DIN-rail mounting kit for UC-8210 with 4 M3 screws	<b>15,00 €</b>	4~8W
<b>UC-8210-T-LX-S</b>	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, 1 CAN port, 4 Dis, 4 DOs, -40 to 85°C operating temperature	<b>1.017,00 €</b>	2~4W
<b>UC-8220 DIN-rail Mounting Kit</b>	DIN-rail mounting kit for UC-8220 with 4 M3 screws	<b>15,00 €</b>	4~8W
<b>UC-8220-T-LX</b>	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with 2 expansion slots for a Wi-Fi and LTE module, 1 CAN port, 4 Dis, 4 DOs, -40 to 85°C operating temperature	<b>1.255,00 €</b>	4~8W
<b>UC-8220-T-LX-AP-S</b>	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, Asia-Pacific region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 Dis, 4 DOs, -40 to 70°C operating temperature	<b>1.688,00 €</b>	12~16W
<b>UC-8220-T-LX-EU-S</b>	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, EU region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 Dis, 4 DOs, -40 to 70°C operating temperature	<b>1.688,00 €</b>	4~8W
<b>UC-8220-T-LX-US-S</b>	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, US region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 Dis, 4 DOs, -40 to 70°C operating temperature	<b>1.688,00 €</b>	4~8W
<b>UC-8410A DIN-rail Kit</b>	DIN-rail kit with 6 M3 screws (also included in the UC-8410A Series package)	<b>21,00 €</b>	4~8W
<b>UC-8410A LTE-CAT4-AP</b>	Telit LE910C4-AP LTE Cat. 4 mini card with 2 M2.5 screws for the Asia-Pacific region, compatible with UC-8410A hardware rev. 2.1.0 and higher	<b>278,00 €</b>	56~60W
<b>UC-8410A LTE-CAT4-EU</b>	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2.5 screws for the EMEA region, compatible with UC-8410A hardware rev. 2.1.0 and higher	<b>278,00 €</b>	56~60W
<b>UC-8410A-LX</b>	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 Dis, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -10 to 60°C operating temperature	<b>1.395,00 €</b>	2~4W
<b>UC-8410A-NW-LX</b>	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 Dis, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -10 to 60°C operating temperature	<b>1.367,00 €</b>	8~12W
<b>UC-8410A-NW-T-LX</b>	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 Dis, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -40 to 75°C operating temperature	<b>1.718,00 €</b>	8~12W
<b>UC-8410A-T-LX</b>	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 Dis, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -40 to 75°C operating temperature	<b>1.749,00 €</b>	4~8W
<b>UC-8500-4GCat6-Q-APAC</b>	LTE Cat. 6 module for North America and Europe, 2 QMA connectors with cables, -40 to 60°C operating temperature	<b>587,00 €</b>	56~60W
<b>UC-8500-4GCat6-Q-NAMEU</b>	LTE Cat. 6 module for North America and Europe, 2 QMA connectors with cables, -40 to 60°C operating temperature	<b>816,00 €</b>	56~60W
<b>UC-8500-WLAN33-Q-AC</b>	3 transmitter 3 receiver Wi-Fi card module, 3 QMA connectors with cables	<b>497,00 €</b>	56~60W
<b>UC-8500-WLAN33-Q-AC-TELEC</b>	2 transmitter 2 receiver Wi-Fi card module with TELEC certification, 2 QMA connectors with cables	<b>497,00 €</b>	28~32W
<b>UC-8540-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, -25 to 55°C operating temperature	<b>3.129,00 €</b>	12~16W
<b>UC-8540-T-CT-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, -40 to 70°C operating temperature, conformal coating	<b>4.606,00 €</b>	12~16W

<b>UC-8540-T-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, -40 to 70°C operating temperature	<b>3.788,00 €</b>	12~16W
<b>UC-8580-4G-Cat6-NAMEU</b>	LTE Cat. 6 module for North America and Europe, 2 SMA connectors with cables, -40 to 60°C operating temperature	<b>794,00 €</b>	56~60W
<b>UC-8580-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -25 to 55°C operating temperature	<b>7.615,00 €</b>	12~16W
<b>UC-8580-Q-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -25 to 55°C operating temperature	<b>8.057,00 €</b>	12~16W
<b>UC-8580-T-CT-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -40 to 70°C operating temperature, conformal coating	<b>11.196,00 €</b>	12~16W
<b>UC-8580-T-CT-Q-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -40 to 70°C operating temperature, conformal coating	<b>11.870,00 €</b>	12~16W
<b>UC-8580-T-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -40 to 70°C operating temperature	<b>8.789,00 €</b>	20~24W
<b>UC-8580-T-Q-LX</b>	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -40 to 70°C operating temperature	<b>9.314,00 €</b>	12~16W
<b>UC-8580-WLAN33-AC</b>	3 transmitter 3 receiver Wi-Fi card module, 3 SMA connectors with cables	<b>691,00 €</b>	56~60W
<b>UC-LTE-CAT1-AP</b>	LTE cellular module with 2 M2 and 2 M2.5 mounting screws for Asia-Pacific bands 1, 3, 5, 8, 9, 18(26), 19, 28	<b>275,00 €</b>	56~60W
<b>UC-LTE-CAT1-EU</b>	LTE cellular module with 2 M2 and 2 M2.5 mounting screws for EMEA bands 1, 3, 7, 8, 20, 28A	<b>275,00 €</b>	20~24W
<b>UC-WiFi-USB</b>	802.11 a/b/g/n/ac, 2.4/5 GHz Wi-Fi module with 2 each of M2 and M2.5 screws	<b>99,00 €</b>	28~32W
<b>UPort 1110</b>	1-port RS-232 USB-to-serial converter	<b>54,00 €</b>	8~12W
<b>UPort 1130</b>	1-port RS-422/485 USB-to-serial converter	<b>98,00 €</b>	8~12W
<b>UPort 1130I</b>	1-port RS-422/485 USB-to-serial converter with 2 kV optical isolation	<b>186,00 €</b>	8~12W
<b>UPort 1150</b>	1-port RS-232/422/485 USB-to-serial converter	<b>145,00 €</b>	8~12W
<b>UPort 1150I</b>	1-port RS-232/422/485 USB-to-serial converter with optical isolation protection	<b>246,00 €</b>	2~4W
<b>UPort 1250</b>	USB to 2-port RS-232/422/485 serial hub	<b>212,00 €</b>	8~12W
<b>UPort 1250-G2</b>	2-port RS-232/422/485 USB-to-serial converter, 0 to 60°C operating temperature	<b>212,00 €</b>	8~12W
<b>UPort 1250-G2-T</b>	2-port RS-232/422/485 USB-to-serial converter, -40 to 75°C operating temperature	<b>263,00 €</b>	12~16W
<b>UPort 1250I</b>	USB to 2-port RS-232/422/485 serial hub with 2 kV isolation	<b>380,00 €</b>	8~12W
<b>UPort 1250I-G2</b>	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, 0 to 60°C operating temperature	<b>371,00 €</b>	8~12W
<b>UPort 1250I-G2-T</b>	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, -40 to 75°C operating temperature	<b>467,00 €</b>	12~16W
<b>UPort 1410</b>	USB to 4-port RS-232 serial hub	<b>311,00 €</b>	2~4W
<b>UPort 1410-G2</b>	USB to 4-port RS-232 converter, 0 to 60°C operating temperature	<b>329,00 €</b>	8~12W
<b>UPort 1450</b>	USB to 4-port RS-232/422/485 serial hub	<b>449,00 €</b>	2~4W
<b>UPort 1450-G2</b>	USB to 4-port RS-232/422/485 converter, 0 to 60°C operating temperature	<b>400,00 €</b>	8~12W
<b>UPort 1450-G2-T</b>	USB to 4-port RS-232/422/485 converter, -40 to 75°C operating temperature	<b>502,00 €</b>	12~16W
<b>UPort 1450I</b>	USB to 4-port RS-232/422/485 serial hub with 2 kV isolation	<b>755,00 €</b>	2~4W
<b>UPort 1450I-G2</b>	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	<b>732,00 €</b>	8~12W
<b>UPort 1450I-G2-T</b>	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	<b>914,00 €</b>	12~16W
<b>UPort 1610-16</b>	USB to 16-port RS-232 serial hub	<b>897,00 €</b>	4~8W
<b>UPort 1610-8</b>	USB to 8-port RS-232 serial hub	<b>483,00 €</b>	2~4W
<b>UPort 1610-8-G2</b>	USB to 8-port RS-232 converter, 0 to 60°C operating temperature	<b>467,00 €</b>	8~12W
<b>UPort 1650-16</b>	USB to 16-port RS-232/422/485 serial hub	<b>1.239,00 €</b>	4~8W
<b>UPort 1650-8</b>	USB to 8-port RS-232/422/485 serial hub	<b>726,00 €</b>	2~4W
<b>UPort 1650-8-G2</b>	USB to 8-port RS-232/422/485 converter, 0 to 60°C operating temperature	<b>701,00 €</b>	8~12W
<b>UPort 1650-8-G2-Hub</b>	USB to 8-port RS-232/422/485 converter with 3 extra downstream USB ports, 0 to 60°C operating temperature	<b>906,00 €</b>	8~12W
<b>UPort 1650-8-G2-T</b>	USB to 8-port RS-232/422/485 converter, -40 to 75°C operating temperature	<b>874,00 €</b>	12~16W
<b>UPort 1650I-8-G2</b>	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	<b>1.259,00 €</b>	8~12W
<b>UPort 1650I-8-G2-T</b>	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	<b>1.576,00 €</b>	12~16W
<b>UPort 204</b>	4-port entry-level USB hub, adaptor included	<b>246,00 €</b>	2~4W
<b>UPort 204A</b>	4-port general-purpose USB 3.2 hubs	<b>262,00 €</b>	4~8W
<b>UPort 207</b>	7-port entry-level USB hub, adaptor included	<b>298,00 €</b>	4~8W
<b>UPort 207A</b>	7-port general-purpose USB 3.2 hubs	<b>317,00 €</b>	8~12W
<b>UPort 2210</b>	2-port RS-232 USB-to-serial converter	<b>209,00 €</b>	4~8W
<b>UPort 2410</b>	4-port RS-232 USB-to-serial converter	<b>275,00 €</b>	4~8W
<b>UPort 404</b>	4-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	<b>352,00 €</b>	2~4W
<b>UPort 404A</b>	4-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	<b>368,00 €</b>	4~8W
<b>UPort 404A-T</b>	4-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	<b>497,00 €</b>	12~16W
<b>UPort 404-T</b>	4-port industrial USB hub, -40 to 85°C operating temperature	<b>405,00 €</b>	16~20W
<b>UPort 404-T w/o Adapter</b>	4-port industrial USB hub, without adapter, -40 to 85°C operating temperature	<b>439,00 €</b>	4~8W
<b>UPort 407</b>	7-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	<b>418,00 €</b>	2~4W
<b>UPort 407A</b>	7-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	<b>445,00 €</b>	4~8W
<b>UPort 407A-T</b>	7-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	<b>582,00 €</b>	4~8W
<b>UPort 407-T w/o Adapter</b>	7-port industrial USB hub, without adapter, -40 to 85°C operating temperature	<b>535,00 €</b>	4~8W
<b>V2201 Wi-Fi mini Card</b>	SparkLAN WPEA-252NI Wi-Fi mini card with 4 black screws	<b>380,00 €</b>	56~60W

<b>V2201-E1-T</b>	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	<b>2.070,00 €</b>	8~12W
<b>V2201-E1-T-LX</b>	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Linux Debian 8 preinstalled, -40 to 85°C operating temperature	<b>2.194,00 €</b>	8~12W
<b>V2201-E1-T-W7E</b>	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Windows Embedded Standard 7 preinstalled, -40 to 85°C operating temperature	<b>2.406,00 €</b>	8~12W
<b>V2201-E1-W-T</b>	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Wi-Fi and cellular antenna SMA-type connectors, -40 to 85°C operating temperature	<b>2.194,00 €</b>	8~12W
<b>V2201-E2-T</b>	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	<b>2.166,00 €</b>	8~12W
<b>V2201-E2-W-T</b>	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 85°C operating temperature	<b>2.286,00 €</b>	8~12W
<b>V2201-E4-T</b>	x86 embedded computer with Intel Atom® E3845, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, -40 to 70°C operating temperature	<b>2.255,00 €</b>	8~12W
<b>V2201-E4-W-T</b>	x86 embedded computer with Intel Atom® E3845 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 70°C operating temperature	<b>2.376,00 €</b>	8~12W
<b>V2201-E4-W-T-LX</b>	x86 embedded computer with Intel Atom® E3845 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot with 16 GB card preinstalled, 1 mSATA slot with 32 GB preinstalled, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, Linux Debian 8 preinstalled, -40 to 70°C operating temperature	<b>2.385,00 €</b>	8~12W
<b>V2400 Cover-DB9</b>	Dual DB9 expansion cover, 4 male hex standoff spacer pillars	<b>23,00 €</b>	4~8W
<b>V2400 Isolated Wall Mount Kit</b>	Wall-mounting kit with isolation protection, 2 wall-mounting brackets, 4 screws	<b>62,00 €</b>	4~8W
<b>V2400-WLAN22-AC</b>	SparkLAN WPEQ-261ACNI (BT) Wi-Fi mini card, 4 black screws	<b>157,00 €</b>	20~24W
<b>V2403C-KL1-T</b>	x86 computer with Intel® 7th Gen Celeron® 3965U 2.2 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	<b>3.485,00 €</b>	8~12W
<b>V2403C-KL3-T</b>	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	<b>4.028,00 €</b>	8~12W
<b>V2403C-KL5-T</b>	x86 computer with Intel® 7th Gen Core™ i5-7300U 3.5 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	<b>4.698,00 €</b>	8~12W
<b>V2403C-KL7-T</b>	x86 computer with Intel® 7th Gen Core™ i7-7600U 3.9 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	<b>5.233,00 €</b>	8~12W
<b>V2403C-LTECat4-AP</b>	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region, 3 SMA antenna cables	<b>237,00 €</b>	56~60W
<b>V2403C-LTECat4-EU</b>	Telit LE910C4 LTE Cat. 4 mini card for Europe, 3 SMA antenna cables	<b>237,00 €</b>	56~60W
<b>V2403C-LTECat4-NF</b>	Telit LE910C4 LTE Cat. 4 mini card for North America, 3 SMA antenna cables	<b>237,00 €</b>	56~60W
<b>V2406C TPM2.0 CT Module</b>	SLB9665XT2.0 TPM 2.0 module with conformal coating	<b>52,00 €</b>	56~60W
<b>V2406C TPM2.0 Module</b>	SLB9665XT2.0 TPM 2.0 module without conformal coating	<b>48,00 €</b>	56~60W
<b>V2406C Wall mount kit</b>	Single-bracket wall-mounting kit for the V2406C Series with 8 M3 x 6 mm screws	<b>48,00 €</b>	10~12W
<b>V2406C-KL1-CT-T</b>	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature, conformal coating	<b>6.143,00 €</b>	12~16W
<b>V2406C-KL1-T</b>	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	<b>5.115,00 €</b>	12~16W
<b>V2406C-KL3-T</b>	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	<b>5.887,00 €</b>	12~16W
<b>V2406C-KL5-T</b>	x86 computer with Intel® 7th Gen Core™ i5-7300U 2.6 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	<b>6.786,00 €</b>	12~16W
<b>V2406C-KL7-CT-T</b>	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature, conformal coating	<b>9.603,00 €</b>	12~16W
<b>V2406C-KL7-T</b>	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	<b>8.006,00 €</b>	12~16W
<b>V2406C-LTECat4-AP</b>	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region	<b>237,00 €</b>	20~24W
<b>V2406C-LTECat4-EU</b>	Telit LE910C4 LTE Cat. 4 mini card for European region	<b>237,00 €</b>	20~24W
<b>V2406C-LTECat4-NF</b>	Telit LE910C4 LTE Cat. 4 mini card for the North American region	<b>237,00 €</b>	20~24W

<b>V2406C-WL1-CT-T</b>	x86 computer with Intel 8th Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature, conformal coating	<b>5.233,00 €</b>	12~16W
<b>V2406C-WL1-T</b>	x86 computer with Intel 8th Gen Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	<b>4.334,00 €</b>	8~12W
<b>V2406C-WL3-T</b>	x86 computer with Intel 8th Gen Core™ i3-8145UE 3.90 GHz processor, 1 HDMI port, 1 VGA port, 2 Gigabit Ethernet ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	<b>5.030,00 €</b>	8~12W
<b>V2406C-WL5-T</b>	x86 computer with Intel 8th Gen Core™ i5-8365UE 4.1 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	<b>5.821,00 €</b>	8~12W
<b>V2406C-WL7-CT-T</b>	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature, conformal coating	<b>8.377,00 €</b>	12~16W
<b>V2406C-WL7-T</b>	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 Dis, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°C operating temperature	<b>6.970,00 €</b>	8~12W
<b>V3210-TL1-4L-T</b>	x86 computer with Intel® Celeron® 6305E processor, 4 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD/HDD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	<b>4.706,00 €</b>	8~12W
<b>V3210-TL1-8L-CT-T</b>	x86 computer with Intel® Celeron® 6305E processor, 8 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>5.634,00 €</b>	12~16W
<b>V3210-TL3-4L-CT-T</b>	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>5.369,00 €</b>	12~16W
<b>V3210-TL3-4L-T</b>	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	<b>5.104,00 €</b>	8~12W
<b>V3210-TL5-8L-CT-T</b>	x86 computer with Intel® Core™ i5-1145G7E processor, 8 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>6.496,00 €</b>	12~16W
<b>V3210-TL7-4L-T</b>	x86 computer with Intel® Core™ i7-1185GRE processor, 4 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	<b>7.331,00 €</b>	8~12W
<b>V3210-TL7-8L-CT-T</b>	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>8.882,00 €</b>	12~16W
<b>V3210-TL7-8L-TSN-CT-T</b>	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 Dis, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, native TSN support, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	<b>9.014,00 €</b>	12~16W
<b>VP-06TC1L</b>	Top cover of VPort P06-1MP-M12 (LED)	<b>43,00 €</b>	8~12W
<b>VP-06TC2CS</b>	Top cover of VPort 06-2L, coating dome cover, smoked dome	<b>72,00 €</b>	8~12W
<b>VP-DP01</b>	silica gel dry pack (2 x 0.6 g) with sticker	<b>7,00 €</b>	4~8W
<b>VP-DP02</b>	15 g dry pack with hook-and-loop fastener	<b>7,00 €</b>	4~8W
<b>VP-FMK1</b>	Flush-mounting kit for the VPort P16	<b>159,00 €</b>	8~12W
<b>VP-FP1</b>	Fixed plate for mounting the VPort P06-1MP-M12	<b>20,00 €</b>	4~8W
<b>VP-FP2</b>	Fixed plate for mounting the VPort 06	<b>19,00 €</b>	4~8W
<b>VPort 06-2L28M</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	<b>1.118,00 €</b>	20~24W
<b>VPort 06-2L28M-T</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	<b>1.319,00 €</b>	20~24W
<b>VPort 06-2L36M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	<b>1.120,00 €</b>	20~24W
<b>VPort 06-2L36M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort 06-2L42M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	<b>1.120,00 €</b>	20~24W
<b>VPort 06-2L42M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort 06-2L60M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	<b>1.105,00 €</b>	20~24W
<b>VPort 06-2L60M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort 06-2L80M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	<b>1.120,00 €</b>	20~24W
<b>VPort 06-2L80M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort 06-2M28M</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	<b>1.173,00 €</b>	20~24W
<b>VPort 06-2M28M-T</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	<b>1.345,00 €</b>	20~24W
<b>VPort 06-2M36M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W

<b>VPort 06-2M36M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	<b>1.375,00 €</b>	20~24W
<b>VPort 06-2M42M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort 06-2M42M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	<b>1.375,00 €</b>	20~24W
<b>VPort 06-2M60M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort 06-2M60M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	<b>1.375,00 €</b>	20~24W
<b>VPort 06-2M80M</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort 06-2M80M-T</b>	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	<b>1.375,00 €</b>	20~24W
<b>VPort 06EC-2V36M</b>	EN50155, 1080P, day and night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature	<b>2.372,00 €</b>	12~16W
<b>VPort 06EC-2V36M-CT</b>	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature, conformal coating	<b>2.852,00 €</b>	16~20W
<b>VPort 06EC-2V36M-CT-T</b>	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature, conformal coating	<b>3.060,00 €</b>	16~20W
<b>VPort 06EC-2V36M-T</b>	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature	<b>2.550,00 €</b>	12~16W
<b>VPort 06EC-2V42M</b>	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature	<b>2.372,00 €</b>	12~16W
<b>VPort 06EC-2V42M-CT</b>	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature, conformal coating	<b>2.852,00 €</b>	16~20W
<b>VPort 06EC-2V42M-CT-T</b>	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature, conformal coating	<b>3.060,00 €</b>	16~20W
<b>VPort 06EC-2V42M-T</b>	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature	<b>2.550,00 €</b>	16~20W
<b>VPort 06EC-2V60M</b>	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature	<b>2.372,00 €</b>	12~16W
<b>VPort 06EC-2V60M-CT</b>	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature, conformal coating	<b>2.852,00 €</b>	16~20W
<b>VPort 06EC-2V60M-CT-T</b>	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature, conformal coating	<b>3.060,00 €</b>	16~20W
<b>VPort 06EC-2V60M-T</b>	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature	<b>2.550,00 €</b>	16~20W
<b>VPort 06EC-2V80M</b>	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature	<b>2.372,00 €</b>	12~16W
<b>VPort 06EC-2V80M-CT</b>	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature, conformal coating	<b>2.852,00 €</b>	16~20W
<b>VPort 06EC-2V80M-CT-T</b>	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature, conformal coating	<b>3.060,00 €</b>	16~20W
<b>VPort 06EC-2V80M-T</b>	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature	<b>2.550,00 €</b>	16~20W
<b>VPort 461A</b>	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -25 to 60°C operating temperature	<b>958,00 €</b>	4~8W
<b>VPort 461A-T</b>	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -40 to 75°C operating temperature	<b>1.137,00 €</b>	4~8W
<b>VPort 464</b>	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -25 to 60°C operating temperature	<b>2.013,00 €</b>	4~8W
<b>VPort 464-T</b>	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -40 to 75°C operating temperature	<b>2.181,00 €</b>	4~8W
<b>VPort P06-1MP-M12-CAM28</b>	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	<b>904,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM28-T</b>	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	<b>1.082,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM36</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	<b>912,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM36-T</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	<b>1.092,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM42</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	<b>912,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM42-T</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	<b>1.092,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM60</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	<b>912,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM60-T</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -40 to 70°C operating temperature	<b>1.092,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM80</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	<b>912,00 €</b>	12~16W
<b>VPort P06-1MP-M12-CAM80-T</b>	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	<b>1.092,00 €</b>	16~20W
<b>VPort P06-2L28M</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	<b>1.118,00 €</b>	20~24W
<b>VPort P06-2L28M-T</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	<b>1.289,00 €</b>	20~24W
<b>VPort P06-2L36M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -25 to 55°C operating temperature	<b>1.105,00 €</b>	20~24W
<b>VPort P06-2L36M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort P06-2L42M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -25 to 55°C operating temperature	<b>1.105,00 €</b>	20~24W

<b>VPort P06-2L42M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort P06-2L60M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -25 to 55°C operating temperature	<b>1.105,00 €</b>	20~24W
<b>VPort P06-2L60M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	20~24W
<b>VPort P06-2L80M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -25 to 55°C operating temperature	<b>1.105,00 €</b>	20~24W
<b>VPort P06-2L80M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -40 to 70°C operating temperature	<b>1.286,00 €</b>	12~16W
<b>VPort P06-2M28M</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -25 to 55°C operating temperature	<b>1.210,00 €</b>	20~24W
<b>VPort P06-2M28M-T</b>	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -40 to 70°C operating temperature	<b>1.382,00 €</b>	20~24W
<b>VPort P06-2M36M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort P06-2M36M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	<b>1.376,00 €</b>	20~24W
<b>VPort P06-2M42M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort P06-2M42M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	<b>1.376,00 €</b>	20~24W
<b>VPort P06-2M60M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort P06-2M60M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 built-in mic, PoE, 6.0 mm lens, -40 to 70°C operating temperature	<b>1.375,00 €</b>	20~24W
<b>VPort P06-2M80M</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	<b>1.211,00 €</b>	20~24W
<b>VPort P06-2M80M-T</b>	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	<b>1.376,00 €</b>	20~24W
<b>VPort P06HC-1V28M</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature	<b>945,00 €</b>	12~16W
<b>VPort P06HC-1V28M-CT</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature, conformal coating	<b>1.036,00 €</b>	12~16W
<b>VPort P06HC-1V36M</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature	<b>945,00 €</b>	12~16W
<b>VPort P06HC-1V36M-CT</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature, conformal coating	<b>1.036,00 €</b>	12~16W
<b>VPort P06HC-1V42M</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature	<b>945,00 €</b>	12~16W
<b>VPort P06HC-1V42M-CT</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature, conformal coating	<b>1.036,00 €</b>	12~16W
<b>VPort P06HC-1V60M</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature	<b>945,00 €</b>	12~16W
<b>VPort P06HC-1V60M-CT</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature, conformal coating	<b>1.036,00 €</b>	12~16W
<b>VPort P06HC-1V80M</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature	<b>945,00 €</b>	12~16W
<b>VPort P06HC-1V80M-CT</b>	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature, conformal coating	<b>1.036,00 €</b>	12~16W
<b>VPort P16-1MP-M12-CAM36</b>	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 3.6mm lens, -25 to 55°C operating temperature	<b>1.286,00 €</b>	16~20W
<b>VPort P16-1MP-M12-CAM36-T</b>	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 3.6mm lens, -40 to 70°C operating temperature	<b>1.465,00 €</b>	16~20W
<b>VPort P16-1MP-M12-CAM80</b>	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 8.0mm lens, -25 to 55°C operating temperature	<b>1.286,00 €</b>	16~20W
<b>VPort P16-1MP-M12-CAM80-T</b>	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 8.0mm lens, -40 to 70°C operating temperature	<b>1.465,00 €</b>	16~20W
<b>VPort P16-1MP-M12-IR-CAM36</b>	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 3.6mm lens, -25 to 55°C operating temperature	<b>1.452,00 €</b>	12~16W
<b>VPort P16-1MP-M12-IR-CAM36-T</b>	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 3.6mm lens, -40 to 70°C operating temperature	<b>1.627,00 €</b>	12~16W
<b>VPort P16-1MP-M12-IR-CAM80</b>	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 8.0mm lens, -25 to 55°C operating temperature	<b>1.452,00 €</b>	12~16W
<b>VPort P16-1MP-M12-IR-CAM80-T</b>	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 8.0mm lens, -40 to 70°C operating temperature	<b>1.627,00 €</b>	12~16W
<b>VPort P16-2MR36M</b>	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	<b>1.480,00 €</b>	12~16W
<b>VPort P16-2MR36M-T</b>	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	<b>1.630,00 €</b>	12~16W
<b>VPort P16-2MR42M</b>	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	<b>1.480,00 €</b>	12~16W
<b>VPort P16-2MR42M-T</b>	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	<b>1.630,00 €</b>	12~16W
<b>VPort P16-2MR60M</b>	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	<b>1.480,00 €</b>	12~16W

<b>VPort P16-2MR60M-T</b>	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	<b>1.630,00 €</b>	12~16W
<b>VPort P16-2MR80M</b>	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	<b>1.480,00 €</b>	12~16W
<b>VPort P16-2MR80M-T</b>	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	<b>1.630,00 €</b>	12~16W
<b>VP-SC02</b>	Side-cable-out adapter for surface mounting a VPort 06-2	<b>10,00 €</b>	4~8W
<b>VP-SCO1</b>	Side-cable-out adapter for mounting the VPort P06-1MP-M12	<b>10,00 €</b>	4~8W
<b>VP-SScrew</b>	VPort P06-1MP series security screw 1000 pcs	<b>387,00 €</b>	4~8W
<b>WAC-1001</b>	Industrial wireless access controller, 0 to 60°C operating temperature	<b>3.393,00 €</b>	8~12W
<b>WAC-1001-T</b>	Industrial wireless access controller, -40 to 75°C operating temperature	<b>4.067,00 €</b>	12~16W
<b>WAC-2004A</b>	Industrial wireless access controller with EU power cord, 0 to 50°C operating temperature	<b>28.620,00 €</b>	8~12W
<b>WALLMOUNT-8100-01</b>	Wall-mounting kit for the UC-8100 with screws	<b>44,00 €</b>	4~8W
<b>WIFI module</b>	Wi-Fi module with 2 built-in antennas and 4 screws	<b>185,00 €</b>	12~16W
<b>WiFi-BGN</b>	802.11ac/a/b/g/n Wi-Fi module x1, i-PEX MHF male connector to RP-SMA female connector x2, ANT-WDB-ARM-02 x1, M2 screw x2	<b>116,00 €</b>	28~32W
<b>Wi-Fi-BGN(252NI)</b>	Wi-Fi module with 2 antennas, antenna cables and connectors, 2 black screws, 2 lock washers, 2 nuts, 1 thermal pad	<b>532,00 €</b>	56~60W
<b>WK-112-01</b>	Wall-mounting kit, 2 plates, 8 screws	<b>33,00 €</b>	4~8W
<b>WK-160-01</b>	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, black	<b>77,00 €</b>	4~8W
<b>WK-160-02</b>	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, gray	<b>77,00 €</b>	4~8W
<b>WK-18</b>	Wall-mounting kit, 1 plate (18 x 120 x 8.5 mm)	<b>10,00 €</b>	4~8W
<b>WK-195</b>	Wall Mounting Kit for PT-7710 series modular Ethernet Switches	<b>75,00 €</b>	4~8W
<b>WK-20-02</b>	Wall-mounting kit, 3 screws, 20 x 140 x 2 mm	<b>26,00 €</b>	4~8W
<b>WK-25</b>	Wall-mounting kit, 2 plates, 4 screws, 25 x 43 x 2 mm	<b>39,00 €</b>	4~8W
<b>WK-30</b>	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	<b>8,00 €</b>	4~8W
<b>WK-30-02</b>	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	<b>19,00 €</b>	4~8W
<b>WK-35-01</b>	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm) and 6 screws	<b>17,00 €</b>	4~8W
<b>WK-35-02</b>	Wall-mounting kit with 2 plates (35 x 24 x 1.2 mm) and 6 screws	<b>17,00 €</b>	4~8W
<b>WK-35-04</b>	Wall-mount kit with 2 plates (35 x 44 x 2.5 mm), 6 screws (FTS x 6 M3 x 4 mm)	<b>17,00 €</b>	4~8W
<b>WK-36-02</b>	DIN-rail/wall-mounting kit, 2 plates, 6 screws	<b>36,00 €</b>	4~8W
<b>WK-40-01</b>	Wall-mounting kit, 2 plates, 6 screws, 40 x 58 x 2 mm	<b>17,00 €</b>	4~8W
<b>WK-41-01</b>	Wall-mounting kit with 1 plate (41 x 144 x 7.5 mm)	<b>54,00 €</b>	4~8W
<b>WK-44-01</b>	Rack-mounting kit, 2 L-shaped plates, 8 screws, 44 x 57.5 x 1.6 mm	<b>17,00 €</b>	4~8W
<b>WK-45-01</b>	Rack-mounting kit, 2 L-shaped plates, 8 screws, 45 x 57 x 2.5 mm	<b>22,00 €</b>	4~8W
<b>WK-46</b>	Wall-mounting kit, 2 plates, 8 screws, 46.5 x 66.8 x 1 mm	<b>8,00 €</b>	4~8W
<b>WK-46-01</b>	Wall-mounting kit, 2 plates, 8 screws, 46 x 66.8 x 2 mm	<b>13,00 €</b>	4~8W
<b>WK-51-01</b>	Wall mounting kit with 2 plates (51.6 x 67 x 2 mm) and 6 screws	<b>20,00 €</b>	4~8W
<b>WK-55</b>	Wall mounting kit with 2 plates (55 x 34.5 x 2.5 mm) and 6 screws	<b>20,00 €</b>	4~8W
<b>WK-60-01</b>	Wall-mounting kit, 2 plates, 6 screws, 60 x 70 x 2 mm	<b>16,00 €</b>	4~8W
<b>WK-75</b>	Wall-mounting kit, 2 plates, 8 screws, 75 x 90 x 2.5 mm	<b>33,00 €</b>	4~8W
<b>WK-90-01</b>	Wall-mounting kit, 2 plates, 6 screws, 90 x 62 x 2.5 mm	<b>28,00 €</b>	4~8W
<b>WK-UP-14168</b>	Wall-mounting kit with 2 plates (35 x 44 mm), 6 screws (FMS M3 x 4 mm) for the UPort 1400 and 1600-8 models	<b>13,00 €</b>	4~8W
<b>WK-UP200A-BAK-SI</b>	Rear-panel wall-mounting kit for the UPort 200A Series, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in) with 2 plates and 6 M3 x 5 mm screws	<b>22,00 €</b>	8~10W
<b>WK-UP200A-BOT-SI</b>	Bottom-panel wall-mounting kit for the UPort 200A Series, 43 x 30 x 2 mm (1.69 x 1.18 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	<b>19,00 €</b>	8~10W
<b>WK-UP400A-BAK-BK</b>	Rear-panel wall-mounting kit for the UPort 400A, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	<b>22,00 €</b>	4~8W
<b>WK-UP400A-BOT-BK</b>	Bottom-panel wall-mounting kit for the UPort 400A/1400-G2/1600-G2 Series with 2 plates (43 x 30 x 2 mm or 1.69 x 1.18 x 0.08 in), 6 M3 x 5 mm screws	<b>19,00 €</b>	4~8W
<b>WM-UC-5000</b>	Wall-mounting kit with screws for the UC-5000 Series	<b>22,00 €</b>	4~8W
<b>XM-4000-16GSFP</b>	Gigabit Ethernet module with 16 1000BaseSFP ports	<b>3.019,00 €</b>	8~12W
<b>XM-4000-16GTX</b>	Gigabit Ethernet module with 16 1000BaseT(X) ports	<b>3.019,00 €</b>	8~12W
<b>XM-4000-16QGSFP</b>	2.5 Gigabit Ethernet module with 16 1000/2500BaseSFP ports	<b>6.031,00 €</b>	8~12W
<b>XM-4000-16QGTX</b>	2.5 Gigabit Ethernet module with 16 1000/2500BaseT(X) ports	<b>6.031,00 €</b>	8~12W
<b>XM-4000-FAN-R</b>	Exhaust fan module for MRX switches	<b>320,00 €</b>	8~12W