



C&D ELETTRONICA SRL

BERGAMO 24126
Via Oprandi, 17
Tel. 035 199 55 011
Fax 035 199 55 099

E-COMMERCE
www.cedelettronica.com
E-MAIL
mail@cedelettronica.com
cedelettronica@pec.it



LABORATORIO EMC
PROVE DI COMPATIBILITA'
ELETTROMAGNETICA



WWW.CEDELETRONICA.COM

WWW.MTEK.IT

C.F. 00895950160
P.IVA IT00895950160

Cap. Soc. 500.000,00 Euro i.v.
R.E.A. BG-180921



Registro A.E.E. n.IT0802000003208
Registro PILE n. IT16010P00003973

Listino prezzi MOXA - www.moxa.com

Prezzi IVA esclusa f.co ns magazzino

Gennaio 2025

Per quantità e offerte speciali contattare:

C&D Elettronica srl

tel. **035.19955011** info@mtek.it

www.mtek.it

MODELLO	DESCRIZIONE	PREZZO	consegna prevista
3G Antenna Package	3G external antenna with QMA (male) to SMA (female) adapter and 2 50 cm cables, 3G external antenna with 2 SMA connectors, cellular extension cable	€ 283,00	8~12W
45ML-5401	Module for the ioThinX 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -20 to 60°C operating temperature	€ 716,00	8~12W
45ML-5401-T	Module for the ioThinX 4530 Series, 4 serial ports (RS-232/422/485 3-in-1), -40 to 75°C operating temperature	€ 859,00	8~12W
45MR-1600	Module for the ioThinX 4500 Series, 16 DIs, 24 VDC, PNP, -20 to 60°C operating temperature	€ 226,00	2~4W
45MR-1600-T	Module for the ioThinX 4500 Series, 16 DIs, 24 VDC, PNP, -40 to 75°C operating temperature	€ 304,00	4~8W
45MR-1601	Module for the ioThinX 4500 Series with 16 DIs, 24 VDC, NPN, -20 to 60°C operating temperature	€ 226,00	4~8W
45MR-1601-T	Module for the ioThinX 4500 Series with 16 DIs, 24 VDC, NPN, -40 to 75°C operating temperature	€ 304,00	12~16W
45MR-2404	Module for the ioThinX 4500 Series with 4 relays, form A, -20 to 60°C operating temperature	€ 202,00	4~8W
45MR-2404-T	Module for the ioThinX 4500 Series, 4 relays, form A, -40 to 75°C operating temperature	€ 284,00	12~16W
45MR-2600	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, sink, -20 to 60°C operating temperature	€ 242,00	4~8W
45MR-2600-T	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	€ 325,00	4~8W
45MR-2601	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, source, -20 to 60°C operating temperature	€ 242,00	4~8W
45MR-2601-T	Module for the ioThinX 4500 Series, 16 DOs, 24 VDC, source, -40 to 75°C operating temperature	€ 325,00	12~16W
45MR-2606	Module for the ioThinX 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -20 to 60°C operating temperature	€ 252,00	4~8W
45MR-2606-T	Module for the ioThinX 4500 Series, 8 DIs, 8 DOs, 24 VDC, PNP, source, -40 to 75°C operating temperature	€ 328,00	12~16W
45MR-3800	Module for the ioThinX 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	€ 536,00	4~8W
45MR-3800-T	Module for the ioThinX 4500 Series, 8 AIs, 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	€ 700,00	12~16W
45MR-3810	Module for the ioThinX 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -20 to 60°C operating temperature	€ 536,00	4~8W
45MR-3810-T	Module for the ioThinX 4500 Series, 8 AIs, -10 to 10 V or 0 to 10 V, -40 to 75°C operating temperature	€ 700,00	12~16W
45MR-4420	Module for the ioThinX 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -20 to 60°C operating temperature	€ 464,00	4~8W
45MR-4420-T	Module for the ioThinX 4500 Series, 4 AOs, 0 to 10 V or 0 to 20 mA or 4 to 20 mA, -40 to 75°C operating temperature	€ 626,00	8~12W
45MR-6600	Module for the ioThinX 4500 Series, 6 RTDs, -20 to 60°C operating temperature	€ 503,00	4~8W
45MR-6600-T	Module for the ioThinX 4500 Series, 6 RTDs, -40 to 75°C operating temperature	€ 655,00	12~16W
45MR-6810	Module for the ioThinX 4500 Series, 8 TCs, -20 to 60°C operating temperature	€ 508,00	4~8W
45MR-6810-T	Module for the ioThinX 4500 Series, 8 TCs, -40 to 75°C operating temperature	€ 655,00	12~16W
45MR-7210	Module for the ioThinX 4500 Series, system and field power inputs, -20 to 60°C operating temperature	€ 245,00	4~8W
45MR-7210-T	Module for the ioThinX 4500 Series, system and field power inputs, -40 to 75°C operating temperature	€ 282,00	12~16W
45MR-7820	Module for the ioThinX 4500 Series, potential distributor module, -20 to 60°C operating temperature	€ 150,00	4~8W
45MR-7820-T	Module for the ioThinX 4500 Series, potential distributor module, -40 to 75°C operating temperature	€ 190,00	8~12W
85M-1602-T	Module for the ioPAC 8500/8600 Series, 16 DIs, 24 VDC, sink/source, -40 to 75°C operating temperature	€ 535,00	8~12W
85M-2600-T	Module for the ioPAC 8500/8600 Series, 16 DOs, 24 VDC, sink, -40 to 75°C operating temperature	€ 535,00	8~12W
85M-3800-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, -40 to 75°C operating temperature	€ 892,00	8~12W
85M-3801-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 4 to 20 mA, 40 kHz, -40 to 75°C operating temperature	€ 1.063,00	8~12W
85M-3810-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, -40 to 75°C operating temperature	€ 892,00	8~12W
85M-3811-T	Module for the ioPAC 8500/8600 Series, 8 AIs, 0 to 10 V, 40 kHz, -40 to 75°C operating temperature	€ 1.063,00	8~12W
85M-5401-T	Module for the ioPAC 8500/8600 Series, 4-port serial, DB44 connectors, -40 to 75°C operating temperature	€ 1.191,00	8~12W
85M-6600-T	Module for the ioPAC 8500/8600 Series, 6 RTDs, -40 to 75°C operating temperature	€ 1.006,00	8~12W
85M-6810-T	Module for the ioPAC 8500/8600 Series, 8 TCs, -40 to 75°C operating temperature	€ 1.113,00	8~12W
85M-BKTES	Empty slot cover (3 pieces per package)	€ 70,00	4~8W
86M-1620D-T	Module for the ioPAC 8600 Series, 16 DIs, 24 to 110 VDC, sink, channel LED, -40 to 75°C operating temperature	€ 807,00	8~12W
86M-1832D-T	Module for the ioPAC 8600 Series with 8 DIs, 24 VDC, sink/source, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	€ 725,00	8~12W
86M-2604D-T	Module for the ioPAC 8600 Series, 6 Relays, form A (N.O.), channel LED, -40 to 75°C operating temperature	€ 553,00	8~12W
86M-2821D-T	Module for the ioPAC 8600 Series, 8 DOs, 24 to 110 VDC, source, channel LED, -40 to 75°C operating temperature	€ 1.001,00	8~12W
86M-2830D-T	Module for the ioPAC 8600 Series with 8 DOs, 24 VDC, sink, channel-to-channel isolation, channel LED, -40 to 75°C operating temperature	€ 1.001,00	8~12W
86M-4420-T	Module for the ioPAC 8600 Series, 4 AOs, 0 to 10 V, -10 to 10 V, 0 to 20 mA, or 4 to 20 mA, -40 to 75°C operating temperature	€ 892,00	8~12W
86M-5212U-T	Module for the ioPAC 8600 Series, 2-port 2-wire Ethernet switch, -40 to 75°C operating temperature	€ 1.409,00	8~12W
86M-5250-T	Module for the ioPAC 8600 Series, 2 CAN ports, -40 to 75°C operating temperature	€ 806,00	8~12W
A52-DB25F w/ Adapter	RS-232/422/485 converter with adapter, DB25F cable	€ 69,00	8~12W
A52-DB25F w/o Adapter	RS-232/422/485 converter with DB25F cable	€ 58,00	8~12W

A52-DB9F w/ Adapter	RS-232/422/485 converter with adapter, DB9F cable	€ 69,00	2~4W
A52-DB9F w/o Adapter	RS-232/422/485 converter with DB9F cable	€ 58,00	2~4W
A53-DB25F w/ Adapter	RS-232/422/485 converter with 2 kV isolation, adapter, DB25F cable	€ 127,00	8~12W
A53-DB25F w/o Adapter	RS-232/422/485 converter with 2 kV isolation, DB25F cable	€ 113,00	8~12W
A53-DB9F w/ Adapter	RS-232/422/485 converter with 2 kV isolation, adapter, DB9F cable	€ 127,00	2~4W
A53-DB9F w/o Adapter	RS-232/422/485 converter with 2 kV isolation, DB9F cable	€ 113,00	4~8W
A-ADP-QMAM-RF	Antenna adapter with QMA (male) to SMA (female) connectors	€ 21,00	12~14W
A-ADP-RJ458P-DB9F-ABC	DB9 female to RJ45 connector for the ABC-01 Series	€ 21,00	12~14W
A-ADP-SM-RF Golden	SMA adapter for UC-2104 and UC-5100 Series	€ 11,00	10~12W
ABC-01	Configuration backup and restoration tool for managed Ethernet switches and AWK Series wireless APs/bridges/clients, 0 to 60°C operating temperature	€ 103,00	4~8W
ABC-01-M12	Configuration backup and restoration tool with M12 connector for managed Ethernet switches and wireless APs/Bridges/Clients, 0 to 60°C operating temperature	€ 143,00	8~12W
ABC-01-P-M12-CT-T	Configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	€ 260,00	4~8W
ABC-02-P-USB-M12-CT-T	USB-based configuration backup and restoration tool with M12 connector for Moxa's ToughNet series of managed Ethernet switches and wireless APs/bridges/clients, -40 to 75°C operating temperature, conformal coating	€ 303,00	12~16W
ABC-02-USB	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, 0 to 60°C operating temperature	€ 213,00	2~4W
ABC-02-USB-T	Configuration backup and restoration tool, firmware upgrade, and log file storage tool for managed Ethernet switches and routers, -40 to 75°C operating temperature	€ 247,00	4~8W
ABC-03-microSD-T	MicroSD-based configuration backup and restoration tool, firmware upgrades, and log file storage tool for managed Ethernet switches and WLAN products, -40 to 85°C operating temperature	€ 85,00	8~12W
A-CAP-M12F-M	Metal cap for M12 female connector	€ 11,00	56~60W
A-CAP-M12F-M-PP	Metal cap for M12 female push-pull connector	€ 6,00	8~10W
A-CAP-M12M-M	Metal cap for M12 male connector	€ 11,00	56~60W
A-CAP-M30M-MIP67	Metal cap for M30 male connector	€ 21,00	10~12W
A-CAP-NM-MIP67	A-CAP-NM-MIP67	€ 14,00	10~12W
A-CAP-WPRJ45-MC	Metal cap with chain for RJ45 connector	€ 27,00	12~14W
A-CRF-CTPSF-R2-50	GPS Extension Cable TNC to SMA (female) adapter with 50 cm cable x 1	€ 69,00	16~20W
A-CRF-MHFQMAF-D1.13-1	Digital Interface Mini card internal antenna with QMA connector x 1, locking washer x 1, O-ring x 1, nut x 1	€ 17,00	16~20W
A-CRF-MHFSF	A-CRF-MHFSF	€ 18,00	10~12W
A-CRF-NMNM-LL4-300	N-type (male) to N-type (male) LMR-400 Lite cable, 3 m	€ 118,00	10~12W
A-CRF-NMNM-LL4-600	N-type (male) to N-type (male) LMR-400 Lite cable, 6 m	€ 174,00	10~12W
A-CRF-NMNM-LL4-900	N-type (male) to N-type (male) LMR-400 Lite cable, 9 m	€ 275,00	10~12W
A-CRF-QMAMNM-R2-50	QMA (male) to N-type (male) RG-316 cable, 0.5 m	€ 93,00	12~16W
A-CRF-RFRM-C2-300	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 3 m	€ 38,00	8~10W
A-CRF-RFRM-C2-500	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, CFD-200 type, 5 m	€ 51,00	8~10W
A-CRF-RFRM-J1-60	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, JSF-141 type, 0.6 m	€ 93,00	12~14W
A-CRF-RFRM-R4-150	Wireless antenna cable with RP-SMA (female) to RP-SMA (male) connectors, magnetic base, RG-174 type, 1.5 m	€ 47,00	10~12W
A-CRF-RMNM-L1-300	N-type (male) to RP SMA (male) LMR-195 Lite cable, 3 m	€ 115,00	10~12W
A-CRF-RMNM-L1-600	N-type (male) to RP SMA (male) LMR-195 Lite cable, 6 m	€ 169,00	10~12W
A-CRF-RMNM-L1-900	N-type (male) to RP SMA (male) LMR-195 Lite cable, 9 m	€ 265,00	10~12W
A-CRF-SMIF-100	Wireless antenna cable package with 2 100-cm cables (SMA connectors)	€ 11,00	10~12W
A-CRF-SMSF-C2-300	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 3 m	€ 38,00	4~8W
A-CRF-SMSF-C2-500	Wireless antenna cable with SMA (male) to SMA (female) connectors, CFD-200 type, 5 m	€ 51,00	8~10W
A-CRF-SMSF-L1-300	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, LMR195 type, 3 m	€ 62,00	16~20W
A-CRF-SMSF-R3-100	Wireless antenna cable with SMA (male) to SMA (female) connectors, magnetic base, RG-174 type, 1 m	€ 41,00	10~12W
ADP-DB9M-DB9M	DB9 to DB9 male connector	€ 7,00	12~14W
ADP-RJ458P-DB9F	DB9 female to RJ45 connector	€ 11,00	12~14W
ADP-RJ458P-DB9M	RJ45 to DB9 male connector	€ 11,00	12~14W
ADP-SCm-STf-M	Multi-mode male SC to female ST duplex adapter, grey color	€ 84,00	4~8W
ADP-SCm-STf-S	Single-mode male SC to female ST duplex adapter, blue color	€ 84,00	4~8W
AIG-101-T	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with -40 to 70°C operating temperature	€ 960,00	4~8W
AIG-101-T-AP	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the Asia-Pacific region, -40 to 70°C operating temperature	€ 1.275,00	12~16W
AIG-101-T-EU	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the EU region, -40 to 70°C operating temperature	€ 1.275,00	12~16W
AIG-101-T-US	2-port Modbus RTU/ASCII/TCP to MQTT/Azure/AWS cloud-ready gateway with built-in LTE Cat. 1 module for the U.S. region, -40 to 70°C operating temperature	€ 1.275,00	12~16W
AIG-301-AP-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -20 to 70°C operating temperature	€ 1.892,00	12~16W
AIG-301-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -20 to 70°C operating temperature	€ 1.247,00	4~8W
AIG-301-EU-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -20 to 70°C operating temperature	€ 1.892,00	12~16W
AIG-301-T-AP-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	€ 2.035,00	4~8W

AIG-301-T-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	€ 1.371,00	4~8W
AIG-301-T-EU-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	€ 2.035,00	4~8W
AIG-301-T-US-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	€ 2.035,00	4~8W
AIG-301-US-AZU-LX	2-port Modbus to Azure advanced IIoT gateways with Arm® Cortex™-A7 dual-core 1 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -20 to 70°C operating temperature	€ 1.892,00	12~16W
AIG-302-T-AP-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the Asia-Pacific region with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature	€ 2.053,00	12~16W
AIG-302-T-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature	€ 1.389,00	12~16W
AIG-302-T-EU-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the EU region with Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature	€ 2.053,00	12~16W
AIG-302-T-US-AZU-LX	2-port Modbus RTU/ASCII/TCP to MQTT/Azure cloud-ready gateway for the U.S. region with LTE Cat. 4 support, Arm® Cortex™-A7 dual-core 1GHz processor, Azure IoT Edge software, -40 to 70°C operating temperature.	€ 2.053,00	12~16W
AIG-501-T-AP-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for Asia-Pacific region, -40 to 70°C operating temperature	€ 3.322,00	8~12W
AIG-501-T-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, -40 to 70°C operating temperature	€ 2.639,00	8~12W
AIG-501-T-EU-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for EU region, -40 to 70°C operating temperature	€ 3.322,00	8~12W
AIG-501-T-US-AZU-LX	4-port Modbus to Azure advanced IIoT gateways with Intel Atom® quad-core 1.91 GHz processor, Azure IoT Edge, LTE Cat. 4 module for U.S. region, -40 to 70°C operating temperature	€ 3.322,00	8~12W
AIG-502-T-AZU-LX	AIG-502-T-AZU-LX	€ 6.600,00	
AIG-502-T-EU-AZU-LX	AIG-502-T-EU-AZU-LX	€ 6.849,00	
ANT-3G-SMA	ANT-3G-SMA	€ 32,00	
ANT-5G-ASM-02	2 dBi LTE/5G NR dipole antenna with SMA (male) connector	€ 29,00	12~14W
ANT-5G-ASM-03	3 dBi GSM/UMTS/LTE/5G NR dipole antenna with SMA (male) connector	€ 26,00	10~12W
ANT-5G-ASM-07	7 dBi, omnidirectional rubber-duck antenna for GSM, UMTS, LTE, and 5G NR applications	€ 55,00	4~8W
ANT-5G-OSM-03-1.5m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1.5 m cable	€ 45,00	10~12W
ANT-5G-OSM-03-1m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 1 m cable	€ 43,00	10~12W
ANT-5G-OSM-03-2m	3 dBi LTE/5G NR omnidirectional adhesive antenna, 2 m cable	€ 47,00	10~12W
ANT-GNSS-CSM-02-3m	2 dBic GNSS antenna with SMA (male) connector, 3 m cable	€ 353,00	10~12W
ANT-GPS-CSM-04-0.2m BK	1575 MHz active GPS/GLONASS 4 dBi antenna with SMA (male) connector and 20-cm cable	€ 53,00	
ANT-GPS-OSM-05-3M	26 dBi at 1575.42 MHz, SMA (male), omnidirectional active GPS antenna, 3 m cable	€ 93,00	12~16W
ANT-LTE-ASM-02	GPRS/EDGE/UMTS/HSPA/LTE, 2 dBi, omnidirectional rubber-duck antenna	€ 27,00	10~12W
ANT-LTE-ASM-04 BK	704 to 960/1710 to 2620 MHz, LTE omnidirectional stick antenna, 4.5 dBi	€ 42,00	4~8W
ANT-LTE-ASM-05 BK	704-960/1710-2620 MHz, LTE stick antenna, 5 dBi	€ 70,00	4~8W
ANT-LTE-OSM-03-3m BK	700-2700 MHz, multiband antenna, specifically designed for 2G, 3G, and 4G applications, 3 m cable	€ 97,00	8~10W
ANT-LTE-OSM-06-3m BK	Multiband antenna with screw-fastened mounting option for 700-2700/2400-2500/5150-5850 MHz frequencies	€ 223,00	4~8W
ANT-LTEUS-ASM-01	GSM/GPRS/EDGE/UMTS/HSPA/LTE, 1 dBi, omnidirectional rubber-duck antenna	€ 31,00	10~12W
ANT-LTEUS-OSM-02	698 to 960/1710 to 2700 MHz, 1/4 λ omnidirectional 1.5 dBi antenna with SMA (male) connector	€ 14,00	
ANT-WDB-ANM-0306	3 dBi at 2.4 GHz or 6 dBi at 5 GHz, N-type (male), omnidirectional antenna	€ 45,00	10~12W
ANT-WDB-ANM-0502	5 dBi at 2.4 GHz or 2 dBi at 5 GHz, N-type (male), omnidirectional antenna	€ 30,00	10~12W
ANT-WDB-ARM-02	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male) omnidirectional rubber-duck antenna	€ 8,00	10~12W
ANT-WDB-ARM-0202	2 dBi at 2.4 GHz or 2 dBi at 5 GHz, RP-SMA (male), dual-band, omnidirectional antenna	€ 9,00	10~12W
ANT-WDB-ARM-0202 plus	2.4/5 GHz omni-directional antenna, 2/2 dBi, RP-SMA-type (male) connector	€ 14,00	10~12W
ANT-WDB-ARM-0405	2.4/5 GHz 1/2 λ 4 to 5 dBi omnidirectional antenna with RP-SMA (female) connector	€ 14,00	
ANT-WDB-ONF-0709	7 dBi at 2.4 GHz or 9 dBi at 5 GHz, N-type (female), dual-band, omnidirectional antenna	€ 187,00	16~20W
ANT-WDB-ONM-0707	07 dBi at 2.4 GHz and 07 dBi at 5 GHz, N-type (male), dual-band omnidirectional antenna	€ 155,00	12~14W
ANT-WDB-PNF-1011	10 dBi at 2.4 GHz and 11 dBi at 5 GHz, N-type (female), dual-band directional antenna	€ 408,00	10~12W
ANT-WSB5-PNF-16	16 dBi at 5 GHz, N-type (female), single-band directional antenna	€ 332,00	10~12W
ANT-WSB-AHRM-05-1.5m	5 dBi at 2.4 GHz, RP-SMA (male), omnidirectional/dipole antenna, 1.5 m cable	€ 27,00	10~12W
ANT-WSB-PNF-12-02	12 dBi at 2.4 GHz, N-type (female), single-band directional antenna	€ 319,00	10~12W
A-PLG-WPM23-01-IP67	Crimp type M23 connector, female 6-pin, IP67-rated	€ 143,00	32~36W
A-PLG-WPM30IP67-01	Field-Installation for M30 plug	€ 77,00	28~32W
A-PLG-WPRJ	Field-installation RJ-type plug	€ 11,00	12~14W
A-SA-NFNF-02	0 to 6 GHz, N-type (female) to N-type (female) surge arrester	€ 86,00	10~12W
A-SA-NMNF-02	0 to 6 GHz, N-type (male) to N-type (female) surge arrester	€ 86,00	10~12W
A-TRM-50-NM	50-ohm termination resistor with N-type male connector	€ 37,00	10~12W
A-TRM-50-RM	50-ohm terminating resistor with RP-SMA male connector	€ 40,00	20~24W
AVK-17	Anti-vibration wiring kit	€ 17,00	4~8W
AWK-1131A-EU	802.11a/b/g/n access point, EU band, 0 to 60°C operating temperature	€ 748,00	2~4W
AWK-1131A-EU-T	802.11a/b/g/n access point, EU band, -40 to 75°C operating temperature	€ 844,00	4~8W
AWK-1131A-JP	802.11a/b/g/n access point, JP band, 0 to 60°C operating temperature	€ 748,00	4~8W
AWK-1131A-JP-T	802.11a/b/g/n access point, JP band, -40 to 75°C operating temperature	€ 844,00	12~16W
AWK-1131A-US	802.11a/b/g/n access point, US band, 0 to 60°C operating temperature	€ 748,00	2~4W
AWK-1131A-US-T	802.11a/b/g/n access point, US band, -40 to 75°C operating temperature	€ 844,00	4~8W
AWK-1137C-EU	802.11a/b/g/n wireless client, EU band, 0 to 60°C operating temperature	€ 663,00	2~4W

AWK-1137C-EU-T	802.11a/b/g/n wireless client, EU band, -40 to 75°C operating temperature	€ 743,00	2~4W
AWK-1137C-JP	802.11a/b/g/n wireless client, JP band, 0 to 60°C operating temperature	€ 663,00	12~16W
AWK-1137C-JP-T	802.11a/b/g/n wireless client, JP band, -40 to 75°C operating temperature	€ 743,00	12~16W
AWK-1137C-US	802.11a/b/g/n wireless client, US band, 0 to 60°C operating temperature	€ 663,00	2~4W
AWK-1137C-US-T	802.11a/b/g/n wireless client, US band, -40 to 75°C operating temperature	€ 743,00	4~8W
AWK-1151C-UN	Industrial 802.11a/b/g/n/ac wireless client, IP30, universal band, 0 to 60°C operating temperature	€ 696,00	12~16W
AWK-1151C-UN-T	Industrial 802.11a/b/g/n/ac wireless client, IP30, universal band, -40 to 75°C operating temperature	€ 793,00	12~16W
AWK-1151C-US	Industrial 802.11a/b/g/n/ac wireless client, IP30, US band, 0 to 60°C operating temperature	€ 696,00	12~16W
AWK-1151C-US-T	Industrial 802.11a/b/g/n/ac wireless client, IP30, US band, -40 to 75°C operating temperature	€ 793,00	12~16W
AWK-1161A-UN	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	€ 886,00	8~12W
AWK-1161A-UN-T	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	€ 1.020,00	8~12W
AWK-1161A-US	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	€ 886,00	8~12W
AWK-1161A-US-T	Industrial 802.11ax wireless AP with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	€ 1.020,00	8~12W
AWK-1161C-UN	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -25 to 60°C operating temperature	€ 772,00	8~12W
AWK-1161C-UN-T	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, UN band, -40 to 75°C operating temperature	€ 886,00	8~12W
AWK-1161C-US	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -25 to 60°C operating temperature	€ 772,00	8~12W
AWK-1161C-US-T	Industrial 802.11ax wireless client with 1 10/100/1000BaseT(X) port, IP30, US band, -40 to 75°C operating temperature	€ 886,00	8~12W
AWK-1165A-UN	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	€ 993,00	8~12W
AWK-1165A-UN-T	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	€ 1.174,00	8~12W
AWK-1165A-US	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	€ 993,00	8~12W
AWK-1165A-US-T	Industrial 802.11ax wireless AP with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	€ 1.174,00	8~12W
AWK-1165C-UN	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -25 to 60°C operating temperature	€ 872,00	8~12W
AWK-1165C-UN-T	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, UN band, -40 to 75°C operating temperature	€ 1.047,00	8~12W
AWK-1165C-US	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -25 to 60°C operating temperature	€ 872,00	8~12W
AWK-1165C-US-T	Industrial 802.11ax wireless client with 5 10/100/1000BaseT(X) ports, IP30, US band, -40 to 75°C operating temperature	€ 1.047,00	8~12W
AWK-3131A-EU	802.11a/b/g/n access point, EU band, -25 to 60°C operating temperature	€ 893,00	2~4W
AWK-3131A-EU-T	802.11a/b/g/n access point, EU band, -40 to 75°C operating temperature	€ 1.049,00	4~8W
AWK-3131A-JP	802.11a/b/g/n access point, JP band, -25 to 60°C operating temperature	€ 893,00	4~8W
AWK-3131A-JP-T	802.11a/b/g/n access point, JP band, -40 to 75°C operating temperature	€ 1.049,00	12~16W
AWK-3131A-M12-RCC-EU	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -25 to 60°C operating temperature	€ 2.125,00	12~16W
AWK-3131A-M12-RCC-EU	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -25 to 60°C operating temperature, conformal coating	€ 2.520,00	12~16W
AWK-3131A-M12-RCC-EU	802.11n railway onboard indoor single radio access point/client, EU band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.738,00	12~16W
AWK-3131A-M12-RCC-EU	802.11n rail onboard indoor single-radio AP/client, IP30, EU band, -40 to 75°C operating temperature	€ 2.282,00	12~16W
AWK-3131A-M12-RCC-JP	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -25 to 60°C operating temperature	€ 2.125,00	12~16W
AWK-3131A-M12-RCC-JP	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -25 to 60°C operating temperature, conformal coating	€ 2.520,00	12~16W
AWK-3131A-M12-RCC-JP	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.738,00	12~16W
AWK-3131A-M12-RCC-JP	802.11n railway onboard indoor single radio access point/client, JP band, IP30, -40 to 75°C operating temperature	€ 2.282,00	12~16W
AWK-3131A-M12-RCC-US	802.11n railway onboard indoor single radio access point/client, US band, IP30, -25 to 60°C operating temperature	€ 2.125,00	12~16W
AWK-3131A-M12-RCC-US	802.11n railway onboard indoor single radio access point/client, US band, IP30, -25 to 60°C operating temperature, conformal coating	€ 2.520,00	12~16W
AWK-3131A-M12-RCC-US	802.11n railway onboard indoor single radio access point/client, US band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.738,00	12~16W
AWK-3131A-M12-RCC-US	802.11n rail onboard indoor single-radio AP/client, IP30, US band, -40 to 75°C operating temperature	€ 2.282,00	12~16W
AWK-3131A-M12-RTG-EU	802.11n railway onboard indoor single radio access point/client, M12, EU band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.333,00	12~16W
AWK-3131A-M12-RTG-EU	802.11n railway onboard indoor single radio access point/client, M12, EU band, IP30, -40 to 75°C operating temperature	€ 2.018,00	12~16W
AWK-3131A-M12-RTG-JP	802.11n railway onboard indoor single radio access point/client, M12, JP band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.333,00	12~16W

AWK-3131A-M12-RTG-JP-	802.11n railway onboard indoor single radio access point/client, M12, JP band, IP30, -40 to 75°C operating temperature	€ 2.018,00	12~16W
AWK-3131A-M12-RTG-US-	802.11n railway onboard indoor single radio access point/client, M12, US band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.333,00	12~16W
AWK-3131A-M12-RTG-US-	802.11n railway onboard indoor single radio access point/client, M12, US band, IP30, -40 to 75°C operating temperature	€ 2.018,00	12~16W
AWK-3131A-SSC-RTG-EU-	802.11n railway trackside indoor single radio access point/client, SC, EU band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.628,00	12~16W
AWK-3131A-SSC-RTG-EU-	802.11n railway trackside indoor single radio access point/client, SC, EU band, IP30, -40 to 75°C operating temperature	€ 2.303,00	12~16W
AWK-3131A-SSC-RTG-JP-	802.11n railway trackside indoor single radio access point/client, SC, JP band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.628,00	12~16W
AWK-3131A-SSC-RTG-JP-	802.11n railway trackside indoor single radio access point/client, SC, JP band, IP30, -40 to 75°C operating temperature	€ 2.303,00	12~16W
AWK-3131A-SSC-RTG-US-	802.11n railway trackside indoor single radio access point/client, SC, US band, IP30, -40 to 75°C operating temperature, conformal coating	€ 2.628,00	12~16W
AWK-3131A-SSC-RTG-US-	802.11n railway trackside indoor single radio access point/client, SC, US band, IP30, -40 to 75°C operating temperature	€ 2.303,00	12~16W
AWK-3131A-US	802.11a/b/g/n access point, US band, -25 to 60°C operating temperature	€ 893,00	2~4W
AWK-3131A-US-T	802.11a/b/g/n access point, US band, -40 to 75°C operating temperature	€ 1.049,00	2~4W
AWK-3251A-M12-RCC-UN	Railway Wi-Fi 5 AP/client, universal band, IP30, -25 to 60°C operating temperature	€ 2.503,00	12~16W
AWK-3251A-M12-RCC-UN-	Railway Wi-Fi 5 AP/client, universal band, IP30, -40 to 75°C operating temperature, conformal coating	€ 3.198,00	12~16W
AWK-3251A-M12-RCC-UN-	Railway Wi-Fi 5 AP/client, universal band, IP30, -40 to 75°C operating temperature	€ 2.711,00	12~16W
AWK-3251A-M12-RCC-US	Railway Wi-Fi 5 AP/client, US band, IP30, -25 to 60°C operating temperature	€ 2.503,00	12~16W
AWK-3251A-M12-RCC-US-	Railway Wi-Fi 5 AP/client, US band, IP30, -40 to 75°C operating temperature, conformal coating	€ 3.198,00	12~16W
AWK-3251A-M12-RCC-US-	Railway Wi-Fi 5 AP/client, US band, IP30, -40 to 75°C operating temperature	€ 2.711,00	12~16W
AWK-3252A-UN	802.11a/b/g/n/ac access point, UN band, -25 to 60°C operating temperature	€ 1.074,00	4~8W
AWK-3252A-UN-T	802.11a/b/g/n/ac access point, UN band, -40 to 75°C operating temperature	€ 1.264,00	4~8W
AWK-3252A-US	802.11a/b/g/n/ac access point, US band, -25 to 60°C operating temperature	€ 1.074,00	4~8W
AWK-3252A-US-T	802.11a/b/g/n/ac access point, US band, -40 to 75°C operating temperature	€ 1.264,00	4~8W
AWK-4131A-EU-T	802.11a/b/g/n access point, EU band, IP68, -40 to 75°C operating temperature	€ 1.895,00	2~4W
AWK-4131A-JP-T	802.11a/b/g/n access point, JP band, IP68, -40 to 75°C operating temperature	€ 1.895,00	4~8W
AWK-4131A-US-T	802.11a/b/g/n access point, US band, IP68, -40 to 75°C operating temperature	€ 1.895,00	2~4W
AWK-4252A-UN-T	802.11a/b/g/n/ac access point, UN band, IP68, -40 to 75°C operating temperature	€ 2.288,00	4~8W
AWK-4252A-US-T	802.11a/b/g/n/ac access point, US band, IP68, -40 to 75°C operating temperature	€ 2.288,00	4~8W
BKT-DB44L	Cannot find any data	€ 9,00	8~10W
BKT-PWR	Chassis converter rackmount kit accessory package, 2 L-shaped metal plates, 8 screws (FMS M4 x 6 mm)	€ 43,00	4~8W
BXP-A100-E2-2L3C-T	Box computer with Intel Atom® x6211E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.632,00	4~8W
BXP-A100-E2-8C-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.585,00	4~8W
BXP-A100-E2-8L-T	Box computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.108,00	4~8W
BXP-A100-E2-T	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.061,00	4~8W
BXP-A100-E2-T-Win10	Box computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating	€ 2.933,00	4~8W
BXP-A100-E4-2L3C-T	Box computer with Intel Atom® x6425E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.727,00	4~8W
BXP-A100-E4-8C-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.696,00	4~8W
BXP-A100-E4-8L-T	Box computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.124,00	4~8W
BXP-A100-E4-T	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.315,00	4~8W
BXP-A100-E4-T-Win10	Box computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating	€ 2.997,00	4~8W
BXP-C100-C1-2L3C-T	Box computer with Intel® Celeron® 6305E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.680,00	4~8W
BXP-C100-C1-8C-T	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.648,00	4~8W

BXP-C100-C1-8L-T	Box computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.029,00	4~8W
BXP-C100-C1-T	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.363,00	4~8W
BXP-C100-C1-T-Win10	Box computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.457,00	4~8W
BXP-C100-C5-2L3C-T	Box computer with Intel® Core® i5-1145G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.980,00	4~8W
BXP-C100-C5-8C-T	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.011,00	4~8W
BXP-C100-C5-8L-T	Box computer with Intel® Core® i5-1145G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.360,00	4~8W
BXP-C100-C5-T	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.536,00	4~8W
BXP-C100-C5-T-Win10	Box computer with Intel® Core® i5-1145G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 4.677,00	4~8W
BXP-C100-C7-2L3C-T	Box computer with Intel® Core® i7-1185G7E processor, 4 LAN ports, 5 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.360,00	4~8W
BXP-C100-C7-8C-T	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 10 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.329,00	4~8W
BXP-C100-C7-8L-T	Box computer with Intel® Core® i7-1185G7E processor, 10 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.772,00	4~8W
BXP-C100-C7-T	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.075,00	4~8W
BXP-C100-C7-T-Win10	Box computer with Intel® Core® i7-1185G7E processor, 2 LAN ports, 2 serial ports, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 5.391,00	4~8W
CA-104	PC/104 bus, 4-port RS-232 module, 0 to 55°C operating temperature	€ 168,00	8~12W
CA-104-T	PC/104 bus, 4-port RS-232 module, -40 to 85°C operating temperature	€ 227,00	8~12W
CA-108	PC/104 bus, 8-port RS-232 module, 0 to 55°C operating temperature	€ 279,00	4~8W
CA-108-T	PC/104 bus, 8-port RS-232 module, -40 to 85°C operating temperature	€ 377,00	8~12W
CA-114	PC/104 bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	€ 279,00	4~8W
CA-114-T	PC/104 bus with 4-port RS-232/422/485 module, -40 to 85°C operating temperature	€ 377,00	8~12W
CA-132	PC/104 bus, 2-port RS-422/485 module, 0 to 55°C operating temperature	€ 187,00	8~12W
CA-132I	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation	€ 279,00	8~12W
CA-132I-T	PC/104 bus, 2-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	€ 377,00	8~12W
CA-132-T	PC/104 bus, 2-port RS-422/485 module, -40 to 85°C operating temperature	€ 244,00	8~12W
CA-134I	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	€ 507,00	8~12W
CA-134I-T	PC/104 bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	€ 669,00	8~12W
CB-108	PC/104-Plus bus, 8-port RS-232 module, 0 to 55°C operating temperature	€ 377,00	8~12W
CB-108-T	PC/104-Plus bus, 8-port RS-232 module, -40 to 85°C operating temperature	€ 479,00	8~12W
CB-114	PC/104-Plus bus, 4-port RS-232/422/485 module, 0 to 55°C operating temperature	€ 408,00	8~12W
CB-114-T	PC/104-Plus bus, 4-port RS-232/422/485 module, -40 to 85°C operating temperature	€ 522,00	8~12W
CB-134I	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, 0 to 55°C operating temperature	€ 669,00	8~12W
CB-134I-T	PC/104-Plus bus, 4-port RS-422/485 module with 2 kV optical isolation, -40 to 85°C operating temperature	€ 855,00	8~12W
CB-602I w/o Cable	2-port CAN bus PC/104-Plus module, with isolation, 0 to 55°C operating temperature	€ 546,00	8~12W
CB-602I-T w/o Cable	2-port CAN bus PC/104-Plus module, with isolation, -40 to 85°C operating temperature	€ 627,00	8~12W
CBL-F37M37-1M	DB37 female to 4 x DB37 male serial cable, 1 m	€ 28,00	
CBL-F9DPF1x4-BK-100	Console cable with 4-pin connector, 1 m	€ 6,00	12~14W
CBL-F9M9-150	DB9 female to DB9 male serial cable, 1.5 m	€ 21,00	12~14W
CBL-F9M9-20	DB9 female to DB9 male serial cable, 20 cm	€ 14,00	12~14W
CBL-HSF2x10-15	20-pin female to 20-pin female serial cable, 15 cm	€ 14,00	8~10W
CBL-M12(FF4P)Open-BK	A-coded female M12-to-4-pin open cable, black, IP68-rated, 1 m	€ 77,00	16~20W
CBL-M12(FF5P)OPEN-100	A-coded female M12-to-5-pin open wire cable, black, IP67-rated, 1 m	€ 30,00	10~12W
CBL-M12(FF5P)OPEN-200	M12 IP67 5 pin to Open 200m cable	€ 41,00	16~20W
CBL-M12BMM5PF9-BK-15	B-coded male M12-to-5-pin DB9 console cable, black, IP68-rated, 1.5 m	€ 86,00	10~12W
CBL-M12D(MM4P)/RJ45-1	D-coded male M12-to-RJ45 Ethernet cable, black, IP67-rated, 1 m	€ 30,00	10~12W
CBL-M12DFF4PRJ45-BK-1	M12 D-coded IP67 to RJ45 10m cable	€ 57,00	10~12W
CBL-M12DMM4PM12DMM	D-coded male M12-to-D-coded female M12 Ethernet cable, black, IP67-rated, 1 m	€ 121,00	10~12W
CBL-M12FF4POPEN-150 I	M12-Open power cable, 4-pin A-coded female connector, IP67, 1.5 m	€ 82,00	24~28W

CBL-M12FF4POPEN-300 II	M12-Open power cable, 4-pin A-coded female connector, IP67, 3 m	€ 100,00	24~28W
CBL-M12FF5PF9-BK-150-I	A-coded female M12-to-5-pin DB9 console cable, black, IP67-rated, 1.5 m	€ 72,00	10~12W
CBL-M12KFF5POPEN-O-1	K-coded female M12-to-5-pin open wire power cable, orange, IP67-rated, 1.5 m	€ 378,00	24~28W
CBL-M12MM8PRJ45-BK-1	M12 IP67 to RJ45 100m cable	€ 63,00	16~20W
CBL-M12XMM8PRJ45-BK	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 1 m	€ 405,00	24~28W
CBL-M12XMM8PRJ45-BK	M12-to-RJ45 Cat-5E UTP gigabit Ethernet cable, 8-pin X-coded male connector, IP67, 2 m	€ 223,00	24~28W
CBL-M12XMM8PRJ45-Y-2	X-coded male M12-to-RJ45 Ethernet cable, yellow, IP67-rated, 2 m	€ 218,00	16~20W
CBL-M12XMM8P-Y-100-IP	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 1 m	€ 343,00	56~60W
CBL-M12XMM8P-Y-300-IP	X-coded male M12-to-8-pin open wire cable, yellow, IP67-rated, 3 m	€ 385,00	56~60W
CBL-M23(FF6P)/OPEN-BK	M23 female M23-to-6-pin open wire power cable, black, IP67-rated, 1 m	€ 161,00	4~8W
CBL-M25M9x2-50	DB25 male to 2 x DB9 male serial cable, 50 cm	€ 14,00	16~20W
CBL-M44M25x4-50	DB44 male to 4 DB25 male serial cable, 50 cm	€ 28,00	16~20W
CBL-M44M9x4-50	DB44 male to DB9 male serial cable, 50 cm	€ 24,00	16~20W
CBL-M44M9x4-50 (POS)	DB44 male to 4 x DB9 male serial cable, 50 cm	€ 24,00	16~20W
CBL-M62F62-150	DB62 male to DB62 female serial cable, 1.5 m	€ 52,00	12~14W
CBL-M62M25x8-100	DB62 male to 8 x DB25 male serial cable, 1 m	€ 55,00	16~20W
CBL-M62M62-150	DB62 male to DB62 male serial cable, 1.5 m	€ 48,00	16~20W
CBL-M62M9x8-100	DB62 male to 8 x DB9 male serial cable, 1 m	€ 48,00	16~20W
CBL-M68F62-150	DB68 male to DB62 female serial cable, 1.5 m	€ 62,00	16~20W
CBL-M68M25x8-100	SCSI VHDCI 68 to 8 x DB25 male serial cable, 1 m	€ 88,00	16~20W
CBL-M68M62-150	DB68 male to DB62 male serial cable, 1.5 m	€ 82,00	16~20W
CBL-M68M9x8-100	SCSI VHDCI 68 to 8 x DB9 male serial cable, 1 m	€ 85,00	16~20W
CBL-M78M25x8-100	DB78 male to 8 x DB25 male serial cable, 1 m	€ 94,00	16~20W
CBL-M78M9x8-100	DB78 male to 8 x DB9 male serial cable, 1 m	€ 91,00	16~20W
CBL-M9HSF1x10H-15-01	10-pin female to 1 DB9 male serial cable, 15 cm	€ 11,00	10~12W
CBL-M9HSF1x10H-15-02	10-pin female to 1 DB9 male serial cable, 15 cm	€ 11,00	10~12W
CBL-M9x2HSF2x10H-15	20-pin female to 2 DB9 male serial cables, 15 cm	€ 18,00	10~12W
CBL-PJ21NOPEN-BK-30 w	CBL-PJ21NOPEN-BK-30 w/Nut	€ 11,00	10~12W
CBL-PJTB-10	Non-locking barrel plug to bare-wire cable	€ 6,00	4~8W
CBL-RJ458P-100	8-pin RJ45 CAT5 Ethernet cable, 1 m	€ 8,00	12~14W
CBL-RJ458P-Cisco-BK-18	8-pin RJ45 to 8-pin RJ45 serial cable, 1.8 m, for Cisco console port	€ 15,00	16~20W
CBL-RJ45F25-150	8-pin RJ45 to DB25 female serial cable, 1.5 m	€ 8,00	12~14W
CBL-RJ45F9-150	8-pin RJ45 to DB9 female serial cable, 1.5m	€ 14,00	12~14W
CBL-RJ45M25-150	8-pin RJ45 to DB25 male serial cable, 1.5m	€ 8,00	16~20W
CBL-RJ45M9-150	8-pin RJ45 to DB9 male serial cable, 1.5m	€ 14,00	12~14W
CBL-RJ45SF25-150	8-pin RJ45 to DB25 female serial cable with shielding, 1.5m	€ 14,00	12~14W
CBL-RJ45SF9-150	8-pin RJ45 to DB9 female serial cable with shielding, 1.5m	€ 11,00	12~14W
CBL-RJ45SM25-150	8-pin RJ45 to DB25 male serial cable with shielding, 1.5m	€ 11,00	16~20W
CBL-RJ45SM9-150	8-pin RJ45 to DB9 male serial cable with shielding, 1.5m	€ 11,00	12~14W
CBL-USB3-BA-BK-120	USB 3.2 Gen 1 cable, type A-to-type B, 1.2 m	€ 20,00	10~12W
CBL-USB3-BA-G-028	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 0.28 m	€ 30,00	10~12W
CBL-USB3-BA-G-120	USB 3.2 Gen 1 cable, type A-to-type B with latch and screw, 1.2 m	€ 28,00	10~12W
CBL-USBA/B-100	USB 2.0 cable, type A-to-type B, 1 m	€ 6,00	16~20W
CBL-USBAMM12BMM5P-E	120cm B-coded USB-to-5-pin cable with IP68-rated, 5-pin male M12 connector	€ 92,00	20~24W
CBL-USBAP-50	USB A male/2.1 mm DC Jack cable, 50 cm	€ 6,00	16~20W
CCG-1510-T	Industrial private 5G cellular gateway, n1, n3, n28, n41, n48, n77, n78 bands, IP30, -40 to 70°C operating temperature	€ 1.811,00	12~16W
CM-600-2MSC/2TX	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	€ 699,00	4~8W
CM-600-2SSC/2TX	Fast Ethernet interface module with 2 10/100BaseT(X) ports, RJ45 connectors, and 2 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	€ 1.597,00	4~8W
CM-600-3MSC/1TX	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	€ 876,00	8~12W
CM-600-3SSC/1TX	Fast Ethernet interface module with 1 10/100BaseT(X) port, RJ45 connector, and 3 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	€ 1.990,00	4~8W
CM-600-4MSC	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, SC connectors, -40 to 75°C operating temperature	€ 1.063,00	4~8W
CM-600-4MST	Fast Ethernet interface module with 4 100BaseFX multi-mode ports, ST connectors, -40 to 75°C operating temperature	€ 1.063,00	4~8W
CM-600-4SSC	Fast Ethernet interface module with 4 100BaseFX single-mode ports, SC connectors, -40 to 75°C operating temperature	€ 2.552,00	4~8W
CM-600-4TX	Fast Ethernet interface module with 4 10/100BaseT(X) ports, RJ45 connectors, -40 to 75°C operating temperature	€ 329,00	4~8W
CN20030	10-pin RJ45 to DB25 female serial cable	€ 11,00	16~20W
CN20040	10-pin RJ45 to DB25 male serial cable	€ 11,00	16~20W
CN20060	10-pin RJ45 to DB9 male serial cable	€ 11,00	16~20W
CN20070	10-pin RJ45 to DB9 female serial cable	€ 8,00	16~20W
CN2510-16	16-port RS-232 Async Server, 100 to 240 VAC power input	€ 1.534,00	4~8W
CN2510-16-48V	16-port RS-232 Async Server, +/-48 VDC power input	€ 1.625,00	8~12W
CN2510-8	8-port RS-232 Async Server, 100 to 240 VAC power input	€ 1.375,00	8~12W
CN2510-8-48V	8-port RS-232 Async Server, +/-48 VDC power input	€ 1.473,00	8~12W
CN2610-16	Dual-LAN terminal server with 16 RS-232 ports	€ 2.159,00	8~12W
CN2610-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232 ports	€ 2.315,00	8~12W
CN2610-8	Dual-LAN terminal server with 8 RS-232 ports	€ 1.704,00	8~12W

CN2610-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232 ports	€ 1.860,00	8~12W
CN2650-16	Dual-LAN terminal server with 16 RS-232/422/485 ports	€ 2.253,00	4~8W
CN2650-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports	€ 2.409,00	4~8W
CN2650-16-2AC-T	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, -40 to 75°C operating temperature	€ 3.284,00	4~8W
CN2650-8	Dual-LAN terminal server with 8 RS-232/422/485 ports	€ 1.739,00	4~8W
CN2650-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports	€ 1.895,00	4~8W
CN2650-8-2AC-T	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, -40 to 75°C operating temperature	€ 2.579,00	8~12W
CN2650I-16	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	€ 3.117,00	4~8W
CN2650I-16-2AC	Dual-LAN, dual-AC-power terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation	€ 3.268,00	4~8W
CN2650I-16-HV-T	Dual-LAN terminal server with 16 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 3.753,00	8~12W
CN2650I-8	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	€ 2.176,00	4~8W
CN2650I-8-2AC	Dual-LAN, dual-AC-power terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation	€ 2.330,00	4~8W
CN2650I-8-HV-T	Dual-LAN terminal server with 8 RS-232/422/485 ports, 2 kV optical isolation, 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 2.710,00	8~12W
CP-102E	2-port RS-232 PCI Express x1 serial board	€ 135,00	2~4W
CP-102EL-DB9M	2-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	€ 146,00	2~4W
CP-102N-I-T	2-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	€ 340,00	8~12W
CP-102N-T	2-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	€ 188,00	8~12W
CP-102U	2-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	€ 84,00	2~4W
CP-102UL-DB9M	2-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 94,00	4~8W
CP-102UL-T	2-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	€ 135,00	8~12W
CP-102U-T	2-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	€ 116,00	8~12W
CP-104EL-A w/o Cable	4-port RS-232 low-profile PCI Express x1 serial board, without cable	€ 247,00	2~4W
CP-104EL-A-DB25M	4-port RS-232 low-profile PCI Express x1 serial board (includes DB25 male cable)	€ 260,00	2~4W
CP-104EL-A-DB9M	4-port RS-232 low-profile PCI Express x1 serial board (includes DB9 male cable)	€ 260,00	2~4W
CP-104JU	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, 0 to 55°C operating temperature	€ 179,00	8~12W
CP-104JU-T	4-port RS-232 Universal PCI serial board with RJ45 ports on the board, -40 to 85°C operating temperature	€ 200,00	8~12W
CP-104N-I-T	4-port RS-232 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	€ 608,00	8~12W
CP-104N-T	4-port RS-232 Mini PCI Express serial board, -40 to 85°C operating temperature	€ 335,00	8~12W
CP-104UL w/o Cable	4-port RS-232 low-profile Universal PCI serial board, without cable	€ 146,00	2~4W
CP-104UL-DB25M	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	€ 157,00	2~4W
CP-104UL-DB9M	4-port RS-232 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 157,00	2~4W
CP-104UL-T	4-port RS-232 low-profile Universal PCI serial board, -40 to 85°C operating temperature	€ 217,00	8~12W
CP-112N-T	2-port RS-232/422/485 Mini PCI Express serial board, -40°C to 85 operating temperature	€ 248,00	8~12W
CP-112UL-DB9M	2-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 178,00	4~8W
CP-112UL-I-DB9M	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	€ 313,00	4~8W
CP-112UL-I-T	2-port RS-232/422/485 low-profile Universal PCI board with optical isolation, -40 to 85°C operating temperature	€ 399,00	8~12W
CP-112UL-T	2-port RS-232/422/485 low-profile Universal PCI board, -40 to 85°C operating temperature	€ 267,00	8~12W
CP-114EL	4-port RS-232/422/485 low-profile PCI Express x1 serial board	€ 299,00	2~4W
CP-114EL-DB25M	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB25 male cable)	€ 313,00	2~4W
CP-114EL-DB9M	4-port RS-232/422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	€ 313,00	2~4W
CP-114EL-I	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation	€ 612,00	2~4W
CP-114EL-I-DB25M	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB25 male cable)	€ 627,00	2~4W
CP-114EL-I-DB9M	4-port RS-232/422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	€ 627,00	2~4W
CP-114N-T	4-port RS-232/422/485 Mini PCI Express serial board, -40°C to 85 operating temperature	€ 420,00	8~12W
CP-114UL w/o Cable	4-port RS-232/422/485 low-profile Universal PCI board, 0 to 55°C operating temperature	€ 290,00	4~8W
CP-114UL-DB25M	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	€ 308,00	4~8W
CP-114UL-DB9M	4-port RS-232/422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 308,00	4~8W
CP-114UL-I	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	€ 643,00	4~8W
CP-114UL-I-DB25M	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB25 male cable)	€ 649,00	4~8W
CP-114UL-I-DB9M	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	€ 649,00	4~8W
CP-114UL-I-T	4-port RS-232/422/485 low-profile Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	€ 807,00	8~12W
CP-114UL-T	4-port RS-232/422/485 low-profile Universal PCI serial board, -40 to 85°C operating temperature	€ 323,00	8~12W

CP-116E-A w/o cable	16-port RS-232/422/485 PCI Express board with 4 kV surge protection, 0 to 55°C operating temperature	€ 1.144,00	2~4W
CP-118E-A-I w/o cable	8-port RS-232/422/485 PCI Express x1 serial board with surge protection and electrical isolation	€ 1.253,00	4~8W
CP-118EL-A w/o Cable	8-port RS-232/422/485 low-profile PCI Express x1 serial board	€ 583,00	2~4W
CP-118U	8-port RS-232/422/485 Universal PCI serial board, 0 to 55°C operating temperature	€ 501,00	2~4W
CP-118U-I	8-port RS-232/422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	€ 1.159,00	4~8W
CP-118U-I-T	8-port RS-232/422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	€ 1.205,00	8~12W
CP-118U-T	8-port RS-232/422/485 Universal PCI serial board, -40 to 85°C operating temperature	€ 532,00	8~12W
CP-132EL-DB9M	2-port RS-422/485 low-profile PCI Express x1 serial board (includes DB9 male cable)	€ 179,00	2~4W
CP-132EL-I-DB9M	2-port RS-422/485 low-profile PCI Express x1 serial board with optical isolation (includes DB9 male cable)	€ 317,00	2~4W
CP-132N-I-T	2-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	€ 354,00	8~12W
CP-132N-T	2-port RS-422/485 Mini PCI Express serial board, -40 to 85°C operating temperature	€ 193,00	8~12W
CP-132UL-DB9M	2-port RS-422/485 low-profile Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 142,00	2~4W
CP-132UL-I-DB9M	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, 0 to 55°C operating temperature (includes DB9 male cable)	€ 342,00	2~4W
CP-132UL-I-T	2-port RS-422/485 low-profile Universal PCI serial board with optical isolation, -40°C to 85 operating temperature	€ 314,00	8~12W
CP-132UL-T	2-port RS-422/485 low-profile Universal PCI serial board, -40°C to 85 operating temperature	€ 179,00	8~12W
CP-134EL-A-I w/o cable	4-port RS-422/485 low-profile PCI Express x1 serial board with surge protection and electrical isolation	€ 597,00	2~4W
CP-134EL-A-I-DB25M	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	€ 612,00	2~4W
CP-134EL-A-I-DB9M	4-port RS-422/485 low-profile PCI Express board with 4 kV surge protection, 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	€ 612,00	2~4W
CP-134N-I-T	4-port RS-422/485 Mini PCI Express serial board with 2.5 kV capacitive isolation, -40 to 85°C operating temperature	€ 709,00	8~12W
CP-134U w/o Cable	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	€ 281,00	4~8W
CP-134U-DB25M	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB25 male cable)	€ 303,00	4~8W
CP-134U-DB9M	4-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature (includes DB9 male cable)	€ 303,00	4~8W
CP-134U-I w/o Cable	4-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	€ 649,00	4~8W
CP-134U-I-DB25M	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB25 male cable, 0 to 55°C operating temperature	€ 675,00	4~8W
CP-134U-I-DB9M	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, DB9 male cable, 0 to 55°C operating temperature	€ 675,00	4~8W
CP-134U-I-T	4-port RS-422/485 Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	€ 661,00	8~12W
CP-134U-T	4-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	€ 295,00	8~12W
CP-138E-A-I w/o cable	8-port RS-422/485 PCI Express board with 4 kV surge protection, 2 kV electrical isolation, 0 to 55°C operating temperature	€ 1.083,00	4~8W
CP-138U	8-port RS-422/485 Universal PCI serial board, 0 to 55°C operating temperature	€ 473,00	4~8W
CP-138U-I	8-port RS-422/485 Universal PCI serial board with optical isolation, 0 to 55°C operating temperature	€ 939,00	8~12W
CP-138U-I-T	8-port RS-422/485 Universal PCI serial board with optical isolation, -40 to 85°C operating temperature	€ 1.003,00	8~12W
CP-138U-T	8-port RS-422/485 Universal PCI serial board, -40 to 85°C operating temperature	€ 485,00	8~12W
CP-168EL-A w/o Cable	8-port RS-232 low-profile PCI Express x1 serial board	€ 317,00	2~4W
CP-168U	8-port RS-232 Universal PCI serial board, 0 to 55°C operating temperature	€ 233,00	2~4W
CP-168U-T	8-port RS-232 Universal PCI serial board, -40 to 85°C operating temperature	€ 295,00	8~12W
CP-602E-I w/o Cable	2-port CAN bus PCI Express board with 2 kV electrical isolation, 0 to 55°C operating temperature	€ 570,00	4~8W
CP-602E-I-T w/o Cable	2-port CAN bus PCI Express board with 2 kV electrical isolation, -40 to 85°C operating temperature	€ 661,00	4~8W
CP-602U-I w/o Cable	2-port CAN bus Universal PCI board with 2 kV electrical isolation, 0 to 55°C operating temperature	€ 507,00	8~12W
CP-602U-I-T w/o Cable	2-port CAN bus Universal PCI board with 2 kV electrical isolation, -40 to 85°C operating temperature	€ 589,00	8~12W
CRF-MHF/SMA(M)-14.2	CRF-MHF/SMA(M)-14.2	€ 11,00	10~12W
CRF-SMA(M)/N(M)-300	N-type (male) to SMA (male) CFD200 cable, 3 m	€ 60,00	10~12W
CSM-200-1213	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode ST connector	€ 339,00	4~8W
CSM-200-1214	10/100BaseT(X) to 100BaseFX slide-in module media converter, multi-mode SC connector	€ 339,00	4~8W
CSM-200-1218	10/100BaseT(X) to 100BaseFX slide-in module media converter, single-mode SC connector	€ 476,00	2~4W
CSM-400-1213	10/100BaseT(X)-to-100BaseFX slide-in management module converter with ST connector, multi-mode, 0 to 55°C operating temperature	€ 383,00	8~12W
CSM-400-1213-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode ST connector, -40 to 75°C operating temperature	€ 476,00	8~12W
CSM-400-1214	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -20 to 55°C operating temperature	€ 383,00	8~12W
CSM-400-1214-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, multi-mode SC connector, -40 to 75°C operating temperature	€ 476,00	8~12W
CSM-400-1218	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -20 to 55°C operating temperature	€ 507,00	4~8W
CSM-400-1218-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, single-mode SC connector, -40 to 75°C operating temperature	€ 627,00	8~12W

CSM-400-1224	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -20 to 55°C operating temperature	€ 507,00	8~12W
CSM-400-1224-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-A single-mode SC connector, -40 to 75°C operating temperature	€ 627,00	8~12W
CSM-400-1225	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -20 to 55°C operating temperature	€ 507,00	8~12W
CSM-400-1225-T	10/100BaseT(X) to 100BaseFX slide-in management module converter, WDM-B single-mode SC connector, -40 to 75°C operating temperature	€ 627,00	8~12W
CSM-G200-1221	10/100/1000BaseT(X)-to-100/1000BaseSFP slide-in media converter module	€ 380,00	4~8W
DA-680-I-16-WL3-H	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operat	€ 4.241,00	12~16W
DA-680-I-16-WL3-HH	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 16 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operati	€ 4.352,00	12~16W
DA-680-I-8-WL3-H	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC single power input, -25 to 55°C operati	€ 3.824,00	12~16W
DA-680-I-8-WL3-HH	IEC 61850-3 1U rackmount computer with 8th Gen Intel® Core™ i3-8145UE processor, 8 GbE ports, 8 RS-485 serial ports, 2 DOs, 1 VGA port, 3 USB 3.0 ports, 2 USB 2.0 ports, 1 mSATA slot, 1 SATA slot, 100 to 240 VAC/VDC dual power inputs, -25 to 55°C operatin	€ 3.921,00	12~16W
DA-681C-KL1-HH-T	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	€ 5.206,00	8~12W
DA-681C-KL1-H-T	Intel® 7th Gen Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, single power, -40 to 70°C operating temperature	€ 4.305,00	8~12W
DA-681C-KL3-HH-T	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 10 RS-485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 1 SSD slot, dual power, -40 to 70°C operating temperature	€ 6.849,00	8~12W
DA-682C-KL1-HH-T	Intel® Celeron® 3965U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	€ 5.548,00	8~12W
DA-682C-KL3-HH-T	Intel® 7th Gen Core™ i3-7100U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	€ 6.938,00	8~12W
DA-682C-KL5-HH-T	Intel® 7th Gen Core™ i5-7300U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	€ 8.094,00	8~12W
DA-682C-KL7-HH-T	Intel® 7th Gen Core™ i7-7600U processor, 2 HDMI ports, 2 PS/2 ports, 6 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual power, -40 to 70°C operating temperature	€ 9.129,00	4~8W
DA-720 HDD Kit	DA-720 HDD/SSD kit	€ 56,00	8~10W
DA-720-C5-DPP	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperat	€ 7.301,00	4~8W
DA-720-C5-DPP-LX	Rackmount computer with Core i5-6300U, 2.4 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1	€ 7.709,00	12~16W
DA-720-C7-DPP	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 3 PCIe expansion slots, 1 VGA port, 1 DVI-D port, IEC 61850-3 compliant, -25 to 55°C operating temperat	€ 8.457,00	4~8W
DA-720-C7-DPP-LX	Rackmount computer with Core i7-6600U, 2.6 GHz processor, dual-core processor, 4 GB RAM and Linux Debian 8 64-bit, 14 Gigabit Ethernet ports, 2 isolated RS-232/422/485 ports, 4 USB ports, 1 mSATA slot with 8 GB SSD preinstalled, 3 PCIe expansion slots, 1	€ 8.855,00	12~16W
DA-820C-KL3-HH-T	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	€ 7.454,00	12~16W
DA-820C-KL3-H-T	x86 computer with Intel® Core™ i3-7102E processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	€ 6.986,00	12~16W
DA-820C-KL5-HH-T	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	€ 9.139,00	4~8W
DA-820C-KL5-H-T	x86 computer with Intel® Core™ i5-7442EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	€ 8.691,00	12~16W
DA-820C-KL7-H	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	€ 9.298,00	12~16W
DA-820C-KL7-HH	x86 computer with Intel® Core™ i7-7820EQ processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	€ 9.768,00	4~8W
DA-820C-KLXL-HH-T	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, dual AC power, -40 to 70°C operating temperature	€ 10.295,00	4~8W

DA-820C-KLXL-H-T	x86 computer with Intel® Core™ Xeon E3-1505L v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 4 SSD slots, single AC power, -40 to 70°C operating temperature	€ 9.823,00	12~16W
DA-820C-KLXM-H	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, single AC power, -25 to 55°C operating temperature	€ 10.141,00	12~16W
DA-820C-KLXM-HH	x86 computer with Intel® Core™ Xeon E3-1505M v6 processor, 2 HDMI ports, 1 VGA port, 2 PS/2 ports, 4 Gigabit Ethernet ports, 2 RS/232/422/485 serial ports, 6 DIs, 2 DOs, 1 mSATA slot, 2 SSD slots, dual AC power, -25 to 55°C operating temperature	€ 10.608,00	4~8W
DA-820E-C3-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power m	€ 8.224,00	
DA-820E-C3-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power m	€ 7.647,00	
DA-820E-C3-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power m	€ 7.994,00	
DA-820E-C3-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i3-1320PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power m	€ 7.536,00	
DA-820E-C5-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power m	€ 8.398,00	
DA-820E-C5-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power m	€ 7.828,00	
DA-820E-C5-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power m	€ 8.175,00	
DA-820E-C5-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i5-1340PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power m	€ 7.709,00	
DA-820E-C7-HH-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-150-HV power m	€ 8.669,00	
DA-820E-C7-H-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-150-HV power m	€ 8.092,00	
DA-820E-C7-LL-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 2 DA-PWR-120-LV power m	€ 8.439,00	
DA-820E-C7-L-T	IEC 61850-3 3U rackmount computer with 13th Gen Intel® Core™ i7-1370PE processor, 4 GbE ports, 2 RS-232/422/485 serial ports, 6 DIs, 2 DOs, 3 USB 3.0 ports, 2 USB 2.0 ports, 2 HDMI ports, 1 VGA port, 1 M.2 M-key slot, 4 SATA slots, 1 DA-PWR-120-LV power m	€ 7.980,00	
DA-GX02-SFP-T	2-port 100/1000 Mbps fiber card with 2 SFP slots, 1 PCIe interface	€ 807,00	
DA-IRIG-B-S-02-T	IRIG-B expansion module, PCI interface, 1 fiber IRIG-B input, 1 DB9M input/output, 1 DB9M output, -40 to 75°C operating temperature	€ 467,00	4~8W
DA-PRP-HSR-I210	PRP/HSR expansion card with RJ45 and SFP combo port	€ 2.205,00	4~8W
DA-PWR-120-LV	Hot-swappable power-supply module (48 VDC) with system power input and terminal block for DA-820E computers	€ 466,00	
DA-PWR-150-HV	Hot-swappable power-supply module (100 to 240 VAC/VDC) with system power input and terminal block for DA-820E computers	€ 577,00	
DE-211	1-port RS-232/422/485 device server with 10 Mbps Ethernet connection	€ 210,00	4~8W
DE-2-IRIG-B-4-DI/DO	2-port IRIG-B time synchronization module with 4DI/DO	€ 681,00	12~16W
DE-2-SATA	Expansion module with 2 2.5-inch SSD/HDD slots	€ 739,00	12~16W
DE-311	1-port RS-232/422/485 device server with 10/100 Mbps Ethernet connection	€ 220,00	2~4W
DE-FX02-SFP-T	2-port 100 Mbps fiber card, 2 SFP slots, PCIe interface, -40 to 75°C operating temperature (SFP module excluded)	€ 840,00	8~12W
DE-LN04-RJ	4-port 10/100/1000 Mbps PCIe LAN module	€ 525,00	12~16W
DE-LN08-RJ	8-port 10/100/1000 Mbps PCIe LAN module	€ 674,00	12~16W
DE-PRP-HSR-EF	2-port 100/1000 Mbps PCIe PRP/HSR LAN module	€ 2.205,00	8~12W
DE-SP08-I-TB	8-port RS-232/422/485 PCIe serial module	€ 697,00	4~8W
DK-107-01	DK-107-01	€ 20,00	4~8W
DK-25-01	DIN-rail mounting kit, 2 screws	€ 9,00	16~20W
DK35A	DIN-rail mounting kit, 35 mm	€ 6,00	8~10W
DK-DC50131	DIN-rail mounting kit	€ 36,00	12~14W
DK-M12-305	DIN-rail mounting kit for EDS-305-M12	€ 21,00	8~10W
DK-TN-5305A	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5305A Series	€ 25,00	4~8W
DK-TN-5308	DIN-rail mounting kit for the TN-5308 Series	€ 36,00	8~12W
DK-TN-5308A	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5308A non-PoE Series	€ 42,00	4~8W
DK-TN-5308A-PoE	DIN-rail mounting kit with 1 plate, 3 screws for the TN-5308A PoE Series	€ 42,00	4~8W
DK-UC-5000	DIN-rail mounting kit with screws for the UC-5000 Series	€ 24,00	4~8W
DK-UP1200	DIN rail (25x48.3 mm) with 2 screws (FMS M3X6)	€ 21,00	10~12W
DK-UP1400	DIN-rail/wall-mounting kit, 2 plates, 6 screws, and 2 DIN-rail plates, 4 screws	€ 21,00	10~12W
DK-UP1400-G2	DIN Rail mounitng kits for UPort 1400-G2	€ 33,00	4~8W

DK-UP-14168	DIN-rail kit with 2 plates (89 x 19 mm), 6 screws (FMS M3 x 5 mm) for the UPort 1400 (V1.5.0 and after) and 1600-8 (V1.4.0 and after) models	€ 46,00	4~8W
DK-UP1600-G2	DIN Rail mounting kits for UPort 1600-G2	€ 39,00	4~8W
DK-UP-42A	DIN-rail mounting kit for the UPort 400A/200A Series, 107 x 29 mm (4.21 x 1.14 in), with 4 M3 x 5 mm screws	€ 19,00	4~8W
DN-FX04	4-port 100M/1000M SFP Ethernet module	€ 1.307,00	4~8W
DN-LN04-RJ	4-port 10/100/1000 Mbps PCIe LAN module with RJ45 connectors	€ 926,00	4~8W
DN-PRP-HSR-I210	PRP/HSR expansion module with RJ45 and SFP combo port	€ 2.211,00	8~12W
DN-SP08-I-DB	8-port software-selectable RS-232/422/485 PCIe serial module with DB9 connector	€ 1.114,00	4~8W
DN-SP08-I-TB	8-port software-selectable RS-232/422/485 PCIe serial module with terminal-block connector	€ 1.114,00	4~8W
DRP-A100-E2-2L4C-T	DIN-rail computer with Intel Atom® x6211E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.854,00	4~8W
DRP-A100-E2-6C-T	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.727,00	4~8W
DRP-A100-E2-8L-T	DIN-rail computer with Intel Atom® x6211E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.140,00	4~8W
DRP-A100-E2-T	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.165,00	4~8W
DRP-A100-E2-T-Win10	DIN-rail computer with Intel Atom® x6211E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.029,00	4~8W
DRP-A100-E4-2L4C-T	DIN-rail computer with Intel Atom® x6425E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.981,00	4~8W
DRP-A100-E4-6C-T	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.807,00	4~8W
DRP-A100-E4-8L-T	DIN-rail computer with Intel Atom® x6425E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.235,00	4~8W
DRP-A100-E4-T	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.379,00	4~8W
DRP-A100-E4-T-Win10	DIN-rail computer with Intel Atom® x6425E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.092,00	4~8W
DRP-C100-C1-2L4C-T	DIN-rail computer with Intel® Celeron® 6305E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.965,00	4~8W
DRP-C100-C1-6C-T	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.838,00	4~8W
DRP-C100-C1-8L-T	DIN-rail computer with Intel® Celeron® 6305E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.250,00	4~8W
DRP-C100-C1-T	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.236,00	4~8W
DRP-C100-C1-T-Win10	DIN-rail computer with Intel® Celeron® 6305E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.171,00	4~8W
DRP-C100-C5-2L4C-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.329,00	4~8W
DRP-C100-C5-6C-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.122,00	4~8W
DRP-C100-C5-8L-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.455,00	4~8W
DRP-C100-C5-T	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.536,00	4~8W
DRP-C100-C5-T-Win10	DIN-rail computer with Intel® Core™ i5-1145G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 4.550,00	4~8W
DRP-C100-C7-2L4C-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 4 LAN ports, 6 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.058,00	4~8W
DRP-C100-C7-6C-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 8 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.820,00	4~8W

DRP-C100-C7-8L-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 10 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.359,00	4~8W
DRP-C100-C7-T	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.408,00	4~8W
DRP-C100-C7-T-Win10	DIN-rail computer with Intel® Core™ i7-1185G7E processor, 2 LAN ports, 2 serial ports, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 1 CFast slot, 1 SD slot, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 5.613,00	4~8W
EDF-G1002-BP	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -10 to 60°C operating temperature	€ 1.235,00	8~12W
EDF-G1002-BP-CT	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -10 to 60°C operating temperature	€ 1.536,00	
EDF-G1002-BP-CT-T	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -40 to 75°C operating temperature	€ 1.711,00	
EDF-G1002-BP-T	Industrial next-gen LAN firewall with 2 10/100/1000BaseT(X) ports, 1 Ethernet-based management port, Intrusion Prevention System (IPS), Deep Packet Inspection (DPI), Gen3 bypass, centralized management through MXsecurity, -40 to 75°C operating temperature	€ 1.369,00	12~16W
EDR-8010-2GSFP	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	€ 1.516,00	4~8W
EDR-8010-2GSFP-CT	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	€ 1.879,00	12~16W
EDR-8010-2GSFP-CT-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	€ 2.046,00	12~16W
EDR-8010-2GSFP-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	€ 1.691,00	4~8W
EDR-8010-VPN-2GSFP	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	€ 1.691,00	4~8W
EDR-8010-VPN-2GSFP-CT	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	€ 2.046,00	12~16W
EDR-8010-VPN-2GSFP-CT-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	€ 2.227,00	12~16W
EDR-8010-VPN-2GSFP-T	8 FE copper and 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	€ 1.865,00	8~12W
EDR-810-2GSFP	8+2G SFP industrial multiport secure router with Firewall/NAT, -10 to 60°C operating temperature	€ 1.520,00	2~4W
EDR-810-2GSFP-T	8+2G SFP industrial multiport secure router with Firewall/NAT, -40 to 75°C operating temperature	€ 1.692,00	2~4W
EDR-810-VPN-2GSFP	8+2G SFP industrial multiport secure router with Firewall/NAT/VPN, -10 to 60°C operating temperature	€ 1.692,00	2~4W
EDR-810-VPN-2GSFP-T	8+2G SFP industrial multiport secure router with Firewall/NAT/VPN, -40 to 75°C operating temperature	€ 1.865,00	4~8W
EDR-G9004-VPN-2MGTXS	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	€ 2.630,00	8~12W
EDR-G9004-VPN-2MGTXS	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature, conformal coating	€ 3.287,00	12~16W
EDR-G9004-VPN-2MGTXS	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature, conformal coating	€ 3.461,00	12~16W
EDR-G9004-VPN-2MGTXS	Industrial secure router with 2 Gigabit copper ports with Gen3 Bypass, 2 Gigabit copper/SFP combo ports with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	€ 2.777,00	12~16W
EDR-G9010-VPN-2MGSFP	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -10 to 60°C operating temperature	€ 3.751,00	4~8W
EDR-G9010-VPN-2MGSFP	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -10 to 60°C operating temperature	€ 4.091,00	8~12W
EDR-G9010-VPN-2MGSFP	8 GbE copper + 2 GbE SFP multiport industrial secure router with Firewall/NAT/VPN, 120/220 VDC/VAC input voltage, -40 to 75°C operating temperature	€ 4.245,00	8~12W
EDR-G9010-VPN-2MGSFP	8 GbE copper + 2 GbE SFP multiport industrial secure router with firewall/NAT/VPN, 12/24/48 VDC input voltage, -40 to 75°C operating temperature	€ 4.108,00	4~8W
EDR-G902	Industrial Gigabit firewall/NAT secure router with 1 WAN port, 10 VPN tunnels, 0 to 60°C operating temperature	€ 2.160,00	8~12W
EDR-G902-T	Industrial Gigabit firewall/NAT secure router with 1 WAN port, 10 VPN tunnels, -40 to 75°C operating temperature	€ 2.395,00	8~12W
EDR-G903	Industrial Gigabit firewall/VPN secure router with 3 combo 10/100/1000BaseT(X) ports or 100/1000BaseSFP slots, 0 to 60°C operating temperature	€ 2.848,00	8~12W
EDR-G903-T	Industrial Gigabit firewall/VPN secure router with 3 combo 10/100/1000BaseT(X) ports or 100/1000BaseSFP slots, -40 to 75°C operating temperature	€ 3.079,00	8~12W
EDS-2005-EL	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 138,00	2~4W
EDS-2005-ELP	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	€ 119,00	2~4W
EDS-2005-EL-T	Unmanaged Fast Ethernet switch with 5 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 204,00	2~4W
EDS-2008-EL	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 201,00	2~4W

EDS-2008-EL-M-SC	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 313,00	4~8W
EDS-2008-EL-M-SC-T	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 389,00	8~12W
EDS-2008-EL-M-ST	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 313,00	8~12W
EDS-2008-EL-M-ST-T	Unmanaged Fast Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 389,00	8~12W
EDS-2008-ELP	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	€ 173,00	2~4W
EDS-2008-EL-T	Unmanaged Fast Ethernet switch with 8 10/100BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 279,00	4~8W
EDS-2010-ML-2GTXSFP	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 power inputs, -10 to 60°C operating temperature	€ 660,00	2~4W
EDS-2010-ML-2GTXSFP-T	Unmanaged Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 power inputs, -40 to 75°C operating temperature	€ 780,00	4~8W
EDS-2016-ML	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 power inputs, -10 to 60°C operating temperature	€ 605,00	2~4W
EDS-2016-ML-MM-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	€ 856,00	4~8W
EDS-2016-ML-MM-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 954,00	8~12W
EDS-2016-ML-MM-ST	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	€ 856,00	8~12W
EDS-2016-ML-MM-ST-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 954,00	8~12W
EDS-2016-ML-SS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60°C operating temperature	€ 1.236,00	4~8W
EDS-2016-ML-SS-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.344,00	8~12W
EDS-2016-ML-T	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 power inputs, -40 to 75°C operating temperature	€ 716,00	4~8W
EDS-2018-ML-2GTXSFP	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	€ 1.006,00	4~8W
EDS-2018-ML-2GTXSFP-T	Unmanaged Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	€ 1.115,00	4~8W
EDS-205	Entry-level unmanaged Ethernet switch with 5 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	€ 137,00	2~4W
EDS-205A	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -10 to 60°C operating temperature	€ 162,00	2~4W
EDS-205A-M-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	€ 335,00	2~4W
EDS-205A-M-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	€ 460,00	4~8W
EDS-205A-M-ST	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	€ 335,00	2~4W
EDS-205A-M-ST-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	€ 460,00	4~8W
EDS-205A-S-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	€ 558,00	2~4W
EDS-205A-S-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	€ 683,00	2~4W
EDS-205A-T	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 308,00	2~4W
EDS-208	Entry-level unmanaged Ethernet switch with 8 10/100BaseT(X) ports, plastic housing, -10 to 60°C operating temperature	€ 201,00	2~4W
EDS-208A	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -10 to 60°C operating temperature	€ 235,00	2~4W
EDS-208A-MM-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	€ 559,00	2~4W
EDS-208A-MM-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 644,00	4~8W
EDS-208A-MM-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	€ 559,00	4~8W
EDS-208A-MM-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 644,00	4~8W
EDS-208A-M-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	€ 414,00	2~4W
EDS-208A-M-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	€ 505,00	4~8W
EDS-208A-M-ST	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	€ 414,00	4~8W
EDS-208A-M-ST-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	€ 505,00	4~8W
EDS-208A-S-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	€ 636,00	2~4W
EDS-208A-S-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	€ 760,00	4~8W

EDS-208A-SS-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -10 to 60°C operating temperature	€ 902,00	2~4W
EDS-208A-SS-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.033,00	4~8W
EDS-208A-T	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 390,00	2~4W
EDS-208-M-SC	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, plastic housing, -10 to 60°C operating temperature	€ 348,00	2~4W
EDS-208-M-ST	Entry-level unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, plastic housing, -10 to 60°C operating temperature	€ 348,00	4~8W
EDS-305	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	€ 284,00	2~4W
EDS-305-M-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	€ 436,00	4~8W
EDS-305-M-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 539,00	4~8W
EDS-305-M-ST	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, 0 to 60°C operating temperature	€ 436,00	4~8W
EDS-305-M-ST-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	€ 539,00	4~8W
EDS-305-S-SC	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	€ 635,00	4~8W
EDS-305-S-SC-80	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	€ 1.793,00	8~12W
EDS-305-S-SC-T	Unmanaged Ethernet switch with 4 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 702,00	4~8W
EDS-305-T	Unmanaged Ethernet switch with 5 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	€ 351,00	4~8W
EDS-308	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, 0 to 60°C operating temperature	€ 357,00	2~4W
EDS-308-MM-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	€ 627,00	2~4W
EDS-308-MM-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	€ 702,00	4~8W
EDS-308-MM-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	€ 627,00	4~8W
EDS-308-MM-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connector, -40 to 75°C operating temperature	€ 702,00	4~8W
EDS-308-M-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	€ 517,00	4~8W
EDS-308-M-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 565,00	8~12W
EDS-308-S-SC	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, 0 to 60°C operating temperature	€ 639,00	4~8W
EDS-308-S-SC-80	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector for 80 km transmission, relay output warning, 0 to 60°C operating temperature	€ 1.574,00	8~12W
EDS-308-S-SC-T	Unmanaged Ethernet switch with 7 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 746,00	8~12W
EDS-308-SS-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	€ 891,00	2~4W
EDS-308-SS-SC-80	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, 0 to 60°C operating temperature	€ 2.690,00	8~12W
EDS-308-SS-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	€ 1.007,00	4~8W
EDS-308-T	Unmanaged Ethernet switch with 8 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	€ 417,00	2~4W
EDS-309-3M-SC	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, 0 to 60°C operating temperature	€ 855,00	4~8W
EDS-309-3M-SC-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	€ 941,00	4~8W
EDS-309-3M-ST	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, 0 to 60°C operating temperature	€ 855,00	4~8W
EDS-309-3M-ST-T	Unmanaged Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	€ 941,00	8~12W
EDS-316	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -10 to 60°C operating temperature	€ 754,00	2~4W
EDS-316-MM-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	€ 1.081,00	2~4W
EDS-316-MM-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	€ 1.206,00	4~8W
EDS-316-MM-ST	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -10 to 60°C operating temperature	€ 1.081,00	4~8W
EDS-316-MM-ST-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, relay output warning, -40 to 75°C operating temperature	€ 1.206,00	4~8W
EDS-316-M-SC	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	€ 962,00	4~8W
EDS-316-M-SC-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 1.096,00	4~8W

EDS-316-MS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with SC connector, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	€ 1.320,00	8~12W
EDS-316-M-ST	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -10 to 60°C operating temperature	€ 962,00	4~8W
EDS-316-M-ST-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX multi-mode port with ST connectors, relay output warning, -40 to 75°C operating temperature	€ 1.096,00	8~12W
EDS-316-S-SC	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -10 to 60°C operating temperature	€ 1.137,00	4~8W
EDS-316-S-SC-T	Unmanaged Ethernet switch with 15 10/100BaseT(X) ports, 1 100BaseFX single-mode port with SC connector, relay output warning, -40 to 75°C operating temperature	€ 1.238,00	8~12W
EDS-316-SS-SC	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -10 to 60°C operating temperature	€ 1.574,00	4~8W
EDS-316-SS-SC-80	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, relay output warning, -10 to 60°C operating temperature	€ 3.608,00	8~12W
EDS-316-SS-SC-T	Unmanaged Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, relay output warning, -40 to 75°C operating temperature	€ 1.679,00	4~8W
EDS-316-T	Unmanaged Ethernet switch with 16 10/100BaseT(X) ports, relay output warning, -40 to 75°C operating temperature	€ 885,00	2~4W
EDS-4008-2GT-2GS-HV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 1.730,00	8~12W
EDS-4008-2GT-2GS-HV-T	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 1.932,00	12~16W
EDS-4008-2GT-2GS-LV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.567,00	4~8W
EDS-4008-2GT-2GS-LV-T	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 1.769,00	12~16W
EDS-4008-2MSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 1.994,00	8~12W
EDS-4008-2MSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.178,00	12~16W
EDS-4008-2MSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.845,00	8~12W
EDS-4008-2MSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.030,00	12~16W
EDS-4008-2MST-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 1.994,00	8~12W
EDS-4008-2MST-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.178,00	12~16W
EDS-4008-2MST-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.845,00	8~12W
EDS-4008-2MST-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.030,00	12~16W
EDS-4008-2SSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.324,00	8~12W
EDS-4008-2SSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.501,00	12~16W
EDS-4008-2SSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.178,00	8~12W
EDS-4008-2SSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.355,00	12~16W
EDS-4008-4P-2GT-2GS-LV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	€ 2.038,00	8~12W
EDS-4008-4P-2GT-2GS-LV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	€ 2.231,00	12~16W
EDS-4008-4P-2GT-2GS-LV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.215,00	8~12W
EDS-4008-4P-2GT-2GS-LV	Managed Gigabit Ethernet switch with 4 10/100BaseT(X) ports with 802.3bt PoE, 2 10/100/1000BaseT(X), 2 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.408,00	12~16W
EDS-4008-HV	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 1.523,00	8~12W
EDS-4008-HV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 1.699,00	12~16W
EDS-4008-LV	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.374,00	4~8W
EDS-4008-LV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 1.554,00	12~16W
EDS-4009-3MSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.403,00	8~12W
EDS-4009-3MSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.588,00	12~16W

EDS-4009-3MSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.254,00	8~12W
EDS-4009-3MSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.434,00	12~16W
EDS-4009-3MST-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.403,00	8~12W
EDS-4009-3MST-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.588,00	12~16W
EDS-4009-3MST-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.254,00	8~12W
EDS-4009-3MST-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.434,00	12~16W
EDS-4009-3SSC-HV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.895,00	8~12W
EDS-4009-3SSC-HV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 3.072,00	12~16W
EDS-4009-3SSC-LV	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.748,00	8~12W
EDS-4009-3SSC-LV-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.926,00	12~16W
EDS-4012-4GC-HV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.061,00	4~8W
EDS-4012-4GC-HV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.239,00	12~16W
EDS-4012-4GC-LV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.915,00	4~8W
EDS-4012-4GC-LV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.092,00	4~8W
EDS-4012-4GS-HV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 1.915,00	8~12W
EDS-4012-4GS-HV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.092,00	12~16W
EDS-4012-4GS-LV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 1.769,00	4~8W
EDS-4012-4GS-LV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 1.946,00	12~16W
EDS-4012-8P-4GS-LVA	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 48 VDC for PoE, -10 to 60°C operating temperature	€ 2.540,00	8~12W
EDS-4012-8P-4GS-LVA-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 48 VDC for PoE, -40 to 75°C operating temperature	€ 2.717,00	4~8W
EDS-4012-8P-4GS-LVB	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.702,00	8~12W
EDS-4012-8P-4GS-LVB-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports with 802.3bt PoE, 4 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.879,00	12~16W
EDS-4014-4GS-2QGS-HV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.403,00	8~12W
EDS-4014-4GS-2QGS-HV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.588,00	12~16W
EDS-4014-4GS-2QGS-LV	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.254,00	4~8W
EDS-4014-4GS-2QGS-LV-T	Managed Gigabit Ethernet switch with 8 10/100BaseT(X) ports, 4 100/1000BaseSFP ports, 2 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.434,00	12~16W
EDS-405A	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -10°C to 60°C operating temperature	€ 476,00	2~4W
EDS-405A-EIP	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	€ 476,00	4~8W
EDS-405A-EIP-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	€ 598,00	8~12W
EDS-405A-MM-SC	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 855,00	2~4W
EDS-405A-MM-SC-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.004,00	2~4W
EDS-405A-MM-ST	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 855,00	4~8W
EDS-405A-MM-ST-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 1.004,00	4~8W
EDS-405A-PN	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	€ 476,00	4~8W
EDS-405A-PN-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	€ 598,00	8~12W
EDS-405A-PTP	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PT-Pv2 protocol support, -10°C to 60°C operating temperature	€ 1.347,00	4~8W

EDS-405A-PTP-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, hardware-based IEEE 1588 PT-Pv2 protocol support, -40°C to 75°C operating temperature	€ 1.503,00	8~12W
EDS-405A-SS-SC	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.160,00	2~4W
EDS-405A-SS-SC-T	Entry-level managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.284,00	2~4W
EDS-405A-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 598,00	2~4W
EDS-408A	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -10°C to 60°C operating temperature	€ 754,00	2~4W
EDS-408A-1M2S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.739,00	8~12W
EDS-408A-1M2S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 1 100BaseFX multi-mode port, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.861,00	8~12W
EDS-408A-2M1S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, 0 to 60°C operating temperature	€ 1.582,00	8~12W
EDS-408A-2M1S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports, 1 100BaseFX single-mode port with SC connectors, -40 to 75°C operating temperature	€ 1.723,00	8~12W
EDS-408A-3M-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.441,00	4~8W
EDS-408A-3M-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.566,00	4~8W
EDS-408A-3M-ST	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 1.441,00	4~8W
EDS-408A-3M-ST-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 1.566,00	8~12W
EDS-408A-3S-SC	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.880,00	4~8W
EDS-408A-3S-SC-48	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, ±24/±48 VDC input voltage, 0 to 60°C operating temperature	€ 2.209,00	8~12W
EDS-408A-3S-SC-48-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, ±24/±48 VDC input voltage, -40 to 75°C operating temperature	€ 2.359,00	12~16W
EDS-408A-3S-SC-T	Entry-level managed Ethernet switch with 5 10/100BaseT(X) ports, 3 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 2.003,00	4~8W
EDS-408A-EIP	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, 0 to 60°C operating temperature	€ 754,00	4~8W
EDS-408A-EIP-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, EtherNet/IP enabled, -40 to 75°C operating temperature	€ 1.035,00	8~12W
EDS-408A-MM-SC	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.097,00	2~4W
EDS-408A-MM-SC-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.377,00	2~4W
EDS-408A-MM-ST	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 1.097,00	2~4W
EDS-408A-MM-ST-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 1.377,00	2~4W
EDS-408A-PN	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, 0 to 60°C operating temperature	€ 754,00	4~8W
EDS-408A-PN-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, PROFINET enabled, -40 to 75°C operating temperature	€ 1.035,00	4~8W
EDS-408A-SS-SC	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.547,00	2~4W
EDS-408A-SS-SC-T	Entry-level managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.675,00	2~4W
EDS-408A-T	Entry-level managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 1.035,00	2~4W
EDS-505A	Managed Ethernet switch with 5 10/100BaseT(X) ports, 0 to 60°C operating temperature	€ 862,00	4~8W
EDS-505A-MM-SC	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.567,00	8~12W
EDS-505A-MM-SC-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.782,00	8~12W
EDS-505A-MM-ST	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 1.567,00	8~12W
EDS-505A-MM-ST-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 1.782,00	8~12W
EDS-505A-SS-SC	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.942,00	4~8W
EDS-505A-SS-SC-T	Managed Ethernet switch with 3 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 2.128,00	4~8W
EDS-505A-T	Managed Ethernet switch with 5 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 1.189,00	4~8W
EDS-508A	Managed Ethernet switch with 8 10/100BaseT(X) ports, 0 to 60°C operating temperature	€ 1.189,00	2~4W
EDS-508A-MM-SC	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 1.801,00	2~4W
EDS-508A-MM-SC-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 1.956,00	4~8W

EDS-508A-MM-ST	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 1.801,00	4~8W
EDS-508A-MM-ST-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 1.956,00	4~8W
EDS-508A-SS-SC	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 0 to 60°C operating temperature	€ 2.253,00	4~8W
EDS-508A-SS-SC-80	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 0 to 60°C operating temperature	€ 5.189,00	8~12W
EDS-508A-SS-SC-80-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, -40 to 75°C operating temperature	€ 5.346,00	8~12W
EDS-508A-SS-SC-T	Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, -40 to 75°C operating temperature	€ 2.407,00	4~8W
EDS-508A-T	Managed Ethernet switch with 8 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 1.347,00	4~8W
EDS-510A-1GT2SFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 2.034,00	4~8W
EDS-510A-1GT2SFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 1 10/100/1000BaseT(X) port, 2 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 2.209,00	4~8W
EDS-510A-3GT	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	€ 2.034,00	4~8W
EDS-510A-3GT-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	€ 2.209,00	4~8W
EDS-510A-3SFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 2.034,00	4~8W
EDS-510A-3SFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 SFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 2.209,00	4~8W
EDS-510E-3GTXSFP	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	€ 1.487,00	2~4W
EDS-510E-3GTXSFP-T	Managed Gigabit Ethernet switch with 7 10/100BaseT(X) ports, 3 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	€ 1.610,00	2~4W
EDS-516A	Managed Ethernet switch with 16 10/100BaseT(X) ports, 0 to 60°C operating temperature	€ 1.861,00	2~4W
EDS-516A-MM-SC	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature	€ 2.345,00	4~8W
EDS-516A-MM-SC-T	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 2.488,00	4~8W
EDS-516A-MM-ST	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 0 to 60°C operating temperature	€ 2.345,00	4~8W
EDS-516A-MM-ST-T	Managed Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 2.488,00	12~16W
EDS-516A-T	Managed Ethernet switch with 16 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 2.005,00	4~8W
EDS-518A	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 2.674,00	4~8W
EDS-518A-MM-SC	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 3.220,00	4~8W
EDS-518A-MM-SC-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 3.409,00	12~16W
EDS-518A-MM-ST	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 3.220,00	4~8W
EDS-518A-MM-ST-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with ST connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 3.409,00	12~16W
EDS-518A-SS-SC	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating temperature	€ 3.625,00	4~8W
EDS-518A-SS-SC-80	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors for 80 km transmission, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, 0 to 60°C operating	€ 6.672,00	8~12W
EDS-518A-SS-SC-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 2 100BaseFX single-mode ports with SC connectors, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 3.830,00	4~8W
EDS-518A-T	Managed Gigabit Ethernet switch with 16 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 1000BaseSFP slots for adding SFP-1G Series Gigabit Ethernet modules, -40 to 75°C operating temperature	€ 2.865,00	4~8W
EDS-518E-4GTXSFP	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -10 to 60°C operating temperature	€ 2.096,00	2~4W
EDS-518E-4GTXSFP-T	Managed Gigabit Ethernet switch with 14 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, -40 to 75°C operating temperature	€ 2.253,00	2~4W
EDS-518E-MM-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX (multi-mode, SC Connector), -10 to 60°C operating temperature	€ 2.537,00	4~8W
EDS-518E-MM-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with SC connector, -40 to 75°C operating temperature	€ 2.686,00	8~12W

EDS-518E-MM-ST-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	€ 2.537,00	8~12W
EDS-518E-MM-ST-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 2.686,00	8~12W
EDS-518E-SS-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	€ 2.865,00	4~8W
EDS-518E-SS-SC-4GTXSFP	Managed Gigabit Ethernet switch with 12 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	€ 3.000,00	4~8W
EDS-528E-4GTXSFP-HV	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -10 to 60°C operating temperature	€ 3.082,00	4~8W
EDS-528E-4GTXSFP-HV-T	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, 110/220 VAC/VDC power input, -40 to 75°C operating temperature	€ 3.220,00	4~8W
EDS-528E-4GTXSFP-LV	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -10 to 60°C operating temperature	€ 3.082,00	4~8W
EDS-528E-4GTXSFP-LV-T	Managed Gigabit Ethernet switch with 24 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48/-48 VDC power inputs, -40 to 75°C operating temperature	€ 3.220,00	4~8W
EDS-608	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, 0 to 60°C operating temperature	€ 1.722,00	4~8W
EDS-608-T	Compact managed Ethernet switch system with 2 slots for 4-port Fast Ethernet interface modules, for a total of up to 8 ports, -40 to 75°C operating temperature	€ 1.972,00	4~8W
EDS-611	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, 0 to 60°C operating temperature	€ 2.690,00	8~12W
EDS-611-T	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 slots for 4-port fast Ethernet interface modules, for a total of up to 11 ports, -40 to 75°C operating temperature	€ 2.956,00	12~16W
EDS-616	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, 0 to 60°C operating temperature	€ 2.878,00	4~8W
EDS-616-T	Compact managed Ethernet switch system with 4 slots for 4-port fast Ethernet interface modules, for a total of up to 16 ports, -40 to 75°C operating temperature	€ 3.145,00	4~8W
EDS-619	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, 0 to 60°C operating temperature	€ 3.753,00	4~8W
EDS-619-T	Compact managed Ethernet switch system with 3 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 slots for 4-port Fast Ethernet interface modules, for a total of up to 19 ports, -40 to 75°C operating temperature	€ 4.020,00	4~8W
EDS-G2005-EL	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 276,00	2~4W
EDS-G2005-ELP	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	€ 245,00	2~4W
EDS-G2005-EL-T	Unmanaged full Gigabit Ethernet switch with 5 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 336,00	2~4W
EDS-G2008-EL	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -10 to 60°C operating temperature	€ 381,00	2~4W
EDS-G2008-ELP	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, plastic housing, -10 to 60°C operating temperature	€ 314,00	2~4W
EDS-G2008-EL-T	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000 BaseT(X) ports, 12/24/48 power input, metal housing, -40 to 75°C operating temperature	€ 440,00	2~4W
EDS-G205-1GTXSFP	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -10 to 60°C operating temperature	€ 323,00	2~4W
EDS-G205-1GTXSFP-T	Unmanaged full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 1 combo 10/100/1000BaseT(X) or 100/1000BaseSFP port, -40 to 75°C operating temperature	€ 430,00	2~4W
EDS-G205A-4PoE	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, 0 to 60°C operating temperature	€ 862,00	2~4W
EDS-G205A-4PoE-1GSFP	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, 0 to 60°C operating temperature	€ 921,00	4~8W
EDS-G205A-4PoE-1GSFP-T	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseX (SFP slot) port, -40 to 75°C operating temperature	€ 1.013,00	4~8W
EDS-G205A-4PoE-T	Unmanaged Gigabit PoE switch with 4 PoE 10/100/1000BaseT(X) ports, 1 1000BaseT port, -40 to 75°C operating temperature	€ 953,00	2~4W
EDS-G308	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 0 to 60°C operating temperature	€ 473,00	2~4W
EDS-G308-2SFP	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	€ 584,00	2~4W
EDS-G308-2SFP-T	Unmanaged full Gigabit Ethernet switch with 6 10/100/1000BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	€ 683,00	2~4W
EDS-G308-T	Unmanaged full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	€ 574,00	2~4W
EDS-G4008-HV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.308,00	8~12W

EDS-G4008-HV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 2.486,00	12~16W
EDS-G4008-LV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.162,00	4~8W
EDS-G4008-LV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.341,00	12~16W
EDS-G4012-4GC-HV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 2.848,00	4~8W
EDS-G4012-4GC-HV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 3.025,00	12~16W
EDS-G4012-4GC-LV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 2.694,00	4~8W
EDS-G4012-4GC-LV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 2.879,00	4~8W
EDS-G4012-8P-4QGS-LVA	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -10 to 60°C operating temperature	€ 3.675,00	8~12W
EDS-G4012-8P-4QGS-LVA	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, 48 VDC for PoE, -40 to 75°C operating temperature	€ 3.860,00	4~8W
EDS-G4012-8P-4QGS-LVB	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 3.844,00	4~8W
EDS-G4012-8P-4QGS-LVB	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports with 802.3bt PoE, 4 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature,	€ 4.022,00	4~8W
EDS-G4014-6QGS-HV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -10 to 60°C operating temperature	€ 3.775,00	8~12W
EDS-G4014-6QGS-HV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, single power supply 110/220 VAC/VDC, -40 to 75°C operating temperature	€ 3.952,00	12~16W
EDS-G4014-6QGS-LV	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -10 to 60°C operating temperature	€ 3.628,00	8~12W
EDS-G4014-6QGS-LV-T	Managed Full Gigabit Ethernet switch with 8 10/100/1000BaseT(X) ports, 6 1000/2500BaseSFP ports, dual power supply 12/24/48 VDC, -40 to 75°C operating temperature	€ 3.813,00	12~16W
EDS-G508E	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	€ 1.849,00	4~8W
EDS-G508E-T	8-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, -40 to 75°C operating temperature	€ 2.034,00	4~8W
EDS-G509	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 0 to 60°C operating temperature	€ 2.054,00	2~4W
EDS-G509-T	Industrial full Gigabit Ethernet switch with 4 10/100/1000BaseT(X) ports, 5 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, -40 to 75°C operating temperature	€ 2.239,00	2~4W
EDS-G512E-4GSFP	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	€ 1.909,00	2~4W
EDS-G512E-4GSFP-T	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	€ 2.082,00	2~4W
EDS-G512E-8PoE-4GSFP	12-port full Gigabit managed Ethernet switch with 8 10/100/1000BaseT(X) PoE/PoE+ ports, 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	€ 2.784,00	2~4W
EDS-G512E-8PoE-4GSFP	12-port full Gigabit managed Ethernet switch, 8 10/100/1000BaseT(X) PoE/PoE+ ports with 4 100/1000BaseSFP slots, -40 to 75°C operating temperature	€ 3.019,00	2~4W
EDS-G516E-4GSFP	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -10 to 60°C operating temperature	€ 2.738,00	2~4W
EDS-G516E-4GSFP-T	16-port full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 4 Gigabit SFP slots, -40 to 75°C operating temperature	€ 2.928,00	2~4W
EDS-P206A-4PoE	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -10 to 60°C operating temperature	€ 532,00	2~4W
EDS-P206A-4PoE-MM-SC	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -10 to 60°C operating temperature	€ 779,00	4~8W
EDS-P206A-4PoE-MM-SC	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with SC connectors, -40 to 75°C operating temperature	€ 883,00	4~8W
EDS-P206A-4PoE-MM-ST	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectors, -10 to 60°C operating temperature	€ 779,00	4~8W
EDS-P206A-4PoE-MM-ST	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX multi-mode ports with ST connectors, -40 to 75°C operating temperature	€ 883,00	4~8W
EDS-P206A-4PoE-M-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 1 100BaseFX multi-mode port with SC connector, -10 to 60°C operating temperature	€ 645,00	4~8W
EDS-P206A-4PoE-M-SC-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with SC connector, -40 to 75°C operating temperature	€ 746,00	4~8W
EDS-P206A-4PoE-M-ST	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -10 to 60°C operating temperature	€ 645,00	4~8W
EDS-P206A-4PoE-M-ST-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX multi-mode port with ST connectors, -40 to 75°C operating temperature	€ 746,00	4~8W
EDS-P206A-4PoE-S-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -10 to 60°C operating temperature	€ 891,00	4~8W
EDS-P206A-4PoE-S-SC-T	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, 1 100BaseFX single-mode port with SC connector, -40 to 75°C operating temperature	€ 976,00	4~8W

EDS-P206A-4PoE-SS-SC	Unmanaged Ethernet switch with 1 10/100BaseT(X) ports, 4 PoE ports, and 2 100BaseFX single-mode ports with SC connector, -10 to 60°C operating temperature	€ 1.113,00	4~8W
EDS-P206A-4PoE-SS-SC-T	Unmanaged Ethernet switch with 4 PoE ports, 2 100BaseFX single-mode ports with SC connector, -40 to 75°C operating temperature	€ 1.236,00	4~8W
EDS-P206A-4PoE-T	Unmanaged Ethernet switch with 2 10/100BaseT(X) ports, 4 PoE ports, -40 to 75°C operating temperature	€ 627,00	2~4W
EDS-P506E-4PoE-2GTXS	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.738,00	2~4W
EDS-P506E-4PoE-2GTXS-T	Managed Ethernet switch with 4 PoE+/60W 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.911,00	2~4W
EDS-P510	Managed Gigabit Ethernet switch with 3 10/100BaseT(X) ports, 4 PoE 10/100BaseT(X) ports, 3 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	€ 1.987,00	8~12W
EDS-P510A-8PoE-2GTXS	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, 0 to 60°C operating temperature	€ 2.221,00	2~4W
EDS-P510A-8PoE-2GTXS-T	Managed Gigabit Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	€ 2.457,00	2~4W
EDS-P510-T	Managed Gigabit Ethernet switch with 3 10/100BaseT(X) ports, 4 PoE 10/100BaseT(X) ports, 3 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots for adding SFP-1G/1FE Series Gigabit/Fast Ethernet modules, -40 to 75°C operating temperature	€ 2.192,00	8~12W
EOM-104	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 344,00	2~4W
EOM-104 20PCS	Embedded managed Ethernet switch module with 4 10/100BaseT(X) ports, 20 pcs, -40 to 75°C operating temperature	€ 6.792,00	8~12W
EOM-104 Evaluation Kit	Evaluation kit with an EOM-104 switch module and evaluation board with 4 10/100BaseT(X) ports for testing and application development	€ 455,00	8~12W
EOM-104-FO	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature	€ 399,00	8~12W
EOM-104-FO 20PCS	Embedded managed Ethernet switch module with 2 10/100BaseT(X) and 2 100BaseFX ports, -40 to 75°C operating temperature, 20 pcs package	€ 7.923,00	8~12W
EOM-104-FO Evaluation Kit	Evaluation kit with an EOM-104-FO switch module and evaluation board with 2 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connector for testing and application development	€ 907,00	8~12W
EXPC-F2120W-TL1-AC	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 6.952,00	8~12W
EXPC-F2120W-TL1-DC	12.1-inch flat-panel fanless industrial computer with Intel® Celeron® 6305E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 6.952,00	8~12W
EXPC-F2120W-TL3-AC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating t	€ 7.508,00	8~12W
EXPC-F2120W-TL3-DC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 7.508,00	8~12W
EXPC-F2120W-TL7-AC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating t	€ 8.898,00	8~12W
EXPC-F2120W-TL7-DC	12.1-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 8.898,00	24~28W
EXPC-F2150W-TL3-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating t	€ 8.342,00	8~12W
EXPC-F2150W-TL3-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i3-1115G4E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 8.203,00	8~12W
EXPC-F2150W-TL5-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating t	€ 9.037,00	8~12W
EXPC-F2150W-TL5-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i5-1145G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 8.898,00	8~12W
EXPC-F2150W-TL7-AC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 100 to 240 VAC power input, IP66 (front), IP42 (rear), -40 to 70°C operating t	€ 9.732,00	8~12W
EXPC-F2150W-TL7-DC	15.6-inch flat-panel fanless industrial computer with Intel® Core™ i7-1185G7E processor, 1200-nit PCAP touchscreen, 4 Ethernet ports, 3 serial ports, 1 VGA port, 1 DisplayPort, 9 to 36 VDC power input, IP66 (front), IP42 (rear), -40 to 70°C operating temp	€ 9.732,00	8~12W
GPS Antenna Package	External antenna with TNC to SMA (female) adapter and a 50-cm cable, SMA antenna (26 dBi, 1572 MHz, L1 band), GPS extension cable	€ 132,00	16~20W
HDR-60-24	60 W/2.5 A DIN-rail 24 VDC power supply, universal 85 to 264 VAC or 120 to 370 VDC input voltage, -30 to 70°C operating temperature	€ 90,00	8~12W
ICF-1150I-M-SC	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	€ 522,00	8~12W

ICF-1150I-M-SC-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	€ 604,00	8~12W
ICF-1150I-M-SC-T	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	€ 684,00	4~8W
ICF-1150I-M-SC-T-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	€ 785,00	8~12W
ICF-1150I-M-ST	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	€ 522,00	4~8W
ICF-1150I-M-ST-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	€ 604,00	8~12W
ICF-1150I-M-ST-T	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	€ 684,00	2~4W
ICF-1150I-M-ST-T-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	€ 785,00	8~12W
ICF-1150I-S-SC	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, 0 to 60°C operating temperature	€ 927,00	4~8W
ICF-1150I-S-SC-IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	€ 1.063,00	4~8W
ICF-1150I-S-SC-T	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, -40 to 85°C operating temperature	€ 1.191,00	4~8W
ICF-1150I-S-SC-T-IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	€ 1.361,00	8~12W
ICF-1150I-S-ST	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, 0 to 60°C operating temperature	€ 927,00	4~8W
ICF-1150I-S-ST-IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEx, 0 to 60°C operating temperature	€ 1.063,00	8~12W
ICF-1150I-S-ST-T	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, -40 to 85°C operating temperature	€ 1.191,00	4~8W
ICF-1150I-S-ST-T-IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 2 kV isolation, IECEx, -40 to 85°C operating temperature	€ 1.361,00	8~12W
ICF-1150-M-SC	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, 0 to 60°C operating temperature	€ 405,00	4~8W
ICF-1150-M-SC-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	€ 465,00	8~12W
ICF-1150-M-SC-T	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, -40 to 85°C operating temperature	€ 522,00	4~8W
ICF-1150-M-SC-T-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	€ 604,00	8~12W
ICF-1150-M-ST	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, 0 to 60°C operating temperature	€ 405,00	4~8W
ICF-1150-M-ST-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	€ 465,00	8~12W
ICF-1150-M-ST-T	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, -40 to 85°C operating temperature	€ 522,00	4~8W
ICF-1150-M-ST-T-IEX	Industrial RS-232/422/485 to multi-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	€ 604,00	8~12W
ICF-1150-S-SC	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, 0 to 60°C operating temperature	€ 705,00	2~4W
ICF-1150-S-SC-IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, 0 to 60°C operating temperature	€ 813,00	8~12W
ICF-1150-S-SC-T	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, -40 to 85°C operating temperature	€ 927,00	4~8W
ICF-1150-S-SC-T-IEX	Industrial RS-232/422/485 to single-mode fiber converter, SC connector, IECEx, -40 to 85°C operating temperature	€ 1.063,00	8~12W
ICF-1150-S-ST	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, 0 to 60°C operating temperature	€ 705,00	4~8W
ICF-1150-S-ST-IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, 0 to 60°C operating temperature	€ 813,00	8~12W
ICF-1150-S-ST-T	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, -40 to 85°C operating temperature	€ 927,00	4~8W
ICF-1150-S-ST-T-IEX	Industrial RS-232/422/485 to single-mode fiber converter, ST connector, IECEx, -40 to 85°C operating temperature	€ 1.063,00	8~12W
ICF-1170I-M-ST	CANbus to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	€ 522,00	4~8W
ICF-1170I-M-ST-T	CANbus to fiber converter, multi-mode, ST connector, -40 to 85°C operating temperature	€ 604,00	4~8W
ICF-1171I-M-ST	Industrial CAN-to-fiber converter for distance extension, ST multi-mode	€ 560,00	8~12W
ICF-1171I-M-ST-T	Industrial CAN-to-fiber converter for distance extension, ST multi-mode, -40 to 75°C	€ 641,00	12~16W
ICF-1171I-S-ST	Industrial CAN-to-fiber converter for distance extension, ST single-mode	€ 726,00	4~8W
ICF-1171I-S-ST-T	Industrial CAN-to-fiber converter for distance extension, ST single-mode, -40 to 75°C	€ 834,00	12~16W
ICF-1180I-M-ST	PROFIBUS to fiber converter, multi-mode, ST connector, 0 to 60°C operating temperature	€ 731,00	2~4W
ICF-1180I-M-ST-T	PROFIBUS to fiber converter, multi-mode, ST connector, -40 to 75°C operating temperature	€ 839,00	4~8W
ICF-1180I-S-ST	PROFIBUS to fiber converter, single-mode, ST connector, 0 to 60°C operating temperature	€ 1.270,00	4~8W
ICF-1180I-S-ST-T	PROFIBUS to fiber converter, single-mode, ST connector, -40 to 75°C operating temperature	€ 1.380,00	12~16W
ICF-1280I-M-ST	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, 0 to 60°C operating temperature	€ 1.127,00	4~8W
ICF-1280I-M-ST-T	PROFIBUS to fiber converter, multi-mode, 2 ST connectors, -40 to 75°C operating temperature	€ 1.285,00	8~12W
ICF-1280I-S-ST	PROFIBUS to fiber converter, single-mode, 2 ST connectors, 0 to 60°C operating temperature	€ 1.942,00	4~8W
ICF-1280I-S-ST-T	PROFIBUS to fiber converter, single-mode, 2 ST connectors, -40 to 75°C operating temperature	€ 2.096,00	12~16W

ICS-G7526A-20GSFP-2XG	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 14.384,00	8~12W
ICS-G7526A-2XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 14.384,00	12~16W
ICS-G7526A-8GSFP-2XG-H	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temper	€ 14.384,00	12~16W
ICS-G7528A-20GSFP-4XG	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 17.964,00	8~12W
ICS-G7528A-4XG-HV-HV-T	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 17.964,00	12~16W
ICS-G7528A-8GSFP-4XG-H	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temper	€ 17.964,00	12~16W
ICS-G7748A-HV-HV	Full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, -10 to 60°C operating temperature	€ 15.814,00	8~12W
ICS-G7750A-2XG-HV-HV	Full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, -10 to 60°C operating temperature	€ 21.090,00	8~12W
ICS-G7752A-4XG-HV-HV	Full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, -10 to 60°C operating temperature	€ 26.368,00	8~12W
ICS-G7826A-20GSFP-2XG	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 15.615,00	8~12W
ICS-G7826A-2XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 15.615,00	12~16W
ICS-G7826A-8GSFP-2XG-H	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temper	€ 15.615,00	4~8W
ICS-G7828A-20GSFP-4XG	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 19.230,00	4~8W
ICS-G7828A-4XG-HV-HV-T	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 19.230,00	4~8W
ICS-G7828A-8GSFP-4XG-H	Layer 3 Full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 4 10GbE SFP+ slots, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temper	€ 19.230,00	4~8W
ICS-G7848A-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G ports, 0 to 60°C operating temperature	€ 17.618,00	4~8W
ICS-G7850A-2XG-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 2 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 2 10GbE ports, 0 to 60°C operating temperatu	€ 22.895,00	12~16W
ICS-G7852A-4XG-HV-HV	Layer 3 full Gigabit modular managed Ethernet switch system with 4 10GbE SFP+ slots, 12 slots for 4-port Gigabit Ethernet interface modules, 2 isolated power supplies (85 to 264 VAC), for a total of up to 48G + 4 10GbE ports, 0 to 60°C operating temperatu	€ 28.174,00	4~8W
IKS-6726A-2GTXSFP-24-2	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	€ 2.663,00	4~8W
IKS-6726A-2GTXSFP-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	€ 2.237,00	4~8W
IKS-6726A-2GTXSFP-48-4	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	€ 2.663,00	8~12W
IKS-6726A-2GTXSFP-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	€ 2.237,00	8~12W
IKS-6726A-2GTXSFP-HV-H	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 2.125,00	2~4W
IKS-6726A-2GTXSFP-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, and 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	€ 1.722,00	2~4W
IKS-6728A-4GTXSFP-24-2	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (24 VDC), -40 to 75°C operating temperature	€ 3.094,00	12~16W
IKS-6728A-4GTXSFP-24-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (24 VDC), -40 to 75°C operating temperature	€ 2.674,00	4~8W

IKS-6728A-4GTXSFP-48-44	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (48 VDC), -40 to 75°C operating temperature	€ 3.094,00	8~12W
IKS-6728A-4GTXSFP-48-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (48 VDC), -40 to 75°C operating temperature	€ 2.674,00	8~12W
IKS-6728A-4GTXSFP-HV-H	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 2.599,00	2~4W
IKS-6728A-4GTXSFP-HV-T	Modular managed Ethernet switch with 8 10/100BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, 2 slots for Fast Ethernet modules, front cabling, 1 isolated power supply (85 to 264 VAC), -40 to 75°C operating temperature	€ 2.162,00	4~8W
IKS-6728A-8PoE-4GTXSFP	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolate	€ 4.289,00	4~8W
IKS-6728A-8PoE-4GTXSFP	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolate	€ 3.817,00	4~8W
IKS-6728A-8PoE-4GTXSFP	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 2 isolate	€ 3.708,00	4~8W
IKS-6728A-8PoE-4GTXSFP	Modular managed rackmount Ethernet PoE+ switch with 8 built-in 10/100BaseT(X) PoE+ ports, 4 Gigabit Copper/SFP combo ports, 2 slots for Fast Ethernet PoE+ modules. Support for up to 24+4G ports with 8 built-in PoE+ ports and up to 24 PoE+ ports, 1 isolate	€ 3.255,00	4~8W
IKS-G6524A-20GSFP-4GT	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 5.786,00	4~8W
IKS-G6524A-20GSFP-4GT	Layer 2 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 6.300,00	4~8W
IKS-G6524A-4GTXSFP-HV	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 5.786,00	2~4W
IKS-G6524A-4GTXSFP-HV	Layer 2 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 6.300,00	4~8W
IKS-G6524A-8GSFP-4GT	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 5.786,00	4~8W
IKS-G6524A-8GSFP-4GT	Layer 2 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 6.300,00	4~8W
IKS-G6824A-20GSFP-4GT	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 7.941,00	4~8W
IKS-G6824A-20GSFP-4GT	Layer 3 full Gigabit managed Ethernet switch with 20 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 8.421,00	12~16W
IKS-G6824A-4GTXSFP-HV	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 7.941,00	4~8W
IKS-G6824A-4GTXSFP-HV	Layer 3 full Gigabit managed Ethernet switch with 20 10/100/1000BaseT(X) ports, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 8.421,00	4~8W
IKS-G6824A-8GSFP-4GT	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), 0 to 60°C operating temperature	€ 7.941,00	4~8W
IKS-G6824A-8GSFP-4GT	Layer 3 full Gigabit managed Ethernet switch with 12 10/100/1000BaseT(X) ports, 8 100/1000BaseSFP slots, 4 10/100/1000BaseT(X) or 100/1000BaseSFP slot combo ports, 2 isolated power supplies (85 to 264 VAC), -40 to 75°C operating temperature	€ 8.421,00	4~8W
IM-6700A-2MSC4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	€ 453,00	4~8W
IM-6700A-2MST4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	€ 453,00	8~12W
IM-6700A-2SSC4TX	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connector, 4 10/100BaseT(X) ports	€ 723,00	4~8W
IM-6700A-4MSC2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connector, 2 10/100BaseT(X) ports	€ 636,00	4~8W
IM-6700A-4MST2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	€ 636,00	8~12W
IM-6700A-4SSC2TX	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	€ 1.159,00	2~4W
IM-6700A-6MSC	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	€ 810,00	4~8W
IM-6700A-6MST	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	€ 810,00	4~8W
IM-6700A-6SSC	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	€ 1.612,00	4~8W
IM-6700A-8PoE	Fast Ethernet PoE+ module with 8 100BaseT(X) PoE/PoE+ ports (for IKS-6728A-8PoE Series only)	€ 801,00	2~4W
IM-6700A-8SFP	Fast Ethernet module with 8 100BaseSFP slots	€ 540,00	2~4W

IM-6700A-8TX	Fast Ethernet module with 8 10/100T(X) ports	€ 241,00	2~4W
IMC-101G	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, 0 to 60°C operating temperature	€ 637,00	2~4W
IMC-101G-IEX	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, 0 to 60°C operating temperature	€ 735,00	8~12W
IMC-101G-T	Industrial 10/100/1000BaseT(X) to 1000BaseSX/LX/LHX/ZX media converter, -40 to 75°C operating temperature	€ 746,00	2~4W
IMC-101G-T-IEX	Industrial 10/100/1000BaseT(X) to 1000BaseSFP media converter, IECEx, -40 to 75°C operating temperature	€ 857,00	4~8W
IMC-101-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, 0 to 60°C operating temperature	€ 349,00	2~4W
IMC-101-M-SC-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, 0 to 60°C operating temperature	€ 399,00	4~8W
IMC-101-M-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	€ 485,00	4~8W
IMC-101-M-SC-T-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector, IECEx, -40 to 75°C operating temperature	€ 555,00	4~8W
IMC-101-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, 0 to 60°C operating temperature	€ 349,00	2~4W
IMC-101-M-ST-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, 0 to 60°C operating temperature	€ 399,00	8~12W
IMC-101-M-ST-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	€ 485,00	4~8W
IMC-101-M-ST-T-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, -40 to 75°C operating temperature	€ 555,00	4~8W
IMC-101-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 40 km, 0 to 60°C operating temperature	€ 561,00	2~4W
IMC-101-S-SC-80	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, 0 to 60°C operating temperature	€ 2.094,00	8~12W
IMC-101-S-SC-80-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, 80 km, -40 to 75°C operating temperature	€ 2.188,00	12~16W
IMC-101-S-SC-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, 0 to 60°C operating temperature	€ 643,00	4~8W
IMC-101-S-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	€ 661,00	2~4W
IMC-101-S-SC-T-IEX	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector, 40 km, IECEx, -40 to 75°C operating temperature	€ 761,00	4~8W
IMC-21A-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -10 to 60°C operating temperature	€ 253,00	2~4W
IMC-21A-M-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC fiber connector, -40 to 75°C operating temperature	€ 326,00	2~4W
IMC-21A-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -10 to 60°C operating temperature	€ 253,00	2~4W
IMC-21A-M-ST-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST fiber connector, -40 to 75°C operating temperature	€ 326,00	2~4W
IMC-21A-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -10 to 60°C operating temperature	€ 380,00	2~4W
IMC-21A-S-SC-T	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fiber connector, -40 to 75°C operating temperature	€ 502,00	2~4W
IMC-21GA	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -10 to 60°C operating temperature	€ 308,00	2~4W
IMC-21GA-LX-SC	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -10 to 60°C operating temperature	€ 598,00	2~4W
IMC-21GA-LX-SC-T	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -40 to 75°C operating temperature	€ 748,00	2~4W
IMC-21GA-SX-SC	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -10 to 60°C operating temperature	€ 433,00	2~4W
IMC-21GA-SX-SC-T	Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -40 to 75°C operating temperature	€ 537,00	4~8W
IMC-21GA-T	Industrial 10/100/1000BaseT(X) to 100/1000BaseSFP media converter, -40 to 75°C operating temperature	€ 387,00	2~4W
IMC-21-M-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, SC connector	€ 253,00	2~4W
IMC-21-M-ST	Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector	€ 253,00	2~4W
IMC-21-S-SC	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC connector	€ 357,00	2~4W
IMC-P101-M-SC	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, 0 to 60°C operating temperature	€ 685,00	4~8W
IMC-P101-M-SC-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with SC connector, -40 to 75°C operating temperature	€ 854,00	12~16W
IMC-P101-M-ST	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, 0 to 60°C operating temperature	€ 754,00	12~16W
IMC-P101-M-ST-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode port with ST connector, -40 to 75°C operating temperature	€ 1.003,00	12~16W
IMC-P101-S-SC	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, 0 to 60°C operating temperature	€ 956,00	4~8W
IMC-P101-S-SC-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with SC connector, -40 to 75°C operating temperature	€ 1.189,00	4~8W

IMC-P101-S-ST	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, 0 to 60°C operating temperature	€ 1.033,00	12~16W
IMC-P101-S-ST-T	PoE industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode port with ST connector, -40 to 75°C operating temperature	€ 1.394,00	12~16W
IMC-P21A-G2-M-SC	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, multi-mode port with SC connector, -10 to 60°C operating temperature	€ 537,00	4~8W
IMC-P21A-G2-M-ST	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, multi-mode port with ST connector, -10 to 60°C operating temperature	€ 537,00	8~12W
IMC-P21A-G2-S-SC	PoE+ industrial 10/100Base-T(X) to 100Base-FX media converter, single-mode port with SC connector, -10 to 60°C operating temperature	€ 651,00	2~4W
IMC-P21GA-G2	PoE+ industrial 10/100/1000Base-T(X) to 100/1000BaseSFP media converter, -10 to 60°C operating temperature	€ 577,00	2~4W
IMC-P21GA-G2-LX-SC	PoE+ industrial 10/100/1000Base-T(X) to 1000Base-LX media converter, single-mode port with SC connector, -10 to 60°C operating temperature	€ 980,00	4~8W
IMC-P21GA-G2-SX-SC	PoE+ industrial 10/100/1000Base-T(X) to 1000Base-SX media converter, multi-mode port with SC connector, -10 to 60°C operating temperature	€ 805,00	4~8W
IM-G7000A-4GSFP	Gigabit Ethernet interface module with 4 100/1000BaseSFP slots, -10 to 60°C operating temperature	€ 1.035,00	2~4W
IM-G7000A-4GTX	Gigabit Ethernet interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	€ 1.035,00	2~4W
IM-G7000A-4PoE	Gigabit Ethernet PoE+ interface module with 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	€ 1.612,00	8~12W
INJ-24	PoE+ Injector, maximum output of 30 W at 24/48 VDC, 0 to 60°C operating temperature	€ 295,00	2~4W
INJ-24A	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, 0 to 60°C operating temperature	€ 476,00	2~4W
INJ-24A-T	Gigabit high-power PoE+ injector, max. output of 36W/60W at 24 or 48 VDC by 2-pair/4-pair mode, -40 to 75°C operating temperature	€ 599,00	2~4W
INJ-24-T	PoE+ Injector, maximum output of 30 W at 24/48 VDC, -40 to 75°C operating temperature	€ 399,00	2~4W
ioLogik 2512	Universal controller, 8 DIs, 8 DIOs, Click&Go Plus, -10 to 60°C operating temperature	€ 784,00	4~8W
ioLogik 2512-T	Universal controller, 8 DIs, 8 DIOs, Click&Go Plus, -40 to 75°C operating temperature	€ 971,00	4~8W
ioLogik 2542	Universal controller, 4 AIs, 12 DIOs, Click&Go Plus, -10 to 60°C operating temperature	€ 1.048,00	4~8W
ioLogik 2542-T	Universal controller, 4 AIs, 12 DIOs, Click&Go Plus, -40 to 75°C operating temperature	€ 1.222,00	4~8W
ioLogik E1210	Universal I/O, 16 DIs, -10 to 60°C operating temperature	€ 261,00	2~4W
ioLogik E1210-T	Universal I/O, 16 DIs, -40 to 75°C operating temperature	€ 429,00	2~4W
ioLogik E1211	Universal I/O, 16 DOs, -10 to 60°C operating temperature	€ 285,00	2~4W
ioLogik E1211-T	Universal I/O, 16 DOs, -40 to 75°C operating temperature	€ 463,00	4~8W
ioLogik E1212	Universal I/O, 8 DIs, 8 DIOs, -10 to 60°C operating temperature	€ 285,00	2~4W
ioLogik E1212-T	Universal I/O, 8 DIs, 8 DIOs, -40 to 75°C operating temperature	€ 463,00	2~4W
ioLogik E1213	Universal I/O, 8 DIs, 4 DOs, 4 DIOs, -10 to 60°C operating temperature	€ 377,00	2~4W
ioLogik E1213-T	Universal I/O, 8 DIs, 4 DOs, 4 DIOs, -40 to 75°C operating temperature	€ 505,00	4~8W
ioLogik E1214	Universal I/O, 6 DIs, 6 relays, -10 to 60°C operating temperature	€ 295,00	2~4W
ioLogik E1214-T	Universal I/O, 6 DIs, 6 relays, -40 to 75°C operating temperature	€ 487,00	2~4W
ioLogik E1240	Universal I/O, 8 AIs, -10 to 60°C operating temperature	€ 409,00	2~4W
ioLogik E1240-T	Universal I/O, 8 AIs, -40 to 75°C operating temperature	€ 653,00	2~4W
ioLogik E1241	Universal I/O, 4 AOs, -10 to 60°C operating temperature	€ 533,00	2~4W
ioLogik E1241-T	Universal I/O, 4 AOs, -40 to 75°C operating temperature	€ 760,00	4~8W
ioLogik E1242	Universal I/O, 4 AIs, 4 DIs, 4 DIOs, -10 to 60°C operating temperature	€ 442,00	2~4W
ioLogik E1242-T	Universal I/O, 4 AIs, 4 DIs, 4 DIOs, -40 to 75°C operating temperature	€ 653,00	4~8W
ioLogik E1260	Universal I/O, 6 RTDs, -10 to 60°C operating temperature	€ 487,00	2~4W
ioLogik E1260-T	Universal I/O, 6 RTDs, -40 to 75°C operating temperature	€ 705,00	4~8W
ioLogik E1262	Universal I/O, 8 TCs, -10 to 60°C operating temperature	€ 533,00	4~8W
ioLogik E1262-T	Universal I/O, 8 TCs, -40 to 75°C operating temperature	€ 760,00	8~12W
ioLogik E1510-M12-CT-T	Rugged I/O, 12 DIs, -40 to 85°C operating temperature, conformal coating	€ 1.940,00	12~16W
ioLogik E1510-M12-T	Rugged I/O, 12 DIs, -40 to 85°C operating temperature	€ 1.502,00	8~12W
ioLogik E1512-M12-CT-T	Rugged I/O, 4 DIs, 4 DIOs, -40 to 85°C operating temperature, conformal coating	€ 1.897,00	12~16W
ioLogik E1512-M12-T	Rugged I/O, 4 DIs, 4 DIOs, -40 to 85°C operating temperature	€ 1.471,00	12~16W
ioLogik E2210	Universal controller, 12 DIs, 8 DOs, Click&Go, -10 to 60°C operating temperature	€ 441,00	2~4W
ioLogik E2210-T	Universal controller, 12 DIs, 8 DOs, Click&Go, -40 to 75°C operating temperature	€ 676,00	4~8W
ioLogik E2212	Universal controller, 8 DIs, 8 DOs, 4 DIOs, Click&Go, -10 to 60°C operating temperature	€ 599,00	4~8W
ioLogik E2212-T	Universal controller, 8 DIs, 8 DOs, 4 DIOs, Click&Go, -40 to 75°C operating temperature	€ 869,00	8~12W
ioLogik E2214	Universal controller, 6 DIs, 6 relays, Click&Go, -10 to 60°C operating temperature	€ 654,00	4~8W
ioLogik E2214-T	Universal controller, 6 DIs, 6 relays, Click&Go, -40 to 75°C operating temperature	€ 933,00	4~8W
ioLogik E2240	Universal controller, 8 AIs, 2 AOs, Click&Go, -10 to 60°C operating temperature	€ 777,00	4~8W
ioLogik E2240-T	Universal controller, 8 AIs, 2 AOs, Click&Go, -40 to 75°C operating temperature	€ 1.113,00	4~8W
ioLogik E2242	Universal controller, 4 AIs, 12 DIOs, Click&Go, -10 to 60°C operating temperature	€ 833,00	2~4W
ioLogik E2242-T	Universal controller, 4 AIs, 12 DIOs, Click&Go, -40 to 75°C operating temperature	€ 1.049,00	4~8W
ioLogik E2260	Universal controller, 6 RTD, 4 DOs, Click&Go, -10 to 60°C operating temperature	€ 747,00	8~12W
ioLogik E2260-T	Universal controller, 6 RTD, 4 DOs, Click&Go, -40 to 75°C operating temperature	€ 1.049,00	12~16W
ioLogik E2262	Universal controller, 8 TCs, 4 DOs, Click&Go, -10 to 60°C operating temperature	€ 833,00	8~12W
ioLogik E2262-T	Universal controller, 8 TCs, 4 DOs, Click&Go, -40 to 75°C operating temperature	€ 1.177,00	12~16W
ioLogik R1210	Universal I/O, 16 DIs, -10 to 75°C operating temperature	€ 259,00	2~4W
ioLogik R1210-T	Universal I/O, 16 DIs, -40 to 85°C operating temperature	€ 348,00	4~8W
ioLogik R1212	Universal I/O, 8 DIs, 8 DIOs, -10 to 75°C operating temperature	€ 289,00	2~4W
ioLogik R1212-T	Universal I/O, 8 DIs, 8 DIOs, -40 to 85°C operating temperature	€ 369,00	8~12W

ioLogik R1214	Universal I/O, 6 DIs, 6 relays, -10 to 75°C operating temperature	€ 298,00	4~8W
ioLogik R1214-T	Universal I/O, 6 DIs, 6 relays, -40 to 85°C operating temperature	€ 433,00	8~12W
ioLogik R1240	Universal I/O, 8 AIs, -10 to 75°C operating temperature	€ 412,00	4~8W
ioLogik R1240-T	Universal I/O, 8 AIs, -40 to 85°C operating temperature	€ 558,00	8~12W
ioLogik R1241	Universal I/O, 4 AOs, -10 to 75°C operating temperature	€ 509,00	4~8W
ioLogik R1241-T	Universal I/O, 4 AOs, -40 to 85°C operating temperature	€ 572,00	12~16W
ioMirror E3210	Universal Peer-to-Peer I/O, 8 DIs, 8 DOs, -10 to 60°C operating temperature	€ 408,00	4~8W
ioPAC 8600-BM005-T	Module for the ioPAC 8600 Series, 5 slots, -40 to 75°C operating temperature	€ 1.445,00	8~12W
ioPAC 8600-BM009-T	Module for the ioPAC 8600 Series, 9 slots, -40 to 75°C operating temperature	€ 2.460,00	8~12W
ioPAC 8600-BM012-T	Module for the ioPAC 8600 Series, 12 slots, -40 to 75°C operating temperature	€ 3.130,00	8~12W
ioPAC 8600-CPU30-M12-C	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, C/C++, -40 to 75°C operating temperature	€ 1.894,00	8~12W
ioPAC 8600-CPU30-M12-E	Rugged controller, 1 GHz CPU, 2-port M12 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	€ 2.489,00	8~12W
ioPAC 8600-CPU30-RJ45-C	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, C/C++, -40 to 75°C operating temperature	€ 1.784,00	8~12W
ioPAC 8600-CPU30-RJ45-E	Rugged controller, 1 GHz CPU, 2-port RJ45 Ethernet, IEC 61131-3, -40 to 75°C operating temperature	€ 2.367,00	8~12W
ioPAC 8600-PW10-30W-T	Module for the ioPAC 8600 Series, 24-110 VDC, 30 W, dual-power inputs, -40 to 75°C operating temperature	€ 1.516,00	12~16W
ioThinX 4510	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -20 to 60°C operating temperature	€ 480,00	2~4W
ioThinX 4510-T	Advanced I/O, Ethernet network adapter, 3-in-1 serial port(s), -40 to 75°C operating temperature	€ 597,00	4~8W
ioThinX 4533-LX	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -20 to 60°C operating temperature	€ 1.257,00	4~8W
ioThinX 4533-LX (V1)	ioThinX 4533-LX (V1)	€ 1.113,00	16~20W
ioThinX 4533-LX-T	Advanced modular controller with built-in serial port, dual-core 1 GHz CPU, Linux, -40 to 75°C operating temperature	€ 1.410,00	4~8W
ioThinX 4533-LX-T (V1)	ioThinX 4533-LX-T (V1)	€ 1.245,00	16~20W
ISD-1110-T	7 data line entry surge protector, RS-232, 4 kV surge protection, -40 to 85°C operating temperature	€ 122,00	4~8W
ISD-1130-T	4 data line entry surge protector, RS-422/485, 4 kV surge protection, -40 to 85°C operating temperature	€ 109,00	4~8W
ISD-1210-T	4 data line advanced surge protector, RS-232, 20 kV surge protection, -40 to 85°C operating temperature	€ 302,00	8~12W
ISD-1230-T	4 data line advanced surge protector, RS-422/485, 20 kV surge protection, -40 to 85°C operating temperature	€ 302,00	2~4W
LB-DB9F-G-01	Serial loopback DB9 adaptor	€ 8,00	12~14W
LB-RJ458P-RS232	RS-232 Loopback Header 8-pin RJ45	€ 6,00	12~14W
LB-RJ458P-RS422	RS-422 Loopback Header 8-pin RJ45	€ 6,00	12~14W
LIC-IPS-DEVICE-NEW-1Y	1-year device-based IPS license	€ 769,00	
LIC-IPS-DEVICE-RENEW-1Y	1-year device-based IPS renewal license	€ 769,00	
LIC-IPS-MXsecurity-ADD-1Y	IPS add-on license for MXsecurity with customizable duration and node quantity (minimum 1 month, minimum 1 node)	€ 65,00	
LIC-IPS-MXsecurity-NEW-1Y	IPS license for MXsecurity with customizable duration and node quantity (minimum 1 month, minimum 1 node)	€ 65,00	
LIC-MRCQL-ADD-1Y-XGB	1-year MRC Quick Link add-on license with customizable data volume (minimum 1 GB)	€ 11,00	
LIC-MRCQL-ADD-1Y-XNS	1-year MRC Quick Link add-on license with customizable node quantity (minimum 1 node)	€ 28,00	
LIC-MXsecurity-NEW-XNS	MXsecurity perpetual node license with customizable node quantity (minimum 1 node)	€ 133,00	
LIC-MXviewOne-ADD-POV	MXview One add-on license for power substation package	€ 20.797,00	
LIC-MXviewOne-ADD-WIR	MXview One add-on license for wireless package	€ 1.280,00	
LIC-MXviewOneCM-ADD-POV	MXview One Central Manager license to enable the Power add-on for MXview One sites, customizable site quantity (minimum 1 site)	€ 20.797,00	
LIC-MXviewOneCM-ADD-WIR	MXview One Central Manager license to enable the Wireless add-on for MXview One sites, customizable site quantity (minimum 1 site)	€ 1.280,00	
LIC-MXviewOneCM-NEW-POV	MXview One Central Manager site license with customizable site quantity (minimum 1 site)	€ 411,00	
LIC-MXviewOne-NEW-XNS	MXview One node license with customizable node quantity (minimum 1 node)	€ 70,00	
LM-7000H-2GPHR	Gigabit Ethernet module with 2 100/1000BaseT(X) PRP/HSR or 100/1000BaseSFP PRP/HSR combo ports, -40 to 75°C operating temperature	€ 2.479,00	4~8W
LM-7000H-4GPoE	Gigabit Ethernet module with 4 10/100/1000BaseT(X) IEEE 802.3af/at PoE+ ports	€ 1.222,00	4~8W
LM-7000H-4GSFP	Gigabit Ethernet module with 4 100/1000BaseSFP slots	€ 839,00	2~4W
LM-7000H-4GTX	Gigabit Ethernet module with 4 10/100/1000BaseT(X) ports	€ 839,00	2~4W
LM-7000H-4PoE	Fast Ethernet module with 4 10/100BaseT(X) IEEE 802.3af/at PoE+ ports	€ 834,00	8~12W
LM-7000H-4TX	Fast Ethernet module with 4 10/100BaseT(X) ports	€ 502,00	2~4W
LM-7000H-DMY	LM-7000H dummy module, 3 pcs	€ 45,00	8~12W
LNA-1120-T	Industrial 5G low-noise amplifier, n48, n78, n79, n1, n3, and n7 bands, IP30, -40°C to 70°C operating temperature	€ 188,00	8~12W
M12A-4PFF-IP67	M12 cable connector, female 4-pin, A-coded	€ 148,00	36~40W
M12A-4PMM-IP67	M12 cable connector, male 4-pin, A-coded	€ 142,00	36~40W
M12A-5PFF-IP67-HTG (5 P)	Crimp type M12 connector, female 5-pin, A-coded, IP67-rated	€ 148,00	16~20W
M12A-5P-IP68	Solder type M12 connector, female 5-pin, A-coded, IP68-rated	€ 24,00	20~24W
M12A-5PMM-IP68	5-pin male circular threaded D-coded M12 USB connector, IP68	€ 34,00	24~28W
M12A-8PFF-IP68	Field-installation A-coded M12 screw-in 8-pin connector, female connector female PIN	€ 27,00	24~28W
M12A-8PMM-IP67	IDC type M12 connector, male 8-pin, A-coded, IP67-rated	€ 148,00	28~32W
M12A-8PMM-IP68	Field-installation A-coded screw-in Gigabit Ethernet connector, 8-pin male M12 connector, IP68-rated	€ 18,00	10~12W
M12D-4P-IP68	Solder type M12 connector, male 4-pin, D-coded, IP68-rated	€ 24,00	20~24W
M12D-4PMM-IP67	IDC type M12 connector, male 4-pin, D-coded, IP67-rated	€ 103,00	28~32W

M12K-5PFF-IP65-PxC	Crimp type M12 connector, female 5-pin, K-coded, IP65-rated	€ 167,00	20~24W
M12X-8PMM-IP65	M12 cable connector, male 8-pin, X-coded	€ 279,00	24~28W
M12X-8PMM-IP67	8-pin male X-coded circular threaded gigabit Ethernet connector, IP67	€ 247,00	24~28W
M12X-8PMM-IP67-HTG	Crimp type M12 connector, male 8-pin, X-coded, IP67-rated	€ 161,00	16~20W
MAT-5G-PA-SM-2-06-3m	6 dBi MIMO panel antenna with 2 SMA (male) connectors for cellular applications, 3 m cable	€ 553,00	12~14W
MAT-5G-PA-SM-3-06-3m	6 dBi MIMO panel antenna with 3 SMA (male) connectors for cellular and GNSS applications, 3 m cable	€ 691,00	12~14W
MAT-5G-PA-SM-4-05-1m	5 dBi at 3300 to 5925 MHz, LTE/NR MIMO panel antenna with 4 SMA connectors (male), 4 1-meter cables	€ 647,00	10~12W
MAT-WDB-CA-RM-2-0205	2.4/5 GHz, ceiling antenna, 2/5 dBi, MIMO 2x2, RP-SMA-type (male)	€ 99,00	10~12W
MAT-WDB-DA-RM-2-0203	2.4/5 GHz, desktop antenna, 2/3 dBi, MIMO 2x2, RP-SMA-type (male), 1 m cable	€ 99,00	12~14W
MAT-WDB-PA-NF-2-0708	2.4/5 GHz, panel antenna, 7/8 dBi, MIMO 2x2, N-type (female)	€ 329,00	10~12W
MC-1100 DIN-Rail Kit	DIN-rail mounting kit, 4 screws	€ 16,00	4~8W
MC-1100 Wallmount Kit	Wall-mounting kit, 4 screws	€ 20,00	4~8W
MC-1111-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	€ 1.645,00	8~12W
MC-1111-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 1 CFast socket, 1 SD slot, 1 DisplayPort, 12 to 36 VDC power, -40 to 70°C operating temperature	€ 1.740,00	8~12W
MC-1112-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	€ 1.674,00	8~12W
MC-1112-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 2 Gigabit Ethernet ports, 2 serial ports, 1 CFast socket, 12 to 36 VDC power, -40 to 70°C operating temperature	€ 1.756,00	8~12W
MC-1121-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power	€ 1.993,00	8~12W
MC-1121-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 SD slot, 1 DisplayPort, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power	€ 2.082,00	4~8W
MC-1121-E4-T-W7E	x86 embedded computer with Intel Atom® quad-core E3845 processor, 1 CFast socket with 32 GB card preinstalled, Windows Embedded Standard 7 preinstalled, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 SD slot,	€ 2.567,00	8~12W
MC-1122-E2-T	x86 embedded computer with Intel Atom® dual-core E3826 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating	€ 1.937,00	8~12W
MC-1122-E4-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating	€ 2.016,00	8~12W
MC-1122-E4-TPM-T	x86 embedded computer with Intel Atom® quad-core E3845 processor, 4 GB RAM, 1 VGA port, 2 USB ports, 4 Gigabit Ethernet ports, 4 serial ports, 4 DIs, 4 DOs, 1 CFast socket, 1 uSIM slot, 1 Mini PCIe expansion slot, 12 to 36 VDC power, -40 to 70°C operating	€ 2.016,00	4~8W
MC-1220 DIN-Rail Kit	DIN-rail mounting kit for MC-1200 with 4 M3 screws	€ 16,00	4~8W
MC-1220 Wallmount Kit	Wall-mounting kit for MC-1200 with 4 M3 screws	€ 19,00	8~10W
MC-1220-KL1-T-S	Intel® Celeron® 3965U 2C/2T 2.2 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	€ 3.312,00	20~24W
MC-1220-KL5-T-S	Intel® Core™ i5-7300U 2C/4T 2.6 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	€ 4.832,00	20~24W
MC-1220-KL7-T-S	Intel® Core™ i7-7600U 2C/4T 2.8 GHz computer with 8 GB RAM, 2 Gigabit Ethernet ports, 2 RS/232/422/485 3-in-1 serial ports, 3 USB 3.0 ports, 3 Mini PCIe expansion slots, 1 HDMI port, TPM 2.0, 9 to 36 VDC power, -40 to 70°C operating temperature	€ 5.493,00	20~24W
MC-1220-LTE Cat4-EU	Wireless package for the MC-1200 Series with LE910C4-NF 4G module and mPCIe module for the EU region	€ 258,00	56~60W
MC-1220-WLAN11-AC	Wireless package for the MC-1200 Series with WPEQ-261ACNI(BT) 802.11ac/a/b/g/n Wi-Fi module and mPCIe module	€ 224,00	20~24W
MC-3201-TGL1-M-S	Intel® Celeron® 6305E, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	€ 3.725,00	8~12W
MC-3201-TGL1-S-S	Intel® Celeron® 6305E, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	€ 2.720,00	8~12W
MC-3201-TGL3-M-S	Intel® Core™ i3-1115G4E, 2C/4T, 2.2 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full C	€ 4.309,00	8~12W
MC-3201-TGL3-S-S	Intel® Core™ i3-1115G4E, 2C/4T, 2.2 GHz computer with 2 DisplayPorts, 4 Gigabit LAN ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	€ 3.586,00	8~12W
MC-3201-TGL5-M-S	Intel® Core™ i5-1145G7E, 4C/8T, 1.5 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CP	€ 5.087,00	8~12W
MC-3201-TGL5-S-S	Intel® Core™ i5-1145G7E, 4C/8T, 1.5 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	€ 4.378,00	8~12W

MC-3201-TGL7-M-S	Intel® Core™ i7-1185G7E, 4C/8T, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 1 NMEA port, 4 DIs, 4 DOs, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CP	€ 5.279,00	8~12W
MC-3201-TGL7-S-S	Intel® Core™ i7-1185G7E, 4C/8T, 1.8 GHz computer with 2 DisplayPorts, 4 GbE ports, 2 RS/232/422/485 3-in-1 serial ports, 2 USB 3.0 ports, 4 USB 2.0 ports, TPM 2.0, 24 VDC power input, -20 to 55°C operating temperature at full CPU speed	€ 5.018,00	8~12W
MC-7410-C1-AC	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power input	€ 4.424,00	8~12W
MC-7410-C1-DC	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power input	€ 4.424,00	8~12W
MC-7410-C5-AC	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and AC power input	€ 6.532,00	8~12W
MC-7410-C5-DC	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 5 Gigabit Ethernet ports, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2 SSD trays, and DC power input	€ 6.532,00	8~12W
MC-7410-C7-AC	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, AC power input	€ 6.828,00	8~12W
MC-7410-C7-DC	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, DC power input	€ 6.973,00	8~12W
MC-7420-C1-AC	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 DIs, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2	€ 5.233,00	8~12W
MC-7420-C1-DC	x86 embedded computer with Intel® Celeron® G3902E processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 DIs, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2	€ 5.233,00	8~12W
MC-7420-C5-AC	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 DIs, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2	€ 7.347,00	8~12W
MC-7420-C5-DC	x86 embedded computer with Intel® Core™ i5 6442EQ processor, fanless, 4 serial ports, 4 NMEA 0183 ports, 5 Gigabit Ethernet ports, 4 DIs, 4 DOs, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/audio out, 2	€ 7.347,00	8~12W
MC-7420-C7-AC	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 4 NMEA 0183 ports, 4 DIs, 4 DOs, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/a	€ 7.721,00	8~12W
MC-7420-C7-DC	x86 embedded fanless computer with Intel® Core™ i7-6822EQ processor, 5 Gigabit Ethernet ports, 4 serial ports, 4 NMEA 0183 ports, 4 DIs, 4 DOs, 2 SSD slots, 5 USB 2.0 ports, 4 USB 3.0 ports, 1 DVI-D port, 1 DVI-I port, 1 DisplayPort, 1 PS/2 port, mic in/a	€ 7.705,00	8~12W
MDR-40-24	DIN-rail 24 VDC power supply with 40W/1.7A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	€ 106,00	2~4W
MDR-60-24	DIN-rail 24 VDC power supply with 60W/2.5A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature	€ 145,00	4~8W
MDS-G4012	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 3.080,00	12~16W
MDS-G4012-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 6.994,00	12~16W
MDS-G4012-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 4.812,00	16~20W
MDS-G4012-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 8 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 9.185,00	16~20W
MDS-G4012-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 5.278,00	16~20W
MDS-G4012-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 2 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 12 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 3.516,00	16~20W
MDS-G4020	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 3.346,00	12~16W
MDS-G4020-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 8.367,00	12~16W
MDS-G4020-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 5.090,00	16~20W
MDS-G4020-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 16 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 10.543,00	16~20W

MDS-G4020-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 5.555,00	16~20W
MDS-G4020-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 4 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 20 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 3.767,00	16~20W
MDS-G4028	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 3.584,00	12~16W
MDS-G4028-4XGS-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 9.726,00	12~16W
MDS-G4028-L3	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -10 to 60°C operating temperature	€ 5.335,00	16~20W
MDS-G4028-L3-4XGS-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed 10GbE SFP+ slots, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 24 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 11.918,00	16~20W
MDS-G4028-L3-T	Layer 3 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 5.809,00	16~20W
MDS-G4028-T	Layer 2 full Gigabit modular managed Ethernet switch with 4 fixed Gigabit Ethernet ports, 6 slots for optional 4-port GE/FE modules, 2 slots for isolated power modules, up to 28 Gigabit Ethernet ports, -40 to 75°C operating temperature	€ 4.005,00	16~20W
ME-10-T	1-slot chassis with redundant 12 to 48 VDC power inputs	€ 166,00	8~12W
MGate 4101I-MB-PBS	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, 0 to 60°C operating temperature	€ 1.064,00	4~8W
MGate 4101I-MB-PBS-T	1-port Modbus-to-PROFIBUS Slave gateway with 2 kV isolation, 12 to 48 VDC, -40 to 75°C operating temperature	€ 1.284,00	8~12W
MGate 4101-MB-PBS	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, 0 to 60°C operating temperature	€ 891,00	4~8W
MGate 4101-MB-PBS-T	1-port Modbus-to-PROFIBUS Slave gateway, 12 to 48 VDC, -40 to 75°C operating temperature	€ 1.126,00	8~12W
MGate 5101-PBM-MN	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, 0 to 60°C operating temperature	€ 1.536,00	4~8W
MGate 5101-PBM-MN-T	1-port PROFIBUS master-to-Modbus TCP gateway, 12 to 48 VDC, -40 to 75°C operating temperature	€ 1.845,00	8~12W
MGate 5102-PBM-PN	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, 0 to 60°C operating temperature	€ 1.536,00	4~8W
MGate 5102-PBM-PN-T	1-port PROFIBUS-to-PROFINET gateway, 12 to 48 VDC, -40 to 75°C operating temperature	€ 1.925,00	8~12W
MGate 5103	1-port Modbus/EtherNet/IP-to-PROFINET gateway, 0 to 60°C operating temperature	€ 846,00	2~4W
MGate 5103-T	1-port Modbus/EtherNet/IP-to-PROFINET gateway, -40 to 75°C operating temperature	€ 1.049,00	4~8W
MGate 5105-MB-EIP	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, 0 to 60°C operating temperature	€ 846,00	2~4W
MGate 5105-MB-EIP-T	1-port MQTT-supported Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	€ 1.065,00	4~8W
MGate 5109	1-port Modbus-to-DNP3 gateway, 0 to 60°C operating temperature	€ 846,00	4~8W
MGate 5109-T	1-port Modbus-to-DNP3 gateway, -40 to 75°C operating temperature	€ 1.065,00	4~8W
MGate 5111	1-port Modbus/PROFINET/EtherNet/IP to PROFIBUS Slave gateway, 0 to 60°C operating temperature	€ 846,00	2~4W
MGate 5111-T	1-port Modbus/PROFINET/EtherNet/IP-to-PROFIBUS Slave gateway, -40 to 75°C operating temperature	€ 1.049,00	8~12W
MGate 5114	1-port Modbus/IEC101 to IEC104 gateway, 0 to 60°C operating temperature	€ 846,00	4~8W
MGate 5114-T	1-port Modbus/IEC101 to IEC104 gateway, -40 to 75°C operating temperature	€ 1.049,00	8~12W
MGate 5118	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, 0 to 60°C operating temperature	€ 846,00	2~4W
MGate 5118-T	1-port J1939 to Modbus/PROFINET/EtherNet/IP gateway, -40 to 75°C operating temperature	€ 1.065,00	4~8W
MGate 5119-T	1-port DNP3/IEC 101/IEC 104/Modbus-to-IEC 61850 gateways, -40 to 75°C operating temperature	€ 1.536,00	4~8W
MGate 5121	1-port CANopen/J1939-to-Modbus TCP gateways, -10 to 60°C operating temperature	€ 1.007,00	8~12W
MGate 5121-T	1-port CANopen/J1939-to-Modbus TCP gateways, -40 to 75°C operating temperature	€ 1.255,00	8~12W
MGate 5122	1-port CANopen/J1939-to-EtherNet/IP gateways, -10 to 60°C operating temperature	€ 1.007,00	8~12W
MGate 5122-T	1-port CANopen/J1939-to-EtherNet/IP gateways, -40 to 75°C operating temperature	€ 1.255,00	8~12W
MGate 5123	1-port CANopen/J1939-to-PROFINET gateways, -10 to 60°C operating temperature	€ 1.007,00	8~12W
MGate 5123-T	1-port CANopen/J1939-to-PROFINET gateways, -40 to 75°C operating temperature	€ 1.255,00	8~12W
MGate 5134	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -10 to 60°C operating temperature	€ 846,00	4~8W
MGate 5134-T	1-port Modbus RTU/ASCII/TCP-to-PROFINET gateways, -40 to 75°C operating temperature	€ 1.049,00	8~12W
MGate 5135	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	€ 846,00	4~8W
MGate 5135-T	1-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	€ 1.049,00	4~8W
MGate 5192-T	1-port IEC 61850-to-DNP3/IEC 101/IEC 104/Modbus gateway with -40 to 75°C operating temperature	€ 1.570,00	8~12W
MGate 5216	2-port serial/Modbus-to-EtherCAT gateway with 0 to 60°C operating temperature	€ 1.275,00	8~12W
MGate 5217I-1200-T	2-port Modbus-to-BACnet/IP gateway, 1200 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	€ 1.571,00	4~8W
MGate 5217I-600-T	2-port Modbus-to-BACnet/IP gateway, 600 points, 2kV isolation, 12 to 48 VDC, 24 VAC, -40 to 75°C operating temperature	€ 866,00	4~8W
MGate 5435	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -10 to 60°C operating temperature	€ 1.409,00	4~8W
MGate 5435-T	4-port Modbus RTU/ASCII/TCP-to-EtherNet/IP gateways, -40 to 75°C operating temperature	€ 1.744,00	12~16W
MGate EIP3170	1-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	€ 488,00	4~8W
MGate EIP3170I	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	€ 561,00	8~12W
MGate EIP3170I-T	1-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, -40 to 75°C operating temperature	€ 736,00	8~12W

MGate EIP3170-T	1-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	€ 635,00	8~12W
MGate EIP3270	2-port EtherNet/IP-to-DF1 gateway, 0 to 60°C operating temperature	€ 807,00	8~12W
MGate EIP3270I	2-port EtherNet/IP-to-DF1 gateway with 2 kV isolation, 0 to 60°C operating temperature	€ 971,00	8~12W
MGate EIP3270-T	2-port EtherNet/IP-to-DF1 gateway, -40 to 75°C operating temperature	€ 1.049,00	8~12W
MGate MB3170	1-port advanced Modbus gateway, 0 to 60°C operating temperature	€ 479,00	2~4W
MGate MB3170I	1-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	€ 561,00	2~4W
MGate MB3170I-M-SC	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	€ 731,00	8~12W
MGate MB3170I-M-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	€ 971,00	8~12W
MGate MB3170I-S-SC	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 60°C operating temperature	€ 846,00	8~12W
MGate MB3170I-S-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	€ 1.113,00	8~12W
MGate MB3170I-T	1-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	€ 814,00	2~4W
MGate MB3170-M-SC	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 60°C operating temperature	€ 626,00	4~8W
MGate MB3170-M-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	€ 818,00	8~12W
MGate MB3170-M-ST	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 60°C operating temperature	€ 626,00	4~8W
MGate MB3170-M-ST-T	1-port advanced Modbus gateway with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	€ 818,00	4~8W
MGate MB3170-S-SC	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 60°C operating temperature	€ 712,00	4~8W
MGate MB3170-S-SC-T	1-port advanced Modbus gateway with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	€ 933,00	4~8W
MGate MB3170-T	1-port advanced Modbus gateway, -40 to 75°C operating temperature	€ 691,00	2~4W
MGate MB3180	1-port standard Modbus gateway	€ 356,00	2~4W
MGate MB3270	2-port advanced Modbus gateway, 0 to 60°C operating temperature	€ 891,00	2~4W
MGate MB3270I	2-port advanced Modbus gateway with 2 kV isolation, 0 to 60°C operating temperature	€ 1.067,00	2~4W
MGate MB3270I-T	2-port advanced Modbus gateway with 2 kV isolation, -40 to 75°C operating temperature	€ 1.377,00	2~4W
MGate MB3270-T	2-port advanced Modbus gateway, -40 to 75°C operating temperature	€ 1.161,00	4~8W
MGate MB3280	2-port standard Modbus gateway	€ 627,00	2~4W
MGate MB3480	4-port standard Modbus gateway	€ 956,00	2~4W
MGate MB3660-16-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	€ 2.592,00	4~8W
MGate MB3660-16-2DC	Modbus gateway with dual LANs, dual DC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature	€ 2.722,00	4~8W
MGate MB3660-16-J-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	€ 2.768,00	4~8W
MGate MB3660-8-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	€ 2.065,00	4~8W
MGate MB3660-8-2DC	Modbus gateway with dual LANs, dual DC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature	€ 2.188,00	4~8W
MGate MB3660-8-J-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, RJ45 serial interface, 0 to 60°C operating temperature	€ 2.188,00	4~8W
MGate MB3660I-16-2AC	Modbus gateway with dual LANs, dual AC power inputs, 16 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	€ 3.753,00	4~8W
MGate MB3660I-8-2AC	Modbus gateway with dual LANs, dual AC power inputs, 8 RS-232/422/485 ports, 0 to 60°C operating temperature, 2 kV isolation	€ 2.517,00	4~8W
MiiNePort E1	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 0 to 55°C operating temperature	€ 87,00	2~4W
MiiNePort E1-H	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	€ 107,00	4~8W
MiiNePort E1-H-ST	Starter Kit for the Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, 0 to 55°C operating temperature	€ 266,00	8~12W
MiiNePort E1-H-T	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, 50 bps to 921.6K baudrate, -40°C to 85°C operating temperature	€ 156,00	8~12W
MiiNePort E1-SDK	MiiNePort E1 software development kit	€ 441,00	8~12W
MiiNePort E1-ST	Starter kit for the MiiNePort E1 Series, module included	€ 259,00	8~12W
MiiNePort E1-ST (w/o Mod)	Starter kit for the MiiNePort E1 Series, module not included	€ 169,00	8~12W
MiiNePort E1-T	Embedded device server for TTL devices, drop-in module, 10/100M with RJ45 connector, -40 to 85°C operating temperature	€ 124,00	2~4W
MiiNePort E2	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	€ 76,00	2~4W
MiiNePort E2-H	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	€ 79,00	4~8W
MiiNePort E2-H-ST	Starter kit for the MiiNePort E2-H Series, module included	€ 267,00	8~12W
MiiNePort E2-H-T	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	€ 107,00	2~4W
MiiNePort E2-SDK	MiiNePort E2 software development kit	€ 441,00	8~12W
MiiNePort E2-ST	Starter kit for the MiiNePort E2 Series, module included	€ 262,00	8~12W
MiiNePort E2-T	Embedded device server for TTL devices, drop-in module, 10/100M without RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	€ 104,00	2~4W

MiiNePort E3	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, 0 to 55°C operating temperature	€ 79,00	2~4W
MiiNePort E3-H	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, 0 to 55°C operating temperature	€ 87,00	4~8W
MiiNePort E3-H-ST	Starter kit for the MiiNePort E3-H Series, module included	€ 230,00	8~12W
MiiNePort E3-H-T	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 921.6 Kbps baudrate, -40 to 85°C operating temperature	€ 114,00	4~8W
MiiNePort E3-ST	Starter kit for the MiiNePort E3 Series, module included	€ 226,00	8~12W
MiiNePort E3-T	Embedded device server for TTL devices, pin header module, 10/100M with RJ45 connector, 50 bps to 230.4 Kbps baudrate, -40 to 85°C operating temperature	€ 111,00	4~8W
Mini DB9F-to-TB	DB9 female to terminal block connector	€ 14,00	2~4W
Moxa EtherNet/IP Demo Kit	EtherNet/IP Demo Kit	€ 7.637,00	12~16W
Moxa PI Demo Kit	PI Demo Kit	€ 10.511,00	8~12W
Moxa PROFINET Demo Kit	PROFINET Demo Kit	€ 13.843,00	8~12W
MPC-2070-E2-LB-T	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	€ 2.627,00	12~16W
MPC-2070-E2-LB-T-W7E	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 350-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	€ 3.540,00	12~16W
MPC-2070-E2-T	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	€ 2.877,00	4~8W
MPC-2070-E2-T-W7E	7-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	€ 3.788,00	12~16W
MPC-2-07-12-VESAMTK	MPC-2-07-12-VESAMTK	€ 45,00	4~8W
MPC-2101-E4-CT-T	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.457,00	12~16W
MPC-2101-E4-CT-T-LX	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN50155, -40 to 70°C operating temperature, conformal coating	€ 6.849,00	12~16W
MPC-2101-E4-CT-T-W7E	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 1000-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature	€ 7.618,00	12~16W
MPC-2101-E4-LB-CT-T	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.037,00	12~16W
MPC-2101-E4-LB-CT-T-LX	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.379,00	12~16W
MPC-2101-E4-LB-CT-T-W7E	10-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature	€ 7.098,00	12~16W
MPC-2120-E2-LB-T	12-inch panel computer with Intel Atom® E3826 1.46 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	€ 3.508,00	12~16W
MPC-2120-E2-LB-T-W7E	12-inch panel computer with Intel Atom® E3826 1.46 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	€ 4.413,00	12~16W
MPC-2120-E2-T	12-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	€ 3.999,00	12~16W
MPC-2120-E2-T-W7E	12-inch panel computer, Intel Atom® E3826 1.46 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	€ 4.609,00	12~16W
MPC-2120-E4-LB-T	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	€ 3.789,00	12~16W
MPC-2120-E4-LB-T-W7E	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature	€ 4.738,00	12~16W
MPC-2120-E4-T	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM	€ 4.159,00	4~8W
MPC-2120-E4-T-W7E	12-inch panel computer, Intel Atom® E3845 1.91 GHz processor, 1000-nit LCD with multi-touch, 10 to 36 VDC, IP66 in front, -40 to 70°C operating temperature, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, W7E OS	€ 4.923,00	12~16W
MPC-2121-E4-CT-T	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1000-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.875,00	12~16W
MPC-2121-E4-CT-T-LX	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 1000-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 7.380,00	12~16W
MPC-2121-E4-CT-T-W7E	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 1000-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature	€ 8.177,00	12~16W
MPC-2121-E4-LB-CT-T	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 500-nit LCD with multi-touch, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.351,00	20~24W

MPC-2121-E4-LB-CT-T-LX	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 16 GB card preinstalled, 500-nit LCD with multi-touch, Linux preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature, conformal coating	€ 6.849,00	20~24W
MPC-2121-E4-LB-CT-T-W7	12-inch panel computer with Intel Atom® E3845 1.91 GHz processor, 4 GB RAM, 1 CFast socket with 32 GB card preinstalled, 500-nit LCD with multi-touch, Windows Embedded Standard 7 preinstalled, 24 to 110 VDC, IP66, EN 50155, -40 to 70°C operating temperature	€ 7.618,00	20~24W
MPC-3070W-E2-LB-T	7-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.183,00	20~24W
MPC-3070W-E2-T	7-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.426,00	20~24W
MPC-3070W-E4-LB-T	7-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.294,00	20~24W
MPC-3070W-E4-T	7-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.531,00	20~24W
MPC-3100-E2-LB-T	10.4-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.691,00	20~24W
MPC-3100-E2-T	10.4-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.934,00	20~24W
MPC-3100-E4-LB-T	10.4-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.809,00	20~24W
MPC-3100-E4-T	10.4-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.038,00	20~24W
MPC-3120-E2-LB-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 2.990,00	20~24W
MPC-3120-E2-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.226,00	20~24W
MPC-3120-E4-LB-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.087,00	20~24W
MPC-3120-E4-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.337,00	20~24W
MPC-3120W-E2-LB-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.226,00	20~24W
MPC-3120W-E2-T	12.1-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.462,00	20~24W
MPC-3120W-E4-LB-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.337,00	20~24W
MPC-3120W-E4-T	12.1-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.573,00	20~24W
MPC-3150-E2-LB-T	15-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.782,00	20~24W
MPC-3150-E2-T	15-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.018,00	20~24W
MPC-3150-E4-LB-T	15-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 3.893,00	20~24W
MPC-3150-E4-T	15-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.130,00	20~24W
MPC-3150W-E2-LB-T	15.6-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.046,00	20~24W
MPC-3150W-E2-T	15.6-inch panel computer with Intel Atom® x6211E dual-core 1.30 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.296,00	20~24W
MPC-3150W-E4-LB-T	15.6-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 400-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.157,00	20~24W
MPC-3150W-E4-T	15.6-inch panel computer with Intel Atom® x6425E quad-core 2.0 GHz processor, 8 GB RAM, 1000-nit multi-touch PCAP LCD, 2 LAN, 2 serial, 2 USB 3.0, 12/24 VDC power input, IP66 front panel, -30 to 60°C operating temperature	€ 4.408,00	20~24W

MRC-1002-LTE-EU	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, EU region, -10 to 60°C operating temperature	€ 1.566,00	8~12W
MRC-1002-LTE-EU-T	Moxa Remote Connect gateway with 1 LTE cellular port and 2 Ethernet ports, EU region, -30 to 70°C operating temperature	€ 1.723,00	12~16W
MRC-1002-LTE-JP	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, Japan region, -10 to 60°C operating temperature	€ 1.566,00	8~12W
MRC-1002-LTE-JP-T	Moxa Remote Connect gateway with 1 LTE cellular port and 2 Ethernet ports, Japan region, -30 to 70°C operating temperature	€ 1.723,00	12~16W
MRC-1002-LTE-US-T	Moxa Remote Connect gateway with 1 LTE cellular port, 2 Ethernet ports, US region, -40 to 70°C operating temperature	€ 1.723,00	12~16W
MRC-1002-T	Moxa Remote Connect gateway with 2 Ethernet ports, -40 to 75°C operating temperature	€ 1.019,00	4~8W
MRX-G4064-L3-8XGS	Layer 3 modular managed Gigabit Ethernet switch with 3 slots for 16-port Gigabit Ethernet modules, 8 10GbE SFP+ slots, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	€ 25.824,00	12~16W
MRX-Q4064-L3-16XGS	Layer 3 modular managed 2.5 Gigabit Ethernet switch with 16 10GbE SFP+ ports, 3 slots for 16-port Gigabit or 2.5 Gigabit Ethernet modules, 2 isolated power supplies (90 to 264 VAC), -10 to 60°C operating temperature	€ 36.354,00	12~16W
MX-AOPC UA Server	OPC UA Server software for converting fieldbus to the OPC UA standard	€ 812,00	
NAT-102	2-port industrial Network Address Translation (NAT) devices, -10 to 60°C operating temperature	€ 819,00	2~4W
NAT-102-T	2-port industrial Network Address Translation (NAT) devices, -40 to 75°C operating temperature	€ 958,00	4~8W
NDR-120-24	120 W/5.0 A DIN-rail 24 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	€ 163,00	8~12W
NDR-120-48	120 W/2.5 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	€ 163,00	8~12W
NDR-240-48	240 W/5.0 A DIN-rail 48 VDC power supply, universal 90 to 264 VAC or 127 to 370 VDC input voltage, -20 to 70°C operating temperature	€ 397,00	8~12W
NE-4100-ST	Starter Kit for NE-4100T, NE-4100T-P	€ 143,00	8~12W
NE-4100T	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package	€ 84,00	2~4W
NE-4100T-P	Programmable 10/100 Mbps embedded serial device servers, wide temp	€ 87,00	8~12W
NE-4100T-T	Device server module for TTL devices, supports 10/100BaseT(x) with DIL package, -40 to 75°C operating temperature	€ 110,00	4~8W
NE-4110A	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	€ 90,00	4~8W
NE-4110A-P	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector	€ 110,00	8~12W
NE-4110A-T	Device server module for RS-422/485 devices, supports 10/100BaseT(x) with RJ45 connector, -40 to 75°C operating temperature	€ 130,00	4~8W
NE-4110S	Device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	€ 90,00	2~4W
NE-4110S-P	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with RJ45 connector	€ 100,00	8~12W
NE-4110S-T	Device server module for RS-232 devices, supports 10/100BaseT(X) with RJ45 connector, -40 to 75°C operating temperature	€ 119,00	4~8W
NE-4110-ST	Starter Kit for NE-4110S, NE-4110A, NE-4110S-P, NE-4110A-P	€ 154,00	8~12W
NE-4120A	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	€ 107,00	8~12W
NE-4120A-P	Programmable device server module for RS-422/485 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	€ 107,00	8~12W
NE-4120A-T	Device server module for RS-422/485 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	€ 163,00	4~8W
NE-4120S	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header	€ 96,00	8~12W
NE-4120S-P	Programmable device server module for RS-232 devices, supports 10/100BaseT(x) with 5-pin Ethernet pin header	€ 96,00	8~12W
NE-4120S-T	Device server module for RS-232 devices, supports 10/100BaseT(X) with 5-pin Ethernet pin header, -40 to 75°C operating temperature	€ 151,00	8~12W
NE-4120-ST	Starter Kit for NE-4120S, NE-4120A, NE-4120S-P, NE-4120A-P	€ 160,00	8~12W
NM-FX01-M-SC	1 100BaseFX port, multi-mode, SC connector	€ 160,00	4~8W
NM-FX01-M-SC-T	1 100BaseFX port, multi-mode, SC connector, -40 to 75°C operating temperature	€ 220,00	8~12W
NM-FX01-S-SC	1 100BaseFX port, single-mode, SC connector	€ 200,00	4~8W
NM-FX01-S-SC-T	1 100BaseFX port, single-mode, SC connector, -40 to 75°C operating temperature	€ 270,00	8~12W
NM-FX02-M-SC	2 100BaseFX ports, multi-mode, SC connector	€ 339,00	8~12W
NM-FX02-M-SC-T	2 100BaseFX ports, multi-mode, SC connector, -40 to 75°C operating temperature	€ 462,00	8~12W
NM-FX02-S-SC	2 100BaseFX ports, single-mode, SC connector	€ 405,00	4~8W
NM-FX02-S-SC-T	2 100BaseFX ports, single-mode, SC connector, -40 to 75°C operating temperature	€ 555,00	8~12W
NM-TX01	1 10/100BaseT(X) port	€ 54,00	8~12W
NM-TX01-T	1 10/100BaseT(X) port, -40 to 75°C operating temperature	€ 71,00	8~12W
NM-TX02	2 10/100BaseT(X) ports	€ 106,00	4~8W
NM-TX02-T	2 10/100BaseT(X) ports, -40 to 75°C operating temperature	€ 144,00	8~12W
NP21101	DB25 male to DB9 female cable for RS-232 transmission, 30 cm	€ 14,00	16~20W
NP21102	DB25 male to DB9 male cable for RS-232 transmission, 30 cm	€ 14,00	16~20W
NP21103	DB25 male to terminal block for RS-422/485 transmission	€ 11,00	4~8W
NPort 5110	1-port RS-232 device server, 0 to 55°C operating temperature	€ 193,00	2~4W
NPort 5110 w/o adapter	1-port RS-232 device server without adapter, 0 to 55°C operating temperature	€ 183,00	2~4W
NPort 5110A	1-port RS-232 device server, 0 to 60°C operating temperature	€ 196,00	2~4W
NPort 5110A-T	1-port RS-232 device server with surge protection, -40 to 75°C operating temperature	€ 303,00	4~8W
NPort 5110-T	1-port RS-232 device server, -40 to 75°C operating temperature	€ 282,00	2~4W
NPort 5130	1-port RS-422/485 device server, 0 to 55°C operating temperature	€ 210,00	2~4W
NPort 5130A	1-port RS-422/485 device server, 0 to 60°C operating temperature	€ 227,00	2~4W

NPort 5130A-T	1-port RS-422/485 device server, -40 to 75°C operating temperature	€ 303,00	2~4W
NPort 5150	1-port RS-232/422/485 device server, 0 to 55°C operating temperature	€ 220,00	2~4W
NPort 5150 w/o adapter	1-port RS-232/422/485 device server without adapter, 0 to 55°C operating temperature	€ 214,00	4~8W
NPort 5150A	1-port RS-232/422/485 device server, 0 to 60°C operating temperature	€ 238,00	2~4W
NPort 5150AI-M12	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature	€ 1.065,00	8~12W
NPort 5150AI-M12-CT	1-port RS-232/422/485 device server with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	€ 1.380,00	12~16W
NPort 5150AI-M12-CT-T	1-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	€ 1.551,00	12~16W
NPort 5150AI-M12-T	1-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	€ 1.331,00	12~16W
NPort 5150A-T	1-port RS-232/422/485 device server, -40 to 75°C operating temperature	€ 313,00	2~4W
NPort 5210	2-port RS-232 device server, 0 to 55°C operating temperature	€ 295,00	2~4W
NPort 5210 w/ adapter	2-port RS-232 device server with adapter, 0 to 55°C operating temperature	€ 314,00	2~4W
NPort 5210A	2-port RS-232 device server, 0 to 60°C operating temperature	€ 317,00	2~4W
NPort 5210A-T	2-port RS-232 device server with surge protection, -40 to 75°C operating temperature	€ 399,00	4~8W
NPort 5210-T	2-port RS-232 device server, -40 to 75°C operating temperature	€ 421,00	4~8W
NPort 5230	2-port device server with 1 RS-232 port and 1 RS-422/485 port, 0 to 55°C operating temperature	€ 295,00	2~4W
NPort 5230 w/ adapter	2-port device server with 1 RS-232 port and 1 RS-422/485 port with adapter, 0 to 55°C operating temperature	€ 314,00	4~8W
NPort 5230A	2-port RS-422/485 device server, 0 to 60°C operating temperature	€ 317,00	2~4W
NPort 5230A-T	2-port RS-422/485 device server, -40 to 75°C operating temperature	€ 399,00	4~8W
NPort 5230-T	2-port device server with 1 RS-232 port and 1 RS-422/485 port, -40 to 75°C operating temperature	€ 412,00	4~8W
NPort 5232	2-port RS-422/485 device server, 0 to 55°C operating temperature	€ 295,00	2~4W
NPort 5232 w/ adapter	2-port RS-422/485 device server with adapter, 0 to 55°C operating temperature	€ 317,00	2~4W
NPort 5232I	2-port RS-422/485 device server with 2 kV optical isolation, 0 to 55°C operating temperature	€ 399,00	2~4W
NPort 5232I w/ adapter	2-port RS-422/485 device server with 2 kV optical isolation, with adapter, -40 to 75°C operating temperature	€ 408,00	4~8W
NPort 5232I-T	2-port RS-422/485 device server with 2 kV optical isolation, -40 to 75°C operating temperature	€ 507,00	4~8W
NPort 5232-T	2-port RS-422/485 device server, -40 to 75°C operating temperature	€ 434,00	4~8W
NPort 5250A	2-port RS-232/422/485 device server, 0 to 60°C operating temperature	€ 355,00	2~4W
NPort 5250A w/o ADP	2-port RS-232/422/485 device server without adapter, 0 to 60°C operating temperature	€ 342,00	4~8W
NPort 5250AI-M12	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	€ 1.252,00	8~12W
NPort 5250AI-M12-CT	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	€ 1.627,00	12~16W
NPort 5250AI-M12-CT-T	2-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	€ 2.005,00	12~16W
NPort 5250AI-M12-T	2-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	€ 1.569,00	12~16W
NPort 5250A-T	2-port RS-232/422/485 device server, -40 to 75°C operating temperature	€ 446,00	4~8W
NPort 5410	4-port RS-232 serial device server	€ 754,00	2~4W
NPort 5410 w/ adapter	4-port RS-232 serial device server with adapter	€ 770,00	2~4W
NPort 5430	4-port RS-422/485 serial device server	€ 862,00	2~4W
NPort 5430 w/ adapter	4-port RS-422/485 serial device server without adapter	€ 870,00	4~8W
NPort 5430I	4-port RS-422/485 serial device server with 2 kV isolation	€ 1.142,00	2~4W
NPort 5430I w/ adapter	4-port RS-422/485 serial device server with 2 kV isolation, with adapter	€ 1.159,00	4~8W
NPort 5450	4-port RS-232/422/485 serial device server	€ 904,00	2~4W
NPort 5450 w/ adapter	4-port RS-232/422/485 serial device server with adapter	€ 926,00	4~8W
NPort 5450AI-M12	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature	€ 1.694,00	4~8W
NPort 5450AI-M12-CT	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -25 to 55°C operating temperature, conformal coating	€ 2.193,00	12~16W
NPort 5450AI-M12-CT-T	4-port RS-232/422/485 device server with M12 connector, M12 power input, -40 to 75°C operating temperature, conformal coating	€ 2.471,00	12~16W
NPort 5450AI-M12-T	4-port RS-232/422/485 device server, 1 10/100BaseT(X) port with M12 connector, M12 power input, -40 to 75°C operating temperature	€ 2.114,00	4~8W
NPort 5450I	4-port RS-232/422/485 device server with 2 kV isolation protection	€ 1.284,00	4~8W
NPort 5450I w/ adapter	4-port RS-232/422/485 device server with 2 kV isolation protection, with adapter	€ 1.297,00	4~8W
NPort 5450I-T	4-port RS-232/422/485 device server with 2 kV isolation protection, -40 to 75°C operating temperature	€ 1.346,00	4~8W
NPort 5450-T	4-port RS-232/422/485 device server, -40 to 75°C operating temperature	€ 1.032,00	2~4W
NPort 5610-16	16-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	€ 1.517,00	2~4W
NPort 5610-16-48V	16-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	€ 1.660,00	4~8W
NPort 5610-8	8-port RS-232 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	€ 1.175,00	2~4W
NPort 5610-8-48V	8-port RS-232 rackmount device server with RJ45 connectors and 48 VDC power input	€ 1.284,00	8~12W
NPort 5610-8-DT	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input	€ 1.175,00	2~4W
NPort 5610-8-DT w/o adapter	8-port RS-232 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	€ 1.051,00	4~8W
NPort 5610-8-DT-J	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input	€ 1.175,00	4~8W
NPort 5610-8-DT-J w/o adapter	8-port RS-232 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	€ 1.051,00	8~12W
NPort 5610-8-DT-T	8-port RS-232 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	€ 1.214,00	8~12W
NPort 5630-16	16-port RS-422/485 rackmount device server with RJ45 connectors, 100 to 240 VAC power input	€ 1.581,00	2~4W

NPort 5630-8	8-port RS-422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	€ 1.253,00	4~8W
NPort 5650-16	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	€ 1.753,00	2~4W
NPort 5650-16-HV-T	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 2.750,00	8~12W
NPort 5650-16-M-SC	16-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	€ 2.207,00	8~12W
NPort 5650-16-S-SC	16-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	€ 2.301,00	8~12W
NPort 5650-16-T	16-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	€ 2.379,00	4~8W
NPort 5650-8	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input	€ 1.502,00	2~4W
NPort 5650-8-DT	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input	€ 1.316,00	2~4W
NPort 5650-8-DT w/o adap	8-port RS-232/422/485 desktop device server with DB9 male connectors and 48 VDC power input, without adapter	€ 1.180,00	4~8W
NPort 5650-8-DT-J	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input	€ 1.316,00	4~8W
NPort 5650-8-DT-J w/o ada	8-port RS-232/422/485 desktop device server with RJ45 connectors and 48 VDC power input, without adapter	€ 1.180,00	4~8W
NPort 5650-8-DT-T	8-port RS-232/422/485 desktop device server with DB9 male connectors, -40 to 75°C operating temperature	€ 1.846,00	4~8W
NPort 5650-8-HV-T	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 2.253,00	8~12W
NPort 5650-8-M-SC	8-port RS-232/422/485 rackmount device server with multi-mode fiber (SC connector)	€ 1.768,00	8~12W
NPort 5650-8-S-SC	8-port RS-232/422/485 rackmount device server with single-mode fiber (SC connector)	€ 1.860,00	8~12W
NPort 5650-8-T	8-port RS-232/422/485 rackmount device server with RJ45 connectors and 100 to 240 VAC power input, -40 to 75°C operating temperature	€ 1.879,00	4~8W
NPort 5650I-8-DT	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation	€ 2.002,00	2~4W
NPort 5650I-8-DT w/o adap	8-port RS-232/422/485 desktop device server with DB9 male connectors, 48 VDC power input, and 2 kV optical isolation, without adapter	€ 1.822,00	4~8W
NPort 5650I-8-DT-T	8-port RS-232/422/485 desktop device server with DB9 male connectors and 2 KV isolation, -40 to 75°C operating temperature	€ 2.877,00	4~8W
NPort 6150	1-port RS-232/422/485 secure device server	€ 390,00	2~4W
NPort 6150-G2	2nd Gen 1-port RS-232/422/485 secure device server	€ 425,00	12~16W
NPort 6150-G2-T	2nd Gen 1-port RS-232/422/485 secure device server, -40 to 75°C operating temperature	€ 533,00	12~16W
NPort 6150-T	1-port RS-232/422/485 secure device server, -40 to 75°C operating temperature	€ 473,00	4~8W
NPort 6250	2-port RS-232/422/485 to Ethernet secure device server	€ 669,00	2~4W
NPort 6250-G2	2nd Gen 2-port RS-232/422/485 to Ethernet secure device server	€ 679,00	10~12W
NPort 6250-G2-T	2nd Gen 2-port RS-232/422/485 to Ethernet secure device server, -40 to 75°C operating temperature	€ 844,00	10~12W
NPort 6250-M-SC	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server	€ 832,00	4~8W
NPort 6250-M-SC-T	2-port RS-232/422/485 to multi-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	€ 847,00	4~8W
NPort 6250-S-SC	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server	€ 933,00	8~12W
NPort 6250-S-SC-T	2-port RS-232/422/485 to single-mode fiber (SC connector) secure device server, -40 to 75°C operating temperature	€ 955,00	8~12W
NPort 6250-T	2-port RS-232/422/485 to Ethernet secure device server, -40 to 75°C operating temperature	€ 754,00	4~8W
NPort 6450	4-port RS-232/422/485 to Ethernet secure serial port server	€ 862,00	2~4W
NPort 6450-T	4-port secure device server, RS-232/422/485 to Ethernet, -40 to 75°C operating temperature	€ 1.054,00	4~8W
NPort 6610-16	16-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	€ 2.051,00	4~8W
NPort 6610-16-48V	16-port RS-232 to Ethernet secure device server, ±48 VDC input	€ 2.080,00	8~12W
NPort 6610-32	32-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	€ 2.554,00	4~8W
NPort 6610-32-48V	32-port RS-232 to Ethernet secure device server, ±48 VDC input	€ 2.813,00	8~12W
NPort 6610-8	8-port RS-232 to Ethernet secure device server, 100 to 240 VAC input	€ 1.566,00	4~8W
NPort 6610-8-48V	8-port RS-232 to Ethernet secure device server, ±48 VDC input	€ 1.645,00	8~12W
NPort 6650-16	16-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	€ 1.860,00	2~4W
NPort 6650-16-48V	16-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	€ 1.862,00	4~8W
NPort 6650-16-HV-T	16-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 2.579,00	8~12W
NPort 6650-16-T	16-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	€ 2.970,00	4~8W
NPort 6650-32	32-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	€ 2.661,00	2~4W
NPort 6650-32-48V	32-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	€ 2.802,00	4~8W
NPort 6650-32-HV-T	32-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 3.066,00	8~12W
NPort 6650-8	8-port RS-232/422/485 to Ethernet secure terminal server, 100 to 240 VAC input	€ 1.831,00	4~8W
NPort 6650-8-48V	8-port RS-232/422/485 to Ethernet secure terminal server, ±48 VDC input	€ 1.691,00	4~8W
NPort 6650-8-HV-T	8-port RS-232/422/485 to Ethernet secure terminal server, 88 to 300 VDC power input, -40 to 85°C operating temperature	€ 2.268,00	8~12W
NPort 6650-8-T	8-port RS-232/422/485 to Ethernet secure terminal server, -40 to 75°C operating temperature, 100 to 240 VAC input	€ 2.285,00	4~8W
NPort IA-5150	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	€ 421,00	2~4W
NPort IA5150A	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	€ 457,00	2~4W

NPort IA5150AI	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	€ 589,00	4~8W
NPort IA5150A-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, 0 to 60°C operating temperature	€ 522,00	8~12W
NPort IA5150AI-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, 0 to 60°C operating temperature	€ 661,00	8~12W
NPort IA5150AI-T	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	€ 746,00	4~8W
NPort IA5150AI-T-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, -40 to 75°C operating temperature	€ 832,00	12~16W
NPort IA5150A-T	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	€ 570,00	4~8W
NPort IA5150A-T-IEEX	1-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, -40 to 75°C operating temperature	€ 661,00	8~12W
NPort IA-5150I	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 KV optical isolation, 0 to 55°C operating temperature	€ 546,00	4~8W
NPort IA-5150I-M-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	€ 784,00	8~12W
NPort IA-5150I-M-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	€ 1.018,00	12~16W
NPort IA-5150I-S-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, 0 to 55°C operating temperature	€ 870,00	8~12W
NPort IA-5150I-S-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors) and 2 kV optical isolation, -40 to 75°C operating temperature	€ 1.127,00	12~16W
NPort IA-5150I-T	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP) and 2 kV optical isolation, -40 to 75°C operating temperature	€ 698,00	4~8W
NPort IA-5150-M-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), 0 to 55°C operating temperature	€ 589,00	4~8W
NPort IA-5150-M-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (SC connectors), -40 to 75°C operating temperature	€ 826,00	12~16W
NPort IA-5150-M-ST	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), 0 to 55°C operating temperature	€ 589,00	8~12W
NPort IA-5150-M-ST-T	1-port RS-232/422/485 device server with 1 100BaseF(X) multi-mode fiber port (ST connectors), -40 to 75°C operating temperature	€ 824,00	12~16W
NPort IA-5150-S-SC	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), 0 to 55°C operating temperature	€ 661,00	4~8W
NPort IA-5150-S-SC-T	1-port RS-232/422/485 device server with 1 100BaseF(X) single-mode fiber port (SC connectors), -40 to 75°C operating temperature	€ 940,00	4~8W
NPort IA-5150-T	1-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	€ 561,00	4~8W
NPort IA-5250	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), 0 to 55°C operating temperature	€ 465,00	2~4W
NPort IA5250A	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	€ 507,00	2~4W
NPort IA5250AI	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation	€ 720,00	2~4W
NPort IA5250A-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, 0 to 60°C operating temperature	€ 583,00	8~12W
NPort IA5250AI-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, 0 to 60°C operating temperature	€ 735,00	8~12W
NPort IA5250AI-T	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation	€ 891,00	2~4W
NPort IA5250AI-T-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 2 kV isolation, IECEX, -40 to 75°C operating temperature	€ 1.006,00	12~16W
NPort IA5250A-T	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	€ 627,00	4~8W
NPort IA5250A-T-IEEX	2-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, IECEX, -40 to 75°C operating temperature	€ 727,00	12~16W
NPort IA-5250I	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, 0 to 55°C operating temperature	€ 630,00	4~8W
NPort IA-5250I-T	2-port RS-232/422/485 device server with 2 100BaseT(X) ports (RJ45 connectors, single IP), 2 KV optical isolation, -40 to 75°C operating temperature	€ 807,00	12~16W
NPort IA-5250-T	2-port RS-232/422/485 device server with 2 10/100BaseT(X) ports (RJ45 connectors, single IP), -40 to 75°C operating temperature	€ 621,00	4~8W
NPort IA5450A	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature	€ 855,00	2~4W
NPort IA5450AI	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, 0 to 60°C operating temperature, 2 kV isolation protection	€ 1.205,00	2~4W
NPort IA5450AI-T	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature, 2 kV isolation protection	€ 1.519,00	2~4W
NPort IA5450A-T	4-port RS-232/422/485 industrial automation device server with serial/LAN/power surge protection, 2 10/100BaseT(X) ports with single IP, -40 to 75°C operating temperature	€ 1.066,00	2~4W
NPort P5150A	1-port RS-232/422/485 PoE device server, 0 to 60°C operating temperature	€ 389,00	2~4W
NPort P5150A-T	1-port RS-232/422/485 PoE device server, -40 to 75°C operating temperature	€ 487,00	4~8W
NPort S8455I	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, 0 to 60°C operating temperature	€ 1.645,00	8~12W

NPort S8455I-MM-SC	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	€ 2.080,00	4~8W
NPort S8455I-MM-SC-T	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	€ 2.265,00	4~8W
NPort S8455I-SS-SC	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, 0 to 60°C operating temperature	€ 2.517,00	4~8W
NPort S8455I-SS-SC-T	4 RS-232/422/485 ports, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connector, 15 KV ESD, 12 to 48 VDC, -40 to 75°C operating temperature	€ 2.907,00	4~8W
NPort S8455I-T	4 RS-232/422/485 ports, 5 10/100BaseT(X) ports, 12 to 48 VDC, 2 kV isolation protection, -40 to 75°C operating temperature	€ 2.032,00	4~8W
NPort S9450I-2M-SC-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	€ 3.016,00	8~12W
NPort S9450I-2M-SC-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	€ 3.016,00	8~12W
NPort S9450I-2M-ST-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	€ 3.016,00	4~8W
NPort S9450I-2M-ST-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M multi-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	€ 3.016,00	8~12W
NPort S9450I-2S-SC-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	€ 3.612,00	8~12W
NPort S9450I-2S-SC-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with SC connectors, 24/48 VDC, -40 to 85°C operating temperature	€ 3.612,00	8~12W
NPort S9450I-2S-ST-HV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	€ 3.612,00	8~12W
NPort S9450I-2S-ST-WV-T	4-port RS-232/422/485 rugged device server, 3 10/100BaseT(X) ports, 2 100M single-mode fiber ports with ST connectors, 24/48 VDC, -40 to 85°C operating temperature	€ 3.612,00	8~12W
NPort S9450I-HV-T	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature	€ 2.253,00	8~12W
NPort S9450I-WV-T	4-port RS-232/422/485 rugged device server, 5 10/100BaseT(X) ports, 24/48 VDC, -40 to 85°C operating temperature	€ 2.253,00	8~12W
NPort S9650I-16-2HV-E-T	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	€ 4.674,00	4~8W
NPort S9650I-16-2HV-MSC	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	€ 5.160,00	8~12W
NPort S9650I-16-2HV-SSC	16-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	€ 6.068,00	8~12W
NPort S9650I-16B-2HV-IRIG	16-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	€ 5.566,00	8~12W
NPort S9650I-16F-2HV-E-T	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	€ 5.082,00	8~12W
NPort S9650I-16F-2HV-MS	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector	€ 5.566,00	8~12W
NPort S9650I-16F-2HV-SS	16-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector	€ 6.551,00	8~12W
NPort S9650I-8-2HV-E-T	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	€ 3.940,00	8~12W
NPort S9650I-8-2HV-MSC	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector fiber module	€ 4.346,00	8~12W
NPort S9650I-8-2HV-SSC	8-port RS-232/422/485 rugged device server, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector fiber module	€ 5.236,00	8~12W
NPort S9650I-8B-2HV-IRIG	8-port RS-232/422/485 rugged device server with IRIG-B signal output on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with IRIG-B BNC module	€ 4.605,00	8~12W
NPort S9650I-8F-2HV-E-T	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet RJ45 module	€ 4.253,00	8~12W
NPort S9650I-8F-2HV-MSC	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet multi-mode SC connector	€ 4.752,00	8~12W
NPort S9650I-8F-2HV-SSC	8-port RS-232/422/485 rugged device server with multi-mode ST connectors on the serial ports, 2 10/100BaseT(X) ports with IEEE 1588v2 support, 88 to 300 VDC or 85 to 264 VAC, -40 to 85°C operating temperature, with 2-port Ethernet single-mode SC connector	€ 5.414,00	8~12W
NPort W2150A-W4-EU	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug, 12 to 48 VDC, 0 to 55°C operating temperature	€ 476,00	4~8W
NPort W2150A-W4-T-EU	1-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	€ 735,00	12~16W

NPort W2250A-W4-EU	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, EU plug. 12 to 48 VDC, 0 to 55°C operating temperature	€ 583,00	4~8W
NPort W2250A-W4-T-EU	2-port RS-232/422/485 wireless device server with 802.11a/b/g/n WLAN EU band, 12 to 48 VDC, -40 to 75°C operating temperature	€ 813,00	8~12W
OBU-102-SS-LC	2-channel optical fiber bypass unit with 4 single-mode ports, LC, -20 to 70°C operating temperature	€ 1.873,00	8~12W
OBU-102-SS-SC	2-channel optical fiber bypass unit with 4 single-mode ports, SC, -20 to 70°C operating temperature	€ 1.873,00	8~12W
OBU-102-SS-ST	2-channel optical fiber bypass unit with 4 single-mode ports, ST, -20 to 70°C operating temperature	€ 1.873,00	8~12W
OnCell 3120-LTE-1-AU	Industrial LTE Cat. 1 cellular gateway, B3/B5/B8/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	€ 891,00	8~12W
OnCell 3120-LTE-1-AU-T	Industrial LTE Cat. 1 cellular gateway, B3/B5/B8/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 956,00	12~16W
OnCell 3120-LTE-1-EU	Industrial LTE Cat. 1 cellular gateway, B1/B3/B8/B20/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	€ 891,00	4~8W
OnCell 3120-LTE-1-EU-T	Industrial LTE Cat. 1 cellular gateway, B1/B3/B8/B20/B28, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 956,00	4~8W
OnCell 3120-LTE-1-US	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/14/B66/B71, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, 0 to 55°C operating temperature	€ 891,00	8~12W
OnCell 3120-LTE-1-US-T	Industrial LTE Cat. 1 cellular gateway, B2/B4/B5/B12/B13/14/B66/B71, 1 RS232/422/485 serial port, 2 10/100BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 956,00	4~8W
OnCell G4302-LTE4-AU	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	€ 1.711,00	4~8W
OnCell G4302-LTE4-AU-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B5/B7/B8/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 1.845,00	4~8W
OnCell G4302-LTE4-EU	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	€ 1.711,00	2~4W
OnCell G4302-LTE4-EU-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B7/B8/B20/B28, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 1.845,00	2~4W
OnCell G4302-LTE4-JP	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	€ 1.711,00	8~12W
OnCell G4302-LTE4-JP-T	Industrial LTE Cat. 4 cellular secure router, B1/B3/B8/B11/B18/B19/B21, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 1.845,00	12~16W
OnCell G4302-LTE4-US	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -10 to 55°C operating temperature	€ 1.711,00	4~8W
OnCell G4302-LTE4-US-T	Industrial LTE Cat. 4 cellular secure router, B2/B4/B5/B12/B13/B14/B17/B66, 2 10/100/1000BaseT(X) RJ45 ports, -30 to 70°C operating temperature	€ 1.845,00	4~8W
OPT 8A	M62 to 8 x DB25 female connection box with DB62 male to DB62 female serial cable	€ 140,00	4~8W
OPT 8A+	VHDCI 68 to 8 x DB25 female connection box	€ 146,00	4~8W
OPT 8B	M62 to 8 x DB25 male connection box with DB62 male to DB62 female cable, 1.5 m	€ 140,00	4~8W
OPT 8B+	VHDCI 68 to 8 x DB25 male connection box	€ 146,00	4~8W
OPT 8S	M62 to 8 x DB25 female connection box with surge protection and a DB62 male to DB62 male cable, 1.5 m	€ 298,00	8~12W
OPT 8S+	VHDCI 68 to 8 x DB25 female connection box with surge protection	€ 298,00	8~12W
OPT8-M9	M62 to 8 x DB9 male connection box, DB62 male to DB62 female cable, 1.5 m	€ 152,00	4~8W
OPT8-M9+	VHDCI 68 to 8 x DB9 male connection box	€ 179,00	2~4W
OPT8-RJ45	M62 to 8 x RJ45 (8-pin) connection box, 30 cm	€ 135,00	8~12W
OPT8-RJ45+	VHDCI 68 to 8 x RJ45 (8-pin) connection box	€ 214,00	4~8W
PK-DC2DOF	Pole mounting kit	€ 60,00	12~14W
PK-DC2DOF-02	PK-DC2DOF-02	€ 68,00	4~8W
Plate-1	Chassis converter bracket accessory package, 9 brackets, 9 screws (FMS M3 X 6 mm)	€ 120,00	4~8W
PM-7500-2GTXSFP	Gigabit Ethernet module with 2 100/1000BaseSFP slots or 2 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 354,00	8~12W
PM-7500-2MSC	Fast Ethernet module with 2 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 517,00	8~12W
PM-7500-2MST	Fast Ethernet module with 2 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 517,00	8~12W
PM-7500-2SSC	Fast Ethernet module with 2 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 776,00	8~12W
PM-7500-4GTXSFP	Gigabit Ethernet module with 4 100/1000BaseSFP slots or 4 100/1000BaseT(X) ports, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 705,00	4~8W
PM-7500-4MSC	Fast Ethernet module with 4 100BaseFX multi-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 892,00	8~12W
PM-7500-4MST	Fast Ethernet module with 4 100BaseFX multi-mode ports with ST connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 892,00	8~12W
PM-7500-4SSC	Fast Ethernet module with 4 100BaseFX single-mode ports with SC connectors, compliant with IEC 61850-3, -40 to 85°C operating temperature	€ 1.456,00	8~12W
POS-104UL w/o Cable	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature, without cable	€ 174,00	8~12W
POS-104UL-DB9M	4-port RS-232 low-profile Universal PCI board with serial port power, 0 to 55°C operating temperature (DB9 male cable included)	€ 190,00	8~12W
POS-104UL-T	4-port RS-232 low-profile Universal PCI board with serial port power, -40 to 85°C operating temperature	€ 220,00	8~12W
PT-508-MM-LC-24	IEC 61850-3 managed DIN-Rail Ethernet switch, with 6 10/100BaseT(X) ports, and 2 100BaseFX multi-mode ports with LC connectors, 1 isolated power supply (24 VDC), -40 to 85°C operating temperature	€ 1.862,00	4~8W

PTC-101-S-LC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with L connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	€ 1.096,00	4~8W
PTC-101-S-LC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with LC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	€ 1.096,00	4~8W
PTC-101-S-SC-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	€ 1.096,00	8~12W
PTC-101-S-SC-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with SC connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	€ 1.096,00	12~16W
PTC-101-S-ST-HV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating temperature	€ 1.096,00	8~12W
PTC-101-S-ST-LV	Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode with ST connector, dual redundant power inputs (20 to 70 VDC), -40 to 85°C operating temperature	€ 1.096,00	12~16W
PT-G503-PHR-PTP-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85°C operating	€ 3.377,00	4~8W
PT-G503-PHR-PTP-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed redundancy box, with 3 10/100/1000BaseT(X) ports or 100/1000Base SFP ports, 1 10/100/1000BaseT(X) Ethernet console port, 1 isolated dual power supply (24/48 VDC), -40 to 85°C operating temperature	€ 3.913,00	4~8W
PT-G510-4GTX4GSFP-PHR	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	€ 3.754,00	12~16W
PT-G510-4GTX4GSFP-PHR	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G510-4GTX4GSFP-PHR	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	€ 3.754,00	12~16W
PT-G510-4GTX4GSFP-PHR	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 4 100/1000BaseT(X) ports, 6 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G510-8GSFP-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	€ 3.754,00	12~16W
PT-G510-8GSFP-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G510-8GSFP-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	€ 3.754,00	12~16W
PT-G510-8GSFP-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 10 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G510-8GTX-PHR-HV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature	€ 3.754,00	8~12W
PT-G510-8GTX-PHR-HV-C	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G510-8GTX-PHR-WV	IEC 61850-3 and IEC 62439-3 full Gigabit managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature	€ 3.754,00	8~12W
PT-G510-8GTX-PHR-WV-C	IEC 61850-3 and IEC 62439-3 full Gigabit Managed Ethernet switch with 8 100/1000BaseT(X) ports, 2 100/1000Base SFP ports, isolated dual power supply (24/48 VDC), -40 to 75°C operating temperature, conformal coating	€ 4.727,00	12~16W
PT-G7728	Layer 2 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	€ 4.334,00	2~4W
PT-G7828	Layer 3 modular managed Ethernet switch with 2 100/1000BaseSFP and 2 10/100/1000BaseT(X), 6 slots for Ethernet modules and 2 slots for power modules, for a maximum of 28G ports total	€ 5.233,00	4~8W
PWC-C13AU-3B-183	Power cord with AU plug, 1.83 m	€ 11,00	4~8W
PWC-C13CN-3B-183	Power cord with three-prong CN plug, 1.83 m	€ 14,00	56~60W
PWC-C13EU-3B-183	Power cord with EU/KR plug, 1.83 m	€ 11,00	10~12W
PWC-C13JP-3B-183	Power cord with JP plug plug, 7A/125V, 1.83 m	€ 14,00	4~8W
PWC-C13UK-3B-183	Power cord with UK plug, 1.83 m	€ 18,00	4~8W
PWC-C13US-3B-183	Power cord with US plug, 1.83 m	€ 11,00	4~8W
PWC-C15CN-3B-183	C15 power cord with CN plug, 1.83 m	€ 27,00	10~12W
PWC-C15EU-3B-183	C15 power cord with EU plug, 1.83 m	€ 27,00	10~12W
PWC-C15US-3B-183	C15 power cord with US plug, 1.83 m	€ 27,00	4~8W
PWR-100-LV	Power module for the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, 9.6 to 60 VDC operating voltage	€ 428,00	4~8W
PWR-101-LV-BP-I	Power module for PoE models in the EDS-4000/G4000 Series with 48 VDC redundant dual inputs, power isolation, 44 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	€ 571,00	4~8W
PWR-103-LV-VB-I	Power module for PoE models in the EDS-4000/G4000 Series with 12/24/48 VDC redundant dual inputs, power isolation, 12 to 57 VDC operating voltage (>52 VDC for PoE+ output recommended)	€ 999,00	4~8W
PWR-105-HV-I	Power module for the EDS-4000/G4000 Series with 110/220 VDC/VAC single input, power isolation, 88 to 300 VDC or 85 to 264 VAC operating voltage	€ 713,00	4~8W
PWR-12050-AU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-AU-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-CN-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	€ 41,00	20~24W

PWR-12050-CN-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-EU-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-EU-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-IN-S2	PWR-12050-IN-S2	€ 41,00	20~24W
PWR-12050-KR-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-KR-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-UK-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-UK-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	€ 41,00	16~20W
PWR-12050-USJP-S1	Locking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12050-USJP-S2	Unlocking barrel plug, 12 VDC, 0.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	€ 41,00	20~24W
PWR-12150-AU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, -40 to 75°C operating temperature	€ 51,00	28~32W
PWR-12150-CN-S2	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, China (CN) plug, 0 to 40°C operating temperature	€ 31,00	
PWR-12150-CN-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, -40 to 75°C operating temperature	€ 51,00	28~32W
PWR-12150-EU-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, -40 to 75°C operating temperature	€ 51,00	28~32W
PWR-12150-IN-SA-T	PWR-12150-IN-SA-T	€ 52,00	28~32W
PWR-12150-UK-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, -40 to 75°C operating temperature	€ 51,00	28~32W
PWR-12150-USJP-SA-T	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, -40 to 75°C operating temperature	€ 52,00	28~32W
PWR-12150-WPAU-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPAU-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPCN-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPCN-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPEU-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPEU-S4	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPIN-S2	PWR-12150-WPIN-S2	€ 41,00	28~32W
PWR-12150-WPIN-S4	PWR-12150-WPIN-S4	€ 41,00	28~32W
PWR-12150-WPKR-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, KR plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPUK-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPUK-S4	Locking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPUSJP-S2	Unlocking barrel plug, 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12150-WPUSJP-S4	Locking barrel plug with 12 VDC, 1.5 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	€ 41,00	24~28W
PWR-12300-WPAU-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, AU plug, 0 to 40°C operating temperature	€ 73,00	24~28W
PWR-12300-WPCN-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, CN plug, 0 to 40°C operating temperature	€ 73,00	24~28W
PWR-12300-WPEU-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, EU plug, 0 to 40°C operating temperature	€ 73,00	24~28W
PWR-12300-WPUK-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, UK plug, 0 to 40°C operating temperature	€ 73,00	24~28W
PWR-12300-WPUSJP-S2	Locking barrel plug with 12 VDC, 3 A, 100 to 240 VAC, US/JP plug, 0 to 40°C operating temperature	€ 73,00	24~28W
PWR-12500-DT-S1	PWR-12500-DT-S1	€ 59,00	32~36W
PWR-190-AC	110 to 240 VAC power supply for the TRC-190-AC	€ 303,00	4~8W
PWR-190-DC-48	36 to 53 VDC power supply for the TRC-190-DC-48	€ 547,00	8~12W
PWR-2190-AC	110 to 240 VAC power supply for the TRC-2190-AC	€ 315,00	8~12W
PWR-2190-DC-48V	36 to 53 VDC power supply for the TRC-2190-DC-48	€ 563,00	8~12W
PWR-24250-DT-S1	Desktop power supply (requires power cord), 24 VDC, 2.5 A, 100 to 240 VAC, 0 to 40°C operating temperature	€ 84,00	32~36W
PWR-300-HVA-IF	Isolated power supply module (110/220 VAC/VDC) with system power input, AC power inlet, intake fan	€ 1.060,00	24~28W
PWR-G7000A-AC	Power supply module (85 to 264 VAC) for ICS-G7748A/G7750A/G7752A/G7848A/G7850A/G7852A Series, -10 to 60°C operating temperature	€ 2.830,00	8~12W
PWR-HV-NP	Power supply module (110/220 VAC/VDC) with system power input, relay	€ 839,00	2~4W
PWR-HV-P48	Power supply module (110/220 VAC/VDC) with system power input, relay, PoE power input	€ 970,00	4~8W
PWR-HV-P48-A	110/220 VAC/VDC power supply module with system power, relay, PoE power input, advanced heat sink	€ 1.112,00	8~12W
PWR-LV-NP	Power supply module (24/48 VDC) with system power input, relay	€ 839,00	4~8W
PWR-LV-P48	Power supply module (24/48 VDC) with system power input, relay, PoE power input	€ 970,00	4~8W
PWR-LV-P48-A	24/48 VDC power supply module with system power, relay, PoE power input, advanced heat sink	€ 1.112,00	8~12W
PWR-Plug-AU-02	AU plug for the PWR-12150-WPAU and the PWR-12300-WPAU	€ 6,00	8~10W
PWR-Plug-AU-03	AU plug for PWR-12300-WPAU	€ 6,00	10~12W
PWR-Plug-CN-02	CN plug for PWR-12150-WPCN and PWR-12300-WPCN	€ 4,00	10~12W
PWR-Plug-EU-02	EU plug for PWR-12150-WPEU and PWR-12300-WPEU	€ 6,00	8~10W
PWR-Plug-IN-02	PWR-Plug-IN-02	€ 6,00	8~10W
PWR-Plug-KR-02	KR plug for the PWR-12150-WPKR and the PWR-12300-WPKR	€ 6,00	8~10W
PWR-Plug-UK-02	UK plug for PWR-12150-WPUK and PWR-12300-WPUK	€ 6,00	8~10W
PWR-Plug-USJP-02	US/JP plug for PWR-12150-WPUSJP and PWR-12300-WPUSJP	€ 4,00	8~10W
PWS-24W24V-OF-01	Open frame power supply	€ 47,00	44~48W
RK-3U-02	Rack-mounting kit with 4 L-shaped plates for the MDS-G4000 and MDS-G4000-4XGS Series	€ 693,00	10~12W
RK-4U	19-inch rack-mounting kit	€ 233,00	10~12W
RKP-A110-E2-2L4C-T	Rackmount 1U computer with Intel Atom® x6211E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.124,00	4~8W

RKP-A110-E2-8C-T	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.997,00	4~8W
RKP-A110-E2-8L-T	Rackmount 1U computer with Intel Atom® x6211E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.472,00	4~8W
RKP-A110-E2-T	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.711,00	4~8W
RKP-A110-E2-T-Win10	Rackmount 1U computer with Intel Atom® x6211E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.409,00	4~8W
RKP-A110-E4-2L4C-T	Rackmount 1U computer with Intel Atom® x6425E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.298,00	4~8W
RKP-A110-E4-8C-T	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.171,00	4~8W
RKP-A110-E4-8L-T	Rackmount 1U computer with Intel Atom® x6425E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.504,00	4~8W
RKP-A110-E4-T	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 2.807,00	4~8W
RKP-A110-E4-T-Win10	Rackmount 1U computer with Intel Atom® x6425E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 3.536,00	4~8W
RKP-C110-C1-2L4C-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.671,00	4~8W
RKP-C110-C1-8C-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.472,00	4~8W
RKP-C110-C1-8L-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.027,00	4~8W
RKP-C110-C1-T	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 3.108,00	4~8W
RKP-C110-C1-T-Win10	Rackmount 1U computer with Intel® Celeron® 6305E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 4.059,00	4~8W
RKP-C110-C5-2L4C-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.947,00	4~8W
RKP-C110-C5-8C-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.836,00	4~8W
RKP-C110-C5-8L-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.311,00	4~8W
RKP-C110-C5-T	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 4.344,00	4~8W
RKP-C110-C5-T-Win10	Rackmount 1U computer with Intel® Core™ i5-145G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 5.343,00	4~8W
RKP-C110-C7-2L4C-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 6 LAN ports, 6 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.597,00	4~8W
RKP-C110-C7-8C-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 10 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.518,00	4~8W
RKP-C110-C7-8L-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 12 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 6.041,00	4~8W
RKP-C110-C7-T	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, -30 to 60°C operating temperature	€ 5.058,00	4~8W
RKP-C110-C7-T-Win10	Rackmount 1U computer with Intel® Core™ i7-185G7E processor, 4 LAN ports, 2 serial ports, 8 DIs, 8 DOs, 3 USB 3.0 ports, 1 VGA port, 1 HDMI port, 2 SSD slots, 12/24 VDC power input, Windows 10 LTSC 2021 preinstalled, -30 to 60°C operating temperature	€ 6.072,00	4~8W
RKS-G4028-4GS-2HV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 4.639,00	4~8W
RKS-G4028-4GS-2LV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 5.472,00	12~16W
RKS-G4028-4GS-HV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 4.462,00	4~8W

RKS-G4028-4GS-LV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 4.878,00	12~16W
RKS-G4028-4GT-2HV-T	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 4.493,00	4~8W
RKS-G4028-4GT-2LV-T	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 5.318,00	12~16W
RKS-G4028-4GT-HV-T	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 4.315,00	4~8W
RKS-G4028-4GT-LV-T	Modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 4.732,00	12~16W
RKS-G4028-L3-4GS-2HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 7.008,00	12~16W
RKS-G4028-L3-4GS-2LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 7.835,00	12~16W
RKS-G4028-L3-4GS-HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 6.831,00	12~16W
RKS-G4028-L3-4GS-LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 7.240,00	12~16W
RKS-G4028-L3-4GT-2HV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 6.862,00	12~16W
RKS-G4028-L3-4GT-2LV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 7.688,00	12~16W
RKS-G4028-L3-4GT-HV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 6.685,00	12~16W
RKS-G4028-L3-4GT-LV-T	Layer 3 modular managed Ethernet switch with 4 10/100/1000BaseT(X) ports, 3 slots for Ethernet modules, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 7.094,00	12~16W
RKS-G4028-L3-PoE-4GS-2HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 9.371,00	12~16W
RKS-G4028-L3-PoE-4GS-2LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 10.197,00	12~16W
RKS-G4028-L3-PoE-4GS-HV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 9.194,00	12~16W
RKS-G4028-L3-PoE-4GS-LV-T	Layer 3 modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 9.603,00	12~16W
RKS-G4028-PoE-4GS-2HV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 7.008,00	12~16W
RKS-G4028-PoE-4GS-2LV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 2 isolated power supplies (24/48 VDC), -40 to 75°C operating temperature	€ 7.835,00	12~16W
RKS-G4028-PoE-4GS-HV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (110/220 VAC/VDC), -40 to 75°C operating temperature	€ 6.831,00	12~16W
RKS-G4028-PoE-4GS-LV-T	Modular managed Ethernet switch with 4 100/1000BaseSFP ports, 3 slots for Ethernet modules, PoE Ethernet module supported, 1 isolated power supply (24/48 VDC), -40 to 75°C operating temperature	€ 7.240,00	12~16W
RK-UP1600-G2	Rack mounting kits for UPort 1400/1600-G2	€ 93,00	8~10W
RM-G4000-2MSC4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	€ 865,00	8~12W
RM-G4000-2MST4TX	Fast Ethernet module with 2 multi-mode 100BaseFX ports with ST connectors, 4 10/100BaseT(X) ports	€ 935,00	8~12W
RM-G4000-2SSC4TX	Fast Ethernet module with 2 single-mode 100BaseFX ports with SC connectors, 4 10/100BaseT(X) ports	€ 1.374,00	8~12W
RM-G4000-4MSC2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	€ 1.320,00	8~12W
RM-G4000-4MST2TX	Fast Ethernet module with 4 multi-mode 100BaseFX ports with ST connectors, 2 10/100BaseT(X) ports	€ 1.467,00	8~12W
RM-G4000-4SSC2TX	Fast Ethernet module with 4 single-mode 100BaseFX ports with SC connectors, 2 10/100BaseT(X) ports	€ 2.341,00	8~12W
RM-G4000-6MSC	Fast Ethernet module with 6 multi-mode 100BaseFX ports with SC connectors	€ 1.778,00	8~12W
RM-G4000-6MST	Fast Ethernet module with 6 multi-mode 100BaseFX ports with ST connectors	€ 1.994,00	8~12W
RM-G4000-6SSC	Fast Ethernet module with 6 single-mode 100BaseFX ports with SC connectors	€ 3.305,00	8~12W
RM-G4000-8GPoE	Gigabit Ethernet module with 8 10/100/1000BaseT(X) IEEE 802.3bt PoE ports	€ 1.637,00	4~8W
RM-G4000-8GSFP	Gigabit Ethernet module with 8 100/1000BaseSFP slots	€ 1.707,00	4~8W
RM-G4000-8GTX	Gigabit Ethernet module with 8 10/100/1000BaseT(X) ports	€ 1.089,00	4~8W
RM-G4000-8PoE	Fast Ethernet module with 8 10/100BaseT(X) IEEE 802.3bt PoE ports	€ 1.089,00	8~12W
RM-G4000-8SFP	Fast Ethernet module with 8 100BaseSFP slots	€ 858,00	4~8W
RM-G4000-8TX	Fast Ethernet module with 8 10/100BaseT(X) ports	€ 548,00	4~8W
S-Cybersecurity_Network	S-Cybersecurity_Network Inspection	€ 4.018,00	
SDS-3006	Compact industrial smart Ethernet switch with 6 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 450,00	8~12W

SDS-3006-2GTXSFP	Compact industrial smart Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 772,00	8~12W
SDS-3006-2GTXSFP-T	Compact industrial smart Ethernet switch with 4 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 886,00	8~12W
SDS-3006-4PoE-2GTXSFP	Compact industrial smart Ethernet switch with 4 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.100,00	
SDS-3006-4PoE-2GTXSFP	Compact industrial smart Ethernet switch with 4 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.215,00	
SDS-3006-T	Compact industrial smart Ethernet switch with 6 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 564,00	8~12W
SDS-3008	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 564,00	2~4W
SDS-3008 Rackmount Kit	1U-high 19" rack mounting kit for SDS-3008	€ 221,00	4~8W
SDS-3008-T	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 624,00	4~8W
SDS-3010-2GTXSFP	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 879,00	8~12W
SDS-3010-2GTXSFP-T	Compact industrial smart Ethernet switch with 8 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 993,00	8~12W
SDS-3010-8PoE-2GTXSFP	Compact industrial smart Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.215,00	
SDS-3010-8PoE-2GTXSFP	Compact industrial smart Ethernet switch with 8 PoE/PoE+ 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.329,00	
SDS-3016	Compact industrial smart Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 899,00	8~12W
SDS-3016-2GSFP	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 993,00	4~8W
SDS-3016-2GSFP-T	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.047,00	4~8W
SDS-3016-2GTX	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 993,00	2~4W
SDS-3016-2GTX-T	Compact industrial smart Ethernet switch with 14 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.047,00	4~8W
SDS-3016-T	Compact industrial smart Ethernet switch with 16 10/100BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.013,00	8~12W
SDS-G3006	Compact industrial full Gigabit smart Ethernet switch with 6 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 591,00	4~8W
SDS-G3006-2GTXSFP	Compact industrial smart Ethernet switch with 4 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 866,00	8~12W
SDS-G3006-2GTXSFP-T	Compact industrial smart Ethernet switch with 4 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 980,00	8~12W
SDS-G3006-4PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 4 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.201,00	
SDS-G3006-4PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 4 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.315,00	
SDS-G3006-T	Compact industrial full Gigabit smart Ethernet switch with 6 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 705,00	4~8W
SDS-G3008	Compact industrial full Gigabit smart Ethernet switch with 8 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 705,00	4~8W
SDS-G3008-T	Compact industrial full Gigabit smart Ethernet switch with 8 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 819,00	4~8W
SDS-G3010-2GTXSFP	Compact industrial smart Ethernet switch with 8 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 973,00	8~12W
SDS-G3010-2GTXSFP-T	Compact industrial smart Ethernet switch with 8 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.094,00	8~12W
SDS-G3010-8PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 8 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.322,00	
SDS-G3010-8PoE-2GTXSFP	Compact industrial full Gigabit smart Ethernet switch with 8 PoE/PoE+ 10/100/1000BaseT(X) ports, 2 10/100/1000BaseT(X) or 100/1000BaseSFP combo ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.436,00	
SDS-G3016	Compact industrial full Gigabit smart Ethernet switch with 16 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.094,00	8~12W

SDS-G3016-2GSFP	Compact industrial full Gigabit smart Ethernet switch with 14 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -10 to 60°C operating temperature	€ 1.241,00	8~12W
SDS-G3016-2GSFP-T	Compact industrial full Gigabit smart Ethernet switch with 14 10/100/1000BaseT(X) ports, 2 100/1000BaseSFP ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.349,00	8~12W
SDS-G3016-T	Compact industrial full Gigabit smart Ethernet switch with 16 10/100/1000BaseT(X) ports, dual 12/24/48 VDC power inputs, -40 to 75°C operating temperature	€ 1.201,00	8~12W
S-Factory Acceptance Test		€ 4.018,00	
SFP-10GERLC-T	SFP+ module with 1 10GBase-ER port, LC connector for 40 km transmission, -40 to 85°C operating temperature	€ 10.527,00	8~12W
SFP-10GLRLC-T	SFP+ module with 1 10GBase-LR port, LC connector for 10 km transmission, -40 to 85°C operating temperature	€ 3.221,00	4~8W
SFP-10GSRLC-T	SFP+ module with 1 10GBase-SR port, LC connector for 33m/82m/300m/400m transmission, -40 to 85°C operating temperature	€ 1.975,00	4~8W
SFP-10GZRLC-T	SFP+ module with 1 10GBase-ZR port, LC connector for 80 km transmission, -40 to 85°C operating temperature	€ 13.964,00	8~12W
SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature	€ 1.423,00	4~8W
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode, LC connector for 2/4 km transmission, -40 to 85°C operating temperature	€ 171,00	2~4W
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature	€ 386,00	2~4W
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	€ 448,00	4~8W
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	€ 549,00	4~8W
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	€ 971,00	4~8W
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	€ 1.065,00	4~8W
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	€ 805,00	8~12W
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	€ 892,00	8~12W
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	€ 1.673,00	8~12W
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	€ 1.752,00	8~12W
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature	€ 2.084,00	8~12W
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature	€ 2.175,00	8~12W
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature	€ 2.286,00	8~12W
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature	€ 2.377,00	8~12W
SFP-1GEZXC	SFP module with 1 1000BaseEZXC port with LC connector for 110 km transmission, 0 to 60°C operating temperature	€ 2.645,00	8~12W
SFP-1GEZXC-120	SFP module with 1 1000BaseEZXC port with LC connector for 120 km transmission, 0 to 60°C operating temperature	€ 3.173,00	8~12W
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature	€ 462,00	2~4W
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature	€ 524,00	2~4W
SFP-1GLHXC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature	€ 1.112,00	4~8W
SFP-1GLHXC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature	€ 1.191,00	4~8W
SFP-1GLSXC	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature	€ 389,00	2~4W
SFP-1GLSXC-T	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature	€ 475,00	2~4W
SFP-1GLXC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature	€ 361,00	2~4W
SFP-1GLXC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature	€ 425,00	2~4W
SFP-1GSXC	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature	€ 204,00	2~4W
SFP-1GSXC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature	€ 277,00	2~4W
SFP-1GTXRJ45-T	SFP module with 1 1000BaseT port with RJ45 connector for 100 m transmission, -40 to 75°C operating temperature	€ 448,00	2~4W
SFP-1GZXC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature	€ 1.862,00	4~8W
SFP-1GZXC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature	€ 1.923,00	4~8W
SFP-2.5GLSLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 20 km transmission, -40 to 85 °C operating temperature	€ 933,00	10~12W

SFP-2.5GMLC-T	SFP module with 1 2.5GBaseFX port with LC connector, multi-mode, for 170, 200, 550, 600 m transmission, -40 to 85 °C operating temperature	€ 376,00	10~12W
SFP-2.5GSLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 5 km transmission, -40 to 85 °C operating temperature	€ 607,00	10~12W
SFP-2.5GSLHLC-T	SFP module with 1 2.5GBaseFX port with LC connector, single-mode, for 45 km transmission, -40 to 85 °C operating temperature	€ 2.784,00	10~12W
S-IIoT-Consulting	Order only against quotation! Engineering Service for IIoT Consulting. See "S-IIOT-Consulting" outline document for details. Prior customer agreement required. Price for full day service.	€ 4.018,00	
S-IIoT-PoC	Order only against quotation! Two Days workshop with PoC for IIOT . Conditions "S-IIOT-PoC" outline document for details. Price for 2 full days service. UC-8112A or similar included	€ 8.032,00	
S-IIoT-SLA-Level1	Order only against quotation! Support for Moxa Industrial Linux. . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	Err:520	
S-IIoT-SLA-Level2	Order only against quotation! Support for Moxa Industrial Linux and ThingsPro Gateway . Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	Err:520	
S-IIoT-SLA-Level3	Order only against quotation! Support for Moxa Industrial Linux and Things pro Edge (incl. cloud-based device management). Conditions see "S-IIOT-SLA" outline document for details. Price charged per service year.	Err:520	
S-MRC-PoC	Order only against quotation! One Day workshop with PoC for MRC . Conditions"S-MRC-PoC" outline document for details. Price for full day service.	€ 4.018,00	
S-Network Consulting-Ad	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Consulting-Aud	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 4.018,00	
S-Network Consulting-Co	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Consulting-Des	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Consulting-On	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Consulting-Pre	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Consulting-Tes	Order only against quotation! Engineering Service for Network Consulting. See "S-Network Consulting" outline document for details . Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Network Inspection	Order only against quotation! Engineering Service for Network Inspection. See "S-Network Inspection" outline document for details. Prior customer agreement required. Price for full day service.	€ 3.214,00	
S-Onsite Support	Order only against quotation! Engineering Service for Onsite Support. Prior customer agreement required. Travel & accomodation excluded. Price for full day service. See onsite outline document for details.	€ 2.679,00	
SPL-24	PoE splitter with maximum output of 12.95 W at 24 VDC, 0 to 60°C operating temperature	€ 220,00	4~8W
SPL-24-T	PoE splitter with maximum output of 12.95 W at 24 VDC, -40 to 75°C operating temperature	€ 328,00	4~8W
S-Project Management-Ex	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	€ 536,00	
S-Project Management-Pr	Order only against quotation! Project Management Service. See "S-Project Management" outline document for details. Prior customer agreement required. Price charged per service hour.	€ 536,00	
S-Sample Provisioning	Order only against quotation! Samples from MEU stock are loaned to customers for evaluation purpose. Conditions see "S-Sample Provisionning" outline document for details.. Price charged per service week.	Err:520	
S-Technical Support-SLA	Order only against quotation! Technical Support service commitment based on deployed hardware/software after warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price cha	Err:520	
S-Technical Support-SLA	Order only against quotation! Technical Support service commitment based on deployed hardware/software under warranty. Respective Customer declaration and contract required. Conditions see "S-Technical Support-SLA" outline document for details. Price cha	Err:520	
S-Training-IES-Standard-C	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order per participant and day. Provide number of participants in comment field. Classroom training is hosted in Munich.	€ 804,00	
S-Training-IES-Standard-c	Order only against quotation! IES Standard Training. See Training Modules as IES-F1, IES-L2, IES-OM, IES-L3, IES-W1, IES-CS1, IES-CS2. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodati	€ 2.679,00	
S-Training-IIoT-Classroom	Order only against quotation! IIoT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order per participant and day. Provide number of participants in comment field.	€ 1.071,00	
S-Training-IIoT-onsite	Order only against quotation! IIoT Special Training. See Training Modules as embedded computing & edge connectivity, in addition . Order for 4* participants and day. Provide number of participants in comment field and location. Travel & accomodation exclu	€ 4.018,00	
S-Training-Power-classro	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEEE 1588. Order per participant and day. Provide number of participants in comment field. Classroom training in Munich.	€ 1.071,00	
S-Training-Power-onsite	Order only against quotation! Power Special Training. See Training Module for power with PRP, HSR and IEEE 1588. Order for 4* participants and by day. Provide number of participants in comment field and location. Travel & accomodation excluded.	€ 4.018,00	
TAP-213-EU-CT-T	802.11n railway onboard outdoor single radio access point/client, M12, EU band, IP68, -40 to 75°C operating temperature, conformal coating	€ 4.376,00	12~16W
TAP-213-JP-CT-T	802.11n railway onboard outdoor single radio access point/client, M12, JP band, IP68, -40 to 75°C operating temperature, conformal coating	€ 4.376,00	12~16W
TAP-213-US-CT-T	802.11n railway onboard outdoor single radio access point/client, M12, US band, IP68, -40 to 75°C operating temperature, conformal coating	€ 4.376,00	12~16W

TAP-323-EU-CT-T	802.11n railway trackside outdoor dual radio access point, EU band, IP68, -40 to 75°C operating temperature, conformal coating	€ 10.222,00	16~20W
TAP-323-JP-CT-T	802.11n railway trackside outdoor dual radio access point, JP band, IP68, -40 to 75°C operating temperature, conformal coating	€ 10.222,00	16~20W
TAP-323-US-CT-T	802.11n railway trackside outdoor dual radio access point, US band, IP68, -40 to 75°C operating temperature, conformal coating	€ 10.222,00	16~20W
TB-F25	DB25 female DIN-rail wiring terminal	€ 68,00	8~12W
TB-F9	DB9 female DIN-rail wiring terminal	€ 52,00	4~8W
TB-M25	DB25 male DIN-rail wiring terminal	€ 68,00	8~12W
TB-M9	DB9 male DIN-rail wiring terminal	€ 52,00	4~8W
TCC-100	RS-232 to RS-422/485 converter	€ 113,00	2~4W
TCC-100I	RS-232 to RS-422/485 converter with optical isolation	€ 181,00	2~4W
TCC-100I-T	RS-232 to RS-422/485 converter with optical isolation, -40 to 85°C operating temperature	€ 227,00	2~4W
TCC-100-T	RS-232 to RS-422/485 converter, -40 to 85°C operating temperature	€ 148,00	4~8W
TCC-120	RS-422/485 converter/repeater	€ 148,00	4~8W
TCC-120I	RS-422/485 converter/repeater with optical isolation	€ 197,00	2~4W
TCC-80	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and terminal block on the RS-422/485 side	€ 62,00	2~4W
TCC-80-DB9	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection and DB9 male connector on the RS-422/485 side	€ 62,00	2~4W
TCC-80I	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection, terminal block on the RS-422/485 side, and 2.5 kV optical isolation	€ 130,00	2~4W
TCC-80I-DB9	Port-powered RS-232 to RS-422/485 converter with 15 kV serial ESD protection, DB9 male connector on the RS-422/485 side, and 2.5 kV optical isolation	€ 130,00	4~8W
TCC-82	Port-powered RS-232 isolator with 4 kV isolation and 15 kV serial ESD protection	€ 104,00	2~4W
TCF-142-M-SC	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	€ 284,00	2~4W
TCF-142-M-SC-RM	RS-232/422/485 to multi-mode fiber slide-in module converter, SC connector	€ 277,00	4~8W
TCF-142-M-SC-T	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	€ 368,00	4~8W
TCF-142-M-ST	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	€ 284,00	2~4W
TCF-142-M-ST-RM	RS-232/422/485 to multi-mode fiber slide-in module converter, ST connector	€ 277,00	8~12W
TCF-142-M-ST-T	RS-232/422/485 to multi-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	€ 368,00	2~4W
TCF-142-S-SC	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, 0 to 60°C operating temperature	€ 683,00	2~4W
TCF-142-S-SC-RM	RS-232/422/485 to single-mode fiber slide-in module converter, SC connector	€ 583,00	4~8W
TCF-142-S-SC-T	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and SC connector, -40 to 75°C operating temperature	€ 904,00	2~4W
TCF-142-S-ST	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, 0 to 60°C operating temperature	€ 683,00	2~4W
TCF-142-S-ST-RM	RS-232/422/485 to single-mode fiber slide-in module converter, ST connector	€ 583,00	8~12W
TCF-142-S-ST-T	RS-232/422/485 to single-mode optical fiber media converter with fiber ring support and ST connector, -40 to 75°C operating temperature	€ 904,00	4~8W
TCF-90-M-ST	RS-232 to multi-mode ST fiber optic converter, port powered	€ 227,00	2~4W
TCF-90-S-ST	RS-232 to single-mode ST fiber optic converter, port powered	€ 383,00	4~8W
TN-4512A-WV-CT-T	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	€ 3.040,00	12~16W
TN-4512A-WV-T	12 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	€ 2.816,00	12~16W
TN-4516A-12PoE-2GPoE-2	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	€ 8.819,00	12~16W
TN-4516A-12PoE-2GPoE-2	12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	€ 8.163,00	12~16W
TN-4516A-12PoE-2GPoE-2	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75	€ 6.957,00	12~16W
TN-4516A-12PoE-2GPoE-2	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector and bypass relay, 1 (dual input) 24 to 110 VDC power supply, -40 to 75	€ 6.461,00	12~16W
TN-4516A-12PoE-4GPoE-V	Layer 2 managed Ethernet switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	€ 6.929,00	12~16W
TN-4516A-12PoE-4GPoE-V	Layer 2 managed switch with 12 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, 12 PoE 10/100BaseT(X) ports with M12 connector, -40 to 75°C operating temperature	€ 6.415,00	12~16W
TN-4516A-4GTXP-WV-CT	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conform	€ 4.674,00	12~16W
TN-4516A-4GTXP-WV-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, 4 Gigabit Ethernet ports with bypass relay function support, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	€ 4.327,00	12~16W

TN-4516A-4GTX-WV-CT-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24 to 110 VDC), -40 to 75°C operating temperature, conformal coating	€ 4.342,00	12~16W
TN-4516A-4GTX-WV-T	Managed Ethernet switch with 12 10/100BaseT(X) ports, and 4 10/100/1000BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	€ 4.024,00	12~16W
TN-4516A-WV-CT-T	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	€ 4.056,00	12~16W
TN-4516A-WV-T	Layer 2 managed Ethernet switch with 16 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	€ 3.760,00	12~16W
TN-4516B-8G-CT-T	EN 50155 16-port L2 switch including 8 FE ports, 8 Gigabit ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 5.422,00	12~16W
TN-4516B-8P-4G-4GP-CT-T	EN 50155 16-port L2 switch including 8 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 6.535,00	12~16W
TN-4516B-8P-4GP-4GBP-CT-T	EN 50155 16-port L2 switch including 8 FE PoE ports, 4 Gigabit ports with bypass relay, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 6.882,00	12~16W
TN-4516B-CT-T	EN 50155 16-port L2 switch with 16 FE ports, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 4.477,00	12~16W
TN-4520A-16PoE-4GPoE-V	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature, conformal coating	€ 6.775,00	12~16W
TN-4520A-16PoE-4GPoE-V	Layer 2 managed Ethernet switch with 16 PoE 10/100BaseT(X) ports with M12 connector, 4 PoE 100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 70°C operating temperature	€ 6.272,00	12~16W
TN-4520B-12P-4G-4GP-CT-T	EN 50155 20-port L2 switch including 12 FE PoE ports, 4 Gigabit ports, 4 Gigabit PoE ports, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 7.786,00	12~16W
TN-4520B-12P-4GP-4GBP-CT-T	EN 50155 20-port L2 switch including 12 FE PoE ports, 4 Gigabit PoE ports, 4 Gigabit ports with bypass relay, 150 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP42, conformal coating	€ 8.133,00	12~16W
TN-4524A-16PoE-WV-CT-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	€ 6.957,00	12~16W
TN-4524A-16PoE-WV-T	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	€ 6.461,00	12~16W
TN-4528A-16PoE-2GPoE-2	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C op	€ 11.462,00	12~16W
TN-4528A-16PoE-2GPoE-2	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 1000BaseLSX fiber optic ports with Q-ODC® interface, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C op	€ 10.601,00	12~16W
TN-4528A-16PoE-2GPoE-2	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -4	€ 9.597,00	12~16W
TN-4528A-16PoE-2GPoE-2	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 2 PoE 10/100/1000BaseT(X) ports with M12 connector, 2 10/100/1000 BaseT(X) ports with M12 connector with bypass relay, 1 (dual input) 24 to 110 VDC power supply, -4	€ 8.901,00	12~16W
TN-4528A-16PoE-4GPoE-V	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature, conformal coating	€ 9.572,00	12~16W
TN-4528A-16PoE-4GPoE-V	16 PoE 10/100BaseT(X) ports with M12 connector, 8 10/100BaseT(X) ports with M12 connector, 4 PoE 10/100/1000BaseT(X) ports with M12 connector, 1 (dual input) 24 to 110 VDC power supply, -40 to 75°C operating temperature	€ 8.855,00	12~16W
TN-4908-4GPoE-4GTX-WV	Industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 7.897,00	16~20W
TN-4908-4GTX-WV-CT-T	Industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 5.979,00	16~20W
TN-4908-8GTX-WV-CT-T	Industrial secure router with 8 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 7.070,00	16~20W
TN-4908-ETBN-4GPoE-4GTX	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 9.551,00	16~20W
TN-4908-ETBN-4GTX-4GTX	IEC 61375 ETBN industrial secure router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.550,00	16~20W
TN-4908-ETBN-4GTXBP-WV	IEC 61375 ETBN industrial secure router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 7.438,00	16~20W
TN-4908-ETBN-4TXBP-WV	IEC 61375 ETBN industrial secure router with 4 Fast Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 6.298,00	16~20W
TN-4908-ETBN-F-4GPoE-4GTX	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 50 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	€ 9.843,00	16~20W
TN-4908-ETBN-F-4GTX-4GTX	IEC 61375 ETBN industrial secure firewall router with 8 Gigabit Ethernet ports including 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.829,00	16~20W

TN-4908-ETBN-F-4GTXBP	IEC 61375 ETBN industrial secure firewall router with 4 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 7.716,00	16~20W
TN-4908-ETBN-F-4TXBP-W	IEC 61375 ETBN industrial secure firewall router with 4 Fast Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 6.576,00	16~20W
TN-4908-WV-CT-T	Industrial secure router with 8 Fast Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 4.797,00	16~20W
TN-4916-12PoE-4GTX-WV	Industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 7.091,00	12~16W
TN-4916-4GTX-WV-CT-T	Industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 6.646,00	12~16W
TN-4916-8PoE-4GPoE-4GTX	Industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.815,00	16~20W
TN-4916-ETBN-12PoE-4GTX	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.620,00	12~16W
TN-4916-ETBN-4GTXBP-W	IEC 61375 ETBN industrial secure router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.064,00	12~16W
TN-4916-ETBN-8PoE-4GTX	IEC 61375 ETBN industrial secure router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP40, -40 t	€ 10.330,00	16~20W
TN-4916-ETBN-F-12PoE-4GTX	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.898,00	12~16W
TN-4916-ETBN-F-4GTXBP	IEC 61375 ETBN industrial secure firewall router with 12 Fast Ethernet ports, 4 Gigabit Ethernet ports with bypass relay, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature, conformal coating	€ 8.342,00	12~16W
TN-4916-ETBN-F-8PoE-4GTX	IEC 61375 ETBN industrial secure firewall router with 8 Fast Ethernet PoE+ ports, 8 Gigabit Ethernet ports including 4 Gigabit Ethernet PoE+ ports, 4 Gigabit Ethernet ports with bypass relay, total 95 W power budget for PoE+, 24 to 110 VDC power input, IP4	€ 10.636,00	16~20W
TN-5305A-WV-CT-T	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 626,00	12~16W
TN-5305A-WV-T	EN 50155 unmanaged Ethernet switch with 5 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	€ 582,00	12~16W
TN-5308A-8PoE-WV-CT-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 1.710,00	16~20W
TN-5308A-8PoE-WV-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) PoE ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	€ 1.585,00	12~16W
TN-5308A-WV-CT-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 1.231,00	12~16W
TN-5308A-WV-T	EN 50155 unmanaged Ethernet switch with 8 10/100BaseT(X) ports, M12 connector, single power input, 24 to 110 VDC, -40 to 70°C operating temperature	€ 1.140,00	12~16W
TN-5508A-8PoE-WV-CT-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 3.617,00	12~16W
TN-5508A-8PoE-WV-T	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	€ 3.348,00	12~16W
TN-5508A-WV-CT-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connector, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature, conformal coating	€ 2.841,00	12~16W
TN-5508A-WV-T	Managed Ethernet switch with 8 10/100BaseT(X) ports with M12 connectors, dual redundant power inputs (24-110 VDC), -40 to 75°C operating temperature	€ 2.629,00	12~16W
TN-5510A-2GLSX-ODC-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	€ 6.140,00	12~16W
TN-5510A-2GLSX-ODC-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 1000 BaseLSX Q-ODC® ports, 24-110 VDC dual power input, -40 to 75°C operating temperature	€ 5.688,00	12~16W
TN-5510A-2GTXBP-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	€ 3.881,00	12~16W
TN-5510A-2GTXBP-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector with bypass relay function, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	€ 3.596,00	12~16W
TN-5510A-2GTX-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature, conformal coating	€ 3.718,00	12~16W
TN-5510A-2GTX-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) and 2 10/100/1000BaseT(X) ports with M12 connector, 24 to 110 VDC dual power input, -40 to 75°C operating temperature	€ 3.440,00	12~16W
TN-5510A-8PoE-2GLSX-ODC	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 6.486,00	12~16W
TN-5510A-8PoE-2GLSX-ODC	8 10/100BaseT(X) with 802.3at PoE+ ports with M12 connector and 2 GE fiber ports, power input 24 to 110 VDC, -40 to 75°C operating temperature	€ 5.958,00	12~16W
TN-5510A-8PoE-2GTXBP-WV	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 4.788,00	12~16W
TN-5510A-8PoE-2GTXBP-WV	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector with bypass function, power input 24 to 110 VDC, -40 to 75°C operating temperature	€ 4.462,00	12~16W

TN-5510A-8PoE-2GTX-WV	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 4.629,00	12~16W
TN-5510A-8PoE-2GTX-WV	8 10/100BaseT(X) with 802.3at PoE+ and 2 GE ports with M12 connector, power input 24 to 110 VDC, -40 to 75°C operating temperature	€ 4.255,00	12~16W
TN-5516A-8PoE-WV-CT-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 4.954,00	12~16W
TN-5516A-8PoE-WV-T	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 24-110 VDC, -40 to 75°C operating temperature	€ 4.592,00	12~16W
TN-5516A-WV-CT-T	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 3.704,00	12~16W
TN-5516A-WV-T	Layer 2 managed switch with 16 10/100BaseT(X) ports with M12 connector, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	€ 3.426,00	12~16W
TN-5518A-2GTXBP-WV-CT	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 4.545,00	12~16W
TN-5518A-2GTXBP-WV-T	Layer 2 managed gig switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, 2 Gigabit Ethernet ports with bypass relay function, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature	€ 4.207,00	12~16W
TN-5518A-2GTX-WV-CT-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 4.465,00	12~16W
TN-5518A-2GTX-WV-T	Layer 2 managed switch with 16 10/100BaseT(X) ports, 2 10/100/1000BaseT(X) ports with M12 connectors, dual power input, 24-110 VDC, -40 to 75°C operating temperature	€ 4.136,00	12~16W
TN-5518A-8PoE-2GTXBP-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 6.023,00	12~16W
TN-5518A-8PoE-2GTXBP-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors with bypass function, 24 to 110 VDC, -40 to 75°C operating temperature	€ 5.581,00	12~16W
TN-5518A-8PoE-2GTX-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature, conformal coating	€ 5.840,00	12~16W
TN-5518A-8PoE-2GTX-WV	Layer 2 managed Ethernet switch with 8 10/100BaseT(X) ports and 8 802.3at PoE+ M12 connectors, 2 10/100/1000BaseT(X) with M12 connectors, 24 to 110 VDC, -40 to 75°C operating temperature	€ 5.407,00	12~16W
TN-G4516-8GPoE-2XGPoE	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	€ 11.496,00	12~16W
TN-G4516-8GPoE-2XGPoE	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 2 10G Ethernet PoE+ ports, 2 10G Ethernet ports with bypass relay, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	€ 11.139,00	12~16W
TN-G4516-8GPoE-4XGPoE	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, -40 to 70°C operating temperature, IP40, conformal coating	€ 11.622,00	12~16W
TN-G4516-8GPoE-4XGPoE	EN 50155 Layer 2 multi-Gigabit switch with 4 Gigabit Ethernet ports, 8 Gigabit Ethernet PoE+ ports, 4 10G Ethernet PoE+ ports, 120 W PoE power budget, 24 to 110 VDC power input, IP40, -40 to 70°C operating temperature	€ 10.773,00	12~16W
TN-G6512-8GPoE-WV-CT-T	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) with 802.3at PoE+, 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature, conformal coating model	€ 6.959,00	12~16W
TN-G6512-8GPoE-WV-T	Layer 2 Managed Ethernet switch, 8 10/100/1000BaseT(X) ports with 802.3at PoE+ and 4 10/100/1000BaseT(X) M12 connectors, 24 to 110 VDC power input, -40 to 70°C operating temperature	€ 6.441,00	12~16W
TRC-190-AC	Rack chassis, 2U, single 110 to 240 VAC input, with 19 slots on front panel	€ 907,00	4~8W
TRC-190-DC-48	Rack chassis, 2U, single 36 to 53 VDC input, with 19 slots on front panel	€ 1.145,00	8~12W
TRC-2190-AC	2U rackmount chassis, with a single 110 to 240 VAC input, 18 slots on the front panel, and CSM-MN01 managed module	€ 1.491,00	4~8W
TRC-2190-DC-48V	2U rackmount chassis, with a single 36 to 53 VDC input, 18 slots on the front panel, and CSM-MN01 managed module	€ 1.744,00	8~12W
TSN-G5004	4G-port full Gigabit managed Ethernet switch, 4 10/100/1000BaseT(X) ports, -10 to 60°C operating temperature	€ 2.080,00	8~12W
TSN-G5008-2GTXSFP	8G-port full Gigabit managed Ethernet switch, 6 10/100/1000BaseT(X) ports, and 2 combo 10/100/1000BaseT(X) or 100/1000BaseSFP slots, -10 to 60°C operating temperature	€ 2.972,00	4~8W
UBLOX LTE module for EU	UBLOX LTE module for the EU region	€ 341,00	56~60W
UC-1222A	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -40 to 60°C operating	€ 682,00	4~8W
UC-2101-LX	Mini RISC-based embedded computer with 600 MHz processor, 1 serial port and 1 LAN port	€ 442,00	2~4W
UC-2102-LX	Mini RISC-based embedded computer with 600 MHz processor and 2 LAN ports	€ 442,00	8~12W
UC-2104-LX	Mini RISC-based embedded computer with 600 MHz processor, 1 LAN port, 1 Mini PCIe slot for wireless capability	€ 467,00	8~12W
UC-2111-LX	Compact RISC-based embedded computer with 600 MHz processor, 2 serial ports, 2 LAN ports, 1 microSD slot	€ 540,00	4~8W
UC-2112-LX	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 LAN ports (1 Gb Ethernet), and microSD slot	€ 645,00	2~4W
UC-2112-T-LX	Compact RISC-based embedded computer with 1 GHz processor, 2 serial ports, 2 Ethernet ports (1 Gigabit Ethernet), microSD slot and -40 to 75°C operating temperature	€ 723,00	4~8W

UC-2222A-T	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10) , -40 to 75°C operating	€ 821,00	12~16W
UC-2222A-T-AP	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the Asia-Pacific region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa I	€ 1.092,00	12~16W
UC-2222A-T-CN	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot for wireless module, 12 to 24 VDC, TPM v2.0 module, Moxa Industrial Linux (Debian 11, kernel 5.10), -4	€ 849,00	12~16W
UC-2222A-T-EU	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the European region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Indus	€ 1.092,00	12~16W
UC-2222A-T-US	Arm® Cortex®-A53 dual-core 64-bit 1-GHz industrial computer with 2 Ethernet ports, 2 RS-232/422/485 serial ports, 1 USB 2.0 port, 1 mPCIe expansion slot with LTE Cat. 4 module for the U.S. region preinstalled, 12 to 24 VDC, TPM v2.0 module, Moxa Industria	€ 1.092,00	12~16W
UC-3100 Antenna Set	4 dBi at 1575 MHz to 1610 MHz, SMA (male), active GPS/GLONASS, adhesive-type antenna with 20-cm cable; 2 4 dBi at 2.4 GHz or 5 dBi at 5 GHz, RP-SMA (female), omnidirectional antennas; 2 1.5 dBi 698 to 960 MHz or 1710 to 2700 MHz, SMA (male), LTE, swivel-t	€ 67,00	16~20W
UC-3100 DIN-Rail Kit	DIN-rail kit with screws	€ 13,00	4~8W
UC-3100 Wall-Mounting Kit	Wall-mounting kit with screws	€ 8,00	4~8W
UC-3101-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	€ 990,00	12~16W
UC-3101-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 module, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -30 to 70°C operating temperature	€ 990,00	8~12W
UC-3101-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	€ 990,00	12~16W
UC-3101-T-US-LX	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 USB port, -40 to 70°C operating temperature	€ 990,00	12~16W
UC-3111-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.344,00	12~16W
UC-3111-T-AP-LX-NW	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.280,00	8~12W
UC-3111-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -30 to 70°C operating temperature	€ 1.344,00	8~12W
UC-3111-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.344,00	4~8W
UC-3111-T-EU-LX-NW	Arm-based computer for the EU region with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.280,00	8~12W
UC-3111-T-US-LX	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.344,00	4~8W
UC-3111-T-US-LX-NW	Arm-based computer for the U.S. region (AT&T, Verizon) with built-in LTE Cat. 1 module, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 2 serial ports, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.280,00	8~12W
UC-3121-T-AP-LX	Arm-based computer for the Asia-Pacific region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.285,00	12~16W
UC-3121-T-AU-LX	Arm-based computer for the AUS and NZ regions with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 512 MB RAM, 4 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, -30 to 70°C operating temperature	€ 1.285,00	8~12W
UC-3121-T-EU-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.285,00	12~16W
UC-3121-T-US-LX	Arm-based computer for the EU region with built-in LTE Cat. 1 and Wi-Fi a/b/g/n modules, 1 GHz processor, 1 GB RAM, 8 GB eMMC, 2 Ethernet ports, 1 serial port, 1 CAN port, 1 USB port, 1 SD slot, -40 to 70°C operating temperature	€ 1.285,00	12~16W
UC-3420A-T-LTE	UC-3420A-T-LTE	€ 1.203,00	
UC-3424A-T-LTE	UC-3424A-T-LTE	€ 1.328,00	
UC-3430A-T-LTE-WiFi	UC-3430A-T-LTE-WiFi	€ 1.370,00	
UC-3434A-T-LTE-WiFi	UC-3434A-T-LTE-WiFi	€ 1.502,00	
UC-4400A Wall-mounting	Wall-mounting kit with 2 plates (44.8 x 99 x 5.7 mm each) and 5 M3 x 5 mm screws for the UC-4400A Series	€ 23,00	8~10W
UC-4400A-LTE-CAT4-WW	LTE package with a Telit LE910C4-WWxD LTE Cat. 4 mPCIe card for global coverage, 2 thermal pads, 2 heat sinks, 3 M2.5 x 5 mm screws for UC-443xA models	€ 164,00	16~20W
UC-4400A-WLAN22-AX	Wi-Fi 6E package with an EMWICOM WMX7205-1 Wi-Fi 6E M.2 card, 2 thermal pads, 2 heat sinks, 2 M2.5 x 5 mm screws for UC-443xA/445xA models	€ 187,00	16~20W
UC-4410A-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 DOs, -40 to 75°C operating temperature	€ 1.128,00	12~16W

UC-4414A-I-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation), 2 CAN ports, 4 DIs, 4 DOs, -40 to 75°C operating temperature	€ 1.407,00	12~16W
UC-4430A-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 DOs, 2 expansion slots (for Wi-Fi 6E and LTE modules), -40 to 70°C operating temperature	€ 1.268,00	12~16W
UC-4434A-I-T	Arm Cortex-A53 quad-core 1.6 GHz industrial computer 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation), 2 CAN ports, 4 DIs, 4 DOs, 2 expansion slots (for Wi-Fi 6E and LTE modules), -40 to 70°C operating temperature	€ 1.551,00	12~16W
UC-4450A-T-5G	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 2 serial ports, 1 CAN port, 4 DIs, 4 DOs, 5G NR module built-in, 1 expansion slot for a Wi-Fi 6E module, -40 to 70°C operating temperature	€ 2.534,00	12~16W
UC-4454A-T-5G	Arm Cortex-A53 quad-core 1.6 GHz industrial computer with 2 Ethernet ports, 4 serial ports (2 with 2-kV isolation), 2 CAN ports, 4 DIs, 4 DOs, 5G NR built-in, 1 expansion slot for a Wi-Fi 6E module, -40 to 70°C operating temperature	€ 2.810,00	12~16W
UC-5101-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	€ 990,00	4~8W
UC-5101-T-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	€ 1.236,00	8~12W
UC-5102-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature	€ 1.177,00	8~12W
UC-5102-T-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature	€ 1.409,00	12~16W
UC-5111-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature range	€ 1.236,00	8~12W
UC-5111-T-LX	Arm-based industrial computing platform with Cortex-A8 1 GHz CPU, 4 serial ports, 2 Ethernet ports, 1 SD slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature range	€ 1.487,00	8~12W
UC-5112-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -10 to 60°C operating temperature	€ 1.409,00	8~12W
UC-5112-T-LX	Arm-based wireless-enabled industrial computing platform with Cortex-A8 1 GHz CPU, 2 Ethernet ports, 4 serial ports, 1 SD slot, 1 Mini PCIe slot, 2 CAN ports, 4 DIs, 4 DOs, 1 USB port, -40 to 85°C operating temperature	€ 1.660,00	8~12W
UC-8100 LTE-CAT4-AP	Telit LE910C4-AP LTE Cat. 4 mini card with 2 M2 screws for the Asia-Pacific region	€ 292,00	56~60W
UC-8100 LTE-CAT4-EU	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2 screws for the EMEA region	€ 292,00	56~60W
UC-8100A-ME DIN-Rail Kit	DIN-rail mounting kit for UC-8100A-ME-T Series	€ 11,00	4~8W
UC-8100A-ME Wall Mount	Wall-mounting kit for UC-8100A-ME-T Series	€ 27,00	4~8W
UC-8100-ME Din-Rail Kit	DIN-rail mounting kit for UC-8100-ME Series	€ 44,00	4~8W
UC-8100-ME Wall Mount Kit	Wall-mounting kit with screws	€ 33,00	
UC-8112A-ME-T-LX	Arm-based DIN-rail industrial computer with 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot for Wi-Fi or LTE, -40 to 75°C operating temperature	€ 957,00	4~8W
UC-8112-LX	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	€ 684,00	2~4W
UC-8112-ME-T-LX	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 512 MB RAM, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot, -40 to 85°C operating temperature	€ 865,00	4~8W
UC-8112-ME-T-LX1	Arm-based wireless-enabled DIN-rail industrial computer with 1 GHz CPU, 1 GB RAM, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot, -40 to 85°C operating temperature	€ 938,00	8~12W
UC-8131-LX	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet, 1 Serial	€ 534,00	8~12W
UC-8132-LX	Arm-based wireless-enabled DIN-rail industrial computer with 300 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	€ 586,00	8~12W
UC-8162-LX	Arm-based wireless-enabled DIN-rail industrial computer with 600 MHz CPU, 2 Ethernet ports, 2 serial ports, 1 Mini PCIe slot	€ 602,00	4~8W
UC-8200 Wall-mounting Kit	Wall-mounting kit for UC-8200 with 4 M3 screws	€ 38,00	4~8W
UC-8200 WiFi-AC	Wi-Fi package for UC-8200, includes Wi-Fi module, 6 screws, 1 heat sink, 1 pad	€ 123,00	56~60W
UC-8200-WLAN22-AC	Wireless package for UC-8200 V2.0 or later with Wi-Fi module, 2 screws, 2 spacers, 1 heat sink, 1 pad	€ 136,00	20~24W
UC-8210 DIN-rail Mounting	DIN-rail mounting kit for UC-8210 with 4 M3 screws	€ 16,00	4~8W
UC-8210-T-LX-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, 1 CAN port, 4 DIs, 4 DOs, -40 to 85°C operating temperature	€ 1.066,00	2~4W
UC-8220 DIN-rail Mounting	DIN-rail mounting kit for UC-8220 with 4 M3 screws	€ 16,00	4~8W
UC-8220-T-LX	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with 2 expansion slots for a Wi-Fi and LTE module, 1 CAN port, 4 DIs, 4 DOs, -40 to 85°C operating temperature	€ 1.316,00	4~8W
UC-8220-T-LX-AP-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, Asia-Pacific region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	€ 1.770,00	12~16W
UC-8220-T-LX-EU-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, EU region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	€ 1.770,00	4~8W
UC-8220-T-LX-US-S	Arm Cortex-A7 dual-core 1 GHz IIoT gateway with built-in TPM module, US region LTE Cat. 4 module preinstalled, 1 Mini PCIe expansion slot for a Wi-Fi module, 1 CAN port, 4 DIs, 4 DOs, -40 to 70°C operating temperature	€ 1.770,00	4~8W
UC-8410A DIN-rail Kit	DIN-rail kit with 6 M3 screws (also included in the UC-8410A Series package)	€ 22,00	4~8W
UC-8410A LTE-CAT4-AP	Telit LE910C4-AP LTE Cat. 4 mini card with 2 M2.5 screws for the Asia-Pacific region, compatible with UC-8410A hardware rev. 2.1.0 and higher	€ 292,00	56~60W
UC-8410A LTE-CAT4-EU	Telit LE910C4-EU LTE Cat. 4 mini card with 2 M2.5 screws for the EMEA region, compatible with UC-8410A hardware rev. 2.1.0 and higher	€ 292,00	56~60W

UC-8410A-LX	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -10 to	€ 1.463,00	2~4W
UC-8410A-NW-LX	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -10 to 60°C operating temperature	€ 1.434,00	8~12W
UC-8410A-NW-T-LX	Arm-based wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 GB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, 1 mSATA slot, 1 USB port, Debian 8, -40 to 75°C operating temperature	€ 1.802,00	8~12W
UC-8410A-T-LX	Arm-based wireless-enabled wall-mount industrial computer with Cortex-A7 1 GHz dual-core, 1 SD slot with 1 GB card preinstalled, 512 MB DDR3L RAM, 8 serial ports, 4 DIs, 4 DOs, 3 Ethernet ports, wireless enabled, 1 mSATA slot, 1 USB port, Debian 8, -40 to	€ 1.834,00	4~8W
UC-8500-4GCat6-Q-APAC	LTE Cat. 6 module for North America and Europe, 2 QMA connectors with cables, -40 to 60°C operating temperature	€ 615,00	56~60W
UC-8500-4GCat6-Q-NAME	LTE Cat. 6 module for North America and Europe, 2 QMA connectors with cables, -40 to 60°C operating temperature	€ 856,00	56~60W
UC-8500-WLAN33-Q-AC	Wi-Fi 5 (802.11ac) module with 2 transmitters and 2 receivers, 2 QMA connectors with cables, 1 mPCIe adapter bracket with 4 screws, 1 thermal pad	€ 521,00	56~60W
UC-8500-WLAN33-Q-AC-T	Wi-Fi 5 (802.11ac) module with 2 transmitters and 2 receivers, 2 QMA connectors with cables, TE-LEC certification	€ 521,00	28~32W
UC-8540-LX	Vehicle-to-ground computing platform with multiple WWAN ports, -25 to 55°C operating temperature	€ 3.281,00	12~16W
UC-8540-T-CT-LX	Vehicle-to-ground computing platform with multiple WWAN ports, -40 to 70°C operating temperature, conformal coating	€ 4.830,00	12~16W
UC-8540-T-LX	Vehicle-to-ground computing platform with multiple WWAN ports, -40 to 70°C operating temperature	€ 3.972,00	12~16W
UC-8580-4GCat6-NAMEU	LTE Cat. 6 module for North America and Europe, 2 SMA connectors with cables, -40 to 60°C operating temperature	€ 833,00	56~60W
UC-8580-LX	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -25 to 55°C operating temperature	€ 7.986,00	12~16W
UC-8580-Q-LX	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -25 to 55°C operating temperature	€ 8.450,00	12~16W
UC-8580-T-CT-LX	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -40 to 70°C operating temperature, conformal coating	€ 11.742,00	12~16W
UC-8580-T-CT-Q-LX	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -40 to 70°C operating temperature, conformal coating	€ 12.449,00	12~16W
UC-8580-T-LX	Vehicle-to-ground computing platform with multiple WWAN ports, SMA connectors, -40 to 70°C operating temperature	€ 9.218,00	12~16W
UC-8580-T-Q-LX	Vehicle-to-ground computing platform with multiple WWAN ports, QMA connectors, -40 to 70°C operating temperature	€ 9.768,00	12~16W
UC-8580-WLAN33-AC	Wi-Fi 5 (802.11ac) module with 2 transmitters and 2 receivers, 2 SMA connectors with cables, 1 mPCIe adapter bracket with 4 screws, 1 thermal pad	€ 725,00	56~60W
UC-LTE-CAT1-AP	LTE cellular module with 2 M2 and 2 M2.5 mounting screws for Asia-Pacific bands 1, 3, 5, 8, 9, 18(26), 19, 28	€ 288,00	56~60W
UC-LTE-CAT1-EU	LTE cellular module with 2 M2 and 2 M2.5 mounting screws for EMEA bands 1, 3, 7, 8, 20, 28A	€ 288,00	20~24W
UC-WiFi-USB	802.11 a/b/g/n/ac, 2.4/5 GHz Wi-Fi module with 2 each of M2 and M2.5 screws	€ 104,00	28~32W
UPort 1110	1-port RS-232 USB-to-serial converter	€ 57,00	2~4W
UPort 1130	1-port RS-422/485 USB-to-serial converter	€ 102,00	2~4W
UPort 1130I	1-port RS-422/485 USB-to-serial converter with 2 kV optical isolation	€ 195,00	2~4W
UPort 1150	1-port RS-232/422/485 USB-to-serial converter	€ 152,00	2~4W
UPort 1150I	1-port RS-232/422/485 USB-to-serial converter with optical isolation protection	€ 258,00	2~4W
UPort 1250	USB to 2-port RS-232/422/485 serial hub	€ 223,00	4~8W
UPort 1250-G2	2-port RS-232/422/485 USB-to-serial converter, 0 to 60°C operating temperature	€ 222,00	8~12W
UPort 1250-G2-T	2-port RS-232/422/485 USB-to-serial converter, -40 to 75°C operating temperature	€ 275,00	12~16W
UPort 1250I	USB to 2-port RS-232/422/485 serial hub with 2 kV isolation	€ 399,00	4~8W
UPort 1250I-G2	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, 0 to 60°C operating temperature	€ 390,00	8~12W
UPort 1250I-G2-T	2-port RS-232/422/485 USB-to-serial converter with 2 kV isolation protection, -40 to 75°C operating temperature	€ 490,00	12~16W
UPort 1410-G2	USB to 4-port RS-232 converter, 0 to 60°C operating temperature	€ 345,00	8~12W
UPort 1450-G2	USB to 4-port RS-232/422/485 converter, 0 to 60°C operating temperature	€ 419,00	8~12W
UPort 1450-G2-T	USB to 4-port RS-232/422/485 converter, -40 to 75°C operating temperature	€ 526,00	12~16W
UPort 1450I-G2	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	€ 768,00	8~12W
UPort 1450I-G2-T	USB to 4-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	€ 958,00	12~16W
UPort 1610-16	USB to 16-port RS-232 serial hub	€ 941,00	4~8W
UPort 1610-8-G2	USB to 8-port RS-232 converter, 0 to 60°C operating temperature	€ 490,00	8~12W
UPort 1650-16	USB to 16-port RS-232/422/485 serial hub	€ 1.299,00	4~8W
UPort 1650-8-G2	USB to 8-port RS-232/422/485 converter, 0 to 60°C operating temperature	€ 736,00	8~12W
UPort 1650-8-G2-Hub	USB to 8-port RS-232/422/485 converter with 3 extra downstream USB ports, 0 to 60°C operating temperature	€ 950,00	8~12W
UPort 1650-8-G2-T	USB to 8-port RS-232/422/485 converter, -40 to 75°C operating temperature	€ 917,00	12~16W
UPort 1650I-8-G2	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, 0 to 60°C operating temperature	€ 1.320,00	8~12W

UPort 1650I-8-G2-T	USB to 8-port RS-232/422/485 converter with 2 kV isolation protection, -40 to 75°C operating temperature	€ 1.653,00	12~16W
UPort 204	4-port entry-level USB hub, adaptor included	€ 258,00	2~4W
UPort 204A	4-port general-purpose USB 3.2 hubs	€ 275,00	4~8W
UPort 207	7-port entry-level USB hub, adaptor included	€ 313,00	4~8W
UPort 207A	7-port general-purpose USB 3.2 hubs	€ 332,00	8~12W
UPort 2210	2-port RS-232 USB-to-serial converter	€ 220,00	4~8W
UPort 2410	4-port RS-232 USB-to-serial converter	€ 288,00	4~8W
UPort 404	4-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	€ 369,00	2~4W
UPort 404A	4-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	€ 386,00	4~8W
UPort 404A-T	4-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	€ 521,00	12~16W
UPort 404-T w/o Adapter	4-port industrial USB hub, without adapter, -40 to 85°C operating temperature	€ 460,00	4~8W
UPort 407	7-port industrial USB hub, adaptor included, 0 to 60°C operating temperature	€ 439,00	2~4W
UPort 407A	7-port industrial-grade USB 3.2 hubs, 0 to 60°C operating temperature	€ 467,00	4~8W
UPort 407A-T	7-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature	€ 610,00	4~8W
UPort 407-T w/o Adapter	7-port industrial USB hub, without adapter, -40 to 85°C operating temperature	€ 561,00	4~8W
V1202-CT-T	V1202-CT-T	€ 1.822,00	
V2201 Wi-Fi mini Card	SparkLAN WPEA-252NI Wi-Fi mini card with 4 black screws	€ 399,00	56~60W
V2201-E1-T	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	€ 2.171,00	8~12W
V2201-E1-T-LX	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Linux Debian 8 preinstalled, -40 to 85°C operating temperature	€ 2.301,00	8~12W
V2201-E1-T-W7E	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Windows Embedded Standard 7 preinstalled, -40 to 85°C operating temperature	€ 2.524,00	8~12W
V2201-E1-W-T	x86 embedded computer with Intel Atom® E3815 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, Wi-Fi and cellular antenna SMA-type connectors, -40 to 85°C operating temperature	€ 2.301,00	8~12W
V2201-E2-T	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 2 Mini PCIe slots, -40 to 85°C operating temperature	€ 2.272,00	8~12W
V2201-E2-W-T	x86 embedded computer with Intel Atom® E3826 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 85°C operating temperature	€ 2.397,00	8~12W
V2201-E4-T	x86 embedded computer with Intel Atom® E3845, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, -40 to 70°C operating temperature	€ 2.365,00	8~12W
V2201-E4-W-T	x86 embedded computer with Intel Atom® E3845 processor, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot, 1 uSIM slot, 1 Wi-Fi Mini PCIe slot, 1 3G/LTE Mini PCIe slot, 5 wireless SMA connectors, -40 to 70°C operating temperature	€ 2.492,00	8~12W
V2201-E4-W-T-LX	x86 embedded computer with Intel Atom® E3845 processor, 4 GB RAM, 1 HDMI port, 2 Ethernet ports, 2 serial ports, 4 DIs, 4 DOs, 1 USB 3.0 port, 2 USB 2.0 ports, 1 SD slot with 16 GB card preinstalled, 1 mSATA slot with 32 GB preinstalled, 1 uSIM slot, 1 Wi-Fi antenna, -40 to 70°C operating temperature	€ 2.502,00	8~12W
V2400 Cover-DB9	Dual DB9 expansion cover, 4 male hex standoff spacer pillars	€ 24,00	4~8W
V2400 Isolated Wall Mount	Wall-mounting kit with isolation protection, 2 wall-mounting brackets, 4 screws	€ 65,00	4~8W
V2400-WLAN22-AC	SparkLAN WPEQ-261ACNI (BT) Wi-Fi mini card, 4 black screws	€ 164,00	20~24W
V2403C-KL1-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.2 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	€ 3.655,00	8~12W
V2403C-KL3-T	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	€ 4.224,00	8~12W
V2403C-KL5-T	x86 computer with Intel® 7th Gen Core™ i5-7300U 3.5 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	€ 4.928,00	8~12W
V2403C-KL7-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 3.9 GHz processor, 4 GbE ports, 4 COM ports, 4 DIs, 4 DOs, 1 HDMI/DP port, 1 mSATA slot, 2 2.5" SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 12 to 48 VDC, -40 to 70°C operating temperature	€ 5.488,00	8~12W
V2403C-LTECat4-AP	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region, 3 SMA antenna cables	€ 249,00	56~60W
V2403C-LTECat4-EU	Telit LE910C4 LTE Cat. 4 mini card for Europe, 3 SMA antenna cables	€ 249,00	56~60W
V2403C-LTECat4-NF	Telit LE910C4 LTE Cat. 4 mini card for North America, 3 SMA antenna cables	€ 249,00	56~60W
V2406C TPM2.0 CT Module	SLB9665XT2.0 TPM 2.0 module with conformal coating	€ 55,00	56~60W
V2406C TPM2.0 Module	SLB9665XT2.0 TPM 2.0 module without conformal coating	€ 50,00	56~60W
V2406C Wall mount kit	Single-bracket wall-mounting kit for the V2406C Series with 8 M3 x 6 mm screws	€ 50,00	10~12W
V2406C-KL1-CT-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	€ 6.443,00	12~16W
V2406C-KL1-T	x86 computer with Intel® 7th Gen Celeron® 3965U 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	€ 5.364,00	12~16W
V2406C-KL3-T	x86 computer with Intel® 7th Gen Core™ i3-7100U 2.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°C operating temperature	€ 6.175,00	12~16W

V2406C-KL5-T	x86 computer with Intel® 7th Gen Core™ i5-7300U 2.6 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°	€ 7.117,00	12~16W
V2406C-KL7-CT-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°	€ 10.071,00	12~16W
V2406C-KL7-T	x86 computer with Intel® 7th Gen Core™ i7-7600U 2.8 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 24 to 110 VDC power input with isolation, -40 to 70°	€ 8.396,00	12~16W
V2406C-LTECat4-AP	Telit LE910C4 LTE Cat. 4 mini card for the Asia-Pacific region	€ 249,00	20~24W
V2406C-LTECat4-EU	Telit LE910C4 LTE Cat. 4 mini card for European region	€ 249,00	20~24W
V2406C-LTECat4-NF	Telit LE910C4 LTE Cat. 4 mini card for the North American region	€ 249,00	20~24W
V2406C-WL1-CT-T	x86 computer with Intel 8th Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to 70°	€ 5.488,00	12~16W
V2406C-WL1-T	x86 computer with Intel 8th Gen Celeron 4305UE 2.0 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 to	€ 4.545,00	8~12W
V2406C-WL3-T	x86 computer with Intel 8th Gen Core™ i3-8145UE 3.90 GHz processor, 1 HDMI port, 1 VGA port, 2 Gigabit Ethernet ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with is	€ 5.275,00	8~12W
V2406C-WL5-T	x86 computer with Intel 8th Gen Core™ i5-8365UE 4.1 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 t	€ 6.105,00	8~12W
V2406C-WL7-CT-T	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 t	€ 8.785,00	12~16W
V2406C-WL7-T	x86 computer with Intel 8th Gen Core™ i7-8665UE 4.4 GHz processor, 1 HDMI port, 1 VGA port, 2 GbE ports, 4 COM ports, 6 DIs, 2 DOs, 1 mSATA slot, dual 2.5-inch SSD/HDD slots, 2 mPCIe slots, 4 USB ports, 1 QMA connector, 24 to 110 VDC with isolation, -40 t	€ 7.310,00	8~12W
V3200-LTECat4-GL	Telit LE910C4 LTE Cat. 4 mPCIe card, 3 coaxial cables (I-PEX MHF male connector to QMA female connector, 160 mm), 1 thermal pad	€ 292,00	8~12W
V3200-WLAN22-AC	Wi-Fi 5 (802.11ac) module, 1 mPCIe adapter bracket with 4 screws, 2 coaxial cables (I-PEX MHF male connector to QMA female connector, 160 mm), 1 thermal pad	€ 292,00	8~12W
V3200-WLAN22-AX	Wi-Fi 6 (802.11ax) module, 2 coaxial cables (I-PEX 4 MHF male connector to QMA female connector, 160 mm), 1 thermal pad	€ 418,00	8~12W
V3210-TL1-4L-T	x86 computer with Intel® Celeron® 6305E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD/HDD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	€ 4.936,00	8~12W
V3210-TL1-8L-CT-T	x86 computer with Intel® Celeron® 6305E processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 5.909,00	12~16W
V3210-TL3-4L-CT-T	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 5.631,00	12~16W
V3210-TL3-4L-T	x86 computer with Intel® Core™ i3-1115G4E processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	€ 5.353,00	8~12W
V3210-TL5-8L-CT-T	x86 computer with Intel® Core™ i5-1145G7E processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 6.813,00	12~16W
V3210-TL7-4L-T	x86 computer with Intel® Core™ i7-1185GRE processor, 4 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature	€ 7.689,00	8~12W
V3210-TL7-8L-CT-T	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, 24 to 110 VDC, -40 to 70°C operating temperature, conformal coating	€ 9.315,00	12~16W
V3210-TL7-8L-TSN-CT-T	x86 computer with Intel® Core™ i7-1185GRE processor, 8 GbE ports, 4 serial ports, 2 DIs, 2 DOs, 2 USB ports, 1 HDMI port, 1 VGA port, 2 2.5" SSD slots, 1 mPCIe slot, built-in TPM module, native TSN support, 24 to 110 VDC, -40 to 70°C operating temperature	€ 9.454,00	12~16W
VP-06TC1L	Top cover of VPort P06-1MP-M12 (LED)	€ 45,00	8~12W
VP-06TC2CS	Top cover of VPort 06-2L, coating dome cover, smoked dome	€ 76,00	8~12W
VP-DP01	silica gel dry pack (2 x 0.6 g) with sticker	€ 7,00	4~8W
VP-DP02	15 g dry pack with hook-and-loop fastener	€ 7,00	4~8W
VP-FMK1	Flush-mounting kit for the VPort P16	€ 166,00	8~12W
VP-FP1	Fixed plate for mounting the VPort P06-1MP-M12	€ 21,00	4~8W
VP-FP2	Fixed plate for mounting the VPort 06	€ 19,00	4~8W
VPort 06-2L28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	€ 1.172,00	12~16W
VPort 06-2L28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	€ 1.384,00	12~16W
VPort 06-2L36M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	€ 1.175,00	12~16W
VPort 06-2L36M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort 06-2L42M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	€ 1.175,00	12~16W

VPort 06-2L42M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort 06-2L60M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	€ 1.159,00	12~16W
VPort 06-2L60M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort 06-2L80M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	€ 1.175,00	12~16W
VPort 06-2L80M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 audio input, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort 06-2M28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -25 to 55°C operating temperature	€ 1.230,00	12~16W
VPort 06-2M28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, 24 VDC, 2.8 mm lens, -40 to 70°C operating temperature	€ 1.410,00	12~16W
VPort 06-2M36M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort 06-2M36M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 3.6 mm lens, -40 to 70°C operating temperature	€ 1.442,00	12~16W
VPort 06-2M42M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort 06-2M42M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 4.2 mm lens, -40 to 70°C operating temperature	€ 1.442,00	12~16W
VPort 06-2M60M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort 06-2M60M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 6.0 mm lens, -40 to 70°C operating temperature	€ 1.442,00	12~16W
VPort 06-2M80M	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort 06-2M80M-T	EN 50155, FHD, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, 24 VDC, 8.0 mm lens, -40 to 70°C operating temperature	€ 1.442,00	12~16W
VPort 06EC-2V36M	EN50155, 1080P, day and night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature	€ 2.488,00	12~16W
VPort 06EC-2V36M-CT	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -25 to 55°C operating temperature, conformal coating	€ 2.991,00	16~20W
VPort 06EC-2V36M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature, conformal coating	€ 3.209,00	16~20W
VPort 06EC-2V36M-T	EN50155, 1080P, day & night outdoor IP camera, 3.6 mm lens, -40 to 70°C operating temperature	€ 2.674,00	12~16W
VPort 06EC-2V42M	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature	€ 2.488,00	12~16W
VPort 06EC-2V42M-CT	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -25 to 55°C operating temperature, conformal coating	€ 2.991,00	16~20W
VPort 06EC-2V42M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature, conformal coating	€ 3.209,00	16~20W
VPort 06EC-2V42M-T	EN50155, 1080P, day & night outdoor IP camera, 4.2 mm lens, -40 to 70°C operating temperature	€ 2.674,00	16~20W
VPort 06EC-2V60M	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature	€ 2.488,00	12~16W
VPort 06EC-2V60M-CT	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -25 to 55°C operating temperature, conformal coating	€ 2.991,00	16~20W
VPort 06EC-2V60M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature, conformal coating	€ 3.209,00	16~20W
VPort 06EC-2V60M-T	EN50155, 1080P, day & night outdoor IP camera, 6 mm lens, -40 to 70°C operating temperature	€ 2.674,00	16~20W
VPort 06EC-2V80M	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature	€ 2.488,00	12~16W
VPort 06EC-2V80M-CT	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -25 to 55°C operating temperature, conformal coating	€ 2.991,00	16~20W
VPort 06EC-2V80M-CT-T	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature, conformal coating	€ 3.209,00	16~20W
VPort 06EC-2V80M-T	EN50155, 1080P, day & night outdoor IP camera, 8 mm lens, -40 to 70°C operating temperature	€ 2.674,00	16~20W
VPort 461A	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -25 to 60°C operating temperature	€ 1.005,00	4~8W
VPort 461A-T	Full Motion, 1-ch industrial video encoder, 2 10/100BaseT(X) Ethernet ports, -40 to 75°C operating temperature	€ 1.193,00	4~8W
VPort 464	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -25 to 60°C operating temperature	€ 2.111,00	4~8W
VPort 464-T	4-channel H.264/MJPEG industrial video encoder, 2 10/100/1000BaseT(X) Ethernet ports, -40 to 75°C operating temperature	€ 2.287,00	4~8W
VPort P06-1MP-M12-CAM2	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	€ 948,00	12~16W
VPort P06-1MP-M12-CAM2	EN 50155, HD image, compact IP camera, M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	€ 1.135,00	12~16W
VPort P06-1MP-M12-CAM3	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	€ 956,00	12~16W
VPort P06-1MP-M12-CAM3	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	€ 1.145,00	12~16W
VPort P06-1MP-M12-CAM4	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	€ 956,00	12~16W
VPort P06-1MP-M12-CAM4	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	€ 1.145,00	12~16W

VPort P06-1MP-M12-CAM6	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	€ 956,00	12~16W
VPort P06-1MP-M12-CAM6	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 6.0 mm lens, -40 to 70°C operating temperature	€ 1.145,00	12~16W
VPort P06-1MP-M12-CAM8	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	€ 956,00	12~16W
VPort P06-1MP-M12-CAM8	EN50155, HD, compact IP camera, M12 connector, 1 audio-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	€ 1.145,00	12~16W
VPort P06-2L28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -25 to 55°C operating temperature	€ 1.172,00	12~16W
VPort P06-2L28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 audio input, PoE, 2.8 mm lens, -40 to 70°C operating temperature	€ 1.352,00	12~16W
VPort P06-2L36M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -25 to 55°C operating temperature	€ 1.159,00	12~16W
VPort P06-2L36M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 3.6 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort P06-2L42M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -25 to 55°C operating temperature	€ 1.159,00	12~16W
VPort P06-2L42M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 4.2 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort P06-2L60M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -25 to 55°C operating temperature	€ 1.159,00	12~16W
VPort P06-2L60M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 6.0 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort P06-2L80M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -25 to 55°C operating temperature	€ 1.159,00	12~16W
VPort P06-2L80M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 audio input, PoE, 8.0 mm lens, -40 to 70°C operating temperature	€ 1.349,00	12~16W
VPort P06-2M28M	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -25 to 55°C operating temperature	€ 1.269,00	12~16W
VPort P06-2M28M-T	EN 50155, 1080P image, compact IP camera with M12 connector, 1 microphone, PoE, 2.8 mm lens, -40 to 70°C operating temperature	€ 1.449,00	12~16W
VPort P06-2M36M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort P06-2M36M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 3.6 mm lens, -40 to 70°C operating temperature	€ 1.444,00	12~16W
VPort P06-2M42M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort P06-2M42M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 4.2 mm lens, -40 to 70°C operating temperature	€ 1.444,00	12~16W
VPort P06-2M60M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 6.0 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort P06-2M60M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 built-in mic, PoE, 6.0 mm lens, -40 to 70°C operating temperature	€ 1.442,00	12~16W
VPort P06-2M80M	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -25 to 55°C operating temperature	€ 1.270,00	12~16W
VPort P06-2M80M-T	EN 50155, 1080P, H.264/MJPEG IP camera with M12 connector, 1 mic built-in, PoE, 8.0 mm lens, -40 to 70°C operating temperature	€ 1.444,00	12~16W
VPort P06HC-1V28M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature	€ 991,00	12~16W
VPort P06HC-1V28M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 2.8 mm lens, -40 to 55°C operating temperature, conformal coating	€ 1.087,00	12~16W
VPort P06HC-1V36M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature	€ 991,00	12~16W
VPort P06HC-1V36M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 3.6 mm lens, -40 to 55°C operating temperature, conformal coating	€ 1.087,00	12~16W
VPort P06HC-1V42M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature	€ 991,00	12~16W
VPort P06HC-1V42M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 4.2 mm lens, -40 to 55°C operating temperature, conformal coating	€ 1.087,00	12~16W
VPort P06HC-1V60M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature	€ 991,00	12~16W
VPort P06HC-1V60M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 6.0 mm lens, -40 to 55°C operating temperature, conformal coating	€ 1.087,00	12~16W
VPort P06HC-1V80M	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature	€ 991,00	12~16W
VPort P06HC-1V80M-CT	EN 50155, HD image, cubic IP camera with M12 connector, PoE, 8.0 mm lens, -40 to 55°C operating temperature, conformal coating	€ 1.087,00	12~16W
VPort P07-3L24M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 2.4 mm lens, -40 to 55°C	€ 1.168,00	12~16W
VPort P07-3L24M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 2.4 mm lens, -40 to 70°C	€ 1.363,00	12~16W
VPort P07-3L36M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 3.6 mm lens, -40 to 55°C	€ 1.168,00	12~16W
VPort P07-3L36M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 3.6 mm lens, -40 to 70°C	€ 1.363,00	12~16W

VPort P07-3L42M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 4.2 mm lens, -40 to 55°C	€ 1.168,00	12~16W
VPort P07-3L42M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 4.2 mm lens, -40 to 70°C	€ 1.363,00	12~16W
VPort P07-3L60M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 6.0 mm lens, -40 to 55°C	€ 1.168,00	12~16W
VPort P07-3L60M-T	EN 50155, 3-megapixels, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 6.0 mm lens, -40 to 70°C	€ 1.363,00	12~16W
VPort P07-3L80M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 8.0 mm lens, -40 to 55°C	€ 1.168,00	12~16W
VPort P07-3L80M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 line-in audio input, PoE, 8.0 mm lens, -40 to 70°C	€ 1.363,00	12~16W
VPort P07-3M24M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 2.4 mm lens, -40 to 55°C	€ 1.196,00	12~16W
VPort P07-3M24M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 2.4 mm lens, -40 to 70°C	€ 1.377,00	12~16W
VPort P07-3M36M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 3.6 mm lens, -40 to 55°C	€ 1.196,00	12~16W
VPort P07-3M36M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 3.6 mm lens, -40 to 70°C	€ 1.377,00	12~16W
VPort P07-3M42M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 4.2 mm lens, -40 to 55°C	€ 1.196,00	12~16W
VPort P07-3M42M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 4.2 mm lens, -40 to 70°C	€ 1.377,00	12~16W
VPort P07-3M60M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 6.0 mm lens, -40 to 55°C	€ 1.196,00	12~16W
VPort P07-3M60M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 6.0 mm lens, -40 to 70°C	€ 1.377,00	12~16W
VPort P07-3M80M	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 8.0 mm lens, -40 to 55°C	€ 1.196,00	12~16W
VPort P07-3M80M-T	EN 50155, 3-megapixel, H.265/H.264/MJPEG IP camera, 1 built-in microphone, PoE, 8.0 mm lens, -40 to 70°C	€ 1.377,00	12~16W
VPort P16-1MP-M12-CAM3	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 3.6mm lens, -25 to 55°C operating temperature	€ 1.348,00	12~16W
VPort P16-1MP-M12-CAM3	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 3.6mm lens, -40 to 70°C operating temperature	€ 1.537,00	12~16W
VPort P16-1MP-M12-CAM8	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 8.0mm lens, -25 to 55°C operating temperature	€ 1.348,00	12~16W
VPort P16-1MP-M12-CAM8	EN50155, HD image, rugged fixed-dome IP camera, PoE, M12 connector, 8.0mm lens, -40 to 70°C operating temperature	€ 1.537,00	12~16W
VPort P16-1MP-M12-IR-CA	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 3.6mm lens, -25 to 55°C operating temperature	€ 1.523,00	12~16W
VPort P16-1MP-M12-IR-CA	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 3.6mm lens, -40 to 70°C operating temperature	€ 1.706,00	12~16W
VPort P16-1MP-M12-IR-CA	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 8.0mm lens, -25 to 55°C operating temperature	€ 1.523,00	12~16W
VPort P16-1MP-M12-IR-CA	EN50155, HD image, fixed-dome IP camera, PoE, M12 connector, IR, MIC, 1DI, 8.0mm lens, -40 to 70°C operating temperature	€ 1.706,00	12~16W
VPort P16-2MR36M	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	€ 1.552,00	12~16W
VPort P16-2MR36M-T	EN50155, day & night, IR, 1080P IP Camera, 3.6 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	€ 1.709,00	12~16W
VPort P16-2MR42M	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	€ 1.552,00	12~16W
VPort P16-2MR42M-T	EN50155, day & night, IR, 1080P IP Camera, 4.2 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	€ 1.709,00	12~16W
VPort P16-2MR60M	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	€ 1.552,00	12~16W
VPort P16-2MR60M-T	EN50155, day & night, IR, 1080P IP Camera, 6.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	€ 1.709,00	12~16W
VPort P16-2MR80M	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -25 to 55°C operating temperature	€ 1.552,00	12~16W
VPort P16-2MR80M-T	EN50155, day & night, IR, 1080P IP Camera, 8.0 mm lens, PoE, M12 connector, -40 to 70°C operating temperature	€ 1.709,00	12~16W
VP-SC02	Side-cable-out adapter for surface mounting a VPort 06-2	€ 10,00	4~8W
VP-SCO1	Side-cable-out adapter for mounting the VPort P06-1MP-M12	€ 11,00	4~8W
VP-SScrew	VPort P06-1MP series security screw 1000 pcs	€ 406,00	4~8W
WAC-1001	Industrial wireless access controller, 0 to 60°C operating temperature	€ 3.558,00	8~12W
WAC-1001-T	Industrial wireless access controller, -40 to 75°C operating temperature	€ 4.266,00	12~16W
WAC-2004A	Industrial wireless access controller with EU power cord, 0 to 50°C operating temperature	€ 30.016,00	8~12W
WALLMOUNT-8100-01	Wall-mounting kit for the UC-8100 with screws	€ 46,00	4~8W
WIFI module	Wi-Fi module with 2 built-in antennas and 4 screws	€ 194,00	12~16W
WiFi-BGN	802.11ac/a/b/g/n Wi-Fi module x1, i-PEX MHF male connector to RP-SMA female connector x2, ANT-WDB-ARM-02 x1, M2 screw x2	€ 122,00	28~32W
Wi-Fi-BGN(252NI)	Wi-Fi module with 2 antennas, antenna cables and connectors, 2 black screws, 2 lock washers, 2 nuts, 1 thermal pad	€ 558,00	56~60W

WK-112-01	Wall-mounting kit, 2 plates, 8 screws	€ 34,00	4~8W
WK-160-01	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, black	€ 81,00	4~8W
WK-160-02	Wall-mounting kit with 1 plate (160 x 89 x 2.0 mm), 4 screws, gray	€ 81,00	4~8W
WK-18	Wall-mounting kit, 1 plate (18 x 120 x 8.5 mm)	€ 11,00	4~8W
WK-195	Wall Mounting Kit for PT-7710 series modular Ethernet Switches	€ 79,00	4~8W
WK-20-02	Wall-mounting kit, 3 screws, 20 x 140 x 2 mm	€ 28,00	4~8W
WK-25	Wall-mounting kit, 2 plates, 4 screws, 25 x 43 x 2 mm	€ 41,00	4~8W
WK-30	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	€ 8,00	4~8W
WK-30-02	Wall-mounting kit, 2 plates, 4 screws, 30 x 66.8 x 2 mm	€ 20,00	4~8W
WK-33-01	Wall-mounting kit with 2 plates (98.6 x 33.8 x 5 mm), 4 TMS M3 4-mm screws	€ 20,00	4~8W
WK-35-01	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm) and 6 screws	€ 18,00	4~8W
WK-35-02	Wall-mounting kit with 2 plates (35 x 24 x 1.2 mm) and 6 screws	€ 18,00	4~8W
WK-35-04	Wall-mount kit with 2 plates (35 x 44 x 2.5 mm), 6 screws (FTS x 6 M3 x 4 mm)	€ 18,00	4~8W
WK-35-05	Wall-mounting kit with 2 plates (35 x 44 x 2.5 mm), 6 NYLOK screws	€ 15,00	8~10W
WK-36-02	DIN-rail/wall-mounting kit, 2 plates, 6 screws	€ 38,00	4~8W
WK-40-01	Wall-mounting kit, 2 plates, 6 screws, 40 x 58 x 2 mm	€ 18,00	4~8W
WK-41-01	Wall-mounting kit with 1 plate (41 x 144 x 7.5 mm)	€ 57,00	4~8W
WK-44-01	Rack-mounting kit, 2 L-shaped plates, 8 screws, 44 x 57.5 x 1.6 mm	€ 18,00	4~8W
WK-45-01	Rack-mounting kit, 2 L-shaped plates, 8 screws, 45 x 57 x 2.5 mm	€ 23,00	4~8W
WK-46	Wall-mounting kit, 2 plates, 8 screws, 46.5 x 66.8 x 1 mm	€ 8,00	4~8W
WK-46-01	Wall-mounting kit, 2 plates, 8 screws, 46 x 66.8 x 2 mm	€ 14,00	4~8W
WK-51-01	Wall mounting kit with 2 plates (51.6 x 67 x 2 mm) and 6 screws	€ 21,00	4~8W
WK-55	Wall mounting kit with 2 plates (55 x 34.5 x 2.5 mm) and 6 screws	€ 21,00	4~8W
WK-60-01	Wall-mounting kit, 2 plates, 6 screws, 60 x 70 x 2 mm	€ 17,00	4~8W
WK-71-01	WK-71-01	€ 34,00	4~8W
WK-75	Wall-mounting kit, 2 plates, 8 screws, 75 x 90 x 2.5 mm	€ 34,00	4~8W
WK-90-01	Wall-mounting kit, 2 plates, 6 screws, 90 x 62 x 2.5 mm	€ 30,00	4~8W
WK-TN-5308A	Transition wall-mounting kit with 1 plate (197 x 60 x 4 mm) for the TN-5308A Series to adapt to the existing TN-5308 Series mounting holes	€ 31,00	8~10W
WK-UP-14168	Wall-mounting kit with 2 plates (35 x 44 mm), 6 screws (FMS M3 x 4 mm) for the UPort 1400 and 1600-8 models	€ 13,00	4~8W
WK-UP200A-BAK-SI	Rear-panel wall-mounting kit for the UPort 200A Series, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in) with 2 plates and 6 M3 x 5 mm screws	€ 23,00	8~10W
WK-UP200A-BOT-SI	Bottom-panel wall-mounting kit for the UPort 200A Series, 43 x 30 x 2 mm (1.69 x 1.18 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	€ 20,00	8~10W
WK-UP400A-BAK-BK	Rear-panel wall-mounting kit for the UPort 400A, 60 x 27 x 2 mm (2.36 x 1.06 x 0.08 in), with 2 plates and 6 M3 x 5 mm screws	€ 23,00	4~8W
WK-UP400A-BOT-BK	Bottom-panel wall-mounting kit for the UPort 400A/1400-G2/1600-G2 Series with 2 plates (43 x 30 x 2 mm or 1.69 x 1.18 x 0.08 in), 6 M3 x 5 mm screws	€ 20,00	4~8W
WM-UC-5000	Wall-mounting kit with screws for the UC-5000 Series	€ 23,00	4~8W
XM-4000-16GSFP	Gigabit Ethernet module with 16 1000BaseSFP ports	€ 3.166,00	8~12W
XM-4000-16GTX	Gigabit Ethernet module with 16 1000BaseT(X) ports	€ 3.166,00	8~12W
XM-4000-16QGSFP	2.5 Gigabit Ethernet module with 16 1000/2500BaseSFP ports	€ 6.325,00	8~12W
XM-4000-16QGTX	2.5 Gigabit Ethernet module with 16 1000/2500BaseT(X) ports	€ 6.325,00	8~12W
XM-4000-FAN-R	Exhaust fan module for MRX switches	€ 336,00	8~12W